

INTERNATIONAL STANDARD

Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS) – Part 6: Navigation with Indian constellation (NavIC)/Indian regional navigation satellite system (IRNSS) – Receiver equipment – Performance requirements, methods of testing and required test results

<https://standards.iteh.ai/catalog/standards/sist/e2397ccc-95c3-4271-a376-c62c03194f7a/iec-61108-6-2023>



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2023 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

[IEC 61108-6:2023](#)

<https://standards.iteh.ai/catalog/standards/sist/c2597ccc-95e3-4271-a376-c62e0319417a/iec-61108-6-2023>

INTERNATIONAL STANDARD

Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS) – Part 6: Navigation with Indian constellation (NavIC)/Indian regional navigation satellite system (IRNSS) – Receiver equipment – Performance requirements, methods of testing and required test results

<https://standards.iteh.ai/catalog/standards/sist/e2397ccc-95c3-4271-a376-c62c03194f7a/iec-61108-6-2023>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 33.060; 47.040; 47.060

ISBN 978-2-8322-6363-1

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references	6
3 Terms, definitions and abbreviated terms	8
3.1 Terms and definitions.....	8
3.2 Abbreviated terms.....	8
4 Minimum performance requirements.....	9
4.1 Object.....	9
4.2 IRNSS/NavIC receiver equipment	10
4.2.1 Minimum facilities	10
4.2.2 Configuration.....	10
4.2.3 Quality assurance.....	10
4.3 Performance of IRNSS/NavIC receiver equipment.....	10
4.3.1 General	10
4.3.2 Equipment interfaces	11
4.3.3 Accuracy	12
4.3.4 Acquisition.....	12
4.3.5 Protection.....	13
4.3.6 Antenna design.....	13
4.3.7 Sensitivity and dynamic range	14
4.3.8 Effects of specific interfering signals.....	14
4.3.9 Position update.....	14
4.3.10 Differential IRNSS/NavIC input	15
4.3.11 Navigation warnings and status indications.....	15
4.3.12 Output of COG, SOG and UTC	17
4.3.13 Typical interference conditions	18
5 Methods of testing and required test results	18
5.1 Test sites	18
5.2 Test sequence	19
5.3 Standard test signals	19
5.4 Determination of accuracy	20
5.5 General requirements and presentation requirements	20
5.5.1 Normal environmental conditions for tests	20
5.5.2 General requirements	20
5.5.3 Presentation requirements.....	20
5.6 Receiver performance tests	20
5.6.1 IRNSS/NavIC receiver equipment.....	20
5.6.2 Position output.....	20
5.6.3 Equipment interfaces	21
5.6.4 Accuracy	21
5.6.5 Acquisition.....	22
5.6.6 Protection.....	23
5.6.7 Antenna design.....	23
5.6.8 Sensitivity and dynamic range	23
5.6.9 Protection from other shipborne transmitters	24
5.6.10 Position update.....	25
5.6.11 Differential IRNSS/NavIC input	25

5.6.12	Navigational warnings and status indications	26
5.6.13	Accuracy of COG and SOG.....	28
5.6.14	Validity of COG and SOG information	29
5.6.15	Output of UTC	29
5.7	Tests for typical RF interference conditions.....	29
5.7.1	Simulator conditions	29
5.7.2	Navigation solution accuracy test.....	29
5.7.3	Re-acquisition test.....	30
Annex A	(normative) Typical IRNSS/NavIC interference environment.....	32
A.1	IRNSS/NavIC CW in-band and near-band interference environment.....	32
A.2	Band-limited noise-like interference	33
A.3	Pulsed interference	34
A.4	IRNSS/NavIC minimum antenna gain	35
Annex B	(normative) Alert management.....	36
Bibliography	37
Figure 1	– Logical interfaces of IRNSS/NavIC receiver	11
Figure A.1	– CW interference thresholds for IRNSS/NavIC L5 band receivers in steady state navigation	33
Figure A.2	– CW interference thresholds for IRNSS/NavIC S band receivers in steady state navigation	33
Figure A.3	– Effect of interference bandwidth on interference thresholds for IRNSS/NavIC receivers (for noise like interference)	34
Table 1	– Acquisition time limits.....	13
Table 2	– RAIM integrity status	17
Table 3	– Accuracy of COG	18
Table 4	– RF interference value	30
Table A.1	– CW interference thresholds for IRNSS/NavIC L5 band receivers in steady-state navigation	32
Table A.2	– CW interference thresholds for IRNSS/NavIC S band receivers in steady-state navigation	32
Table A.3	– Interference threshold for band-limited noise-like interference to IRNSS/NavIC receivers in steady-state navigation	34
Table A.4	– Interference thresholds for pulsed interference	35
Table A.5	– IRNSS/NavIC minimum antenna gain	35
Table B.1	– Required alerts and their classification.....	36

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT
AND SYSTEMS – GLOBAL NAVIGATION SATELLITE SYSTEMS (GNSS) –****Part 6: Navigation with Indian constellation (NavIC)/Indian regional
navigation satellite system (IRNSS) – Receiver equipment – Performance
requirements, methods of testing and required test results**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61108-6 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems. It is an International Standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
80/1055/FDIS	80/1058/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 61108 series, published under the general title *Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS)*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[IEC 61108-6:2023](https://standards.iteh.ai/catalog/standards/sist/e2397ccc-95c3-4271-a376-c62c03194f7a/iec-61108-6-2023)

<https://standards.iteh.ai/catalog/standards/sist/e2397ccc-95c3-4271-a376-c62c03194f7a/iec-61108-6-2023>

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – GLOBAL NAVIGATION SATELLITE SYSTEMS (GNSS) –

Part 6: Navigation with Indian constellation (NavIC)/Indian regional navigation satellite system (IRNSS) – Receiver equipment – Performance requirements, methods of testing and required test results

1 Scope

This part of IEC 61108 specifies the minimum performance requirements, methods of testing and required test results for the Indian regional navigation satellite system (IRNSS), also known as Navigation with Indian Constellation (NavIC), shipborne receiver equipment, based on IMO resolution MSC.449(99), which uses the signals from NavIC/IRNSS in order to determine position.

This document takes account of the general requirements given in IMO resolution A.694(17) and is associated with IEC 60945. When a requirement in this document is different from IEC 60945, the requirement in this document takes precedence. This document also takes into account, as appropriate, requirements for the presentation of navigation-related information on shipborne navigational displays given in IMO resolution MSC.191(79) and is associated with IEC 62288. This document further takes into account, as appropriate, requirements for bridge alert management given in IMO resolution MSC.302(87) and is associated with IEC 62923-1.

This document applies to navigation in ocean waters for the standard positioning service and harbour entrances, harbour approaches and coastal waters, as defined in IMO resolution A.1046(27) within IRNSS/NavIC coverage area as given in IMO resolution MSC 449(99).

All text of this document whose meaning is identical to that in IMO resolution MSC. 449(99) is printed in italics and the resolution and paragraph number indicated between brackets, i.e. "(M.449(99)/A1.2)".

The requirements in Clause 4 are cross-referenced to the tests in Clause 5 and vice versa.

NOTE 1 A description of the IRNSS standard positioning service can be found in the interface control documents which were officially released in 2017 in the public domain (see ISRO-IRNSS-ICD-SPS-1.1).

NOTE 2 The IRNSS constellation was renamed as "NavIC" (navigation with Indian constellation) in 2016.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61108-4, *Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS) – Part 4: Shipborne DGPS and DGLONASS maritime radio beacon receiver equipment – Performance requirements, methods of testing and required test results*

IEC 61108-5:2020, *Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS) – Part 5: BeiDou navigation satellite system (BDS) – Receiver equipment – Performance requirements, methods of testing and required test results*

IEC 61162-1, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners*

IEC 61162-2, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 2: Single talker and multiple listeners, high-speed transmission*

IEC 61162-450, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 450: Multiple talkers and multiple listeners – Ethernet interconnection*

IEC 62288, *Maritime navigation and radiocommunication equipment and systems – Presentation of navigation-related information on shipborne navigational displays – General requirements, methods of testing and required test results*

IEC 62923-1, *Maritime navigation and radiocommunication equipment and systems – Bridge alert management – Part 1: Operational and performance requirements, methods of testing and required test results*

IEC 62923-2, *Maritime navigation and radiocommunication equipment and systems – Bridge alert management – Part 2: Alert and cluster identifiers and other additional features*

IMO resolution A.694(17):1991, *General requirements for shipborne radio equipment forming part of the Global maritime distress and safety system (GMDSS) and for electronic navigational aids*

IMO resolution A.915(22), *Revised maritime policy and requirements for a future Global Navigation Satellite System (GNSS)*

IMO resolution A.1046(27), *Worldwide radio navigation system*

IMO resolution MSC.302(87), *Performance standards for bridge alert management*

IMO resolution MSC.449(99), *Performance Standards for Shipborne IRNSS Receiver Equipment*

ITU-R Recommendation M.823-3, *Technical characteristics of differential transmissions for global navigation satellite systems from maritime radio beacons in the frequency band 283.5-315 kHz in Region 1 and 285-325 kHz in Regions 2 and 3*

ISRO-IRNSS-ICD-SPS-1.1, *Navigation with Indian Constellation System – Signal in Space Interface Control Document for Standard Positioning Service V 1.1*, Aug 2017 [viewed 2022-11-11]. Available at https://www.isro.gov.in/media_isro/pdf/Publications/Vispdf/Pdf2017/irnss_sps_icd_version1.1-2017.pdf

RTCM 10402, *RTCM Recommended Standards for Differential GNSS (Global Navigation Satellite Systems) Service*

3 Terms, definitions and abbreviated terms

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

NOTE All definitions and abbreviations used are the same as those used in ISRO-IRNSS-ICD-SPS-1.1.

3.1 Terms and definitions

3.1.1 integrity

ability of the system to provide users with warnings within a specified time when the system should not be used for navigation

3.1.2 Indian regional navigation satellite system IRNSS

independent satellite navigation system developed and operated by India

Note 1 to entry: IRNSS can provide 3D position, velocity and time information for users within 1 500 km from the Indian geopolitical boundary.

Note 2 to entry: IRNSS is known as NavIC and the words are used interchangeably in this document.

3.1.3 IRNSS/NavIC time

time reference built and kept by IRNSS

Note 1 to entry: The IRNSS system time start epoch is 00:00 UT on Sunday August 22nd 1999 (midnight between August 21st and 22nd). At the start epoch, IRNSS system time is ahead of UTC by 13 leap seconds (i.e. IRNSS time, August 22nd 1999, 00:00:00 corresponds to UTC time August 21st 1999, 23:59:47).

3.2 Abbreviated terms

BAM	bridge alert management
CAM	central alert management
COG	course over ground
CW	continuous wave
DNavIC	differential navigation with Indian constellation
EUT	equipment under test
GNSS	global navigation satellite system
GPS	global positioning system
HAL	horizontal alert limit
HDOP	horizontal dilution of precision
HPL	horizontal protection limit
ICD	interface control document
MKD	minimum keyboard and display
NavIC	navigation with Indian constellation
NB	narrow band
NPLI	national physical laboratory of India

PDOP	position dilution of precision
PNT	position navigation and timing
RAIM	receiver autonomous integrity monitor
RF	radio frequency
RFCS	radio frequency constellation simulator
RFI	radio frequency interference
SOG	speed over ground
SPS	standard positioning service
UTC	universal time coordinated
WB	wide band

4 Minimum performance requirements

4.1 Object

(M.449(99)/A1.2) The IRNSS Standard Positioning Service (SPS) provides positioning, navigation and timing services, free of direct user charges. The IRNSS SPS receiver equipment should be capable of receiving and processing the IRNSS SPS signal. It should be capable of tracking all IRNSS satellites.

(M.449(99)/A1.3) Receiver equipment for the Indian Regional Satellite System (IRNSS) intended for navigational purposes on ships with maximum speeds not exceeding 70 knots shall, in addition to the general requirements contained in resolution A.694(17), comply with the following minimum performance requirements.

(M.449(99)/A1.4) This standard covers the basic requirements of position fixing, determination of course over ground (COG), speed over ground (SOG) and timing either for navigation purposes or as input to other functions. The standards do not cover other computational facilities which may be in the equipment nor cover the requirements for other systems that may take input from the IRNSS receiver.

This document contains the basic minimum performance requirements for use of IRNSS/NavIC standard positioning service (SPS) signals for navigational position fixing, including differential corrections, and, in addition, for the determination of speed and direction of the movement of the antenna over the ground.

Other computational activity, input/output activity or extra display functions which may be provided shall not degrade the performance of the equipment below the minimum performance requirements set out in this document.

The IRNSS/NavIC receiver equipment shall comply with:

- the provisions of IMO resolutions A.1046(27), MSC. 449(99), MSC.302(87) and A.694(17);
- the accuracy requirements of the SPS interface control document;
- tests in accordance with IEC 60945.

4.2 IRNSS/NavIC receiver equipment

4.2.1 Minimum facilities

(M.449(99)/A2.1) The term "IRNSS receiver equipment" as used in these performance standards includes all the components and units necessary for the system to properly perform its intended functions. The equipment shall include the following minimum facilities:

- a) *antenna capable of receiving IRNSS signals;*
- b) *IRNSS receiver and processor;*
- c) *means of accessing the computed latitude/longitude position;*
- d) *data control and interface; and*
- e) *position display and, if required, other forms of output.*

If the IRNSS/NavIC receiver forms part of an approved integrated navigation system (INS), requirements of c), d) and e) may be provided within the INS.

If the IRNSS/NavIC receiver forms part of an approved multi-system PNT, requirements of c), d) and e) may be provided within the multi-system PNT.

4.2.2 Configuration

The IRNSS/NavIC receiver equipment may be supplied in one of several configurations to provide the necessary position information. Examples are as follows:

- stand-alone receiver with means of accessing computed position via a keyboard with the positional information suitably displayed and with means to display alerts and acknowledge alerts via the keyboard;
- IRNSS/NavIC black box receiver fed with operational parameters from external devices/remote locations and feeding an integrated system with means of access to the computed position via an appropriate interface, and the positional information and alert management information available to at least one remote location. With this option, a separate user interface called as MKD shall be provided as a backup;
- as one of the position velocity and time (PVT) methods included in a multi-system PNT equipment based on IMO resolution MSC.401(95).

The above examples should not be implied as limiting the scope of future development.

4.2.3 Quality assurance

The equipment shall be designed, produced and documented by manufacturers complying with approved quality systems as applicable.

4.3 Performance of IRNSS/NavIC receiver equipment

4.3.1 General

(See 5.6.2)

(M.449(99)/A3.1) The IRNSS receiver equipment shall be capable of receiving and processing the IRNSS SPS positioning and velocity, and timing signals, and shall use the ionospheric model broadcast to the receiver by the constellation to generate ionospheric corrections.

A detailed description of the IRNSS/NavIC navigation signal characteristics is given in ISRO-IRNSS-ICD-SPS-1.1, Aug 2017.

(M.449(99)/A3.2) The IRNSS receiver equipment shall provide position information based upon WGS-84 and should be in accordance with international standards.

Means may be provided to transform the computed position based upon WGS-84 into data compatible with the datum of the navigational chart in use. Where this facility exists, the display shall indicate that co-ordinate conversion is being performed and shall identify the co-ordinate system in which the position is expressed.

(M.449(99)/A3.3) The IRNSS receiver equipment shall provide time referenced to universal time coordinated UTC (NPLI).

4.3.2 Equipment interfaces

(See 5.6.3)

(M.449(99)/A3.4) The IRNSS receiver equipment shall be provided with at least two outputs from which position information, UTC, course over ground (COG), speed over ground (SOG) and alarms can be supplied to other equipment. The output of position information shall be based on the WGS 84 datum and shall be in accordance with international standards. The output of UTC, course over ground (COG), speed over ground (SOG) and alarms shall be consistent with the requirements of M.449(99)/A3.16 and M.449(99)/A3.18.

(M.449(99)/A3.17) The IRNSS receiver equipment shall provide at least one normally closed contact, which shall indicate failure of the IRNSS receiver equipment.

(M.449(99)/A3.18). The IRNSS receiver equipment shall have a bidirectional interface to facilitate communication so that alarms can be transferred to external systems and so that audible alarms from the IRNSS receiver can be acknowledged from external systems; the interface shall comply with relevant international standards.

NOTE Alarms are read as alerts in M.449(99)/A3.4 and A3.18 for BAM compliance.

The physical interface shall be based on IEC 61162-1 or IEC 61162-2 or IEC 61162-450. Logical interfaces are shown in Figure 1, where required interfaces are indicated with solid lines and optional interfaces are indicated in dashed lines.




Figure 1 – Logical interfaces of IRNSS/NavIC receiver

IRNSS/NavIC receiver shall use talker ID "GI".

For reporting purposes, the following sentences shall be available in any combination:

- DTM – Datum reference (see IEC 61108-5);
- GBS – GNSS satellite fault detection (see IEC 61108-5);
- GFA – GNSS fix accuracy and integrity (see IEC 61108-5);
- GNS – GNSS fix data (see IEC 61108-5);
- RMC – Recommended minimum specific GNSS data;
- VTG – Course over ground and ground speed;
- ZDA – Time and date.