

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Radio frequency and coaxial cable assemblies –
Part 3-4: Detail specification for semi-flexible cable assemblies (Jumper) –
Frequency range up to 6 GHz, Type 50-141 semi-flexible coaxial cable**

**Cordons coaxiaux et cordons pour fréquences radioélectriques –
Partie 3-4: Spécification particulière relative aux cordons semi-flexibles (câble
de liaison), plage de fréquences jusqu'à 6 GHz, câble coaxial semi flexible
de type 50-141**



THIS PUBLICATION IS COPYRIGHT PROTECTED

Copyright © 2023 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC -

webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 300 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 19 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Radio frequency and coaxial cable assemblies –
Part 3-4: Detail specification for semi-flexible cable assemblies (Jumper) –
Frequency range up to 6 GHz, Type 50-141 semi-flexible coaxial cable**

**Cordons coaxiaux et cordons radioélectriques –
Partie 3-4: Spécification particulière relative aux cordons semi-flexibles (câble
de liaison), plage de fréquences jusqu'à 6 GHz, câble coaxial semi flexible
de type 50-141**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 33.120.01; 33.120.10

ISBN 978-2-8322-6538-3

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references	5
3 Terms and definitions	6
4 Detail specification	7
Annex A (informative) Identification and marking	12
A.1 Identification – Type name	12
A.2 Cable assemblies marking	12
Bibliography.....	13
Figure 1 – Length definition of cable assemblies.....	7
Figure 2 – Semi-flexible cable assemblies with type 50-141 semi-flexible coaxial cable	7
Table A.1 – The meaning of connector variants	12

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[IEC 60966-3-4:2023](https://standards.iteh.ai/catalog/standards/sist/69ebee3-7979-4327-9d57-e3620727bba8/iec-60966-3-4-2023)

<https://standards.iteh.ai/catalog/standards/sist/69ebee3-7979-4327-9d57-e3620727bba8/iec-60966-3-4-2023>

INTERNATIONAL ELECTROTECHNICAL COMMISSION

RADIO FREQUENCY AND COAXIAL CABLE ASSEMBLIES –**Part 3-4: Detail specification for semi-flexible cable assemblies (Jumper) –
Frequency range up to 6 GHz, Type 50-141 semi-flexible coaxial cable**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 60966-3-4 has been prepared by IEC technical committee 46: Cables, wires, waveguides, RF connectors, RF and microwave passive components and accessories. It is an International Standard.

The text of this International Standard is based on the following documents:

Draft	Report on voting
46/928/FDIS	46/932/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC 60966 series, published under the general title *Radio frequency and coaxial cable assemblies*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

ITEH STANDARD PREVIEW
(standards.iteh.ai)

[IEC 60966-3-4:2023](https://standards.iteh.ai/catalog/standards/sist/69ebeb3-7979-4327-9d57-e3620727bba8/iec-60966-3-4-2023)

<https://standards.iteh.ai/catalog/standards/sist/69ebeb3-7979-4327-9d57-e3620727bba8/iec-60966-3-4-2023>

RADIO FREQUENCY AND COAXIAL CABLE ASSEMBLIES –

Part 3-4: Detail specification for semi-flexible cable assemblies (Jumper) – Frequency range up to 6 GHz, Type 50-141 semi-flexible coaxial cable

1 Scope

This part of IEC 60966 is a detail specification that relates to semi-flexible cable assemblies composed of type 50-141 semi-flexible coaxial cables with polytetrafluoroethylene (PTFE) dielectric (IEC 61196-8-4) and connectors such as type 7-16 (IEC 61169-4), type 4,1-9,5 (IEC 61169-11), type S7-16 (IEC 61169-53), type 4,3-10 (IEC 61169-54). It gives subfamily detail requirements and severities which are to be applied.

These cable assemblies are mainly used in the field of mobile communication base station antenna system, terrestrial microwave communication and radar systems. The operating frequency is up to 6 000 MHz.

The qualification will be conducted in accordance with IEC 60966-3. Once one variant obtains the qualification approval, the other variant with the same cable and connection type can obtain the qualification approval by conducting tests whose results might depend on the variants.

Under capability approval, the qualification will be conducted on the relating CQCs (capability qualifying components) as defined in IEC 60966-3 and described in the CM (capability manual). Unless otherwise specified in the CM, only lot-by-lot tests from groups Ba and Eb will be conducted on delivered products, all other tests will be performed on CQCs as defined in IEC 60966-3 and described in the CM.

<https://standards.iec.ch/catalog/standards/sist/69ebee3-7979-4327-9d57-e3620727bba8/iec-60966-3-4-2023>

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-2-11, *Environmental testing – Part 2-11: Tests – Test Ka: Salt mist*

IEC 60966-1:2019, *Radio frequency and coaxial cable assemblies – Part 1: Generic specification – General requirements and test methods*

IEC 60966-3, *Radio frequency and coaxial cable assemblies – Part 3: Sectional specification for semi-flexible coaxial cable assemblies*

IEC 60966-3-1, *Radio frequency and coaxial cable assemblies – Part 3-1: Blank detail specification for semi-flexible coaxial cable assemblies*

IEC 61169-4, *Radio-frequency connectors – Part 4: RF coaxial connectors with inner diameter of outer conductor 16 mm (0,63 in) with screw lock – Characteristic impedance 50 Ω (type 7-16)*

IEC 61169-11, *Radio-frequency connectors – Part 11: Sectional specification for RF coaxial connectors with inner diameter of outer conductor 9,5 mm with threaded coupling – characteristic impedance 50 Ω (Type 4,1-9,5)*

IEC 61169-53, *Radio-frequency connectors – Part 53: Sectional specification for RF coaxial connectors with inner diameter of outer conductor 16 mm with screw lock – Characteristic impedance 50 Ω (Type S7-16)*

IEC 61169-54, *Radio frequency connectors – Part 54: Sectional specification for coaxial connectors with 10 mm inner diameter of outer conductor, nominal characteristic impedance 50 Ω , Series 4,3-10*

IEC 61196-8-4, *Coaxial communication cables – Part 8-4: Detail specification for 50-141 type semi-flexible cables with solid polytetrafluoroethylene (PTFE) insulation*

IEC 61726, *Cable assemblies, cables, connectors and passive microwave components – Screening attenuation measurement by the reverberation chamber method*

3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:




- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

(standards.iteh.ai)

[IEC 60966-3-4:2023](https://standards.iteh.ai/catalog/standards/sist/69ebee3-7979-4327-9d57-e3620727bba8/iec-60966-3-4-2023)

<https://standards.iteh.ai/catalog/standards/sist/69ebee3-7979-4327-9d57-e3620727bba8/iec-60966-3-4-2023>

4 Detail specification

RADIO FREQUENCY AND COAXIAL CABLE ASSEMBLIES – Part 3-4: Detail specification for semi-flexible cable assemblies (Jumper), frequency range up to 6 GHz, Type 50-141 semi-flexible coaxial cable		
[1] Prepared by: IEC TC 46		[2] Document No.: IEC 60966-3-4 Issue: First issue Date:
[3] Available from: IEC	[4] Generic specification: IEC 60966-1 Sectional specification: IEC 60966-3 Blank detail specification: IEC 60966-3-1	
[5] Additional references:		
Outline for semi-rigid coaxial cable assemblies NOTE Example diagram, see Figure 1 and Figure 2, manufacturer to insert actual diagram		
		
Figure 1 – Length definition of cable assemblies		
Figure 2 – Semi-flexible cable assemblies with type 50-141 semi-flexible coaxial cable		
[6] Maximum diameter of type 50-141 semi-flexible coaxial cable < 4,7 mm		
[7] Characteristic impedance: 50 Ω		[8] Frequency: up to 6 000 MHz
[9] Typical weight: Cable: 50 g/m Connector: Type 7-16: 120 g Type S7-16: 25 g Type 4.1-9.5: 85 g Type 4,3-10: 56 g		[10] Minimum inside radius: For static bending: 10 mm For dynamic bending: 40 mm
[11] Climatic category: 40/70/21		[12] Applicable test group: Ba, Eh, Eb, Ez, Ep, Ee, Et, Mn, Vv, Vc, Vt, Vf
[13] Connector reference number: Type (series), style, sex of the connector Reference no, type of the cable Marking method Marking text		IEC 61169-4 (type 7-16), IEC 61169-53 (type S7-16) IEC 61169-11 (type 4,1-9,5) IEC 61169-54 (type 4,3-10) Type 7-16, straight or right angled, male or female Type 4,1-9,5, straight or right angled, male or female Type S7-16, straight or right angled, male or female Type 4,3-10, straight or right angled, male or female IEC 61196-8-4, IEC-50-141 or equivalent (IEC 61196-8-4). Marking of the assembly shall be applied to the sheath of the cable. The marking shall consist at least of the IEC cable assembly type and IEC standard number. (See Clause A.2).
[14] Variants: See Clause A.1		[15] Page 1 of 7 pages

[16] Inspection values, ratings or characteristics	[17] IEC 60966-1: 2019 Subclause	[18] Value	[19] Remarks
Electrical			
Reflection properties (Return loss)	8.1	1) With straight connector ≥ 26,45 dB (DC to 3 000 MHz) ≥ 19,10 dB (> 3 000 MHz to 6 000 MHz) 2) With right angled connector ≥ 23,13 dB (DC to 3 000 MHz) ≥ 17,70 dB (> 3 000 MHz to 6 000 MHz)	
Uniformity of impedance	8.2	50 Ω ± 2 Ω	Rise time of pulse < 150 ps
Insertion loss	8.3	$\leq 0,01 \times a_f \times L + 2 \times 0,05 \sqrt{f}$ a_f : see IEC 61196-8-4, in dB/100 m L : see Figure 1, in m f : in GHz	a_f : see IEC 61196-8-4
Propagation time	8.5	(3,91 ns ± 0,05 ns)/m	
Stability of electrical length	8.6	$\leq 5^\circ$	DC to 6 GHz Mandrel radius: 40 mm Test method: 2 Bending test
Phase difference	8.7	$\leq 4^\circ$	2 GHz
Phase variation with temperature	8.8	$\leq 5^\circ/\text{GHz}$	Length of assemblies: 1 m Test temperature: -40 °C to 70 °C t : 30 min Cycles: 6
Screening effectiveness	8.9	1) ≤ -90 dB (screw thread) 2) ≤ -70 dB (type 4,3-10 quick lock)	According to IEC 61726 1 000 MHz to 6 000 MHz
Voltage proof	8.10	1,5 kV	AC, 1 min
Insulation resistance	8.11	≥ 5 000 MΩ	Test voltage: 500 V, DC 60 s ± 5 s
Inner and outer conductor continuity	8.12	Inner conductor and outer conductor shall be continuous	Test voltage ≤ 36 V DC
Power rating	8.13	≥ 65 W	Temperature: 40 °C DC to 6 000 MHz
Intermodulation level	8.14	≤ -155 dBc	Test power: 2×20 W Test frequency: 700 MHz, 900 MHz, 1 800 MHz, 2 100 MHz, 2 600 MHz

[16] Inspection values, ratings or characteristics	[17] IEC 60966-1: 2019 Subclause	[18] Value	[19] Remarks
Mechanical			
Tensile	9.1	1) Inner conductor and insulator positions shall be in accordance with interface dimensions 2) No visual evidence of the movement of the cable relative to the connector 3) Return loss shall meet 8.1	Force: 100 N Duration: 60 s Test: IEC 60966-1:2019, 8.1
Cable assembly crushing	9.4	1) Inner conductor and insulator positions shall be in accordance with interface dimensions 2) No visual evidence of the movement of the cable relative to the connector 3) Return loss shall meet 8.1	Force: 200 N Duration: 60 s Test: IEC 60966-1:2019, 8.1
Torque	9.5	1) Inner conductor and insulator positions shall be in accordance with interface dimensions 2) No visual damage in cable assembly 3) Return loss shall meet 8.1	≥ 5 Ncm Test: IEC 60966-1:2019, 8.1
Multiple bending	9.6	1) Inner conductor and insulator positions shall be in accordance with interface dimensions 2) No visual damage in cable assembly 3) Return loss shall meet 8.1	Cycles: 20
Environmental			
Vibration	10.2	1) No visual damage in cable assembly 2) No electrical interruptions exceeding 1 μs	98 m/s ² (10 g) 10 Hz to 2 000 Hz
Bumps	10.2	No visual damage in cable assembly	
Shock	10.2	1) No visual damage in cable assembly 2) No electrical interruptions exceeding 1 μs	147 m/s ² (15 g) Half-sine wave, 11 ms
Climatic sequence	10.3	1) No visual damage in cable assembly 2) Insertion loss shall meet 8.3 3) Voltage proof shall meet 8.10 4) Insulation resistance shall meet 8.11	Cycles: 1 (connectors un-mated) Tests: IEC 60966-1:2019, 7.2, 8.3, 8.10, 8.11
Damp heat, steady state	10.4	1) No visual damage in cable assembly 2) Insertion loss shall meet 8.3	Cycles: 1 Days: 21 (connectors un-mated) Tests: IEC 60966-1:2019, 7.2, 8.3
Rapid change of temperature	10.5	1) Inner conductor and insulator positions shall be in accordance with interface dimensions 2) No visual damage in cable assembly 3) Insertion loss shall meet 8.3 4) Voltage proof shall meet 8.10 5) Insulation resistance shall meet 8.11	Test temperature: $T_A = -55\text{ °C}$, $T_B = 125\text{ °C}$ $t: 4\text{ h}$ Cycles: 5 Tests: IEC 60966-1:2019, 7.2, 8.3, 8.10, 8.11

[16] Inspection values, ratings or characteristics	[17] IEC 60966-1: 2019 Subclause	[18] Value	[19] Remarks
Solvents and contaminating fluids	10.6	1) No visual damage in cable assembly 2) Insertion loss shall meet 8.3 3) Insulation resistance shall meet 8.11	Cycles: 5 (connectors un-mated) Tests: IEC 60966-1:2019, 7.2, 8.3, 8.11
Water immersion	10.7	1) Insertion loss shall meet 8.3 2) Insulation resistance shall meet 8.11	(connectors mated) Tests: IEC 60966-1:2019,8.3, 8.11
Salt mist and sulphur dioxide	10.8	1) No visual damage in cable assembly 2) Insertion loss shall meet 8.3 3) Insulation resistance shall meet 8.11	According to IEC 60068-2-11 Duration of spraying: 96 h
Dust tests	10.9	1) No visual damage in cable assembly 2) Insertion loss shall meet 8.3	Cycles: 5 Tests: IEC 60966- 1:2019, 7.2, 8.3
Flammability	10.10	1) The cable shall not continue to burn for more than 15 s after removal from the flame 2) During the test, burning particles shall be not detached from the cable	

iTeh STANDARDS (standards.iteh.ai)

[IEC 60966-3-4:2023](https://standards.iteh.ai/catalog/standards/sist/69ebee3-7979-4327-9d57-e3620727bba8/iec-60966-3-4-2023)

<https://standards.iteh.ai/catalog/standards/sist/69ebee3-7979-4327-9d57-e3620727bba8/iec-60966-3-4-2023>