

Edition 2.0 2022-11 COMMENTED VERSION

INTERNATIONAL STANDARD



Digital addressable lighting interface – Part 103: General requirements – Control devices

Document Preview

IEC 62386-103:2022

ttps://standards.iteh.ai/catalog/standards/iec/af5b6c6d-2e7b-42c9-9dcf-2479eeab1bda/iec-62386-103-2022





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2022 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Tel.: +41 22 919 02 11

IEC Secretariat 3, rue de Varembé CH-1211 Geneva 20

info@iec.ch www.iec.ch

Switzerland

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublishedStay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.





Edition 2.0 2022-11 COMMENTED VERSION

INTERNATIONAL STANDARD



Digital addressable lighting interface – 100 200 S

Part 103: General requirements – Control devices

Document Preview

IEC 62386-103:2022

https://standards.iteh.ai/catalog/standards/iec/af5h6c6d-2e7h-42c9-9dcf-2479eeah1hda/iec-62386-103-2022

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.140.50; 29.140.99

ISBN 978-2-8322-6104-0

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

F	OREWOR	D	8
IN	ITRODUC	TION	11
1	Scope		13
2	Norma	tive references	13
3	Terms	and definitions	13
4		ıl	
7		eneral	
5		ersion numberersion numbereal specification	
		·	
6		se Bus power supply	
7	Transn	nission protocol structure	17
	7.1 G	eneral	17
	7.2 2	4-bit forward frame encoding	
	7.2.1	Frame format for instructions and queries	
	7.2.2	Frame format for event messages	
8	•		
9	Method	of operation	20
	9.1 G	eneral	20
	9.2 D	evice featuresS	20
	9.3 A	pplication controller	20
	9.3.1	General Ceneral Cenera	20
	9.3.2	Single-master application controller	21
	9.3.3	Multi-master application controller	21
	9.4 Ir	nput device	6232622
	9.5 Ir	nstances of input devices	22
	9.5.1	General	22
	9.5.2	Instance number	22
	9.5.3	Instance type	22
	9.5.4	Instance features	22
	9.5.5	Instance groups	23
	9.6 C	ommands excluding event messages	23
	9.6.1	General	23
	9.6.2	Device commands	24
	9.6.3	Instance commands	24
	9.6.4	Feature commands	24
		vent messages	
	9.7.1	Response to event messages	25
	9.7.2	Device power cycle event	
	9.7.3	Input notification event	
	9.7.4	Event message filter	
		nput signal-and input, measured value and "inputValue"	
	9.8.1	General	
	9.8.2	Input resolution	
	9.8.3	Getting the input value	
	9.8.4	Notification of changes	28

9.9	Sys	tem failure	28
9.10	Оре	erating a control device	28
9.1	0.1	Enable/disable the application controller	28
9.1	0.2	Application controller always active	28
9.1	0.3	Enable/disable event messages	29
9.1	0.4	Quiescent mode	29
9.1	0.5	Modes of operation	
9.11	Mer	mory banks	
9.1		General	
9.1	1.2	Memory map	
9.1	1.3	Selecting a memory bank location	
9.1	1.4	Protectable memory locations	
9.1	1.5	Memory bank reading	
9.1	_	Memory bank writing	
9.1		Memory bank 0	
9.1		Memory bank 1 (optional)	
9.1		Manufacturer-specific memory banks	
	1.10	Reserved memory banks	
9.12		set	
9.1		Reset operation	
_	2.2	Reset memory bank operation	
9.13		ver on behaviour	
9.1		Power on	
_	3.2	Power cycle notification	
9.14	-	prity useememex.lew.	
9.1		General	
9.1		Priority of input notifications	
_		igning short addresses	
9.1		General	
9.1	_	Random address allocation	
9.1	_	Identification of a device	
9.16		eption handling	
9.17		rice capabilities and status information	
9.1		Device capabilities	
9.1		Device status	
9.1		Instance status	
9.18	_	n-volatile memory	
9.19		ance types and configuration	
9.20		rent bus unit configuration	
		on of variables	
		of commands	
11.1		neral	
11.2		erview sheets	
11.3		ent messages	
11.		INPUT NOTIFICATION (device/instance, event)	
	3.2	POWER NOTIFICATION (device)	
11.4		rice control instructions	
11.		General	
4.4	1 2		E 1

11.4.3	RESET POWER CYCLE SEEN	55
11.5 Dev	rice configuration instructions	55
11.5.1	General	55
11.5.2	RESET	55
11.5.3	RESET MEMORY BANK (DTR0)	56
11.5.4	SET SHORT ADDRESS (DTR0)	56
11.5.5	ENABLE WRITE MEMORY	
11.5.6	ENABLE APPLICATION CONTROLLER	56
11.5.7	DISABLE APPLICATION CONTROLLER	56
11.5.8	SET OPERATING MODE (DTR0)	56
11.5.9	ADD TO DEVICE GROUPS 0-15 (DTR2:DTR1)	
11.5.10	ADD TO DEVICE GROUPS 16-31 (DTR2:DTR1)	
11.5.11	REMOVE FROM DEVICE GROUPS 0-15 (DTR2:DTR1)	
11.5.12	REMOVE FROM DEVICE GROUPS 16-31 (DTR2:DTR1)	
11.5.13	START QUIESCENT MODE	
11.5.14	STOP QUIESCENT MODE	
11.5.15	ENABLE POWER CYCLE NOTIFICATION	
11.5.16	DISABLE POWER CYCLE NOTIFICATION	
11.5.17 —	SAVE PERSISTENT VARIABLES	
	SET EVENT PRIORITY (DTR0)	
	rice queriesII.Ah. Stamdards	
11.6.1	QUERY DEVICE CAPABILITIES	58
11.6.2		
11.6.3	QUERY DEVICE STATUS	
11.6.4	QUERY APPLICATION CONTROLLER ERROR	
11.6.5	QUERY INPUT DEVICE ERROR	
11.6.6	QUERY MISSING SHORT ADDRESS	
ttps://stan11.6.7.teh	QUERY VERSION NUMBER	
11.6.8	QUERY CONTENT DTR0	
11.6.9	QUERY NUMBER OF INSTANCES	
11.6.10	QUERY CONTENT DTR1	
11.6.11	QUERY CONTENT DTR2	
11.6.12	QUERY RANDOM ADDRESS (H)	
11.6.13	QUERY RANDOM ADDRESS (M)	
11.6.14	QUERY RANDOM ADDRESS (L)	
11.6.15	READ MEMORY LOCATION (DTR1, DTR0)	
11.6.16	QUERY APPLICATION CONTROLLER ENABLED	
11.6.17	QUERY OPERATING MODE	
11.6.18	QUERY MANUFACTURER SPECIFIC MODE	
11.6.19	QUERY QUIESCENT MODE	
11.6.20	QUERY DEVICE GROUPS 0-7	
11.6.21	QUERY DEVICE CROUPS 16 22	
11.6.22	QUERY DEVICE GROUPS 16-23QUERY DEVICE GROUPS 24-31	
11.6.23	QUERY DEVICE GROUPS 24-31QUERY POWER CYCLE NOTIFICATION	
11.6.24		
11.6.25	QUERY EXTENDED VERSION NUMBER(DTR0)	
11.6.26	QUERY RESET STATE	
11.6.27	QUERY APPLICATION CONTROLLER ALWAYS ACTIVE	
11.6.28	QUERY FEATURE TYPE	۱ ۵۰۰۰۰۰۰۰۰۰۰

44.0.00	OUEDVANEVE FEATURE TYPE	0.4
11.6.29	QUERY NEXT FEATURE TYPE	
11.6.30	QUERY EVENT PRIORITY	
	tance control instructions	
	tance configuration instructions	
11.8.1	General	
11.8.2	ENABLE INSTANCE	
11.8.3	DISABLE INSTANCE	
11.8.4	SET PRIMARY INSTANCE GROUP (DTR0)	
11.8.5	SET INSTANCE GROUP 1 (DTR0)	
11.8.6	SET INSTANCE GROUP 2 (DTR0)	
11.8.7	SET EVENT SCHEME (DTR0)	
11.8.8	SET EVENT PRIORITY (DTR0)	
11.8.9	SET EVENT FILTER (DTR2:DTR1:DTR0)	
11.8.10	SET INSTANCE TYPE (DTR0)	
11.8.11	SET INSTANCE CONFIGURATION (DTR0, DTR2:DTR1)	63
11.9 Ins	tance queries	64
11.9.1	General	64
11.9.2	QUERY INSTANCE TYPE	64
11.9.3	QUERY RESOLUTION	64
11.9.4	QUERY INSTANCE ERROR	
11.9.5	QUERY INSTANCE STATUS	64
11.9.6	QUERY INSTANCE ENABLED	
11.9.7	QUERY PRIMARY INSTANCE GROUP	64
11.9.8	QUERY INSTANCE GROUP 1	65
11.9.9	QUERY INSTANCE GROUP 2	65
11.9.10	QUERY EVENT SCHEME	65
11.9.11	QUERY INPUT VALUE:	65
11.9.12	QUERY INPUT VALUE LATCH	65
11.9.13	QUERY EVENT PRIORITY	65
11.9.14	QUERY FEATURE TYPE	65
11.9.15	QUERY NEXT FEATURE TYPE	66
11.9.16	QUERY EVENT FILTER 0-7	66
11.9.17	QUERY EVENT FILTER 8-15	66
11.9.18	QUERY EVENT FILTER 16-23	66
11.9.19	QUERY INSTANCE CONFIGURATION (DTR0)	66
11.9.20	QUERY AVAILABLE INSTANCE TYPES	67
11.10 Spe	ecial commands	67
11.10.1	General	
11.10.2	TERMINATE	67
11.10.3	INITIALISE (device)	67
11.10.4	RANDOMISE	
11.10.5	COMPARE	
11.10.6	WITHDRAW	
11.10.7	SEARCHADDRH (data)	
11.10.8	SEARCHADDRM (data)	
11.10.9	SEARCHADDRL (data)	
	PROGRAM SHORT ADDRESS (data)	
	VERIFY SHORT ADDRESS (data)	
	OUERY SHORT ADDRESS	

Table 15 – Control device capabilities	43
Table 16 – Control device status	44
Table 17 – Instance status	44
Table 18 – Current bus unit configuration	45
Table 19 – Declaration of device variables	46
Table 20 – Declaration of instance variables	47
Table 21 – Instance event messages	47
Table 22 – Device event messages	48
Table 23 – Standard commands	49
Table 24 – Special commands (implemented by both application controller and input device)	53
Table 25 – Device addressing with "INITIALISE (device)"	67
Table 24 – Unexpected outcome	
Table 25 Parameters for test sequence Check Factory Default 103	
Table 26 - Parameters for test sequence CheckFactoryDefault103PerLogicalUnit	
Table 27 Parameters for test sequence Transmitter bit timing	
Table 28 – Parameters for test sequence Maximum and minimum system voltage	
Table 29 Parameters for test sequence Transmitter voltages	
Table 30 – Parameters for test sequence Transmitter rising and falling edges	
Table 31 Parameters for test sequence Transmitter bit timing	
Table 32 - Parameters for test sequence Receiver frame timing	
Table 33 Parameters for test sequence Receiver start-up behavior	
Table 34 Parameters for test sequence Receiver bit timing	
Table 35 Parameters for test sequence extended receiver bit timing	
Table 36 Parameters for test sequence Receiver frame violation and recovering after frame size violation	
Table 37 – Parameters for test sequence Receiver frame timing	
Table 38 - Parameters for test sequence transmitter collision avoidance by priority	
Table 39 – Parameters for test sequence transmitter collision detection for truncated idle phase	
Table 40 Parameters for test sequence transmitter collision detection for extended active phase	
Table 41 Parameters for test sequence RESET instance groups	
Table 42 Parameters for test sequence Send twice timeout (device)	
Table 43 Parameters for test sequence Send twice timeout (instance)	
Table 44 Parameters for test sequence Commands in between (device)	
Table 45 Parameters for test sequence Commands in between	
Table 46 Parameters for test sequence SET SHORT ADDRESS	
Table 47 Parameters for test sequence Reset/Power-on values (device)	
Table 48 Parameters for test sequence Reset/Power-on values (instance)	
Table 49 Parameters for test sequence DTR0 / DTR1 / DTR2	
Table 50 Parameters for test sequence DTR1:DTR0 and DTR2:DTR1	
Table 51 Parameters for test sequence READ MEMORY LOCATION on Memory	
Devile 0	

Table 52 Parameters for test sequence READ MEMORY LOCATION on Memory Bank 1
Table 53 – Parameters for test sequence Memory bank writing
Table 54 Parameters for test sequence ENABLE WRITE MEMORY: writeEnableState
Table 55 - Parameters for test sequence ENABLE WRITE MEMORY: timeout / command in-between
Table 56 – Parameters for test sequence RESET MEMORY BANK: timeout / command in-between
Table 57 Parameters for test sequence RESET MEMORY BANK
Table 58 – Parameters for test sequence INITIALISE - device addressing
Table 59 Parameters for test sequence COMPARE
Table 60 – Parameters for test sequence WITHDRAW
Table 61 Parameters for test sequence PROGRAM SHORT ADDRESS
Table 62 - Parameters for test sequence VERIFY SHORT ADDRESS
Table 63 Parameters for test sequence QUERY SHORT ADDRESS
Table 64 – Parameters for test sequence IDENTIFY DEVICE
Table 65 Parameters for test sequence Addressing 2
Table 66 – Parameters for test sequence Reserved commands: standard device commands
Table 67 Parameters for test sequence Reserved instance commands (instance
type 0)

INTERNATIONAL ELECTROTECHNICAL COMMISSION

DIGITAL ADDRESSABLE LIGHTING INTERFACE -

Part 103: General requirements – Control devices

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This commented version (CMV) of the official standard IEC 62386-103:2022 edition 2.0 allows the user to identify the changes made to the previous IEC 62386-103:2014+ AMD1:2018 CSV edition 1.1. Furthermore, comments from IEC TC 34 experts are provided to explain the reasons of the most relevant changes, or to clarify any part of the content.

A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text. Experts' comments are identified by a blue-background number. Mouse over a number to display a pop-up note with the comment.

This publication contains the CMV and the official standard. The full list of comments is available at the end of the CMV.

IEC 62386-103 has been prepared by IEC technical committee 34: Lighting. It is an International Standard.

This second edition cancels and replaces the first edition published in 2014 and Amendment 1:2018. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) the scope has been updated;
- b) quiescent mode has been updated:
- c) non-volatile memory (NVM) save time has been added, and SAVE PERSISTENT VARIABLES command removed:
- d) memory bank 0 has been modified, and common memory bank requirements have been added:
- e) IDENTIFY DEVICE has been updated;
- f) version number has been changed;
- g) bus unit configuration has been added; and
- h) instance types and configuration have been added.

The text of this International Standard is based on the following documents:

Draft	Report on voting
34/946/FDIS	34/990/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

This Part 103 of IEC 62386 is intended to be used in conjunction with Part 101, which contains general requirements for the relevant product type (system), and with the appropriate Parts 3xx (particular requirements for control devices) containing clauses to supplement or modify the corresponding clauses in Part 101 and Part 103 in order to provide the relevant requirements for each type of product.

A list of all parts in the IEC 62386 series, published under the general title *Digital addressable lighting interface*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- · reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

iTeh Standards (https://standards.iteh.ai) Document Preview

IEC 62386-103:2022

https://standards.iteh.ai/catalog/standards/iec/af5b6c6d-2e7b-42c9-9dcf-2479eeab1bda/iec-62386-103-2022

INTRODUCTION

_ 12 _

IEC 62386 contains several parts, referred to as series. The IEC 62386 series specifies a bus system for control by digital signals of electronic lighting equipment. The IEC 62386-1xx series includes the basic specifications. Part 101 contains general requirements for system components, Part 102 extends this information with general requirements for control gear and Part 103 extends it further with general requirements for control devices. Part 104 and Part 105 can be applied to control gear or control devices. Part 104 gives requirements for wireless and alternative wired system components. Part 105 describes firmware transfer. Part 150 gives requirements for an auxiliary power supply which can be stand-alone, or built into control gear or control devices.

The IEC 62386-2xx series extends the general requirements for control gear with lamp specific extensions (mainly for backward compatibility with Edition 1 of IEC 62386) and with control gear specific features.

The IEC 62386-3xx series extends the general requirements for control devices with input device specific extensions describing the instance types as well as some common features that can be combined with multiple instance types.

This—first second edition of IEC 62386-103 is intended to be used in conjunction with IEC 62386-101:2014, IEC 62386-101:2014/AMD1:2018, IEC 62386-102:2014, IEC 62386-102:2014, IEC 62386-102:2014/AMD1:2018 and with the various parts that make up the IEC 62386-2xx series for control gear, together with the various parts that make up the IEC 62386-3xx series of particular requirements for control devices, and can be used together with IEC 62386-102 and with the various parts that make up the IEC 62386-2xx series for control gear. The division into separately published parts provides for ease of future amendments and revisions. Additional requirements will be added as and when a need for them is recognised.

The setup of the standards is graphically represented in Figure 1 below.

IEC 62386-103:2022

https://standards.iteh.ai/catalog/standards/iec/af5b6c6d-2e7b-42c9-9dcf-2479eeab1bda/iec-62386-103-2022