

Edition 4.0 2024-11

## INTERNATIONAL STANDARD

## NORME INTERNATIONALE

Residual current operated circuit-breakers without integral overcurrent protection for household and similar uses (RCCBs) – Part 1: General rules

Interrupteurs automatiques à courant différentiel résiduel sans dispositif de protection contre les surintensités incorporé pour usages domestiques et analogues (ID) –

Partie 1: Règles générales rds/iec/314d6e0a-2f68-4685-85b7-376bc6f61931/iec-61008-1-2024





### THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2024 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat Tel.: +41 22 919 02 11

3, rue de Varembé info@iec.ch CH-1211 Geneva 20 www.iec.ch

Switzerland

#### About the IFC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

#### **About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

#### IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

#### IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

#### IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

#### Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

#### A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

#### A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

#### Recherche de publications IEC -

#### webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

#### IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

#### Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

#### IEC Products & Services Portal - products.iec.ch

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications, symboles graphiques et le glossaire. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

#### Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 500 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 25 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.



Edition 4.0 2024-11

## INTERNATIONAL **STANDARD**

## **NORME** INTERNATIONALE

Residual current operated circuit-breakers without integral overcurrent protection for household and similar uses (RCCBs) -Part 1: General rules UDS://StandardS.lite

Interrupteurs automatiques à courant différentiel résiduel sans dispositif de protection contre les surintensités incorporé pour usages domestiques et analogues (ID) -Partie 1: Règles générales de l'icc/314d6e0a-2f68-4685-85b7-376bc6f61931/iec-61008-1-2024

**INTERNATIONAL ELECTROTECHNICAL** COMMISSION

COMMISSION **ELECTROTECHNIQUE INTERNATIONALE** 

ICS 29.120.50 ISBN 978-2-8327-0007-5

Warning! Make sure that you obtained this publication from an authorized distributor. Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

### CONTENTS

F	DREWORD		9
IN	TRODUCT	ON	11
1	Scope		12
2	Normativ	re references	13
3	Terms a	nd definitions	14
4		ation	
•		cording to the supply conditions	
	4.1.1	RCCB operating correctly on the occurrence of residual current	
	4.1.2	RCCB with 2 or 4 current paths operating correctly on the occurrence of residual current within the voltage range of 1,1 $U_{\rm e}$ and 85 V	
	4.1.3	RCCB according to 4.1.2 fitted with a functional earth (FE) and able to continue to provide protection when supplied from just one phase and	45
	4.4.4	FE	15
	4.1.4	RCCB with 3 current paths operating correctly on the occurrence of residual current within the voltage range of 1,1 $U_{\rm e}$ and 0,7 $U_{\rm e}$	15
	4.1.5	RCCB operating correctly on the occurrence of residual current within the voltage range 1,1 $U_{\rm e}$ and $U_{\rm X}$	16
	4.1.6	RCCB according to 4.1.5, however reclosing automatically after restoration of the supply voltage	16
	4.2 Acc	cording to the possibility of adjusting the residual operating current	
	4.2.1	RCCB with a single value of rated residual operating current	
	4.2.2	RCCB with multiple settings of residual operating current by fixed steps	16
	4.3 Acc	cording to their operation in response to the type of residual current	16
	4.3.1	RCCB of type AC	16
	4.3.2	RCCB of type A	16
	4.4 Acc	cording to time-delay (in the presence of a residual current)	00816-2024
	4.4.1	RCCB without time-delay: type for general use	16
	4.4.2	RCCB with time-delay: type S for selectivity	
	4.5 Acc	cording to the protection against external influences	16
	4.5.1	Enclosed-type RCCB (not requiring an appropriate enclosure)	
	4.5.2	Unenclosed-type RCCB (for use with an appropriate enclosure)	
		cording to the method of mounting	
	4.6.1	Surface-type RCCB	
	4.6.2	Flush-type RCCB	
	4.6.3	Panel board type RCCB, also referred to as distribution board type	
	4.7 Acc 4.7.1	cording to the method of connection  RCCB for which the electrical connections are not associated with the	16
	4.7.2	mechanical mounting  RCCB for which the electrical connections are associated with the	16
		mechanical mounting	16
		cording to the type of terminals	
	4.8.1	RCCB with screw-type terminals for copper conductors	
	4.8.2	RCCB with screwless type terminals for copper conductors	
	4.8.3	RCCB with flat quick-connect terminals for copper conductors	
	4.8.4	RCCB with screw-type terminals for aluminium conductors	
		cording to the number of poles and current paths	
	4.9.1	Single-pole RCCB with two current paths	17
	д U Э	IWO-DOIR RUUS	1/

	4.9.3	Tillee-pole RCCB	17
	4.9.4	Three-pole RCCB with four current paths	17
	4.9.5	Four-pole RCCB	
5		eristics of RCCBs	
		mmary of characteristics	
		ted quantities and other characteristics	
	5.2.1	Rated voltages	
	5.2.2	Rated current (I <sub>n</sub> )	18
	5.2.3	Rated frequency	
	5.2.4	Rated making and breaking capacity $(I_{m})$	18
	5.2.5	Rated residual operating current ( $I_{\Delta n}$ )	18
	5.2.6	Rated residual non-operating current ( $I_{\Delta no}$ )	18
	5.2.7	Rated residual making and breaking capacity ( $I_{\Delta m}$ )	18
	5.2.8	Rated conditional short-circuit current (Inc)	
	5.2.9	Rated conditional residual short-circuit current ( $I_{\Lambda c}$ )	
	5.2.10	Operating characteristics in response to the type of residual current	
	5.2.11	RCCB type S	
		andard and preferred values	
	5.3.1	Standard values of rated operational voltage ( $U_{\mathbf{e}}$ )	
	5.3.2	Preferred values of rated current (I <sub>n</sub> )	19
	5.3.3	Standard values of rated residual operating current ( $I_{\Delta n}$ )	
	5.3.4	Standard value of residual non-operating current $(I_{\Delta no})$	
	5.3.5	Preferred values of rated frequency	
	5.3.6	Standard values of rated impulse withstand voltage ( $U_{imp}$ )	
	5.3.7 standards.ite	Standard limit values of break time and non-actuating time for RCCB of type AC and A	
	5.3.8	Standard minimum value of non-operating overcurrent in the case of a load through an RCCB with two current paths	20
	5.3.9	Standard minimum value of the non-operating overcurrent in the case of a single-phase load through a three-pole or four-pole RCCB	
	5.3.10	Standard minimum value of the rated making and breaking capacity $(I_{\mathbf{m}})$	20
	5.3.11	Standard minimum value of the rated residual making and breaking capacity ( $I_{\Delta m}$ )	20
	5.3.12	Standard and preferred values of the rated conditional short-circuit current $(I_{ m nc})$	21
	5.3.13	Standard values of the rated conditional residual short-circuit current $(I_{\Delta {f c}})$	21
6	Marking	and other product information	21
7	Standard	d conditions for operation in service and for installation	22
	7.1 Sta	andard conditions	22
	7.2 Co	nditions of installation	22
	7.3 Po	llution degree	22
8	Requirer	ments for construction and operation	23
	8.1 Me	chanical design	23
	8.1.1	General	23
	8.1.2	Mechanism	23

	8.1.3	Clearances, creepage distances and solid insulation	25
	8.1.4	Screws, current-carrying parts and connections	26
	8.1.5	Terminals for external conductors	27
	8.2	Protection against electric shock	28
	8.3	Dielectric properties and isolating capability	29
	8.4	Temperature-rise	29
	8.4.1	General	29
	8.4.2	Temperature-rise limits	29
	8.4.3	Ambient air temperature	30
	8.5	Operating characteristics	30
	8.5.1	General	30
	8.5.2	Operation in response to the type of residual current	30
	8.5.3	Operation in presence of a residual current equal to or greater than $I_{\Delta n}$	30
	8.6	Mechanical and electrical endurance	30
	8.7	Performance at short-circuit currents	31
	8.8	Resistance to mechanical shock and impact	31
	8.9	Resistance to heat	
	8.10	Resistance to abnormal heat and to fire	
	8.11	Test device	
	8.12	Void	32
	8.13	Behaviour of RCCBs in the event of overcurrent in the main circuit	32
	8.14	Behaviour of RCCBs in the event of current surges caused by impulse voltages	32
	8.15	Reliability	
	8.16	Electromagnetic compatibility (EMC)	32
	8.17	Resistance to temporary overvoltages (TOV)	
9			
ittps://s		General::::::dox/standards/iec/3.14.46e0a.2f68.4685.85b7-376bc6f61931/iec.61	
	9.2	Test conditions	
	9.3	Test of indelibility of marking	
	9.4	Test of reliability of screws, current-carrying parts and connections	
	9.5	Test of reliability of screw-type terminals for external copper conductors	
	9.6	Verification of protection against electric shock	
	9.7	Test of dielectric properties	
	9.7.1	Resistance to humidity	
	9.7.2	•	
	9.7.2		
	9.7.4	_	
	9.7.5	•	
	9.7.6		40
		high DC voltages due to insulation measurements	
	9.7.7	·	
	9.8	Test of temperature-rise	
	9.8.1	Ambient air temperature	
	9.8.2	'	
	9.8.3	•	
	9.8.4	•	
	9.9	Verification of the operating characteristics	
	9.10	Verification of mechanical and electrical endurance	43

9.1	0.1	General test conditions	43
9.1	0.2	Test procedure	43
9.1	0.3	Condition of the RCCB after test	44
9.11	Ve	erification of the behaviour of the RCCB under short-circuit conditions	44
9.1	1.1	List of the short-circuit tests	44
9.1	1.2	Short-circuit tests	44
9.12	Ve	erification of resistance to mechanical shock and impact	51
9.1	2.1	Mechanical shock	51
9.1	2.2	Mechanical impact	51
9.13	Te	est of resistance to heat	54
9.1	3.1	Test on complete RCCB	54
9.1	3.2	Ball pressure test	
9.14		est of resistance to abnormal heat and to fire	
9.15		erification of the trip-free mechanism	56
9.16		erification of the operation of the test device at the limits of rated	50
0.47	•	erational voltage	
9.17		oid	57
9.18		erification of the behaviour of RCCBs in the event of overcurrent in the ain circuit	57
9.19		erification of the behaviour of RCCBs in the event of current surges caused	01
0.10		impulse voltages	57
9.1	9.1	Current surge test for all RCCBs (0,5 µs/100 kHz ring wave test)	57
9.1	9.2	Verification of the behaviour at surge currents up to 3 000 A (8/20 μs	
		surge current test)	58
9.20	Ve	erification of reliability	
9.2	0.1	Climatic test	
9.2	0.2	Test with temperature of 40 °C	
9.21		erification of withstand against ageing	
ttps://st9.22	rdsEb	ectromagnetic compatibility (EMC)268468585h7376hc6f61931/iec61	61
9.23		est of resistance to rusting	61
9.24		erification of the behaviour of the RCCB under temporary overvoltage	00
0.0	(1 24.1	OV) conditions	
_	.4. i .4.2	General TOV test for all RCCBs	
_	.4.2 !4.3	Additional tests for RCCBs with a terminal intended to be connected to	02
9.2	.4.3	the PE	62
9.2	4.4	Verification after the tests	
Annex A	A (no	rmative) Test sequence and number of samples to be submitted for	
		purposés	93
Annex E	3 (no	rmative) Determination of clearances and creepage distances	94
B.1	Ge	eneral	94
B.2	Or	ientation and location of a creepage distance	94
B.3	Cr	eepage distances where more than one material is used	94
B.4	Cr	eepage distances split by floating conductive part	94
B.5	М	easurement of creepage distances and clearances	94
		rmative) Arrangement for the detection of the emission of ionized gases	99
Annex [	) (no	rmative) Routine tests	102
D.1	-	eneral	
		inning test	102

D.3	Dielectric strength test	102
D.4	Performance of the test device	102
Annex E (	informative) Methods for determination of short-circuit power-factor	103
E.1	General	103
E.2	Method I – Determination from DC components	103
E.3	Method II – Determination with pilot generator	
•	informative/normative) Void	
Annex G (	informative/normative) Void	106
Annex H (	informative) Examples of terminal designs	107
Annex I (i	nformative) Correspondence between ISO and AWG copper conductors	110
Annex J (i	nformative) Follow-up testing program for RCCBs	111
J.1	General	111
J.2	Follow-up testing program	111
J.2.1	General	111
J.2.2	- 7 1 31 3	
J.2.3	1 31 3	
J.2.4	Sampling procedure	
	informative) SCPDs for short-circuit tests	
K.1	Introductory remark	
K.2	Silver wires	
K.3	Other means	
K.4		
Bibliograp	Document Preview	1 17
Figure 1	- Standard test finger	7.1
	- Void	
	Void ai/catalog/standards/iec/314d6e0a-2f68-4685-85b7-376bc6f61931/iec	
· ·		
· ·	- Void	75
	Typical diagram for all short circuit tests except for the verification of the in IT systems	76
	Typical diagram for the verification of the suitability in IT systems	
_		
	- Detail of impedances $Z$ , $Z_{ extstyle 1}$ and $Z_{ extstyle 2}$	
_	- Mechanical shock test apparatus	
Figure 9 –	- Mechanical impact test apparatus	79
Figure 10	- Striking element for pendulum impact test apparatus	80
Figure 11	- Mounting support for sample for mechanical impact test	81
	– Example of mounting an unenclosed or flush-type RCCB for mechanical	82
	– Example of mounting of panel mounting type RCCB for the mechanical	83
Figure 14	- Application of force for mechanical test of rail mounted RCCB	84
Figure 15	- Ball-pressure test apparatus	84
_	- Current ring wave 0,5 μs/100 kHz	
_	Test circuit for the ring wave test on RCCBs	
_	-	
1 14410 10	- Surge current impulse 8/20 us	86
•	- Surge current impulse 8/20 µs	86 86

Figure 20 – Stabilizing period for reliability test	87
Figure 21 – Reliability test cycle	88
Figure 22 – Void	88
Figure 23 – Example of records for short-circuit tests	89
Figure 24 – Test circuit for the verification of the behaviour under temporary overvoltage (TOV) conditions for RCCBs with a terminal intended to be connected to the PE	90
Figure 25 – Test apparatus for the verification of the minimum $I^2t$ and $I_{p}$ values to be	
withstood by the RCCB	91
Figure 26 – Void	91
Figure 27 – Diagrammatic representation for glow-wire test	92
Figure B.1 – Measuring creepage distances and clearances: Example 1	95
Figure B.2 – Measuring creepage distances and clearances: Example 2	95
Figure B.3 – Measuring creepage distances and clearances: Example 3	95
Figure B.4 – Measuring creepage distances and clearances: Example 4	96
Figure B.5 – Measuring creepage distances and clearances: Example 5	96
Figure B.6 – Measuring creepage distances and clearances: Example 6	96
Figure B.7 – Measuring creepage distances and clearances: Example 7	97
Figure B.8 – Measuring creepage distances and clearances: Example 8	97
Figure B.9 – Measuring creepage distances and clearances: Example 9	97
Figure B.10 – Measuring creepage distances and clearances: Example 10	98
Figure B.11 – Measuring creepage distances and clearances: Example 11	98
Figure C.1 – Example of test arrangement	100
Figure C.2 – Grid	101
Figure C.3 – Grid circuit	101
Figure H.1 – Examples of pillar terminals	107
Figure H.2 – Examples of screw terminals and stud terminals	108
Figure H.3 – Examples of saddle terminals	109
Figure H.4 – Examples of lug terminals	109
Table 1 – Marking	63
Table 2 – Void	64
Table 3 – Void	64
Table 4 – Void	64
Table 5 – Void	
Table 6 – Void	64
Table 7 – Void	64
Table 8 – Void	64
Table 9 – Void	64
Table 10 – Void	64
Table 11 – Standard limit values of break time and non-actuating time for alternating	
residual currents (RMS values) for type AC and A	64

Table 13 – Void	65
Table 14 – Tripping current limits	65
Table 15 – Void	65
Table 16 – Void	65
Table 17 – Void	65
Table 18 – Void	65
Table 19 – Rated impulse withstand voltage as a function of the nominal vo	
Table 20 – Minimum clearances and creepage distances	66
Table 21 – Test voltage of auxiliary circuits	68
Table 22 – Test voltage for verification of rated impulse withstand voltage	68
Table 23 – Test voltage for verifying the suitability for isolation, with referent impulse withstand voltage of the RCCB and the altitude where the test is ca	
Table 24 – Connectable cross-sections of copper conductors for screw-type	terminals69
Table 25 – Test copper conductors corresponding to the rated currents	69
Table 26 – Screw thread diameters and applied torques	69
Table 27 – Pulling forces	70
Table 28 – Temperature-rise values	70
Table 29 – Power factor ranges of the test circuit	70
Table 30 – Withstand values and duration of temporary overvoltages	70
Table 31 – Void	71
Table 32 – Void	71
Table 33 – Void	71
Table 34 – Void	71
Table 35 – Tests to be made to verify the behaviour of RCCBs under short-conditions	circuit 61931/iec-61008 <mark>71</mark> -20
Table 36 – Minimum values of $I^2t$ and $I_{p}$	71
Table 37 – Void	
Table 38 – Void	
Table 39 – Void	
Table 40 – Void	
Table 41 – Void	
Table 42 – Void	
Table 43 – Void	
Table 44 – Void	
Table 45 – Void	
Table 46 – Standard values of rated operational voltage	
Table 47 – Values of influencing quantities	
Table J.1 – Test sequences during follow-up inspections	
Table J.2 – Number of samples to be tested	
Table K.1 – Indication of silver wire diameters as a function of rated current	
short-circuit currents	

#### INTERNATIONAL ELECTROTECHNICAL COMMISSION

# RESIDUAL CURRENT OPERATED CIRCUIT-BREAKERS WITHOUT INTEGRAL OVERCURRENT PROTECTION FOR HOUSEHOLD AND SIMILAR USES (RCCBS) –

#### Part 1: General rules

#### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication. 67-376bc6f61931/iec-61008-1-2024
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61008-1 has been prepared by subcommittee 23E: Circuit-breakers and similar equipment for household use, of IEC technical committee 23: Electrical accessories. It is an International Standard.

This fourth edition cancels and replaces the third edition published in 2010, Amendment 1:2012 and Amendment 2:2013. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) harmonization of all clauses between the IEC 61008, IEC 61009 and IEC 60755 series using blocks and modules approach;

- b) harmonization of all tables and figures between the IEC 61008, IEC 61009 and IEC 60755 series:
- c) terms and definitions are now referred to IEC 62873-2;
- d) modification of 4.1 for classification according to supply conditions;
- e) new subclauses 8.17 and 9.24 for requirements and tests for the resistance to temporary overvoltages (TOV);
- f) improvement of 9.8 for test of dielectric properties;
- g) tests for screwless, flat-quick terminals and aluminium conductors are now referred to the IEC 62873-3 series.

The text of this International Standard is based on the following documents:

Draft	Report on voting
23E/1368/FDIS	23E/1385/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This International Standard is to be used in conjunction with the relevant product standard, either IEC 61008-2-1:2024 or IEC 61008-2-2:2024. The chosen standard, IEC 61008-2-1:2024 or IEC 61008-2-2:2024, shall be used consistently throughout the standard.

In order to maintain the same structure throughout the IEC 61008 and IEC 61009 series, some elements that are not applicable to the particular device within the scope of this document are labelled void.

In this document, the following print types are used:

- https://stacompliance statements: in italic type; 14d6e0a-2f68-4685-85b7-376bc6f61931/iec-61008-1-2024
  - other statements: in normal type.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at <a href="https://www.iec.ch/members\_experts/refdocs">www.iec.ch/members\_experts/refdocs</a>. The main document types developed by IEC are described in greater detail at <a href="https://www.iec.ch/publications">www.iec.ch/publications</a>.

A list of all parts in the IEC 61008 series, published under the general title *Residual current* operated circuit-breakers without integral overcurrent protection for household and similar uses (RCCBs), can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- · withdrawn, or
- revised.

#### INTRODUCTION

The purpose of this document is to harmonize as far as practicable all rules and requirements of a general nature applicable to RCCBs in order to obtain uniformity of requirements and tests and to avoid the need for testing to different standards.

All those parts which can be considered as general have therefore been gathered in this document, e.g. temperature-rise, dielectric properties, etc.

For each type of RCCB, only two main documents are used to determine all requirements and tests:

- 1) this document;
- 2) the relevant product standard covering RCCBs:
  - IEC 61008-2-1, Residual current operated circuit-breakers without integral overcurrent protection for household and similar uses (RCCBs) – Part 2-1: RCCBs according to classification 4.1.1; or
  - IEC 61008-2-2, Residual current operated circuit-breakers without integral overcurrent protection for household and similar uses (RCCBs) – Part 2-2: RCCBs according to classification 4.1.2, 4.1.3, 4.1.4, 4.1.5 and 4.1.6

For Type F and Type B RCCBs, IEC 62423 applies in addition to the IEC 61008 series.

iTeh Standards (https://standards.iteh.ai) Document Preview

IEC 61008-1:2024

https://standards.iteh.ai/catalog/standards/iec/314d6e0a-2f68-4685-85b7-376bc6f61931/iec-61008-1-2024

# RESIDUAL CURRENT OPERATED CIRCUIT-BREAKERS WITHOUT INTEGRAL OVERCURRENT PROTECTION FOR HOUSEHOLD AND SIMILAR USES (RCCBS) –

Part 1: General rules

#### 1 Scope

This document gives general requirements and tests for residual current operated circuit-breakers without integral overcurrent protection for household and similar uses (hereafter referred to as RCCBs), for rated operational voltages not exceeding 440 V AC, with rated frequencies of 50 Hz, 60 Hz or 50/60 Hz and rated currents not exceeding 125 A, intended principally for protection against shock hazard.

RCCBs are intended to provide fault protection (previously referred to as protection against indirect contact), the exposed conductive parts of the installation being connected to an appropriate earth electrode. They are also intended to be used to provide protection against fire hazards due to a persistent earth fault current.

RCCBs having a rated residual operating current not exceeding 30 mA are used for fault protection and additional protection in the case of failure of the protective provisions against electric shock.

This document applies to RCCBs performing simultaneously the functions of detection of the residual current, of comparison of the value of this current with the residual operating value and of opening of the protected circuit when the residual current exceeds this value.

- NOTE 1 The requirements for RCCBs are in line with the group safety publication IEC 60755.
- NOTE 2 RCCBs of type AC and type A are covered by the IEC 61008 series. RCCBs of type F and type B are covered by IEC 62423 in conjunction with the IEC 61008 series.
- NOTE 3 Installation and selection rules for RCCBs are given in the IEC 60364 series.
- NOTE 4 Installation and application rules of RCCBs in ZA is given in SANS 10142-1.

RCCBs are intended to be operated by ordinary or uninstructed persons and designed not to require maintenance.

The requirements of this document apply for standard conditions (see 7.1). Additional requirements can be necessary for RCCBs used in locations which have severe environmental conditions. RCCBs within the scope of this document are intended for use in an environment with pollution degree 2 (see 7.3).

- NOTE 5 For environments with higher pollution degrees, enclosures giving the appropriate degree of protection can be used.
- NOTE 6 For RCCBs having a degree of protection higher than IP20, special constructions can be required.

RCCBs are suitable for isolation.

Special precautions (e.g. surge protective devices) can be necessary when excessive overvoltages are likely to occur on the supply side (for example in the case of supply through overhead lines, see IEC 60364-4-44 and IEC 60364-5-53).

RCCBs, with the exception of those with an uninterrupted neutral, are suitable for use in IT systems.