



Designation: F2359 – 04 (Reapproved 2019)

Standard Test Method for Determining Color of a Membrane Switch Backlit with Diffuse Light Source¹

This standard is issued under the fixed designation F2359; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method covers procedures for determining the luminous color of a backlit membrane switch. As written, it applies to a fully assembled switch. For specific purposes, it can be applied to partially assembled switches, with the understanding that the results pertain only to the partial assembly and will be modified as the further assembly proceeds.

1.2 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.4 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Terminology

2.1 Definitions:

2.1.1 *graphic overlay*—a graphically illustrated layer, often attached to the top side of the switch assembly for protection, cosmetic purposes, or to indicate the location and function of the switch keys.

2.1.2 *illumination layer*—a layer in the construction of a membrane switch, which may or may not be a physically distinct layer which contains or supports the source of illumination for the switch. Examples are a flexible layer containing light emitting diodes (LEDs), often either the top or bottom

layer of the switch, or a flexible layer of electroluminescent (EL) material, often a distinct and separate layer added at assembly.

2.1.3 *membrane switch*—a momentary switching device, in which at least one contact is on, or made of, a flexible substrate.

2.1.4 *UUT*—unit under test.

3. Significance and Use

3.1 Illumination of a switch or of certain features of a switch often has a functional purpose and must meet specification to satisfy the functional requirements of the switch.

3.2 Illumination of the switch can be affected by variations in the quality and design of the overlay and its application.

3.3 This test method addresses only the optical and visual appearance of the switch and not its electrical function.

3.4 This test method is non-destructive.

3.5 If this test method is applied to the entire switch assembly, the results can be applied to the whole device. However, it may be sufficient and practical to apply the test either to a subassembly only, or to the illumination only, in which case the results apply to that layer only and the net effect on the fully assembled device must be extrapolated.

4. Interferences

4.1 Tests on incomplete assemblies give results appropriately to that state of assembly. Specifically, later application of a graphic overlay may alter the results.

4.2 Failure to fill the sampling aperture of the colorimeter will bias the results in a way which is not necessarily predictable and for which compensation cannot be made.

4.3 Since every light source changes characteristics as it ages, it must be recognized that the results apply to a particular interval in the lifetime of the system. Characterization of the aging properties may be addressed in a separate test method.

4.4 *Perpendicularity*—Since the angular distribution of emitted light can be altered by any material through which it passes, it is important that photometer be held perpendicular to the area to be sampled.

¹ This test method is under the jurisdiction of ASTM Committee F01 on Electronics and is the direct responsibility of Subcommittee F01.18 on Printed Electronics.

Current edition approved Dec. 1, 2019. Published December 2019. Originally approved in 2004. Last previous edition approved in 2011 as F2359 – 04 (2011). DOI: 10.1520/F2359-04R19.