



Edition 3.0 2023-03 REDLINE VERSION

INTERNATIONAL STANDARD



Lightning protection system components (LPSC) – Part 1: Requirements for connection components

Document Preview

IEC 62561-1:2023

https://standards.iteh.ai/catalog/standards/iec/c9364a5c-835f-47e9-a302-68b60dbe11a3/iec-62561-1-2023





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2023 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Tel.: +41 22 919 02 11 info@iec.ch www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.







Edition 3.0 2023-03 REDLINE VERSION

INTERNATIONAL STANDARD



Lightning protection system components (LPSC) – Part 1: Requirements for connection components

Document Preview

IEC 62561-1:2023

https://standards.iteh.ai/catalog/standards/iec/c9364a5c-835f-47e9-a302-68b60dbe11a3/iec-62561-1-2023

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.020; 91.120.40

ISBN 978-2-8322-6744-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FC	OREWO	RD	4
INTRODUCTION			6
1	Scop	e	7
2	Norm	native references	
- 3	Term	is and definitions	7
1	4 Classification		
4	Class		
	4.1	According to the ability to withstand lightning current	
	4.2	According to the installation location	
	4.3	According to the mechanical behaviour of connection components	
Б	4.4 Bogu	According to whether or not a connection is permanent	
5	Requ		
	5.1		
	5.2	Documentation and installation instructions	
	5.3	Marking	
	5.3.1	Content of marking	
	5.3.2	Durability and legibility	
	5.4	Lightning current carrying capability	
	5.5	Static mechanical stress withstand capability	
	5.6	Permanent connection	
	5.7		
	5.8	Dismantling of test joints	13
	5.8	Damage to conductors and metal installations	
	5.9	Reliable connection	
	5.10	LEC 62561-1:2023	
nttps://	5.9 sta n daro	Expansion piece Is.iteh.ai/catalog/standards/iec/c9364a5c-8351-47e9-a302-68b60dbe11a3/iec	
10	lest	5	
	6.1	General test conditions	
	6.2	Documentation and installation instructions	14
	6.2.1	General test conditions	
	6.2.2	Acceptance criteria	
	6.3	Marking test	
	6.3.1	General test conditions	
	6.3.2	Acceptance criteria	
	6.4	Preparation of the specimen	
	6.5	Conditioning ⁴ and ageing	21
	6.3.1	Connection components not embedded in concrete	·····
	6.3.2	Connection components embedded in concrete	
	6.6	Electrical test	
	6.6.1	General test conditions	
	6.6.2	Acceptance criteria	
_	6.7	Static mechanical withstand-capability test	
7	Elect	romagnetic compatibility (EMC)	24
8	Struc	sture and content of the test report	24
	8.1	General	24
	8.2	Report identification	25
	8.3	Specimen description	25

8.4	Conductor	25
8.5	Standards and references	25
8.6	Test procedure	26
8.7	Testing equipment description	26
8.8	Measuring instruments description	26
8.9	Results and parameters recorded	26
8.10	Statement of pass or fail	26
Annex A	normative) Summary of the requirements and corresponding tests	27
Annex B LPSC	informative) Typical connection-configurations arrangements for various	28
Annex C	(normative) Flowchart of tests for connection components	29
Annex D	(normative) Conditioning and ageing for connection components	30
D.1	General	30
D.2	Salt mist treatment	30
D.3	Humid sulphurous atmosphere treatment	30
D.4	Ammonia atmosphere treatment	30
Annex E	normative) Reduced test procedures	31
Bibliograp	ohy	32
Figure 1 - Figure 2 - Figure 3 -	- Basic arrangement of specimen with cross-connection component - Basic arrangement of specimen with parallel connection component - Basic arrangement of specimen with bridging component	16 17
Figure 3 - compone	- Basic arrangement of specimen with expansion piece or bridging	19
Figure 4 -	- Basic arrangement of specimen with equipotential bonding bar	20
Figure 5 - rods	- Basic arrangement of specimen with clamped connection of reinforcing	2002
Figure 6 - connectio	- Basic arrangement of specimen with welded,brazed or exothermic ns of reinforcing rods	21
Figure 7 - compone	- Basic arrangement for contact measurement of expansion piece or bridging	22
Figure 8 -	- Examples of sequence of loosening of bolts and screws	23
Figure B.	1 – Typical arrangements for various LPSC	28
Figure C.	1 – Flowchart of tests for connection components	29
Table 1 –	Lightning impulse current (<i>I</i> _{imp}) parameters	22
Table A.1	- Requirements and corresponding tests	27
Table E.1 IEC 6256	 Reduced test procedures for connection components complying with 1-1:2017 or IEC 62561-1:2012 	31

INTERNATIONAL ELECTROTECHNICAL COMMISSION

_ 4 _

LIGHTNING PROTECTION SYSTEM COMPONENTS (LPSC) -

Part 1: Requirements for connection components

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
 - 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
 - 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition IEC 62561-1:2017. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

IEC 62561-1 has been prepared by IEC technical committee 81: Lightning protection. It is an International Standard.

This third edition cancels and replaces the second edition published in 2017. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) definitions of connection types mentioned in the scope have been added;
- b) location classification has been expanded in detail;
- c) the document has been updated in line with the new edition of ISO 22479:2019 on humid sulphurous atmosphere treatment;
- d) a new normative Annex E for reduced test procedures has been introduced.

The text of this International Standard is based on the following documents:

Draft	Report on voting
81/721/FDIS	81/724/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

EC 62561-1:2023

A list of all parts in the IEC 62561 series, published under the general title *Lightning protection system components (LPSC),* can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This part of IEC 62561 deals with the requirements and tests for lightning protection system components (LPSC) used for the installation of a lightning protection system (LPS) designed and implemented according to the IEC 62305 series.

iTeh Standards (https://standards.iteh.ai) Document Preview

IEC 62561-1:2023

https://standards.iteh.ai/catalog/standards/iec/c9364a5c-835f-47e9-a302-68b60dbe11a3/iec-62561-1-2023

LIGHTNING PROTECTION SYSTEM COMPONENTS (LPSC) -

Part 1: Requirements for connection components

1 Scope

This part of IEC 62561 specifies the requirements and tests for metallic connection components that form part of a lightning protection system (LPS). Typically, these can be connectors, clamps, bonding and bridging components, expansion pieces and test joints.

For the purposes of this document the following connection types are considered as connection components: exothermic, brazing, welding, clamping, crimping, seaming, screwing or bolting.

Testing of components for an explosive atmosphere is not covered by this document.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-2-52:19962017, Environmental testing – Part 2-52: Tests – Test Kb: Salt mist, cyclic (sodium chloride solution)

IEC 62561-2, Lightning protection system components (LPSC) – Part 2: Requirements for conductors and earth electrodes

ISO 6957:1988, Copper alloys – Ammonia test for stress corrosion resistance

ISO 6988:1985, Metallic and other non-organic coatings – Sulphur dioxide test with general condensation of moisture

ISO 22479:2019, Corrosion of metals and alloys – Sulfur dioxide test in a humid atmosphere (fixed gas method)

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1

connection component

part of an external LPS which is used for the connection of conductors to each other or to metallic metal installations

Note 1 to entry: connection components include connectors, clamps, bridging components, expansion pieces and test joints.

EXAMPLE Examples of connection components are given in Clause 1.

3.2

metal installation

extended metal items in the structure to be protected which may can form a path for lightning current

EXAMPLE Pipes, staircases, elevator guide rails, ventilation, heating and air conditioning ducts, and interconnected reinforcing steel.

3.3

conductor

element intended to carry electric current

Note 1 to entry: A metal installation is not intended to carry electrical current.

[SOURCE: IEC 60050-151:2001, 151-12-05, modified – The notes have been replaced with a new Note 1 to entry.]

3.4

bridging component

connection component for the connection of metal installations

3.5

expansion piece

connection component designed to compensate for changes in length in conductors and/or metal installations or both caused by temperature changes

Document Preview

3.6

connector

connection component to interconnect two or more conductors

ttps://standards.iteh.ai/catalog/standards/iec/c9364a5c-835f-47e9-a302-68b60dbe11a3/iec-62561-1-2023

3.7 clamp

connection component for the connection of conductors to metal installations

3.8

pipe clamp

clamp for the connection of conductors to metal pipes

3.9

test joint

joint connection component designed to facilitate electrical testing and measurement of LPS components

3.10

connection range

minimum to maximum range for which a specific connection component is designed to be used

3.11

bonding technique for joining one object to another

[SOURCE: IEC 60050-523:2018, 523-06-01, modified – The example has been deleted.]

3.12

bonding bar

connection component such as a metal bar on which metal installations, external conductive parts, electric power and telecommunication lines and other cables can be connected to an LPS

3.13

type test

test-required to be made before supplying a type of material covered by IEC 62561-1 on a general commercial basis, in order to demonstrate satisfactory performance characteristics to meet the intended application

Note 1 to entry: These tests are of such a nature that, after they have been made, they need not be repeated unless changes are made to the accessory materials, design or type of manufacturing process which might change the performance characteristics.

3.14

permanent connection

connection that cannot or is not intended to be dismantled

3.15

non-permanent connection

connection that can or is intended to be dismantled

3.16

exothermic connection

welding process that employs molten metal to permanently join the conductors

Note 1 to entry: The electrical connection suitability and electrical durability of the exothermic connection is tested using a lightning current test.

3.17

brazed connection

metal-joining process in which two or more metal-items are joined together by melting and http flowing a filler metal into the joint s/jec/c9364a5c-835[-47e9-a302-68b60dbe11a3/jec-6256]-1-2023

Note 1 to entry: The electrical connection suitability and electrical durability of the brazed connection is tested using a lightning current test.

3.18

welded connection

fabrication process that joins materials, usually metals

Note 1 to entry: The electrical connection suitability and electrical durability of the welded connection is tested using a lightning current test.

3.19

force-locked connection

connection between two metal parts which does not allow any relative movement due to thermal expansion and to environmental load, for example snow, ice, wind

EXAMPLE Connection by means of crimping, clamping, bolting or screwing.

Note 1 to entry: The electrical connection suitability and electrical durability of the force-locked connection is tested using a lightning current test.

3.20 form-locked connection

connection between two metal parts which allows a small relative movement of metal parts due to thermal expansion and to environmental load, for example snow, ice, wind

EXAMPLE Connection by means of seaming, overlapping and zipping, locked overlapping or hooking.

Note 1 to entry: The electrical connection suitability and electrical durability of the form-locked connection is tested using a lightning current test.

3.21

clamped connection

force-locked connection, which can usually be disassembled, between two components

Note 1 to entry: The electrical connection suitability and electrical durability of the clamped connection is tested using a lightning current test.

3.22

crimped connection

connection method of permanently attaching a termination to a conductor by pressure deformation or by reshaping the barrel around the conductor to establish good electrical and mechanical connection

Note 1 to entry: Crimping as a means of achieving a connection between two conductors may not always require an additional component to achieve the final connection.

Note 2 to entry: The electrical connection suitability and electrical durability of the crimped connection is tested using a lightning current test.

[SOURCE: IEC 60050-581:2008, 581-23-10, modified – The term "crimping" has been replaced with "crimped connection", in the definition "method" has been replaced with "connection method" and the notes to entry have been added.]

3.23

seamed connection

iTeh Standards

form-locked connection created by bending of the edges of two adjacent metal sheets bringing them into intimate contact in a way that they cannot be separated by natural action

Note 1 to entry: The electrical connection suitability and electrical durability of the seamed connection is tested using a lightning current test.

3.24

screwed connection

IEC 62561-1:2023

force-locked connection, which can be disassembled, between two components which have threads of their own and can be bolted directly

Note 1 to entry: The electrical connection suitability and electrical durability of the screwed connection is tested using a lightning current test.

3.25

bolted connection

force-locked connection, which can be disassembled, between two components which can be bolted indirectly by means of third components (bolts and nuts)

Note 1 to entry: The electrical connection suitability and electrical durability of the bolted connection is tested using a lightning current test.

3.26

stranded conductor

conductor consisting of a number of individual wires or strands all or some of which generally have helical form

Note 1 to entry: The cross-section of a stranded conductor can be circular or otherwise shaped.

Note 2 to entry: The term "strand" is also used to designate a single wire.

[SOURCE: IEC 60050-461:2008, 461-01-07]

3.27

rope lay conductor

conductor composed of a central core surrounded by one or more layers of helically laid groups of wires

3.28

smooth weave stranded conductor

conductor constructed of multi-strand soft drawn wire, interwoven in a basket weave configuration so as to avoid fraying in application

4 Classification

4.1 According to the ability to withstand lightning current

- a) class H for heavy duty;
- b) class N for normal duty.

The selection of classes H-and or N should be performed by the manufacturer in accordance with the test parameters identified in Table 1.

4.2 According to the installation location

a) general use;

- a) outdoors;
- b) indoors;
- c) buried in ground; http://ctg
- d) embedded in concrete;
- e) embedded in materials with thermal insulation. Preview

The manufacturer's declaration of installation location shall determine whether it is necessary to carry out the conditioning and ageing test as identified in 6.5.

tps://standards.iteh.ai/catalog/standards/iec/c9364a5c-835f-47e9-a302-68b60dbe11a3/iec-62561-1-2023

4.3 According to the mechanical behaviour of connection components

- a) intended to withstand a static mechanical-load stress;
- b) not intended to withstand a static mechanical-load stress.

The manufacturer's declaration of ability to withstand a static mechanical load shall determine the need or otherwise whether it is necessary to carry out the static mechanical test as identified in 6.7.

4.4 According to whether or not a connection is permanent

- a) permanent connection such as exothermic process, brazing, welding, crimping, seaming;
- b) non-permanent connection such as screwing or bolting.

5 Requirements

5.1 General

Connection components shall be designed in such a manner that, when they are installed in accordance with the manufacturer's instructions, their performance shall be reliable, stable and safe to persons and surrounding equipment.

NOTE A summary of the requirements and their corresponding tests is given in Annex A.

5.2 Documentation and installation instructions

The manufacturer of the connection component shall provide adequate instructions in their literature to ensure that the installer of the connection component can select and install the components in a suitable and safe manner, containing at least the following information:

a) the classification of the component;

b) the recommended tightening torque;

- a) classification and lightning current capability (I_{imp}) ;
- b) classification according to the installation location;
- c) classification according to the mechanical behaviour;
- d) classification according to whether or not the connection is permanent;
- e) the range of conductor sizes and materials;
- f) the connection configuration;
- g) assembly instructions for permanent or non-permanent connection components (e.g. whether special tools are necessary, tightening torque, etc.).

Compliance is checked by inspection in accordance with 6.2.

5.3 Marking

5.3.1 Content of marking iTeh Standards

The connection components shall be marked at least with the following:

- a) the manufacturer's or responsible vendor's name or trademark;
- b) identifying symbol (picture, product number, etc.);
- c) classification, i.e. class N or H;
- d) classification according to the installation location.

http Compliance is checked by review in accordance with 6.3.1, a).02-68b60dbe11a3/iec-62561-1-2023

Where this proves to be impractical the marking in accordance with b), c) and d) may be given on the smallest packing unit label or on the accompanying documentation.

NOTE 1 Marking can be applied for example by moulding, pressing, engraving, printing and environmental stress adhesive labels.

NOTE 2 Marking can be applied by water slide transfers only for components classified as indoors.

5.3.2 Durability and legibility

The marking shall be durable and legible.

NOTE Marking can be applied for example by moulding, pressing, engraving, printing adhesive labels or water slide transfers.

Compliance is checked by test in accordance with 6.3.1 b).

5.4 Lightning current carrying capability

Connection components shall have sufficient lightning current carrying capability.

Compliance is checked in accordance with 6.6 following the manufacturer's declaration for the class (H or N) of the connection components in accordance with 4.1.