



Designation: **C1529 – 06a (Reapproved 2011) C1529 – 19**

Standard Specification for Quicklime, Hydrated Lime, and Limestone for Environmental Uses¹

This standard is issued under the fixed designation C1529; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This specification covers lime and limestone products and by-product alkaline materials suitable for environmental uses as shown in **Table 1**.

1.2 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.3 The buyer shall designate the use, as listed in **Table 1**, and may specify one or more of the type designations listed below **Table 1**.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory requirements/limitations prior to use.*

1.5 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*²

C25 Test Methods for Chemical Analysis of Limestone, Quicklime, and Hydrated Lime

E50/C50/C50M Practice for Sampling, Sample Preparation, Packaging, and Marking of Lime and Limestone Products

C51 Terminology Relating to Lime and Limestone (as used by the Industry)

C110 Test Methods for Physical Testing of Quicklime, Hydrated Lime, and Limestone

C400 Test Methods for Quicklime and Hydrated Lime for Neutralization of Waste Acid

D6249 Guide for Alkaline Stabilization of Wastewater Treatment Plant Residuals

3. Terminology

3.1 *By-product alkaline materials*—By-product lime (such as lime kiln dust) or other secondary materials (such as high-lime fly ash) that contain adequate amounts and types of calcium and/or magnesium oxides or hydroxides to meet the physical and chemical requirements in this specification. It is advised that the specific compositions, physical properties, performance characteristics, and anticipated variabilities of such materials be evaluated for the service intended.

3.1 *Definitions:*

3.1.1 For definitions of terms relating to this specification, refer to Terminology **C51**.

4. Chemical Composition and Physical Properties

4.1 The requirements for quicklime, hydrated lime, and limestone for the designated end uses are as shown in **Table 1**, and are on the basis of the weight of sample taken at the place of manufacture.

¹ This specification is under the jurisdiction of ASTM Committee **C07** on Lime and Limestone and is the direct responsibility of Subcommittee **C07.02** on Specifications and Guidelines.

Current edition approved June 1, 2011; Dec. 1, 2019. Published July 2011/December 2019. Originally approved in 2002. Last previous edition approved in 2006/2011 as **C1529 – 06a/C1529 – 06a** (2011). DOI: 10.1520/C1529-06AR11; 10.1520/C1529-19.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

*A Summary of Changes section appears at the end of this standard