

# INTERNATIONAL STANDARD



**Cooking fume extractors – Methods for measuring performance**

(standards.iteh.ai)

IEC 61591:2023

<https://standards.iteh.ai/catalog/standards/sist/1acd5f26-09b7-46c3-a392-5663457941dd/iec-61591-2023>



**THIS PUBLICATION IS COPYRIGHT PROTECTED**  
**Copyright © 2023 IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

**About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

**About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

**IEC publications search - [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)**

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

**IEC Products & Services Portal - [products.iec.ch](http://products.iec.ch)**

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

**IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)**

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

**Electropedia - [www.electropedia.org](http://www.electropedia.org)**

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

**IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)**

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

[IEC 61591-2023](https://standards.iteh.ai/catalog/standards/sist/1acd5f26-09b7-46c3-a392-5663457941dd/iec-61591-2023)

<https://standards.iteh.ai/catalog/standards/sist/1acd5f26-09b7-46c3-a392-5663457941dd/iec-61591-2023>



IEC 61591

Edition 3.0 2023-03  
COMMENTED VERSION

# INTERNATIONAL STANDARD



**Cooking fume extractors – Methods for measuring performance**  
(standards.iteh.ai)

[IEC 61591:2023](https://standards.iteh.ai/catalog/standards/sist/1acd5f26-09b7-46c3-a392-5663457941dd/iec-61591-2023)

<https://standards.iteh.ai/catalog/standards/sist/1acd5f26-09b7-46c3-a392-5663457941dd/iec-61591-2023>

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

ICS 97.040.20

ISBN 978-2-8322-6733-2

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD .....	4
1 Scope .....	7
2 Normative references .....	7
3 Terms and definitions .....	8
4 Classification .....	11
5 List of measurements .....	11
6 General conditions for measurements .....	11
6.1 Test room .....	11
6.2 Installation and positioning .....	12
6.3 Electricity supply .....	12
6.4 Filters .....	13
6.5 Fan control .....	13
6.6 Instrumentation and measurements .....	13
7 Dimensions and mass .....	14
7.1 Overall dimensions .....	14
7.2 Distance between cooking fume extractor and cooking appliance .....	14
7.3 Mass .....	14
8 Power measurement of low -power modes .....	14
8.1 Purpose and combination of appliances .....	14
8.2 Measurement .....	15
8.2.1 Principles .....	15
8.2.2 Determination of power consumption in off mode .....	16
8.2.3 Determination of power consumption in standby mode .....	16
8.2.4 Determination of consumption in standby mode in condition of networked standby .....	16
9 Airborne acoustical noise .....	16
10 Volumetric airflow .....	17
10.1 Purpose and test set up .....	17
<del>10.2 Measuring setup .....</del>	<del>19</del>
10.2 Measurement of the volumetric airflow .....	19
10.3 Calculation of the volumetric airflow .....	22
<del>10.4 Calculation of the fluid dynamic efficiency (<math>FDE_{hood}</math>) .....</del>	<del>23</del>
11 Fluid dynamic efficiency .....	23
11.1 Purpose .....	23
11.2 Determining the working points .....	23
11.3 Calculation of the fluid dynamic efficiency (FDE) .....	25
11.3.1 Conversion to reference air density .....	25
11.3.2 Calculating the corrected working points $WP_{C_s,j}$ .....	26
11.3.3 Calculating the fluid dynamic efficiency (FDE) .....	27
12 Effectiveness of the lighting system .....	28
12.1 Purpose .....	28
12.2 Measurement .....	28
12.3 Assessment .....	29

13	Odour reduction .....	29
13.1	Purpose .....	29
13.2	Measuring setup .....	29
13.3	Measurement .....	31
13.4	Calculation of the odour reduction factor .....	31
14	Grease absorption.....	32
14.1	Purpose .....	32
14.2	Measuring setup .....	32
14.3	Preparation .....	37
14.3.1	Determining the mass .....	37
14.3.2	Warm-up period.....	38
14.3.3	Determining the working point <i>WP</i> .....	38
14.4	Measurement .....	38
14.5	Assessment.....	38
	Annex A (informative) Assumption for the parameter <i>b</i> (see Table 3) .....	40
	Annex B (normative) Low power mode measurements .....	41
	Bibliography.....	42
	List of comments.....	43
	Figure 1 – Measurement of airflow .....	18
	<del>Figure 2 – Example working point of a cooking fume extractor in extraction mode .....</del>	<del>.....</del>
	<del>Figure 3 – Example diagram of the best efficiency point (BEP) .....</del>	<del>.....</del>
	Figure 2 – 9 working points of a cooking fume extractor in extraction mode (example).....	24
	Figure 3 – Measurement points for assessing the effectiveness of the lighting system.....	29
	Figure 4 – Example of a test room .....	30
	Figure 5 – Chamber for the grease absorption of a range hood or a microwave hood combination .....	34
	Figure 6 – Chamber for the grease absorption of a down-draft system .....	36
	Figure 7 – Cookware used for measuring the grease absorption .....	37
	Figure A.1 – Typical ducting .....	40
	Table 1 – Instruments.....	13
	Table 2 – Measurements .....	14
	Table 3 – Parameters for the calculation of resistance curves – .....	19
	Table 4 – Relevant measurement points for assessing the effectiveness of the lighting system.....	28
	Table B.1 – Step by step instruction for measuring low power modes.....	41

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**COOKING FUME EXTRACTORS –  
METHODS FOR MEASURING PERFORMANCE**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

**This commented version (CMV) of the official standard IEC 61591:2023 edition 3.0 allows the user to identify the changes made to the previous IEC 61591:2019 edition 2.0. Furthermore, comments from IEC SC 59K experts are provided to explain the reasons of the most relevant changes, or to clarify any part of the content.**

**A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text. Experts' comments are identified by a blue-background number. Mouse over a number to display a pop-up note with the comment.**

**This publication contains the CMV and the official standard. The full list of comments is available at the end of the CMV.**

IEC 61591 has been prepared by subcommittee 59K: Performance of household and similar electrical cooking appliances, of IEC technical committee 59: Performance of household and similar electrical appliances. It is an International Standard.

This third edition cancels and replaces the second edition published in 2019. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) new definition of **working point**, see 3.19;
- b) new definition for **lowest setting** and **automatic setting**, see 3.17 and 3.18;
- c) revised requirements for installation and positioning, see 6.2;
- d) added a normative reference ISO 5801 for the specification of the pressure compensation chamber, see Clause 10;
- e) separate clauses for determining the volumetric airflow and fluid dynamic efficiency, see Clauses 10 and 11;
- f) new approach for determining the fluid dynamic efficiency ("9-point calculation");
- g) new definitions, new clause and new Annex B regarding the measurement of low-power modes;
- h) new Annex A: assumption for the parameter *b*.

The text of this International Standard is based on the following documents:

Draft	Report on voting
59K/352/CDV	59K/361/RVC

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at [www.iec.ch/members\\_experts/refdocs](http://www.iec.ch/members_experts/refdocs). The main document types developed by IEC are described in greater detail at [www.iec.ch/publications](http://www.iec.ch/publications).

In this standard, the following print types are used:

- terms listed in Clause 3: **Arial bold**.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](http://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

[IEC 61591:2023](#)

<https://standards.iteh.ai/catalog/standards/sist/1acd5f26-09b7-46c3-a392-5663457941dd/iec-61591-2023>



# COOKING FUME EXTRACTORS – METHODS FOR MEASURING PERFORMANCE

## 1 Scope

This document applies to **cooking fume extractors** incorporating a fan for the **recirculation** or **extraction mode** situated in a household kitchen.

It can also be used for **cooking fume extractors** where the fan is mounted separately from the appliance, but controlled by the appliance when the fan is defined in the technical documentation (e.g. name plate data) and instructions for installation.

This document deals also with **down-draft systems** arranged beside, behind or under the cooking appliance.

This document defines the main performance characteristics of these appliances, which are of interest to the user, and specifies methods for measuring these characteristics.

This document does not specify a classification or ranking for performance.

NOTE 1 This document does not deal with safety requirements that are in accordance with IEC 60335-1 and IEC 60335-2-31.

NOTE 2 **Cooking fume extractors** without fans operated by a central ventilation system are covered in EN 13141-3.

## 2 Normative references

[IEC 61591:2023](https://standards.iteh.ai/catalog/standards/sist/1acd5f26-09b7-46c3-a392-5663457941dd/iec-61591-2023)

[https://standards.iteh.ai/catalog/standards/sist/1acd5f26-09b7-46c3-a392-5663457941dd/iec-](https://standards.iteh.ai/catalog/standards/sist/1acd5f26-09b7-46c3-a392-5663457941dd/iec-61591-2023)

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60584-1, *Thermocouples – Part 1: EMF specifications and tolerances*

IEC 60704-2-13, *Household and similar electrical appliances – Test code for the determination of airborne acoustical noise – Part 2-13: Particular requirements for range hoods and other cooking fume extractors*

IEC 60751, *Industrial platinum resistance thermometers and platinum temperature sensors*

IEC 62301:2011, *Household electrical appliances – Measurement of standby power*

IEC 63474:—<sup>1</sup>, *Electrical and electronic household and office equipment – Measurement of networked standby power consumption of edge equipment*

ISO 5167-1, *Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full – Part 1: General principles and requirements*

ISO 5167-2, *Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full – Part 2: Orifice plates*

---

<sup>1</sup> Under preparation. Stage at the time of development: IEC CDV 63474:2022.

ISO 5167-3, *Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full – Part 3: Nozzles and Venturi nozzles*

ISO 5167-4, *Measurement of fluid flow by means of pressure differential devices inserted in circular cross-section conduits running full – Part 4: Venturi tubes*

ISO 5801:2017, *Fans – Performance testing using standardized airways*

ISO 80000-1:2009, *Quantities and units – Part 1: General*

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

#### 3.1

##### **active mode**

mode in which the appliance is connected to a mains power source, has been activated, and is performing any of the intended functions

EXAMPLE Intended functions are running the fan or operating the lighting system.

Note 1 to entry: Associated activities include displaying information, software download, sensor controlled automatic mode and communication with the hob.

#### 3.2

##### **cooking fume extractor**

##### **CFE**

appliance with fan and filter intended to collect and treat cooking fumes, which can be operated in **recirculation mode** or **extraction mode**

#### 3.3

##### **range hood**

**cooking fume extractor** installed over a cooking appliance

##### 3.3.1

##### **wall range hood**

**range hood** mounted to the wall

##### 3.3.2

##### **island range hood**

**range hood** mounted to the ceiling

##### 3.3.3

##### **ceiling range hood**

**range hood** integrated onto or into the ceiling

##### 3.3.4

##### **built-in range hood**

**range hood** mounted onto or into a cabinet

**3.4****microwave hood combination**

**cooking fume extractor** integrated in a microwave oven

**3.5****multiple combination hood**

**cooking fume extractor** where the fan is mounted separately of the appliance, but controlled by the appliance

**3.6****down-draft system**

**cooking fume extractor** intended for installation adjacent to a cooking appliance or integrated in a cooking appliance that draws vapour down into a duct

Note 1 to entry: A **down-draft system** can also be a system where the fan is mounted separately from the appliance but controlled by the appliance.

**3.7****recirculation mode**

mode of a **cooking fume extractor** that discharges air back into the room, which includes an **odour-reduction filter**

**3.8****extraction mode**

vented mode

ducted mode

mode of a **cooking fume extractor** that discharges the air to the outside of the building by means of ducting

Note 1 to entry: **Extraction mode** is also known as "vented mode" or "ducted mode".

**3.9****rated voltage**

voltage assigned to the **cooking fume extractor** by the manufacturer

**3.10****grease absorption factor**

$G_{FE}$

percentage of grease retained within a **grease filter**

**3.11****grease filter**

components for absorbing grease, which are intended to be replaced or removed for cleaning without tools

**3.12****odour-reduction filter**

components for reducing odour

**3.13****odour reduction factor**

capability of the **cooking fume extractor** to reduce odours

**3.14****odour dispersion time**

time taken to reduce odours to a defined level after the odour generating source has been switched off

**3.15****highest continuous setting for normal use**

control setting of **cooking fume extractor** at highest speed, excluding the **boost position setting**

Note 1 to entry: Marked setting on the appliance, which is described in the instructions for use.

**3.16****boost position setting**

marked control setting at maximum fan speed, which is automatically limited in duration

Note 1 to entry: Marked setting on the appliance, which is described in the instructions for use.

**3.17****lowest setting**

marked control setting at which the **cooking fume extractor** operates at its lowest speed

**3.18****automatic setting**

control setting of **cooking fume extractor** where the fan speed is altered by a sensor or time

Note 1 to entry: Automatic settings are not used for calculation of the fluid dynamic efficiency (FDE).

**3.19****working point***WP*

intersection point of pressure/airflow curve and resistance curve – measured *WP* and compensated to reference air density  $WP_C$

**3.17****best efficiency point****BEP**

maximum value of the efficiency of a **cooking fume extractor**

~~Note 1 to entry: This term applies to the French language only.~~

**3.20****lighting system**

devices used for the illumination of the cooking surface, excluding ambient illumination unless there is only one control switch

Note 1 to entry: Power supply units and controllers are included.

**3.21****illumination** $E_{middle}$ 

average illumination of the **lighting system** on the cooking surface, measured in lux, under standard conditions

**3.22****network**

communication infrastructure with a topology of links, an architecture and which includes the physical components, organizational principles, communication procedures and formats (protocols)

Note 1 to entry: An infrared (IR) remote control is not considered to be a **network**.

### 3.23

#### off mode

condition in which the appliance is connected to the mains and is not providing any active mode or standby function and where the mode may persist for an indefinite time

Note 1 to entry: The following shall also be considered as off mode

- a) conditions providing only an indication of off mode;
- b) conditions providing only functionalities intended to ensure electromagnetic compatibility.

### 3.24

#### standby mode

condition where the appliance is connected to the mains and provides only the following functions, which may persist for an indefinite time:

- a) reactivation function, or reactivation function and a mere indication of enabled reactivation function; and/or
- b) information or status display; and/or
- c) detection function for emergency measures.

### 3.25

#### standby mode in condition of networked standby

condition where the appliance is connected to the mains and provides only the reactivation function through a connection to a **network**, which may persist for an indefinite time.

Note 1 to entry: This mode is only applicable to appliances that provide a connection function to a **network**.

## 4 Classification

According to the mode:

- **recirculation mode**;
- **extraction mode**.

A **cooking fume extractor** ~~may~~ can be constructed to incorporate both modes.

## 5 List of measurements

Performance is determined by assessing the following:

- overall dimensions;
- mass;
- power measurement of low-power modes;
- airborne acoustical noise;
- volumetric airflow;
- fluid dynamic efficiency;
- effectiveness and electric power input of the **lighting system**;
- ability to reduce odours;
- ability to absorb grease.

## 6 General conditions for measurements

### 6.1 Test room

The tests are carried out in a draught-free room. The ambient temperature of the room is maintained at  $(23 \pm 2)$  °C. The absolute air pressure shall be between 91,3 kPa and 106,3 kPa.

## 6.2 Installation and positioning

The appliance has to be clean and free of any residues of packaging material and protective foil.

All tests have to be carried out following the order of the clauses of this document with one and the same appliance.

The **cooking fume extractor** (except for the **down-draft system**) is installed above a cooking appliance with the distance of  $(600 \pm 10)$  mm. The distance is determined between the lowest level of the **cooking fume extractor** and the highest level of the cooking appliance. ~~The cooking fume extractor is installed and operated in accordance with the manufacturer's instructions (except for the distance above the cooking appliance).~~

~~Any extendible visor, which is extendable for normal use in accordance with the manufacturer's instructions, shall be opened accordingly. If no instructions are given, the extendible visor is fully opened.~~

Any pull-out or swing-out mechanism that can be opened to a position for normal use in accordance with the manufacturer's instructions shall be opened during all tests. Positions that are for cleaning and maintenance purposes only shall be not considered. If the manufacturer's instruction does not state any information, the pull-out or swing-out mechanism shall be completely closed.

The position for the pull-out or swing-out mechanism shall be maintained unchanged for all tests except low power mode measurements in Clause 8. **1**

If the **down-draft system** can be elevated, the manufacturer's instructions are followed; otherwise, it shall be measured in its maximum elevated position for use.

~~The maximum sized duct in accordance with the manufacturer's instructions is to be used.~~

~~For all tests, the appliance is operated with unchanged default factory settings (e.g. brightness of the display or changeable light colour). Supplementary parts that are part of the appliance are mounted in accordance with the manufacturer's instructions. Ensure that no network is connected to the appliance for the duration of the measurement, except for the remote control.~~

If there are different options delivered with the **CFE**, then, for all tests, the air outlet with its properties closest to a theoretical resistance curve for a flue pipe with  $b = 0,000\ 125$  shall be used. This setup shall be kept for all measurements described in this document.

NOTE More information for  $b$  is given in Table 3.

All tests, except the measurements for low-power modes (see Clause 8), are carried out:

- with the default factory settings except adjusting extraction or recirculation mode, if necessary;
- ensure that no **network** is connected to the appliance for the duration of the measurement.

Before the measurement is made, any conditioning of the **CFE**, unless explicitly required in this document, is not allowed.

Ensure that any ~~automatic modes settings, where the fan speed is altered,~~ are switched off.

## 6.3 Electricity supply

The **cooking fume extractor** is supplied at the **rated voltage**  $\pm 1$  %. The supply voltage shall be recorded at the point where the appliance is connected to the mains supply during all tests. **2**

If the appliance has a **rated voltage** range, the tests are carried out at the nominal voltage of the country where the appliance is intended to be used.

The supply frequency shall be at the rated frequency  $\pm 1$  % throughout the test. If a frequency range is indicated, then the test frequency shall be that of the nominal frequency of the country in which the appliance is intended to be used.

#### 6.4 Filters

For all tests, it shall be ensured that all filters are positioned correctly.

For appliances with more than one **grease filter**, the filters shall be positioned with no gap in between (centrally positioned).

#### 6.5 Fan control

**Cooking fume extractors** shall be tested in the **highest continuous setting for normal use**, as stated in the manufacturer's instructions.

#### 6.6 Instrumentation and measurements

Instruments used and measurements made for this document shall comply with the specifications in Table 1 and Table 2. The accuracy is applied to the measured value.

**Table 1 – Instruments**

Parameter	Unit	Minimum resolution	Accuracy	Additional requirements
Mass	g	0,1 g	$\pm 0,5$ g	
Temperature	$^{\circ}\text{C}$	0,1 $^{\circ}\text{C}$	$\pm 1,5$ K	Thermocouple type J or K in accordance with IEC 60584-1 or PT100 sensor in accordance with IEC 60751.
Time	s	1 s	$\pm 1$ s	
Power	W	-	$\pm 1$ %	
Illuminance	lx	-	$\pm 10$ %	Value under consideration – International standard about illuminance classification is pending.
Pressure/Air pressure	Pa	-	$\pm 1$ %	The accuracy is for pressures $\leq 150$ Pa and at least 1,5 Pa.