



Designation: E1839 – 20

# Standard Practice for Efficacy of Slimicides for the Paper Industry—Bacterial and Fungal Slime<sup>1</sup>

This standard is issued under the fixed designation E1839; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

## 1. Scope

1.1 This practice presents a procedure to evaluate the efficacy of slimicides for the control of bacterial and fungal slimes in paper mill systems and their counterparts.

1.2 It is the responsibility of the investigator to determine whether Good Laboratory Practices (GLP) are required and to follow them where appropriate (40 CFR 160).

1.3 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.5 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

## 2. Referenced Documents

2.1 *ASTM Standards:*<sup>2</sup>

[D1193 Specification for Reagent Water](#)

[E1054 Test Methods for Evaluation of Inactivators of Antimicrobial Agents](#)

[E2756 Terminology Relating to Antimicrobial and Antiviral Agents](#)

<sup>1</sup> This practice is under the jurisdiction of ASTM Committee E35 on Pesticides, Antimicrobials, and Alternative Control Agents and is the direct responsibility of Subcommittee E35.15 on Antimicrobial Agents.

Current edition approved Jan. 1, 2020. Published March 2020. Originally approved in 1996. Last previous edition approved in 2013 as E1839 – 13. DOI: 10.1520/E1839-20.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

2.2 *TAPPI Standard:*

[T 205 Forming Handsheets for Physical Tests of Pulp](#)<sup>3</sup>

2.3 *CFR Standard:*

[40 CFR Part 160 Good Laboratory Practice Standards](#)<sup>4</sup>

## 3. Terminology

3.1 For definitions of terms related to this practice, see Terminology [E2756](#).

3.2 *Definitions:*

3.2.1 *furnish, n*—pulp slurry fed to a paper machine. The type of pulp (sulfite, Kraft, mechanical), the source of fiber (virgin, recycled including pre- or post-consumer waste paper), and the pH are used to designate a specific type of furnish.

3.2.2 *microbicide, n*—a physical or chemical agent that kills microorganisms.

3.2.3 *pulp, n*—wood separated by chemical or mechanical means into their fibrous components. The pulp is used to make paper, paper board, or pulp sheets after specific treatments. Hardwood pulp is made from trees, such as maples or oaks, and softwood pulp is produced from trees, such as pines.

3.2.4 *pulp slurry, n*—an aqueous combination of cellulosic fibers, fillers, and other additives used for specific grades of paper.

3.2.5 *slime, n*—biofilm.

3.2.6 *slimicides, n*—chemical agent added during pulp and paper processing to reduce the growth of slime-forming microorganisms.

## 4. Summary of Practice

4.1 Bacterial cells or fungal spores are added to acid or alkaline pulp slurries, or both, treated with slimicides to achieve final concentrations of  $2 \times 10^6$  to  $1 \times 10^7$  bacteria/mL and/or  $10^5$  to  $10^6$  fungal spores/mL, and incubated at appropriate temperature for determined time periods. Aliquots of the test suspension are then neutralized, plated onto bacterial or

<sup>3</sup> Available from Technical Association of the Pulp and Paper Industry (TAPPI), 15 Technology Parkway South, Norcross, GA 30092, <http://www.tappi.org>.

<sup>4</sup> Available from U.S. Government Printing Office Superintendent of Documents, 732 N. Capitol St., NW, Mail Stop: SDE, Washington, DC 20401, <http://www.access.gpo.gov>.

fungal medium, and observed for growth. Results with biocide are compared to results without biocide (control).

4.2 As a performance standard, an effective slimicide is one that shows a continued reduction in bacterial and fungal counts relative to the control over the duration of the test.

## 5. Significance and Use

5.1 This practice is to be used to determine if a slime control agent has application in the paper industry for control of bacterial or fungal slime/biofilm.

5.2 This practice is run in acid, alkaline, or acid and alkaline conditions to determine the efficacy of the slime control agent.

5.3 The test conditions may be modified to reflect intended use patterns in typical paper mill systems, including use of actual paper mill furnish.

## 6. Apparatus

### 6.1 Balance:

6.1.1 *Plant Balance*, one sensitive to 0.1 g at load of 200 g, with platform to weigh furnish and bottles used in the test.

6.1.2 *Analytical Balance*, one sensitive to 0.1 mg used for weighing the candidate slime control agent.

6.2 *Sample Containers (Sterile)*, 120-mL plastic specimen containers with screw-cap lids are ideal for holding test materials. Other suitable containers include 150/160 mL milk dilution bottles or WHIRL-PAKS.

6.3 *Culture Containers*, Petri plates, tissue culture bottles, or glass tubes (15 × 125 mm or 18 × 150 mm without lip, preferably of borosilicate glass).

6.4 *Closures*, for tubes and containers.

6.5 *Disintegrators*, Appendix A (Specifications and Care of Apparatus (Disintegrator)) of T 205.

6.6 *Flaming Equipment*—Depending upon circumstances, either an alcohol lamp, a Bunsen burner, or electric incinerator may be used to flame inoculating needles and other equipment.

6.7 *Incubators* Capable of maintaining temperatures of 28 to 70 ± 2 °C to provide proper incubation temperatures. Temperature should be consistent with the temperature of the product to be preserved.

6.8 *pH Meter*—Any suitable for standardizing the pH of the culture medium.

6.9 *Pipets*—1.1-mL milk dilution type, 1.0 mL graduated in 0.01 mL, and 10 mL graduated in 0.1 mL. Pipetters may be used, but not for highly viscous materials.

6.9.1 *Pipetting Aid*—Rubber bulb or other device to accomplish the transfer of liquid.

6.10 *Sterilizers*, pressurized steam sterilizer or hot-air oven capable of 180 ± 2 °C for 2 ± 0.2 h.

6.11 *Filter Apparatus for Filter Sterilizing*, Disposable filter units, appropriate volume, 0.2-µm pore size.

6.12 *Sterile Funnel*, with sterile glass wool or sterile cotton gauze for filtration of spores.

6.13 *Colony counter*, manual, such as Quebec, Buck, and Wolfhugel, or proven colony image analyzer (electronic/scanner type) are suitable for counting plates after incubation.

6.14 *Swabs*, sterile, for aiding in removal of fungal spores from agar surface.

6.15 *Hemocytometer*, for counting spore suspension.

6.16 *Microscope*, providing a magnification range of 400 to 1000× with a suitable light source. Phase contrast or dark field capability may be necessary.

6.17 *Constant Temperature Shaker*—A reliable constant-temperature shaker (water bath or incubator type), shall be used to provide mixing and aeration and to maintain a selected temperature (±2 °C) during the contact period.

6.18 *Mechanical Stirrer*—Magnetic or propeller-type stirrers or any other suitable device.

## 7. Reagents and Materials

7.1 *Purity of Reagents*—Reagent chemicals shall be used in all tests. Unless otherwise indicated, it is intended that all reagents shall conform to the specifications of the Committee on Analytical Reagents of the American Chemical Society, where such specifications are available.<sup>5</sup> Other grades may be used, provided it is first ascertained that the reagent is of sufficiently high purity to permit its use without lessening the accuracy of the determination.

7.2 *Purity of Water*—Unless otherwise indicated, references to water shall be understood to mean distilled water or water of equal purity (see Specification **D1193**, Type III).

7.3 *Buffer for Suspending Spores and for Dilutions*, sample containers having 100-mL phosphate buffer dilution water, sterile, for spore suspension have solid, sterile glass beads in container.

7.3.1 *0.25 M Phosphate Buffer Stock Solution*—Dissolve 34 g of reagent grade KH<sub>2</sub>PO<sub>4</sub> in 500 mL of distilled water and mix. Adjust to pH 7.2 with 1 N NaOH and dilute to 1 l.

7.3.2 *Phosphate Buffer Dilution Water*—Add 1.25 mL of 0.25 M phosphate buffer stock solution to 1 L of distilled water and mix. Dispense to sample container and sterilize.

7.4 *Aluminum Sulfate (Alum)* [Al<sub>2</sub>(SO<sub>4</sub>)<sub>3</sub> · 18H<sub>2</sub>O]—Prepare a 0.4 % solution of the hydrated aluminum in distilled water and sterilize in an autoclave. Any loss of water during sterilization is made up by adding sterile distilled water. Alternatively, the solution may be filter sterilized.

7.5 *Acid and Base for pH Adjustment to Make Acid and Alkaline Furnish:*

7.5.1 Prepare a 2.0 N solution of sulfuric acid in water. Sterilize by filtration.

7.5.2 Prepare a 2.0 N solution of sodium hydroxide in water. Sterilize by filtration.

<sup>5</sup> *Reagent Chemicals, American Chemical Society Specifications*, American Chemical Society, Washington, DC. For suggestions on the testing of reagents not listed by the American Chemical Society, see *Analar Standards for Laboratory Chemicals*, BDH Ltd., Poole, Dorset, U.K., and the *United States Pharmacopeia and National Formulary*, U.S. Pharmacopeial Convention, Inc. (USPC), Rockville, MD.