

INTERNATIONAL STANDARD

IEC 60335-2-29

Edition 4.1
2004-12

Edition 4:2002 consolidated with amendment 1:2004

Household and similar electrical appliances – Safety –

Part 2-29: Particular requirements for battery chargers

iTech Standards

(<https://standards.iteh.ai>)

Document Preview

[IEC 60335-2-29:2002](https://standards.iteh.ai/catalog/standards/iec/384b0eea-d246-4cc3-8f5e-9fdeeb5f303f/iec-60335-2-29-2002)

<https://standards.iteh.ai/catalog/standards/iec/384b0eea-d246-4cc3-8f5e-9fdeeb5f303f/iec-60335-2-29-2002>

*This **English-language** version is derived from the original **bilingual** publication by leaving out all French-language pages. Missing page numbers correspond to the French-language pages.*



Reference number
IEC 60335-2-29:2002+A1:2004(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site** (www.iec.ch)

- **Catalogue of IEC publications**

The on-line catalogue on the IEC web site (www.iec.ch/searchpub) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

- **IEC Just Published**

This summary of recently issued publications (www.iec.ch/online_news/justpub) is also available by email. Please contact the Customer Service Centre (see below) for further information.

- **Customer Service Centre**

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: custserv@iec.ch
Tel: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

IEC 60335-2-29

Edition 4.1
2004-12

Edition 4:2002 consolidated with amendment 1:2004

Household and similar electrical appliances – Safety –

Part 2-29: Particular requirements for battery chargers

iTeh Standards
(<https://standards.itih.ai>)
Document Preview

<https://standards.itih.ai/catalog/standards/iec/384b0eea-d246-4cc3-8f5e-9fdeeb5f303f/iec-60335-2-29-2002>

<https://standards.itih.ai/catalog/standards/iec/384b0eea-d246-4cc3-8f5e-9fdeeb5f303f/iec-60335-2-29-2002>

© IEC 2004 Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembe, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

CF

For price, see current catalogue

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	9
1 Scope.....	11
2 Normative references	13
3 Definitions	13
4 General requirement.....	15
5 General conditions for the tests	15
6 Classification.....	15
7 Marking and instructions.....	15
8 Protection against access to live parts.....	17
9 Starting of motor-operated appliances	19
10 Power input and current.....	19
11 Heating.....	19
12 Void.....	19
13 Leakage current and electric strength at operating temperature.....	19
14 Transient overvoltages	19
15 Moisture resistance	21
16 Leakage current and electric strength.....	21
17 Overload protection of transformers and associated circuits	21
18 Endurance.....	21
19 Abnormal operation	21
20 Stability and mechanical hazards.....	23
21 Mechanical strength	23
22 Construction.....	23
23 Internal wiring.....	25
24 Components	25
25 Supply connection and external flexible cords.....	25
26 Terminals for external conductors.....	27
27 Provision for earthing	27
28 Screws and connections	27
29 Clearances, creepage distances and solid insulation	27
30 Resistance to heat and fire	27
31 Resistance to rusting	27
32 Radiation, toxicity and similar hazards.....	27
Annexes.....	31
Annex A (informative) Routine tests.....	31
Annex AA (normative) Battery chargers for use by children.....	33
Bibliography.....	41
Figure 101 – Circuit for testing battery chargers.....	29

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**HOUSEHOLD AND SIMILAR ELECTRICAL APPLIANCES –
SAFETY –****Part 2-29: Particular requirements for battery chargers**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This part of International Standard IEC 60335 has been prepared by IEC technical committee 61: Safety of household and similar electrical appliances.

This consolidated version of IEC 60335-2-29 consists of the fourth edition (2002) [documents 61/2169/FDIS and 61/2250/RVD], its amendment 1 (2004) [documents 61/2536/FDIS and 61/2580/RVD] and its corrigendum of November 2004.

The technical content is therefore identical to the base edition and its amendment and has been prepared for user convenience.

It bears the edition number 4.1.

A vertical line in the margin shows where the base publication has been modified by amendment 1.

This part 2 is to be used in conjunction with the latest edition of IEC 60335-1 and its amendments. It was established on the basis of the fourth edition (2001) of that standard.

NOTE 1 When "Part 1" is mentioned in this standard, it refers to IEC 60335-1.

This part 2 supplements or modifies the corresponding clauses in IEC 60335-1, so as to convert that publication into the IEC standard: Safety requirements for electric battery chargers. When a particular subclause of Part 1 is not mentioned in this part 2, that subclause applies as far as is reasonable. When this standard states "addition", "modification", or "replacement", the relevant text in Part 1 is to be adapted accordingly.

NOTE 2 The following numbering system is used:

- subclauses, tables and figures that are numbered starting from 101 are additional to those in Part 1;
- unless notes are in a new subclause or involve notes in Part 1, they are numbered starting from 101, including those in a replaced clause or subclause;
- additional annexes are lettered AA, BB, etc.

NOTE 3 The following print types are used:

- requirements: in roman type;
- test specifications: in italic type;
- notes: in small roman type.

Words in **bold** in the text are defined in Clause 3. When a definition concerns an adjective, the adjective and the associated noun are also in bold.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

The following differences exist in the countries indicated below.

- 3.1.9: The artificial load may not be used (USA).
- 6.1: The voltage limits for appliances suitable for outdoor use are different (USA).
- 10.101: The d.c. output voltage is not to exceed 30 V (USA).
- 11.2: The appliance is not placed in a test corner (USA).
- 21.101: The drop test is carried out differently on battery chargers with a mass less than 18 kg (USA).
- 21.102: The test is different (USA).
- 22.26: Basic insulation is allowed between live parts and SELV circuits (USA).
- 25.7: Special rubber insulated and sheathed cords are required for some types of battery chargers. (Finland).
- Annex AA, 11.8: Higher temperature rises are allowed (USA).
- Annex AA, Clause 17: Higher temperature rises are allowed (USA).
- Annex AA, 19.13: Higher temperature rises are allowed (USA).

INTRODUCTION

It has been assumed in the drafting of this International Standard that the execution of its provisions is entrusted to appropriately qualified and experienced persons.

This standard recognizes the internationally accepted level of protection against hazards such as electrical, mechanical, thermal, fire and radiation of appliances when operated as in normal use taking into account the manufacturer's instructions. It also covers abnormal situations that can be expected in practice and takes into account the way in which electromagnetic phenomena can affect the safe operation of appliances.

This standard takes into account the requirements of IEC 60364 as far as possible so that there is compatibility with the wiring rules when the appliance is connected to the supply mains. However, national wiring rules may differ.

If an appliance within the scope of this standard also incorporates functions that are covered by another part 2 of IEC 60335, the relevant part 2 is applied to each function separately, as far as is reasonable. If applicable, the influence of one function on the other is taken into account.

This standard is a product family standard dealing with the safety of appliances and takes precedence over horizontal and generic standards covering the same subject.

An appliance that complies with the text of this standard will not necessarily be considered to comply with the safety principles of the standard if, when examined and tested, it is found to have other features that impair the level of safety covered by these requirements.

An appliance employing materials or having forms of construction differing from those detailed in the requirements of this standard may be examined and tested according to the intent of the requirements and, if found to be substantially equivalent, may be considered to comply with the standard.

<https://standards.iteh.ai/standards/iec/3c4b0eea-d246-4cc3-8f5e-9fdeeb5f303f/iec-60335-2-29-2002>

<https://standards.iteh.ai/catalog/standards/iec/3c4b0eea-d246-4cc3-8f5e-9fdeeb5f303f/iec-60335-2-29-2002>

HOUSEHOLD AND SIMILAR ELECTRICAL APPLIANCES – SAFETY –

Part 2-29: Particular requirements for battery chargers

1 Scope

This clause of Part 1 is replaced by the following.

This International Standard deals with the safety of electric battery chargers for household and similar use having an output at **safety extra-low voltage**, their **rated voltage** being not more than 250 V.

Battery chargers not intended for normal household use, but which nevertheless may be a source of danger to the public, such as battery chargers intended for use in garages, shops, light industry and on farms, are within the scope of this standard.

As far as is practicable, this standard deals with the common hazards presented by appliances that are encountered by all persons in and around the home. However, in general, it does not take into account

- the use of appliances by young children or infirm persons without supervision;
- playing with the appliance by young children.

NOTE 101 Attention is drawn to the fact that

- for appliances intended to be used in vehicles or on board ships or aircraft, additional requirements may be necessary;
- in many countries additional requirements are specified by the national health authorities, the national authorities responsible for the protection of labour and similar authorities.

NOTE 102 This standard does not apply to

- built-in battery chargers, except those for installing in caravans and similar vehicles;
- battery chargers that are part of an appliance, the battery of which is not accessible to the user;
- battery chargers intended exclusively for industrial purposes;
- battery chargers intended to be used in locations where special conditions prevail, such as the presence of a corrosive or explosive atmosphere (dust, vapour or gas);
- battery chargers comprising more than one unit;
- supply units for electronic equipment;
- battery chargers and supply units for electronic flash apparatus for photographic purposes (IEC 60491);
- battery chargers intended for use in electric vehicles (IEC 61851).

NOTE 103 Requirements for battery chargers for use by children at least 8 years old without supervision are given in Annex AA.

2 Normative references

This clause of Part 1 is applicable except as follows.

Addition:

IEC 60068-2-6, *Environmental testing – Part 2: Tests - Test Fc: Vibration (sinusoidal) – Basic safety publication*

IEC 61558-2-7:1997, *Safety of power transformers, power supply units and similar – Part 2-7: Particular requirements for transformers for toys*

3 Definitions

This clause of Part 1 is applicable except as follows.

3.1.1 *Addition:*

The **rated voltage** is the rated input voltage.

3.1.6 *Addition:*

The **rated current** is the rated input current.

3.1.9 *Replacement:*

normal operation

operation of the appliance under the following conditions

Battery chargers for charging lead-acid batteries, and other battery chargers having a **rated d.c. output current** not exceeding 20 A, are connected to the circuit of Figure 101. The variable resistor is adjusted so that the current in the circuit is the **rated d.c. output current** when the battery charger is supplied at **rated voltage**.

When the charging current is controlled by the state of charge of the battery, the variable resistor and the capacitor are replaced by a discharged battery of the type and having the largest capacity specified in the instructions.

Other battery chargers are connected to a discharged battery of the type and having the largest capacity specified in the instructions.

NOTE 101 Batteries are considered to be discharged when

- for lead-acid batteries, the specific gravity of the electrolyte is less than 1,16;
- for nickel-cadmium batteries, the voltage per cell is less than 0,9 V.

3.101

rated d.c. output voltage

output voltage assigned to the battery charger by the manufacturer

3.102

rated d.c. output current

output current assigned to the battery charger by the manufacturer

3.103

d.c. distribution board

panel having circuits for distributing d.c. power to socket-outlets or terminals

4 General requirement

This clause of Part 1 is applicable.

5 General conditions for the tests

This clause of Part 1 is applicable except as follows.

5.2 Addition:

If the test of 21.101 is carried out, two additional battery chargers are required.

5.101 Battery chargers are tested as **motor-operated appliances**.

6 Classification

This clause of Part 1 is applicable.

7 Marking and instructions

This clause of Part 1 is applicable except as follows.

7.1 Addition:

Battery chargers shall be marked with

- **rated d.c. output voltage**, in volts;
- **rated d.c. output current**, in amperes;
- the rated current, in amperes, of **protective devices** incorporated in a **d.c. distribution board**;
- the polarity of the output terminals. The positive terminal shall be indicated by the colour red or the symbol + and the negative terminal by the colour black or the symbol – ;

NOTE 101 No other output current is to be marked.

- NOTE 102 Marking of the polarity is not required for battery chargers if incorrect polarity connection is prevented.
- the time-current characteristic of fuse-links of the time-lag type;
 - the substance of the following, if the output is at least 20 VA:
 - before charging, read the instructions;
 - for indoor use, or do not expose to rain (unless the battery charger is at least IPX4);
 - the substance of the following, if the output is at least 20 VA and the battery charger is for charging lead-acid batteries:
 - disconnect the supply before making or breaking the connections to the battery;
 - **WARNING:** Explosive gases. Prevent flames and sparks. Provide adequate ventilation during charging.