

# INTERNATIONAL STANDARD

**Coaxial communication cables –  
Part 10-1: Blank detail specification for semi-rigid cables with fluoropolymer  
dielectric**

IEC 61196-10-1:2022

<https://standards.iteh.ai/catalog/standards/sist/03667737-f8d1-4c04-8a48-e1646145dadf/iec-61196-10-1-2022>



**THIS PUBLICATION IS COPYRIGHT PROTECTED**  
**Copyright © 2022 IEC, Geneva, Switzerland**

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat  
3, rue de Varembe  
CH-1211 Geneva 20  
Switzerland

Tel.: +41 22 919 02 11  
[info@iec.ch](mailto:info@iec.ch)  
[www.iec.ch](http://www.iec.ch)

**About the IEC**

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

**About IEC publications**

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

**IEC publications search - [webstore.iec.ch/advsearchform](http://webstore.iec.ch/advsearchform)**

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

**IEC Products & Services Portal - [products.iec.ch](http://products.iec.ch)**

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

**IEC Just Published - [webstore.iec.ch/justpublished](http://webstore.iec.ch/justpublished)**

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

**Electropedia - [www.electropedia.org](http://www.electropedia.org)**

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

**IEC Customer Service Centre - [webstore.iec.ch/csc](http://webstore.iec.ch/csc)**

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: [sales@iec.ch](mailto:sales@iec.ch).

[IEC 61196-10-1-2022](https://standards.iteh.ai/catalog/standards/sist/03667737-f8d1-4c04-8a48-e1646145dadf/iec-61196-10-1-2022)

<https://standards.iteh.ai/catalog/standards/sist/03667737-f8d1-4c04-8a48-e1646145dadf/iec-61196-10-1-2022>



IEC 61196-10-1

Edition 2.0 2022-11

# INTERNATIONAL STANDARD

---

**Coaxial communication cables –  
Part 10-1: Blank detail specification for semi-rigid cables with fluoropolymer  
dielectric**

[IEC 61196-10-1:2022](https://standards.iteh.ai/catalog/standards/sist/03667737-f8d1-4c04-8a48-e1646145dadf/iec-61196-10-1-2022)

<https://standards.iteh.ai/catalog/standards/sist/03667737-f8d1-4c04-8a48-e1646145dadf/iec-61196-10-1-2022>

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 33.120.10

ISBN 978-2-8322-6018-0

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references .....	5
3 Terms and definitions .....	5
4 Guidance for the preparation of detail specifications.....	5
5 Blank detail specification .....	6

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[IEC 61196-10-1:2022](#)

<https://standards.iteh.ai/catalog/standards/sist/03667737-f8d1-4c04-8a48-e1646145dadf/iec-61196-10-1-2022>

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

---

**COAXIAL COMMUNICATION CABLES –****Part 10-1: Blank detail specification for semi-rigid cables  
with fluoropolymer dielectric****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61196-10-1 has been prepared by subcommittee 46A: Coaxial cables, of IEC technical committee 46: Cables, wires, waveguides, RF connectors, RF and microwave passive components and accessories. It is an International Standard.

This second edition cancels and replaces the first edition published in 2014. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) Title was changed to: Blank detail specification for semi-rigid cables with fluoropolymer dielectric.
- b) Further changes in accordance with IEC 61196-10.

The text of this International Standard is based on the following documents:

Draft	Report on voting
46A/1600/FDIS	46A/1607/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This International Standard is to be used in conjunction with IEC 61196-1:2005 and IEC 61196-10:2022.

A list of all parts in the IEC 61196 series, published under the general title *Coaxial communication cables*, can be found on the IEC website.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at [www.iec.ch/members\\_experts/refdocs](http://www.iec.ch/members_experts/refdocs). The main document types developed by IEC are described in greater detail at [www.iec.ch/publications](http://www.iec.ch/publications).

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under [webstore.iec.ch](http://webstore.iec.ch) in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or [IEC 61196-10-1:2022](https://standards.iteh.ai/catalog/standards/sist/03667737-f8d1-4c04-8a48-e1646145dad7/iec-61196-10-1-2022)
- amended.

## COAXIAL COMMUNICATION CABLES –

### Part 10-1: Blank detail specification for semi-rigid cables with fluoropolymer dielectric

#### 1 Scope

This part of IEC 61196 applies to coaxial communication cables described in IEC 61196-10, which specifies the requirements of semi-rigid coaxial communication cables with fluoropolymer dielectric and tubular outer conductors. Semi-rigid coaxial communication cables with fluoropolymer dielectric are widely used in mobile communication systems, microwave test equipment, radar, aerospace, electronic countermeasures and other fields.

This part of IEC 61196 is used in conjunction with IEC 61196-1 and IEC 61196-10, which determines the layout and style for detail specifications, based on the blank detail specification, that can be prepared by a national organization, a manufacturer, or a user.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61196-1:2005, *Coaxial communication cables – Part 1: Generic specification: General, definitions and requirements*

IEC 61196-10:2022, *Coaxial communication cables – Part 10: Sectional specification for semi-rigid cables with fluoropolymer dielectric*

IEC 61169-4, *Radio-frequency connectors – Part 4: RF coaxial connectors with inner diameter of outer conductor 16 mm (0,63 in) with screw lock-Characteristic impedance 50  $\Omega$  (type 7-16)*

#### 3 Terms and definitions

No terms and definitions are listed in this document.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

#### 4 Guidance for the preparation of detail specifications

The detail specification shall be written in accordance with the layout of the blank detail specification, which forms part of this document.

When a characteristic does not apply, then NA (not applicable) should be entered in the appropriate space.

When a characteristic applies but a specific value is not considered necessary, then NS (not specified) should be entered.

The numbers shown in brackets in Clause 5 correspond to the following items of required information, which should be entered in the space provided.

- [1] Name and address of the organization that has prepared the document.
- [2] IEC document number and date of issue.
- [3] Address of the organization from which the document is available.
- [4] Related documents.
- [5] Any other references to the cable, national reference, trade name, etc.
- [6] Complete description of the cable.
- [7] Cable construction.
- [8] Engineering information.
- [9] Parameter or characteristic.
- [10] Reference to the relevant subclause of the sectional specification.
- [11] Minimum requirements, the values entered shall meet as a minimum the requirements of the sectional specification.
- [12] Remarks.

### 5 Blank detail specification

Title	
<b>[1] Prepared by:</b>	<b>[2] Document No.:</b>
	<b>Issue:</b> IEC 61196-10-1
	<b>Date:</b> 18d1-4c04-8a48-e1646145dadf/iec-
<b>[3] Available from:</b>	<b>[4] Generic specification</b> IEC 61196-1
	<b>Sectional specification</b> IEC 61196-10
<b>[5] Additional references:</b>	
References to the different test procedures of Column 8 are given in IEC 61196-10.	
<b>[6] Cable description:</b>	
a) Cable variant	
b) Material of inner conductor	
c) Material and construction of dielectric	
d) Outer conductor	
e) Material of sheath (if any)	



Title
<p><b>[7] Cable construction</b></p> <p><b>a) Inner conductor</b>  Material:  Diameter (mm) nominal:  Tolerance (mm): <math>\pm \dots</math></p> <p><b>b) Dielectric</b>  Material:  Construction:  Diameter (mm) nominal:  Tolerance (mm) tube: <math>\pm \dots</math> (for cable with smooth tube outer conductor)</p> <p><b>c) Outer conductor</b>  Material:  Construction:  For smooth tube outer conductor:  Diameter and tolerance (mm): <math>\dots \pm \dots</math>  For corrugated outer conductor:  Peak diameter and tolerance(mm): <math>\dots \pm \dots</math>  Root diameter and tolerance(mm): <math>\dots \pm \dots</math>  Pitch and tolerance(mm): <math>\dots \pm \dots</math></p> <p><b>d) Sheath(if any)</b>  Material  Minimum thickness(mm)  Diameter (mm)  Tolerance(mm): <math>\pm \dots</math></p>
<p><b>[8] Engineering information (reference only)</b></p> <p>a) Operating temperature range, storage temperature range, installation temperature range:  b) Maximum recommended operating frequency, cut-off frequency:  c) Nominal characteristic impedance:  d) Relative propagation velocity (velocity ratio):  e) Maximum continue working voltage:  f) Minimum bending radius(static state):  g) Minimum bending radius(dynamic state for corrugated outer conductor):  h) Nominal weight:  i) Capacitance:  j) Maximum tensile force:  k) Average power (when required):  l) Peak power (when required):</p>

[9] Parameter	[10] IEC 61196-10:2022 Subclause	[11] Value	[12] Remarks
<b>Electrical characteristics</b>	<b>8.2</b>		
Continuity	8.2.1	Inner conductor shall be continuous. Outer conductor shall be continuous.	
Inner and outer conductor direct current resistance	8.2.2	≤ ... Ω/km (Inner conductor) ≤ ... Ω/km (Outer conductor)	
Withstand voltage of dielectric	8.2.3	... kV RMS	40 Hz to 60 Hz
Withstand voltage of sheath(or spark test) <sup>a</sup>	8.2.4	... kV RMS	40 Hz to 60 Hz
Insulation resistance	8.2.5	≥ 10 <sup>4</sup> MΩ·km	
Capacitance	8.2.6	≤ ... pF/m	The value of typical cable; see IEC 61196-10:2022, Annex A
Characteristic impedance	8.2.7	(…±…) Ω	
Regularity of impedance <sup>b</sup>	8.2.8	≥ 40 dB or resp ≤ 1 %	
Propagation velocity <sup>b</sup>	8.2.9	≥ ...% or ...%±...%	The value of typical cable; see IEC 61196-10:2022, Annex A
Return loss	8.2.10	...MHz to MHz ≥ ...dB	Specimen length: ≥ 2m
Attenuation constant	8.2.11	... MHz ≤... dB/m at 20 °C	The value of typical cable; see IEC 61196-10:2022, Annex A
Attenuation stability <sup>b</sup>	8.2.12	See 8.3.1	
Phase stability vs temperature <sup>c</sup>	8.2.13	≤...PPM Frequency: ...GHz Test temperature:	The value of typical cable; see IEC 61196-10:2022, Annex A
Phase stability vs bending (for cable with corrugated tube outer conductor) <sup>c</sup>	8.2.14	±...° (...GHz to...GHz) Mandrel diameter: ...mm	
Corona voltage <sup>b</sup>	8.2.15	≥... kV	
RF power <sup>b</sup>	8.2.16	... W Frequency: ...GHz	
Passive Intermodulation <sup>b c</sup>	8.2.17	Better than -158 dBc	This test is only applicable to the cable with characteristic impedance of 50 Ω.  Both ends of the specimen should be attached with suitable RF connectors (recommended type 7-16 connectors, in accordance with IEC 61169-4).  PIM should be performed under the minimum bending radius.  Input power: 2 × 20 W Test frequency: ...MHz