



Designation: **F1805 – 18 F1805 – 20**

Standard Test Method for Single Wheel Driving Traction in a Straight Line on Snow- and Ice-Covered Surfaces¹

This standard is issued under the fixed designation F1805; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method covers a procedure for measuring the driving traction of passenger car and light truck tires while traveling in a straight line on snow- or ice-covered surfaces.

1.2 This test method utilizes a dedicated, instrumented, four-wheel rear-wheel drive test vehicle with a specially instrumented drive axle to measure fore-aft and vertical forces acting on a single driven test tire.

1.3 This test method is suitable for research and development purposes where tires are compared during a single series of tests. They may not be suitable for regulatory statutes or specification acceptance because the values obtained may not necessarily agree or correlate either in rank order or absolute traction performance level with those obtained under other environmental conditions on other surfaces or the same surface after additional use.

1.4 The values stated in SI units are to be regarded as the standard. Ordinarily, N and kN should be used as units of force. This standard may utilize kgf as a unit of force in order to accommodate the use of load and pressure tables, as found in other standards both domestic and global that are commonly used with this standard. The values given in parentheses are for information only.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.6 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 ASTM Standards:²

- E1136 Specification for P195/75R14 Radial Standard Reference Test Tire
- F377 Practice for Calibration of Braking/Traction Measuring Devices for Testing Tires
- F538 Terminology Relating to the Characteristics and Performance of Tires
- F1046 Guide for Preparing Artificially Worn Passenger and Light Truck Tires for Testing
- F1572 Test Methods for Tire Performance Testing on Snow and Ice Surfaces
- F1650 Practice for Evaluating Tire Traction Performance Data Under Varying Test Conditions
- F2493 Specification for P225/60R16 97S Radial Standard Reference Test Tire

2.2 Other Standards:

- The European Tyre and Rim Technical Organisation Standards Manual³
- The Japan Automobile Tyre Manufacturers Association, Inc. Yearbook⁴
- The Tire & Rim Association, Inc. Year Book⁵
- Tire Information Service Bulletin, Vol. 37/No. 56 U.S. Tire Manufacturers Association (USTMA) Definition for Passenger and

¹ This test method is under the jurisdiction of Committee F09 on Tires and is the direct responsibility of Subcommittee F09.20 on Vehicular Testing. Current edition approved Nov. 1, 2018; May 1, 2020. Published November 2018; May 2020. Originally approved in 1997. Last previous edition approved in 2016 as F1805 – 16; F1805 – 18. DOI: 10.1520/F1805-18.10.1520/F1805-20.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For Annual Book of ASTM Standards volume information, refer to the standard's Document Summary page on the ASTM website.

³ Available from The European Tyre and Rim Technical Organisation, 78/80, rue Defacqz B-1060, Brussels, Belgium.

⁴ Available from The Japan Automobile Tyre Manufacturers Association, Inc., No. 33 Mori Bldg. 8th Floor, 3-8-21 Toranomon, Minato-ku, Tokyo, Japan 105-0001.

⁵ Available from The Tire & Rim Association, Inc., 175 Montrose West Ave., Suite 150, Copley, OH 44321.

Light Truck Tires for Use in Severe Snow Conditions⁶

3. Terminology

3.1 Definitions:

3.1.1 *candidate tire, n*—a test tire that is part of a test program. **F538**

3.1.1.1 Discussion—

The term “candidate object” may be used in the same sense as *candidate tire*.

3.1.2 *control tire, n*—a reference tire used in a specified manner throughout a test program. **F538**

3.1.2.1 Discussion—

A control tire may be of either type and typical tire used is the reference (control) tire in Practice **F1650** that provides algorithms for correcting (adjusting) test data for bias trend variations. (See Practice **F1650**. See also the discussion in **3.1.16**.)

3.1.3 *driving coefficient (nd), n*—the ratio of the driving force to a normal force. **F538**

3.1.4 *driving force (F), n— of a tire*, the positive longitudinal force resulting from the application of driving torque. **F538**

3.1.5 *grooming, v—in tire testing*, mechanically reworking a snow test surface in order to obtain a surface with more consistent properties. **F538**

3.1.6 *ice, dry, n*—smooth ice without loose surface materials. **F538**

3.1.7 *longitudinal force (F), n— of a tire*, the component of the tire force vector in the X' direction. **F538**

3.1.8 *longitudinal slip velocity (LT), n—* the effective rolling radius multiplied by the difference between the spin velocity (in rad/unit time) of a driven or braked tire and that of a free rolling tire when each is traveling in a straight line. **F538**

3.1.9 *maximum rated load, n*—the load corresponding to the maximum tire load capacity at the rated inflation pressure in accordance with the publications of tire and rim standards current at the time of manufacture. **F538**

3.1.10 *reference tire, n*—a special tire included in a test program; the test results for this tire have significance as a base value or internal benchmark. **F538**

3.1.11 *snow, hard pack, n— in tire testing*, packed base without loose snow. **F538**

3.1.12 *snow, medium pack, n— in tire testing*, groomed packed base with 2.5 to 5.0 cm (1 to 2 in.) loose snow. **F538**

3.1.13 *snow, medium hard pack, n— in tire testing*, packed base with some loose snow. **F538**

3.1.14 *snow, soft pack, n— in tire testing*, freshly fallen or deeply groomed base snow with 5.0 to 7.5 cm (2 to 3 in.) loose snow. **F538**

3.1.15 *spin velocity, n*—the angular velocity of the wheel about its spin axis. **F538**

3.1.16 *standard reference test tire (SRTT), n*—a tire that is used as a control tire or surface monitoring tire (for example, Specification **E1136** and Specification **F2493** tires). **F538**

3.1.16.1 Discussion—

While ASTM designates several tire specifications as Standard Reference Test Tires, Test Method F1805 has historically used the Specification **E1136** tire as its primary reference tire and this specification is specifically identified as the control tire in the USTMA Tire Information Service Bulletin Vol. 37/No. 5-6, which specifies requirements for application of the Severe Snow Use Symbol (3 peak mountain snowflake).

3.1.16.2 Discussion—

ASTM has validated Specification **F2493** for future use as a primary reference tire for the Severe Snow Use Symbol (3 peak mountain snowflake). As of 2020 the Specification **E1136** P195/75R14 92S Standard Reference Test Tire is expected to cease production. Upon that occurrence, the Specification **F2493** P225/60R16 97S Standard Reference Test Tire is an acceptable replacement for the Specification **E1136** SRTT.

3.1.17 *surface monitoring tire, n*—a reference tire used to evaluate changes in the test surface over a selected time period. **F538**

⁶ Available from the U.S. Tire Manufacturers Association, 1400 K Street, N.W., Washington D.C. 20005-20005, www.ustires.org/publications.

3.1.18 *test (or testing), n*—a procedure performed on an object (or set of nominally identical objects) using specified equipment that produces data unique to the object (or set). **F538**

3.1.18.1 *Discussion*—

Test data are used to evaluate or model selected properties or characteristics of the object (or set of objects). The scope of testing depends on the decisions to be made for any program, and sampling and replication plans (see definitions below) need to be specified for a complete program description.

3.1.19 *test matrix, n*— *in tire testing* a group of candidate tires, usually with specified reference tires; all tests are normally conducted in one testing program. **F538**

3.1.20 *test run, n*—a single pass of a loaded tire over a given test surface. **F538**

3.1.21 *test tire, n*—a tire used in a test. **F538**

3.1.22 *test tire set, n*—one or more test tires, as required by the test equipment or procedure, to perform a test, thereby producing a single test result. **F538**

3.1.22.1 *Discussion*—

The four nominally identical tires required for vehicle stopping distance testing constitute a test tire set. In the discussion below where the test tire is mentioned, it is assumed that the test tire set may be substituted for the test tire, if a test tire set is required for the testing.

3.1.23 *traction test, n*— *in tire testing*, a series of n test runs at a selected operational condition; a traction test is characterized by an average value for the measured performance parameter. **F538**

3.1.24 *vertical load, n*—the normal reaction of the tire on the road which is equal to the negative of normal force. **F538**

4. Summary of Test Method

4.1 These test methods describe the use of an instrumented vehicle with a single test wheel capable of measuring the tire performance properties under drive torque on snow and ice surfaces when traveling in a straight line.

4.2 The test is conducted by driving the test vehicle over the test surface. Driving torque is gradually increased to the test wheel while maintaining the vehicle speed by applying braking torque to the non-test wheels of the vehicle. The driving traction coefficient is determined from the measured values of longitudinal and vertical forces over a specified slip or time range. The recommended vehicle test speed is 8.0 km/hr (5.0 mph).

5. Significance and Use

5.1 This test method describes a technique for assessing the performance characteristics of tires in a winter environment on snow and ice surfaces. When snow is referred to hereafter, ice is implied as appropriate.

5.2 The measured values quantify the dynamic longitudinal traction properties of tires under driving torque. Dynamic traction properties are obtained on snow surfaces prepared in accordance with the stated test procedures and attempts to quantify the tires' performance when integrated into a vehicle-environmental system. Changing any one of these environmental factors will change the measurements obtained on a subsequent test run.

5.3 This test method addresses longitudinal driving traction properties only on snow and ice surfaces. Refer to Test Methods **F1572** for test methods for braking and lateral traction properties on snow or ice, or both.

6. Interferences

6.1 Factors that may affect tire snow performance and must be considered in the final analysis of data include:

- 6.1.1 Snow temperature,
- 6.1.2 Ambient temperature,
- 6.1.3 Mechanical breakdown of the agglomerated snowflake into granular crystals,
- 6.1.4 Solar load,
- 6.1.5 Tire temperature,
- 6.1.6 Tire wear condition (preparation),
- 6.1.7 Tire pressure,
- 6.1.8 Tire vertical load,
- 6.1.9 Snow surface characteristics, and
- 6.1.10 Rim selection.

7. Apparatus

7.1 The test vehicle shall have the capability of maintaining the specified test speed ± 0.8 km/h (± 0.5 mph) during all levels of driving torque application.

7.2 The test vehicle shall be equipped with an automatic throttle actuator to allow the gradual increase of driving torque at a predetermined (repeatable) rate.

7.3 The test vehicle shall be a rear drive, four wheel passenger car or a light truck less than or equal to 44.5 kN (10 000 lbf) GVW. The range of test tires and load conditions will determine the vehicle size and selection. Utilizing a front wheel drive test vehicle is not addressed in this standard although the basic procedures could be applied with appropriate conditional modifications.

7.4 The test vehicle shall be instrumented to measure longitudinal and vertical forces at the tire and test surface interface during the application of driving torque.

7.5 The test vehicle shall have provisions to automatically and completely disengage the brake on the test wheel (if installed) prior to throttle application. Complete disengagement is necessary to eliminate all drag that might be caused by the brake assembly.

7.6 *Opposite Tire:*

7.6.1 The tire installed opposite the instrumented test wheel shall have a sufficiently large traction coefficient to minimize slip of this tire during the traction test. The opposite tire should have a coefficient at least 50 % greater than the expected coefficient of the test tire. A tire chain may be utilized to increase the traction of the opposite tire when testing on snow surfaces.

7.6.2 The opposite tire shall be selected to have an outside diameter that is within ± 2.5 cm (± 1 in.) of that of the test tire.

7.7 A suitable ride height adjustment system on the rear axle shall be provided to permit adjustment for each tire size and load to minimize transducer crosstalk as established during calibration.

7.8 *Instrumentation*—The test wheel position on the test vehicle shall be equipped with a wheel rotational velocity measuring system and with transducers to measure the dynamic longitudinal force and vertical load at the test wheel.

7.8.1 *General Requirements for Measurement System*—The instrumentation system shall conform to the following overall requirements at ambient temperatures between -23 and 43°C (-10 and 110°F):

7.8.1.1 *Overall system accuracy, force*— ± 1.5 % of vertical load or traction force from 450 N (100 lbf) to full scale.

7.8.1.2 *Overall system accuracy, speed*— ± 1.5 % of speed from 6.4 km/h (4.0 mph) to 48.0 km/h (30.0 mph).

7.8.1.3 *Shunt Calibration*—All strain-gage transducers shall be equipped with shunt calibration resistors that can be connected before or after test runs. The calibration signal shall be in the range of the expected measurement for each analogue channel..

7.8.1.4 *Ruggedness*—The exposed portions of the system shall tolerate 100 % relative humidity (rain or spray) and all other adverse conditions such as dust, shock, and vibrations which may be encountered in regular operation.

7.8.2 *Vehicle Speed*—Vehicle forward speed (normally obtained from a front non-driven wheel on the test vehicle) shall be measured digitally with an encoder or optical system having a minimum of 500 counts per revolution. Output shall be directly visible to the driver and shall be simultaneously recorded. It may be necessary on a very low coefficient surface, that is, ice, to disconnect any braking action to the wheel being utilized for measuring vehicle speed. A separate fifth-wheel system may be utilized to measure vehicle forward speed.

7.8.3 *Test Wheel Speed*—Test wheel speed shall be measured digitally with an encoder or optical system having a minimum of 1000 counts per wheel revolution. The output shall be recorded.

7.8.4 *Vertical Load*—The vertical load-measuring transducer shall measure the vertical load at the test wheel during driving torque application. The transducer full scale range shall be in excess of the dynamic loading during a test. Data points shall be evaluated to ensure dynamic loading is within the calibrated range of the transducer. The static load should be less than 80 % of the calibrated range. The transducer design and location shall minimize inertial effects and vibration-induced mechanical resonance. The transducer shall have an output directly proportional to the force with less than 1 % hysteresis and less than 1 % nonlinearity at full scale. It shall have less than 2 % cross-axis sensitivity at full scale. The transducer shall be installed in such a manner as to experience less than 1° angular rotation with respect to its measuring axes at a maximum expected driving torque. The transducers typically have a minimum full scale range of 0 to 8.9 kN (2000 lbf).

7.8.5 *Driving Traction Forces*—The driving traction force-measuring transducers shall measure longitudinal force generated at the tire-road interface as a result of driving torque application with a full scale range of at least 100 % of the applied static vertical load. Otherwise, the transducers shall have the same specifications as those described in 7.8.4.

7.8.6 *Signal Conditioning and Recording System*—All signal conditioning and recording equipment shall provide linear output with necessary gain and reading resolution to meet the requirements of 7.8.1. Additionally, it shall have the following specifications:

7.8.6.1 *Minimum Frequency Response*—flat from dc to 18 Hz, within ± 1 %,

NOTE 1—Based on a study of a sample acquisition and force transducer system, a resonant frequency of 20 Hz was measured.

7.8.6.2 *Signal-to-Noise Ratio*—at least 20/1,

7.8.6.3 Gain shall be sufficient to permit full-scale display for full-scale input signal level,

7.8.6.4 Input impedance shall be at least ten times larger than the output impedance of the signal source,

7.8.6.5 The system must be insensitive to vibrations, acceleration, and changes in ambient temperature. The error in reading shall not exceed 1 % full scale when subjected to vibration acceleration of 49.0 m/s^2 (5 g's) in the 0.5 to 40 Hz frequency range and operating temperature range from -23 to 43°C (-10 to 110°F),

7.8.6.6 The system shall not be affected by storage temperature variations between -40 and 71°C (-40 and 160°F),

7.8.6.7 The individual data inputs shall have a sample rate of not less than 100 samples/s. For a given sample, vehicle speed, test wheel speed, vertical load, and driving traction force shall all be recorded within 0.0005 s,

7.8.7 *Power Supply*—The power supply for transducers and recording system shall meet or exceed requirements specified by transducer and recorder manufacturers.

7.8.8 Temperature measurement devices for taking surface and ambient temperatures shall have a resolution of 0.5°C (1°F) and an accuracy of $\pm 1^\circ\text{C}$ ($\pm 2^\circ\text{F}$).

7.8.9 Pressure measurement devices for setting tire pressure shall have a resolution of 3.5 kPa ($\frac{1}{2}$ psi) and an accuracy of ± 3.5 kPa ($\pm \frac{1}{2}$ psi).

8. Calibration

8.1 All instrumentation shall be calibrated within six months prior to testing.

8.2 Calibrate the reference load cell by inputting known vertical and horizontal forces. The known forces must be traceable to the National Institute of Standards and Technology (NIST).

8.3 Calibrate the transducer for measuring vertical and horizontal forces on the test wheel with the reference load cell in accordance with Practice **F377**.

8.3.1 For longitudinal force calibration, place vehicle transmission in “park” position. Restrain the test vehicle using the vehicle brakes normally used while testing.

8.4 Calibrate the vehicle and test tire speed transducers and any other instrumentation in accordance with the manufacturers’ specification.

8.5 Calibrate temperature measuring devices (snow and ambient temperatures) in accordance with the manufacturer’s recommendations.

8.6 Calibrate pressure measuring devices in accordance with the manufacturer’s recommendations.

9. Selection and Preparation of Test Tires

9.1 Ensure all test tires are approximately the same age and stored essentially at the same conditions prior to testing unless otherwise specified. When testing to the requirements of the latest version of Tire Information Service Bulletin Vol. 37/No. 5, 37, the SRTT Specification **E1136** (or Specification **F2493**) control tire shall be less than 2 years old based on the week/year manufacture date molded into the tire sidewall.

9.2 Test tires shall have no evidence of force or run-out grinding.

9.3 New test tires shall be trimmed to remove all protuberances in the tread area caused by mold air vents or flashing at mold junctions.

9.4 Any objects (for example, shipping labels) in the tread area shall be removed prior to testing.

9.5 Tires that have been buffed to simulate wear must be prepared and run until all evidence of buffing is removed in accordance with Guide **F1046**.

9.6 Mount the test tires on rims specified by the appropriate tire and rim standards organization, using conventional mounting methods. Ensure proper bead seating by the use of a suitable lubricant. Excessive use of lubricant should be avoided to prevent slipping of the tire on the wheel rim. Ensure tires are mounted so the intended rotational direction of the tire corresponds with the test wheel position of the test vehicle. If rotation direction of the tire is not specified, the tire shall be mounted so during testing it rotates clockwise when viewed from the intended outboard sidewall of the tire.

9.7 Test tire balance is not necessary.

9.8 New test tire break-in is optional, however, the design of the test may necessitate on-the-road conditioning of up to 322 km (200 miles). Tire break-in may improve repeatability of results on ice surfaces.

9.9 Mounted test tires shall be placed near the test site in such a location that they all have the same temperature prior to testing. Test tires should be shielded from the sun to avoid excessive heating by solar radiation.

9.10 Test tires shall be checked and adjusted for specified pressure just prior to testing.

10. Preparation of Apparatus

10.1 All transducers and instrumentation shall have been calibrated in accordance with Section 8.

10.2 Turn on the test vehicle instrumentation and allow it to warm up as required for stabilization.

- 10.3 Ensure the test vehicle has sufficient fuel to complete a test matrix.
- 10.4 Maneuver the test vehicle to the tire changing area.
- 10.5 Position the temperature measurement devices.
- 10.6 Allow sufficient time to ensure that the temperatures of all equipment have stabilized.
- 10.7 Set the front speed reference tire or fifth wheel to the pressure utilized during the speed calibration ± 3.5 kPa (± 0.5 psi). Non-test rear tire pressures should be set as appropriate.
- 10.8 Perform a resistive shunt calibration on the force transducers once per day at a minimum. It is recommended that a resistive shunt calibration check be performed at the start and end of each testing day.

11. Procedure

- 11.1 *Course Surface*—See **Annex A1 – Annex A4** for environmental and snow properties, surface characterization, course preparation, and course maintenance. When testing to the requirements of the Tire Information Service Bulletin Vol. 37/No. 5,6, a medium-packed snow surface shall be used.
- 11.2 Lift the rear axle so that the rear tires are off the ground.
- 11.3 Install a control or candidate tire at the test wheel position with the vehicle jacked up.
- 11.4 Opposite the test wheel position install a tire that has an outside diameter within ± 2.5 cm (± 1 in.) of the test tire. A chained tire is optional in snow.
- 11.5 Record basic test information and tire conditions. Ambient and surface temperatures shall be updated with each control tire.
- 11.6 With the transmission in park or neutral, tare vertical load and tractive force by zeroing the signals.
- 11.7 Verify the vehicle and test wheel speeds are zero.
- 11.8 Lower the rear axle, placing the tires on the ground.
- 11.9 Ballast the test tire for the desired load, ± 22 N (± 5 lbf), and set the tire to the specified test inflation pressure, ± 3.5 kPa (± 0.5 psi). One of the following three options shall be selected for determining load and inflation pressure for testing. The option selected shall be noted in the final report. If computed test load exceeds the test equipment capabilities, test inflation rated load

TABLE 1 Test Load and Test Pressure Options

F1805 Test Option	Tire Type	Marked Sidewall max psi	F1805 Test Load	F1805 Test Pressure psi
1	Passenger car tire (TRA/ETRTO/JATMA)	Any	70 % of Maximum rated load or 567 kgf (1250 lbf) max	36
	Light Truck (TRA/ETRTO/JATMA)	Any	70 % of Maximum rated load or 567 kgf (1250 lbf) max	51
2	Pmetric LL,SL	35	74 % * table value at test pressure	35
		44	74 % * table value at test pressure	35
		51	74 % * table value at test pressure	35
	Pmetric XL	41	74 % * table value at test pressure	41
		50	74 % * table value at test pressure	41
	LT-metric		74 % * table value at test pressure	50
	Flotation-LT		74 % * table value at test pressure	35
	Eurometric C (Commercial LT)		74 % * table value at test pressure	51
	Eurometric SL	32	74 % * table value at test pressure	32
		36	74 % * table value at test pressure	36
		44	74 % * table value at test pressure	36
		51	74 % * table value at test pressure	36
		Eurometric XL	42	74 % * table value at test pressure
			51	74 % * table value at test pressure
3	Any		Any	Any

and its corresponding pressure may be reduced to the next lower load/pressure increment and a new test load/pressure recomputed. See **Annex A5** for examples of load and pressure determination for options 1 and 2. **Table 1** summarizes the various test load and pressure options.

NOTE 2—A P195/75R14 SRTT (Specification **E1136**) control tire is tested at a load of 468 kgf (1031 lbf) and a pressure of 240 kPa (35 psi). A P225/60R16 SRTT (Specification **F2493**) control tire is tested at a load of 531 kgf (1171 lbf) and a pressure of 240 kPa (35 psi).

11.9.1 *Option 1*—The test load for passenger car tires shall be the lower value of 70 % of the maximum rated load of the tire or 567 kgf (1250 lbf). The test load for light truck tires shall be the lower value of 70 % of the maximum rated load of the tire or 567 kgf (1250 lbf). An inflation pressure of 250 kPa (36 psi) shall be used for passenger tires and 350 kPa (51 psi) shall be used for light truck tires.

11.9.2 *Option 2*—The test load shall be equal to 74 % of the rated load at the test inflation pressure as shown in the Tire & Rim Association (TRA) Year Book, in the European Tyre and Rim Technical Organisation Manual (ETRTO), or in the Japan Automobile Tyre Manufacturers Association Manual (JATMA). See **Table 1**. This option meets the requirement for equivalent percentage loads as specified in the USTMA Tire Information Service Bulletin Vol. 37/No. 5-6.

11.9.3 *Option 3*—The test tire loads and inflation pressures shall be any other loads and pressures required to meet the individual requirements of a specific test program.

11.10 Adjust the vehicle ride height to the value established during the calibration for minimum crosstalk taking into account differences in tire dimensions.

11.11 Re-verify test load. Adjusting vehicle ride height may change the test load. Several load/ride height adjustments may be necessary before meeting both requirements.

11.12 Calibrate the test wheel speed for each test tire by bringing the vehicle up to approximately 8 km/h (5.0 mph). Place the vehicle in neutral or reduce throttle position to a minimum. Adjust the test wheel speed to be equal to vehicle speed. Care must be taken to see that the vehicle is going in a straight line without tire slippage during speed calibration.

11.13 Set the automatic throttle applicator to keep fore-aft force increase to less than a maximum of 1780 N/s (400 lbf/s).

11.14 Begin a test by activating the automatic throttle applicator when on the test course. A straight line should be maintained throughout testing and a smooth modulated brake load applied to maintain an 8.0 ± 0.8 km/h (5.0 ± 0.5 mph) test vehicle speed. In the course of testing do not use any test run when a test tire digs through the base material or where the average vehicle speed is outside 8.0 ± 0.8 km/h (5.0 ± 0.5 mph).

11.15 Repeat step 11.14 a minimum of ten times. At the completion of ten or more test runs, process the data and examine for a minimum of eight valid test runs after outliers (individual test run data values more than 1.5 standard deviations from the calculated average) have been eliminated and for a calculated sample coefficient of variation (C.V.) less than 0.15 (15 %). If requirements are met, record data and return to the tire changing area. Rerun the test tire if requirements are not met.

11.16 Run a control tire at the beginning and end of each test sequence or test matrix and every third test in between. For example: C, T1, T2, C, T3, T4, C, where C represents a control tire and T represents a candidate tire.

NOTE 3—A single control or candidate tire may be used repeatedly as long as the tread surface maintains a “new” appearance.

11.17 Each candidate tire should be tested at least three times, preferably on different days.

11.18 Each new test tire shall be run on a surface as near as possible to the previous pass. Care must be taken not to allow the test tire to drift into disturbed snow used during previous test runs.

11.19 Testing continues until the total test sequences or test matrix is completed or the available test surface is exhausted. Regrooming the course will normally allow testing to continue.

12. Calculation

12.1 For each test run of each control and candidate tire, read from accumulated data the values of longitudinal force and vertical load corresponding to the values of longitudinal slip velocity within the range 1.6 and 24 km/h (1 and 15 mph) or a range starting at 3.2 km/h (2 mph) and continuing for 1.5 s. Calculate the average force and load values over the specified slip or time range. Calculate the average values of driving coefficient as follows:

$$u = \frac{F}{W} \quad (1)$$

where:

u = average driving coefficient,

F = average longitudinal force kN or lbf, and

W = average vertical load kN or lbf.

12.2 Calculate the values of longitudinal slip velocity as follows: