# TECHNICAL REPORT

# ISO/IEC TR 10192-2

First edition 2000-10

Information technology – Home Electronic System (HES) interfaces –

Part 2: Simple Interface Type 1

iTeh STANDARD PREVIEW (standards.iteh.ai)



# iTeh STANDARD PREVIEW (standards.iteh.ai)

# TECHNICAL ISO/IEC REPORT – TYPE 2 TR 10192-2

First edition 2000-10

Information technology – Home Electronic System (HES) interfaces –

Part 2: Simple Interface Type 1

iTeh STANDARD PREVIEW (standards.iteh.ai)

ISO/IEC TR 10192-2:2000 https://standards.iteh.ai/catalog/standards/sist/369fbf4b-a780-47b0-9cd1-efla2e179465/iso-iec-tr-10192-2-2000

#### © ISO/IEC 2000

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

ISO/IEC Copyright Office • Case postale 56 • CH-1211 Genève 20 • Switzerland



PRICE CODE

F

# **CONTENTS**

			Page
FO	REW	ORD	4
INT	RODI	JCTION	6
Cla	ıse		
1	Scop	e	7
2	Norm	native references	7
3	Defir	nitions	7
4	Abbr	eviations	8
5	Basi	principles of the Simple Interface type 1 (SI type 1)	9
6	Fund	tional characteristics of the SI type 1	10
	6.1	Signal types and pin assignments	10
7	Elect	rical characteristics of the SI type 1	11
	7.1	Currents and voltages on the SI type 1 conductors	11
	7.2	Signal forms at the SI type 1  Maximum allowed voltages on the SI type 1 conductors	12
	7.3		
	7.4	Isolation characteristics	12
8	Mech	nanical characteristics of the Statype 19192-22000 https://standards.iteh.ai/catalog/standards/sist/369fbf4b-a780-47b0-9cd1-	13
9		Mechanical characteristics of the Stype 10192-2:2000 https://standards.iteh.ai/catalog/standards/sist/369fbf4b-a780-47b0-9cd1- Safety of SI type 1 devices and NAUS 3780-jec-tr-10192-2-2000	
10		ng of SI type 1 devices	
		Test conditions	
		Test circuit for the SI type 1 device	
		Functional test of SI type 1 devices	
	10.4	Short circuit test for SI type 1 devices	13
Anı	nex A	(informative) Photocoupler based implementation	14
		(informative) Characteristics of the SI type 1 connector	
, 1111	B.1	SI type 1 device and NAU connector mechanical characteristics	
	B.2	Connector ratings	
Rih	lioara	phy	17
_ 10	ug.a	r'',	17

Figure 1 – Basic reference model for the SI type 1	9
Figure 2 – Signals passing the SI type 1	10
Figure 3 – Currents and voltages on the SI type 1 conductors	11
Figure 4 – Signal forms at the SI type 1	12
Figure 5 – SI type 1 device testing	13
Figure A.1 – Basic configuration	14
Figure B.1 – SI type 1 device and NAU connector (male)	15
Figure B.2 – SI type 1 cable connector (female)	16
Table 1 – Signal type, symbols, potentials and pin assignments for the SI type 1	10
Table 2 – Electrical characteristics of SI type 1	11

# iTeh STANDARD PREVIEW (standards.iteh.ai)

## INFORMATION TECHNOLOGY – HOME ELECTRONIC SYSTEM (HES) INTERFACES –

### Part 2: Simple Interface Type 1

#### **FOREWORD**

- 1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.
- 2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
- 3) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

The main task of IEC and ISO technical committees is to prepare International Standards. In exceptional circumstances, a technical committee may propose the publication of a technical report of one of the following types:

- type 1, when the required support cannot be obtained for the publication of an International Standard, despite repeated efforts;
- type 2, when the subject is still Sunder Technical Odevelopment or where, for any other reason, there list the notation of t
- type 3, when the technical committee has collected data of a different kind from that which is normally published as an International Standard, for example 'state of the art'.

Technical reports of types 1 and 2 are subject to review within three years of publication to decide whether they can be transformed into International Standards. Technical reports of type 3 do not necessarily have to be reviewed until the data they provide are considered to be no longer valid or useful.

ISO/IEC 10192-2, which is a technical report of type 2, was prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

This publication was drafted in accordance with ISO/IEC directives, Part 3.

This document is issued in the type 2 technical report series of publications (according to 15.2.2 of the Procedures for the technical work of ISO/IEC JTC 1 (1998)) as a prospective standard for provisional application in the field of the Home Electronic System (HES), because there is an urgent requirement for guidance on how standards in this field should be used to meet an identified need.

This document is not to be regarded as an International Standard. It is proposed for provisional application so that information and experience of its use in practice may be gathered. Comments on the content of this document should be sent to IEC Central Office.

A review of this type 2 technical report will be carried out not later than three years after its publication with the option of extension for a further three years or conversion either to an International Standard or withdrawal.

This document which is purely informative is not to be regarded as an International Standard.

Annexes A and B are for information only.

# iTeh STANDARD PREVIEW (standards.iteh.ai)

#### INTRODUCTION

A Simple Interface (SI) is an interface between devices and a home network in the Home Electronic System (HES).

The SI type 1 connects simple devices offering and accepting only a two state signal to an HES home network. Two signals are available at the SI type 1. One is a control signal for turning the device on and off. The other is a monitor signal for checking the state of the device.

ISO/IEC 10192: Information technology – Home Electronic System (HES) interfaces presently consists of two parts:

- Part 1: Universal interface class 1
- Part 2: Simple interface type 1

# iTeh STANDARD PREVIEW (standards.iteh.ai)

# INFORMATION TECHNOLOGY – HOME ELECTRONIC SYSTEM (HES) INTERFACES –

### Part 2: Simple Interface Type 1

#### 1 Scope

This part of ISO/IEC 10192-2 specifies the mechanical, electrical, functional and procedural characteristics of a specific Simple Interface (SI). The SI type 1 is a physical interface realized between the SI type 1 device and the SI type 1 Network Access Unit, NAU. It also serves as a reference point.

#### 2 Normative references

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of ISO/IEC 10192. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of ISO/IEC 10192 are encouraged to investigate the possibility of applying the most recent edition of the normative document indicated below. For undated references, the latest edition of the normative document referred to applies. Members of IEC and ISO maintain registers of currently valid International Standards.

## (standards.iteh.ai)

IEC 60364, Electrical Installations of buildings

ISO/IEC TR 10192-2:2000

IEC 60664 (all parts) Insulation coordination for equipment within low-yoltage systems

efla2e179465/iso-iec-tr-10192-2-2000

IEC 60068-2 (all parts), Environmental testing

IEC 60950, Safety of information technology equipment

#### 3 Definitions

For the purpose of this Technical Report the following definitions apply.

#### 3.1

#### simple interface

interface above the application layer to be used for and by simple devices such as actuators and sensors within an HES

The SI type 1 offers only one/zero commands and accepts only one/zero entries. The specification of the SI type 1 includes the necessary mechanical, electrical, functional and procedural characteristics of the interface.

#### 3.2

#### process interfaces

a family of interfaces above the application layer between a home network and the devices to be connected to it

#### 3.3

#### SI network access unit, SI NAU

NAU supporting and offering an SI

#### 3.4

#### SI device

device supporting and offering an SI

#### 3.5

#### SI conductors

conductors connecting an SI NAU and an SI device

#### 3.6

#### SI connection

connection point between the SI cable (where applicable) and the SI device

#### 3.7

#### isolating functions

functions providing safety isolation between the SI device and the SI NAU

#### 3.8

#### on state

state in which the SI device is performing its intrinsic function

#### 3.9

#### off state

state in which the SI device is not performing its intrinsic function

## iTeh STANDARD PREVIEW

### 3.10

### control signal

signal transmitted via the SI NAU to the SI device to set the state of the SI device

#### ISO/IEC TR 10192-2:2000 3.11

#### monitor signal

https://standards.iteh.ai/catalog/standards/sist/369fbf4b-a780-47b0-9cd1-

signal indicating the state of the SI device transmitted from the SI device to the SI NAU

#### 3.12

#### static monitor signal

one of two forms of the monitor signal, characterized by the high signal state during the device on state and the low signal state during the device off state

#### 3.13

#### dynamic monitor signal

one of two forms of the monitor signal, in which the device on state is represented by the monitor signal continuously being switched between the high and low signal levels

#### **Abbreviations**

The following abbreviations are used in this Technical Report.

HES: Home Electronic System NAU: **Network Access Unit** PI: **Process Interface** 

SI: Simple Interface

### 5 Basic principles of the Simple Interface type 1 (SI type 1)

The SI type 1 is an interface between simple devices and home networks making the devices network independent. It is one of the family of Process Interfaces. The basic reference model for the SI type 1 is the same as for all Process Interfaces (see figure 1). The difference from other PIs lies in the different services offered to the device via the SI type 1.




Figure 1 - Basic reference model for the SI type 1