



Designation: D4150 – 20

Standard Terminology Relating to Gaseous Fuels¹

This standard is issued under the fixed designation D4150; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This standard defines the terms used in standards that are the responsibility of Committee D03 on Gaseous Fuels. These terms are used in:

- 1.1.1 The sampling of gaseous fuels,
- 1.1.2 The analysis of gaseous fuels for composition and various other physical properties, and
- 1.1.3 Other practices related to the processing, transmission, and distribution of gaseous fuels.

1.2 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*²

- D1142 Test Method for Water Vapor Content of Gaseous Fuels by Measurement of Dew-Point Temperature
- D1835 Specification for Liquefied Petroleum (LP) Gases
- D3588 Practice for Calculating Heat Value, Compressibility Factor, and Relative Density of Gaseous Fuels
- D4175 Terminology Relating to Petroleum Products, Liquid Fuels, and Lubricants

2.2 *ISO Standards:*³

- ISO 7504 Gas Analysis—Vocabulary
- ISO 14687 Hydrogen Fuel Quality—Product Specification

2.3 *SAE Standard:*⁴

- SAE J2719 Hydrogen Fuel Quality for Fuel Cell Vehicles

¹ This terminology is under the jurisdiction of ASTM Committee D03 on Gaseous Fuels and is the direct responsibility of Subcommittee D03.92 on Terminology Classification and Specifications.

Current edition approved July 15, 2020. Published August 2020. Originally approved in 1982. Last previous edition approved in 2019 as D4150 – 19. DOI: 10.1520/D4150-20.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ Available from International Organization for Standardization (ISO), ISO Central Secretariat, BIBC II, Chemin de Blandonnet 8, CP 401, 1214 Vernier, Geneva, Switzerland, http://www.iso.org.

⁴ Available from SAE International (SAE), 400 Commonwealth Dr., Warrendale, PA 15096, http://www.sae.org.

2.4 *GPA Standard:*⁵

- GPA 2145 Table of Physical Properties for Hydrocarbons and Other Compounds of Interest to the Natural Gas and Natural Gas Liquids Industries

3. Terminology

absolute pressure, *n*—the pressure relative to an ideal vacuum.

DISCUSSION—The absolute pressure can be expressed in kPa, mm Hg, bar, psia, etc., as defined by the application.

DISCUSSION—An ideal vacuum is the best vacuum available using the application.

acid gas, *n*—natural gas containing high concentrations of hydrogen sulfide or carbon dioxide, or both, which is acidic when in contact with water or water vapor.

associated gas, *n*—natural gas, also known as gas-cap gas or dome gas, that overlies and is in immediate contact, but not in solution, with crude oil in a reservoir.

at-line instrument, *n*—instrument requiring operator interaction to sample gas directly from the pipeline.

base conditions, *n*—temperature and pressure conditions at which natural gas volumes are determined for purposes of custody transfer.

DISCUSSION—In natural gas measurements, the properties of interest are temperature, pressure, and composition. Assuming ideal gas properties, for simplicity, tables of pure compounds can be prepared for use in calculating gas properties for any composition at “base conditions.” These “base conditions” are chosen near ambient.

British thermal unit (Btu or BTU), *n*—the amount of energy required to raise the temperature of one pound of water one-degree Fahrenheit.

DISCUSSION—One Btu is defined in the International Steam Table (IT) as equal to 1055.056 J. The defining relationships are:

(a) $1 \text{ Btu} \cdot \text{lb}^{-1} = 2.326 \text{ J} \cdot \text{g}^{-1}$ (exact)

(b) $1 \text{ lb} = 453.59237 \text{ g}$ (exact).

By these relationships, $1 \text{ Btu} = 1055.05585262 \text{ J}$ (exact). For most purposes, the value rounded to $1 \text{ Btu} = 1055.056 \text{ J}$ is adequate.

⁵ Available from Gas Processors Association (GPA), 66 American Plaza, Suite 700, Tulsa, OK 74135, http://www.gpaglobal.org.

calibration gas mixture, *n*—a certified gas mixture of sufficient stability and homogeneity with known composition used for the calibration of a measuring instrument or for the validation of a measurement or gas analytical method.

DISCUSSION—Calibration Gas Mixtures are the analogues of measurement standards in physical metrology (reference ISO 7504 paragraph 4.1).

DISCUSSION—The accuracy of the calibration gas mixture must meet the requirements of the measurement being performed.

calorimeter, *n*—a device to measure the evolved heat resulting from the combustion of a material.

compressed natural gas (CNG), *n*—natural gas that has been compressed after processing for storage or transportation purposes.

DISCUSSION—CNG is primarily used as a fuel for vehicles, typically compressed up to 24 821 kPa in the gaseous state.

compressibility, *n*—the property of a material that permits it to decrease in volume when subjected to an increase in pressure.

compressibility factor (*z*), *n*—a factor calculated by taking the ratio of the actual volume of a given mass of gas at a specified temperature and pressure to its volume calculated from the ideal gas law at the same conditions.

constituent, *n*—component, compound, or element found within a mixture.

contaminant, *n*—an impurity that could cause reversible or irreversible damage, harm, or be detrimental to transportation and storage systems, end-use equipment, users, or the environment.

continuous fuel monitor, *n*—instrument that samples gas directly from a source and provides an analytical result on a continuous or semi-continuous basis.

dew point, *n*—the temperature at any given pressure at which liquid initially condenses from a gas or vapor and is specifically applied to the temperature at which water vapor starts to condense from a gas mixture (**water dew point**), or at which hydrocarbons start to condense (**hydrocarbon dew point**).

DISCUSSION—Charts of dewpoints versus pressure and water content are found in Test Method **D1142**.

direct sampling, *n*—sampling where there is a direct connection between the sample source and the analyzer.

dissolved gas, *n*—natural gas held in solution in reservoir liquids at the prevailing temperature and pressure of the reservoir.

dry gas, *n*—natural gas containing little or no water vapor.

dynamic calibration, *n*—calibration of an analytical system using a gaseous standard generated by dilution of the flow of a known quantity of gaseous analyte with a known quantity of diluent gas.

DISCUSSION—The analyte does not have to be from only a compressed gas source; it may be from a permeation system, liquid source, chemically generated, etc.

DISCUSSION—The diluent gas does not necessarily need to be purified. The minimum purity depends on the critical impurities in the final gas mixture.

fuel, *n*—any material that can be oxidized with the intent to release energy.

fuel cell grade hydrogen, *n*—hydrogen satisfying the specifications in SAE J2719 or ISO 14687, Grade D.

gas, *n*—a state of matter that shows free flow, has neither a definite shape nor a definite volume, and tends to expand indefinitely to fill any space available, irrespective of its quantity. **[D02.95] D4175**

gas quality, *n*—quality of gaseous fuel, which is defined by its composition and its physical properties.

gaseous, *adj*—describing material exhibiting free flow, with neither a definite shape nor a definite volume, and tending to expand indefinitely to fill any space available, irrespective of its quantity. **[D02.95] D4175**

gaseous fuel, *n*—any gaseous material that can be oxidized with the intent to release energy.

DISCUSSION—Examples of gaseous fuels include, but are not limited to, natural gas, digester gas, landfill gas, process gas, hydrogen gas, or any gaseous fuel stored or transported as a liquid, such as liquefied petroleum gas or liquefied natural gas.

gauge pressure, *n*—the pressure measured relative to atmospheric pressure.

DISCUSSION—The gauge pressure can be expressed in kPag, barg, psig, etc., as defined by the application.

DISCUSSION—Gauge pressure is positive for pressures above atmospheric pressure and negative for pressures below atmospheric pressure. Zero gauge pressure is equal to atmospheric pressure.

gross heating value, *n*—also called **higher heating value**, the amount of energy per volume transferred as heat from the complete, ideal combustion of the gas at standard temperature in which all the water formed by the reaction condenses to liquid.

DISCUSSION—If the gross heating value has a volumetric rather than a mass or molar basis, a base pressure must also be specified.

DISCUSSION—The values for the pure gases appear in GPA Standard 2145. **D3588**

higher heating value, *n*—see **gross heating value**.

hydrate, *n*—a solid, crystalline material composed of water and components of natural gas formed under pressure at temperatures above the freezing point of water.

hydrocarbon dew point, *n*—see **dew point**.

inert components, *n*—those elements or components of natural gas (fuel gas) that do not contribute to the heating value.

in-line instrument, *n*—instrument with an active element installed in the pipeline, measuring pipeline contents or conditions, and measures at pipeline conditions.