



Edition 3.0 2023-04 REDLINE VERSION

INTERNATIONAL STANDARD



Field Device Integration (FDI)® – Standards
Part 101-2: Profiles – Foundation Fieldbus HSE

The standards item at the standards item at the standards item.

IEC 62769-101-2:2023

https://standards.iteh.ai/catalog/standards/iec/221t4dc8-58c6-4ad2-b923-235t25e3det9/iec-62769-101-2-2023





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2023 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Tel.: +41 22 919 02 11

info@iec.ch

IEC Secretariat 3, rue de Varembé CH-1211 Geneva 20

www.iec.ch Switzerland

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublishedStay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.



IEC 62769-101-2

Edition 3.0 2023-04 REDLINE VERSION

INTERNATIONAL STANDARD



Field Device Integration (FDI)® – Standards
Part 101-2: Profiles – Foundation Fieldbus HSE

Document Preview

IEC 62769-101-2:2023

https://standards.iteh.ai/catalog/standards/iec/221f4dc8-58c6-4ad2-h923-235f25e3def9/iec-62769-101-2-2023

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 25.040.40; 35.100.05 ISBN 978-2-8322-6848-3

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

Ε.	JKEWC		4		
1	Scop	oe	6		
2	Normative references				
3	Term	ns, definitions, abbreviated terms and conventions acronyms	7		
	3.1	Terms and definitions			
	3.2	Abbreviated terms and acronyms			
4	Conv	ventions			
	4.1	EDDL syntax	7		
	4.2	XML syntax			
5		le for CP 1/2 (Foundation™ HSE)			
	5.1	General			
	5.2	Catalog profile			
	5.2.1				
	5.2.2				
	5.2.3				
	5.2.4				
	5.3	Associating a Package with a CP 1/2 device			
	5.3.1				
	5.3.2	71	a		
	5.4	Information Model manning	و م		
	5.4.1	Information Model mappingProtocolType definition	a		
	5.4.2		9		
	5.4.3	FunctionalGroup Identification definition	10		
	5.4.4	•			
	5.4.5				
	25.5rds	Topology elements	769-101-2-		
	5.5.1				
	5.5.2				
	5.5.3				
	5.5.4	·			
	5.6		15		
	0.0	mourous			
	5.6.1				
	5.6.2	,			
А		(normative) Topology scan schema			
	A.1	General			
	A.2	Target Namespace			
	A.3	Network			
	A.4	FoundationHSEAddressT			
	A.5	FoundationHSEConnectionPointT			
	A.6	FoundationHSENetworkT			
	A.7	FoundationBlockIdentificationT			
	A.8	FoundationIdentificationT			
		(normative) Transfer service parameters			
Α	nnex C	(informative) Communication service arguments for Transfer Method	27		
В	bliogra	ohy	28		

Table 1 – Capability File part	8
Table 2 – CommunicationProfile definition	8
Table 3 – Device type catalog mapping	9
Table 4 – ProtocolType Foundation_HSE definition	9
Table 5 – Inherited DeviceType property mapping	10
Table 6 – Identification parameters	10
Table 7 – Inherited BlockType property mapping	11
Table 8 – ConnectionPointType ConnectionPoint_Foundation_HSE definition	11
Table 9 – Communication device ParameterSet definition	14
Table 10 – Method Connect arguments	16
Table 11 – Method Disconect arguments	16
Table 12 – Method Transfer arguments	17
Table 13 – Method GetPublishedData arguments	19
Table 14 – Method SetAddress arguments	20
Table A.1 – Attributes of FoundationHSEConnectionPointT	23
Table A.2 – Elements of FoundationHSEConnectionPointT	23
Table A.3 – Elements of FoundationHSENetworkT	24
Table A.4 – Attributes of FoundationBlockIdentificationT	24
Table A.5 – Attributes of FoundationIdentificationT	25

nttps://standards.iten.ai)
Document Preview

IEC 62769-101-2:2023

https://standards.iteh.ai/catalog/standards/iec/221f4dc8-58c6-4ad2-h923-235f25e3def9/iec-62769-101-2-2023

FIELD DEVICE INTEGRATION (FDI®) -

Part 101-2: Profiles – Foundation Fieldbus HSE

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international
 consensus of opinion on the relevant subjects since each technical committee has representation from all
 interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition IEC 62769-101-2:2020. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

IEC 62769-101-2 has been prepared by subcommittee 65E: Devices and integration in enterprise systems, of IEC technical committee 65: Industrial-process measurement, control and automation. It is an International Standard.

This third edition cancels and replaces the second edition published in 2020. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) added namespace to Annex A;
- b) changed content type of cff file to application/vnd.ff.cff.

The text of this International Standard is based on the following documents:

Draft	Report on voting	
65E/861/CDV	65E/918/RVC	

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/standardsdev/publications.

A list of all parts in the IEC 62769 series, published under the general title *Field device* integration (FDI^{\otimes}), can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

FIELD DEVICE INTEGRATION (FDI®) -

Part 101-2: Profiles - Foundation Fieldbus HSE

1 Scope

This part of IEC 62769 specifies the IEC 62769 profile for IEC 61784-1, CP 1/2 (FOUNDATION™ Fieldbus HSE)¹.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61784-1, Industrial communication networks - Profiles - Part 1: Fieldbus Profiles

IEC 61784-2, Industrial communication networks – Profiles – Part 2: Additional fieldbus profiles for real-time networks based on ISO/IEC/IEEE 8802-3

IEC 61804 (all parts), Devices and integration in enterprise systems – Function blocks (FB) for process control and Electronic Device Description Language (EDDL)

IEC 62541-6, OPC Unified Architecture – Part 6: Mappings

IEC 62541-100:2015, OPC unified architecture – Part 100: Device Interface

IEC 62769-2, Field device integration (FDI®) – Part 2: FDI-Client

IEC 62769-3, Field device integration (FDI®) – Part 3: FDI-Server

IEC 62769-4, Field device integration (FDI®) – Part 4: FDI® Packages

IEC 62769-5, Field device integration (FDI®) – Part 5: FDI-Information Model

IEC 62769-6, Field device integration (FDI®) – Part 6: FDI-Technology Mapping

IEC 62769-7, Field device integration (FDI®) – Part 7: FDI-Communication Devices

IEC 62769-101-1, Field device integration (FDI $^{\otimes}$) – Part 101-1: Profiles – Foundation Fieldbus H1

Foundation™ Fieldbus is the trade name of the non-profit consortium Fieldbus Foundation. This information is given for the convenience of users of this technical report and does not constitute an endorsement by IEC of the trademark holder or any of its products. Compliance does not require use of the trade name. Use of the trade name requires permission of the trade name holder.

3 Terms, definitions, abbreviated terms and conventions acronyms

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 61784-1, IEC 61784-2, IEC 61804 (all parts), IEC 62541-100, IEC 62769-2, IEC 62769-3, IEC 62769-4, IEC 62769-5, IEC 62769-6, IEC 62769-7 and IEC 62769-101-1 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at https://www.iso.org/obp
- IEC Electropedia: available at https://www.electropedia.org

3.2 Abbreviated terms and acronyms

For the purposes of this document, the following abbreviations apply:

CFF	Common File format
CP	communication profile (see IEC 61784-1 or IEC 61784-2)
CPF	communication profile family (see IEC 61784-1 or IEC 61784-2)
EDD	Electronic Device Description (see IEC 61804 series)
EDDL	Electronic Device Description Language (see IEC 61804 series)
FB	function block/standards.iteh.ai
IM	Information Model Preview
SMIB	system management information base
VFD	virtual field device 62769-101-2:2023

, https://standards.iteh.ai/catalog/standards/iec/221f4dc8-58c6-4ad2-b923-235f25e3def9/iec-62769-101-2-202

4 Conventions

4.1 EDDL syntax

This document specifies content for the EDD component that is part of FDI^{®2} Communication Packages. EDDL syntax uses the font Courier New. EDDL syntax is used for method signature, variable, data structure and component declarations.

4.2 XML syntax

XML syntax examples use the font Courier New. The XML syntax is used to describe XML document schema.

Example: <xsd:simpleType name="Example">

² FDI is a registered trademark of the non-profit organization Fieldbus Foundation, Inc. This information is given for the convenience of users of this document and does not constitute an endorsement by IEC of the trademark holder or any of its products. Compliance does not require use of the trade name. Use of the trade name requires permission of the trade name holder.

5 Profile for CP 1/2 (FOUNDATION™ HSE)

5.1 General

This profile annex specifies the protocol specifics needed for FDI® Packages describing communication servers, gateways and devices. Requirements for Direct Access transfer service parameters are given in Annex B.

Annex B defines the XML schema for Direct Access Services. Annex C provides an overview of mapping PROFIBUS standard parameters to PA DIM.

5.2 Catalog profile

5.2.1 Protocol support file (Capability File)

Each CP 1/2 FDI[®] Device Package shall contain a capability file. The capability file part is described in Table 1.

 Parameter
 Description

 Content Type
 txt/plain application/vnd.ff.cff

 Root Namespace
 Not applicable

 Source Relationship
 http://fdi-cooperation.com/2010/relationships/attachment-protocol

 Filename
 Use file extension .CFH

Table 1 - Capability File part

5.2.2 CommunicationProfile definition

IEC 62769-4 defines a CommunicationProfileT string type for the Catalog XML schema. Table 2 defines the CP 1/2 specific values for this string.

Table 2 - CommunicationProfile definition

CommunicationProfile	Description		
foundation_hse	CP 1/2 device type		

5.2.3 Profile device

Not supported in this document.

5.2.4 Protocol version information

IEC 62769-4 defines an element type named InterfaceT for the Catalog XML Schema. Element type InterfaceT contains an element named Version which is supposed to provide version information about the applied communication protocol profile. The value follows the IEC 62769-4 defined version information schema defined in element type VersionT.

The major version part of VersionT shall be set to the ITK_VER parameter. The minor and builds parts shall be set to 0.

EXAMPLE For ITK_VER 5, the value for InterfaceT is 5.0.0.

5.3 Associating a Package with a CP 1/2 device

5.3.1 Device type identification mapping

CP 1/2 device types are uniquely identified by the parameters MANUFAC_ID, DEVICE_TYPE and DEV_REV found in the Resource Block of the function block VFD. These parameters are used to associate a given device instance to an FDI® Device Package. These parameters are mapped to the FDI® Device Package Catalog according to Table 3.

Table 3 - Device type catalog mapping

Catalog Element	CP Mapping		
Manufacturer element of InterfaceT (IEC 62769-4)	MANUFAC_ID		
	String format "0xdddd" where dddd is the MANUFAC_ID number in hexadecimal format.		
DeviceModel element of InterfaceT String format	DEVICE_TYPE		
"0xdddd" where dddd is the DEVICE_TYPE number in hexadecimal format. (IEC 62769-4)	String format "0xdddd" where dddd is the DEVICE_TYPE number in hexadecimal format.		
DeviceRevision element	DEV_REV ^a		
ListOfSupportedDeviceRevisionsT (IEC 62769-4)	String format "x.0.0" where x is the DEV_REV in decimal format (no leading zeros).		
a Conditional: Shall be available if the device exposes a Function block VFD.			

5.3.2 Device type revision mapping

Each device type is identified per 5.3.1. A device may also include a parameter COMPATIBILITY_REV from the Resource Block. This parameter specifies the lowest device version (DEV_REV) that a new device can replace while maintaining compatibility with a prior FDI® Device Package.

5.4 Information Model mapping

5.4.1 ProtocolType definition

Table 4 defines the ProtocolType used to identify CP 1/2 network communications.

Table 4 - ProtocolType Foundation_HSE definition

Attribute	Value					
BrowseName	Foundation_HSE					
IsAbstract	False					
References	NodeClass	BrowseName	DataType	TypeDefinition	ModellingRule	
Inherits the properties of ProtocolType defined in IEC 62541-100.						

5.4.2 DeviceType mapping

Each device type inherits the properties of DeviceType. The mapping of the inherited properties from DeviceType is defined in Table 5.

Property	CP Mapping		
SerialNumber	DEV_ID (System Management Information Base)		
RevisionCounter	-1 (not defined)		
Manufacturer	String obtained from FDI [®] package catalog (ManufacturerName from PackageT)		
Model	String obtained from ${\rm FDI}^{\circledR}$ package catalog (Name of DeviceTypeT, which is a localized name)		
DeviceManual	entry text string (not supported) ^a		
DeviceRevision	DEV_REV (Resource Block) ^b		
SoftwareRevision	SOFTWARE_REV (if available, otherwise empty string)		
HardwareRevision	HARDWARE_REV (if available, otherwise empty string)		
Device manuals are exposed as attachments of the FDI [®] Device Package. Conditional: Shall be available if the device exposes a Function block VFD.			

5.4.3 FunctionalGroup Identification definition

As defined in IEC 62541-100, each device representation in the FDI® Server hosted Information Model shall contain a protocol specific FunctionalGroup called Identification. This FunctionalGroup organizes variables found in the Resource Block of the device type instance. The Functional Group Identification for CP 1/2 is defined in Table 6.

Table 6 - Identification parameters

BrowseName	VariableType	Optional/Mandatory			
MANUFAC_ID	UInt324dc8-58c6-4ad2-	Mandatory (2.5e3 de/9/jec-62769-101-2			
DEV_TYPE	UInt16	Mandatory			
DEV_REV	UInt8	Conditional ^a			
HARDWARE_REV	String	Optional			
SOFTWARE_REV	String	Optional			
COMPATIBILITY_REV	UInt8	Optional			
CAPABILITY_LEV	UInt8	Optional			
ITK_VER	UInt16	Conditional ^a			
SIF_ITK_VER	UInt16	Optional			
FD_VER	UInt16	Optional			
Conditional: Shall be available if the device exposes a Function block VFD.					

5.4.4 BlockType property mapping

CP 1/2 device types are block-oriented according to IEC 62541-100. IEC 62769-5 specifies the mapping of EDDL BLOCK A elements to block types and instances.

The BLOCK_A maps as a subtype of the topology element BlockType and inherits the properties as per IEC 62541-100. The mapping of the inherited properties of BlockType is specified in Table 7.



Table 7 - Inherited BlockType property mapping

Property	CP Mapping (Block's ParameterSet)		
RevisionCounter	ST_REV		
ActualMode	MODE_BLK.ACTUAL		
PermittedMode	MODE_BLK.PERMITTED		
NormalMode	MODE_BLK.NORMAL		
TargetMode	MODE_BLK.TARGET		

5.4.5 Mapping to Block ParameterSet

The ParameterSet is relative to each Block. The ParameterSet includes the CHARACTERISTICS records of the block that contains all the parameters found in the PARAMETERS, LOCAL_PARAMETERS and LIST_ITEMS.

The browse name of the parameters found in the PARAMETERS and LOCAL_PARAMETERS is the member name in the respective lists. For example, ST_REV is the browse name of the Static Revision parameter. LIST_ITEMS do not have member names; therefore, the browse name of each LIST in the LIST_ITEMS is the item name of the list.

5.5 Topology elements

5.5.1 ConnectionPoint definition Standards

The ConnectionPoint type ConnectionPoint_Foundation_HSE shall be used to identify CP 1/2 network communication and is defined in Table 8. The ConnectionPoint_Foundation_HSE type is a sub type of the abstract type ConnectionPointType defined in IEC 62541-100.

The Address property can be an IPv4 or IPv6 address. For IPv4 addresses, the address shall be stored in the last 4 octets and all other octets shall be set to zero.

The OrdinalNumber property reflects the position of the VFD within the SMIB VFD list. For devices exposing multiple FB VFDs the OrdinalNumber property is mandatory to address the FB VFD. For devices with a single FB VFD the OrdinalNumber property can be omitted. Devices exposed as instances of type DeviceType define their Connection points as components. Hence Devices with multiple FB VFDs shall contain multiple Connection points, one per FB VFD.

Table 8 - ConnectionPointType ConnectionPoint Foundation HSE definition

Attribute	Value						
BrowseName	ConnectionPoint_Fo	ConnectionPoint_Foundation_HSE					
IsAbstract	False						
References	NodeClass	BrowseName	DataType	TypeDefinition	ModellingRule		
Inherits the properties of ConnectionPointType defined in IEC 62541-100.							
HasProperty	Variable	Address	Octet[16]	PropertyType	Mandatory		
HasProperty	Variable	OrdinalNumber	Int32	PropertyType	Optional		

The ConnectionPoint type ConnectionPoint_Foundation_HSE shall be described by an EDD element contained in a Communication Device related FDI® Package that can drive a CP 1/2 network. Actual ConnectionPoint_ConnectionPoint properties are declared by VARIABLE constructs grouped together in a COLLECTION named Foundation_HSE_ConnectionPoint_Properties.

```
COMPONENT ConnectionPoint Foundation HSE
      LABEL "Foundation HSE Connection point";
      CLASSIFICATION NETWORK CONNECTION POINT;
      CAN DELETE FALSE;
      PROTOCOL Foundation HSE;
      CONNECTION POINT Foundation HSE ConnectionPoint Properties;
    }
    VARIABLE Address
      LABEL "Address";
      HELP "Address";
      CLASS DEVICE;
      TYPE OCTET (16);
      HANDLING READ & WRITE;
    }
    VARIABLE OrdinalNumber
      LABEL "Ordinal Number address property"; S. Item 21
      HELP "Ordinal Number property to address the Function Block
    Application";
      CLASS DEVICE;
      TYPE UNSIGNED INTEGER (4);
      HANDLING READ & WRITE;
https://standards.iteh.ai/catalog/standards/iec/221f4dc8-58c6-4ad2-b923-235f25e3def9/iec-62769-101-2-2023
    COLLECTION Foundation HSE ConnectionPoint Properties
      LABEL "Foundation HSE Connection Point data";
      MEMBERS
        CONNECTION POINT ADDRESS, Address;
        CONNECTION POINT ORDINALNUMBER, Ordinal Number;
      }
    }
```

5.5.2 Communication Device definition

According to IEC 62769-7, each FDI[®] Communication Package shall contain an EDD element describing the device. The following EDDL source code is an example describing an FDI[®] Communication Server.

```
COMPONENT Foundation_HSE_Communication_Server
{
   LABEL "Foundation HSE communication server",
   PRODUCT_URI "urn:Fieldbus Foundation:Foundation HSE Communication
Server";
   CAN_DELETE TRUE;
   CLASSIFICATION NETWORK_COMPONENT;
   COMPONENT_RELATIONS
   {
}
```