

INTERNATIONAL STANDARD



**Touch and interactive displays –
Part 12-10: Measurement methods of touch displays – Touch and electrical
performance**

Document Preview

[IEC 62908-12-10:2023](https://standards.iteh.ai/catalog/standards/iec/936476e1-8531-405d-a99e-3a6b8e7ef1e7/iec-62908-12-10-2023)

<https://standards.iteh.ai/catalog/standards/iec/936476e1-8531-405d-a99e-3a6b8e7ef1e7/iec-62908-12-10-2023>





THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2023 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat
3, rue de Varembe
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

International Standards
Document Preview

[IEC 62908-12-10:2023](https://standards.iteh.ai/catalog/standards/iec/936476e1-8531-405d-a99e-3a6b8e7ef1e7/iec-62908-12-10-2023)

<https://standards.iteh.ai/catalog/standards/iec/936476e1-8531-405d-a99e-3a6b8e7ef1e7/iec-62908-12-10-2023>



IEC 62908-12-10

Edition 2.0 2023-01
REDLINE VERSION

INTERNATIONAL STANDARD



**Touch and interactive displays –
Part 12-10: Measurement methods of touch displays – Touch and electrical
performance**

Document Preview

[IEC 62908-12-10:2023](https://standards.iteh.ai/catalog/standards/iec/936476e1-8531-405d-a99e-3a6b8e7ef1e7/iec-62908-12-10-2023)

<https://standards.iteh.ai/catalog/standards/iec/936476e1-8531-405d-a99e-3a6b8e7ef1e7/iec-62908-12-10-2023>

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 31.120

ISBN 978-2-8322-6440-9

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

| | |
|---|----|
| FOREWORD..... | 5 |
| 1 Scope..... | 7 |
| 2 Normative references | 7 |
| 3 Terms and definitions | 7 |
| 4 Measuring conditions..... | 7 |
| 4.1 Standard measuring environmental conditions | 7 |
| 4.2 Standard atmospheric conditions for reference measurements and tests | 8 |
| 4.3 Standard positioning equipment and setup..... | 8 |
| 4.4 Human operator alternative to standard positioning equipment | 9 |
| 4.5 Test bar size, shape and material parameters touch pen..... | 10 |
| 5 Touch performance measuring measurement methods | 11 |
| 5.1 General..... | 11 |
| 5.2 Accuracy test..... | 11 |
| 5.2.1 Purpose..... | 11 |
| 5.2.2 Test procedure | 11 |
| 5.2.3 Report | 15 |
| 5.3 Repeatability or jitter test | 15 |
| 5.3.1 Purpose..... | 15 |
| 5.3.2 Test procedure | 16 |
| 5.3.3 Report | 18 |
| 5.4 Linearity test..... | 18 |
| 5.4.1 Purpose..... | 18 |
| 5.4.2 Test procedure | 18 |
| 5.4.3 Report | 21 |
| 5.5 Reproducibility test..... | 21 |
| 5.5.1 Purpose..... | 21 |
| 5.5.2 Test procedure | 22 |
| 5.5.3 Report | 23 |
| 5.6 Signal-to-noise ratio (SNR) test | 24 |
| 5.6.1 Purpose..... | 24 |
| 5.6.2 Test procedure | 25 |
| 5.6.3 Report | 26 |
| 5.7 Report rate test..... | 26 |
| 5.7.1 Purpose..... | 26 |
| 5.7.2 Test procedure | 26 |
| 5.7.3 Report | 27 |
| 5.8 Latency test | 27 |
| 5.8.1 Purpose..... | 27 |
| 5.8.2 Test procedure | 27 |
| 5.8.3 Report | 28 |
| 5.9 Electrical noise immunity test..... | 28 |
| 5.9.1 Purpose..... | 28 |
| 5.9.2 Test procedure | 28 |
| 5.9.3 Report | 29 |
| 5.10 Water droplet immunity test | 29 |
| 5.10.1 Purpose..... | 29 |
| 5.10.2 Test procedure | 30 |

| | | |
|-----------------------|---|----|
| 5.10.3 | Report | 30 |
| 5.11 | Optical noise immunity test | 30 |
| 5.11.1 | Purpose | 30 |
| 5.11.2 | Test procedure | 31 |
| 5.11.3 | Report | 31 |
| 5.12 | Power consumption test | 31 |
| 5.12.1 | Purpose | 31 |
| 5.12.2 | Test procedure | 31 |
| 5.12.3 | Report | 31 |
| 5.13 | Perpendicular touch/hover distance test | 31 |
| 5.13.1 | Purpose | 31 |
| 5.13.2 | Test procedure | 31 |
| 5.13.3 | Report | 32 |
| 6 | In-plane hovering performance measurement methods | 32 |
| 6.1 | General | 32 |
| 6.2 | Accuracy test | 32 |
| 6.2.1 | Purpose | 32 |
| 6.2.2 | Test procedure | 32 |
| 6.2.3 | Report | 35 |
| 6.3 | Repeatability or jitter test | 35 |
| 6.3.1 | Purpose | 35 |
| 6.3.2 | Test procedure | 35 |
| 6.3.3 | Report | 38 |
| 6.4 | Report rate test | 38 |
| 6.4.1 | Purpose | 38 |
| 6.4.2 | Test procedure | 38 |
| 6.4.3 | Report | 40 |
| Annex A (informative) | Electrical performance-measuring measurement of touch sensors | 41 |
| A.1 | Resistance | 41 |
| A.1.1 | General | 41 |
| A.1.2 | Test samples | 41 |
| A.1.3 | Measurement equipment | 41 |
| A.1.4 | Procedures | 41 |
| A.1.5 | Data analysis | 42 |
| A.1.6 | Report | 42 |
| A.2 | Trans-capacitance | 42 |
| A.2.1 | General | 42 |
| A.2.2 | Test samples | 42 |
| A.2.3 | Measurement equipment | 42 |
| A.2.4 | Procedure | 42 |
| A.2.5 | Data analysis | 43 |
| A.2.6 | Report | 43 |
| Bibliography | | 44 |
| Figure 1 | – Composition of test equipment | 9 |
| Figure 2 | – Concept of performance measurement | 9 |
| Figure 3 | – Example of manual test tool (left), positioning without triggering a touch event (middle) and recording a touch event (right) | 10 |

| | |
|--|----|
| Figure 4 – Examples of test bars..... | 11 |
| Figure 5 – Location of edge area and centre area | 12 |
| Figure 6 – Point grid | 12 |
| Figure 7 – Accuracy definition..... | 13 |
| Figure 8 – Example of measurement result and calculation of accuracy..... | 15 |
| Figure 9 – Repeatability in the touch sensor module | 16 |
| Figure 10 – Example of measurement result for repeatability | 18 |
| Figure 11 – Dragging line for linearity test..... | 19 |
| Figure 12 – Linearity definition..... | 19 |
| Figure 13 – Example of measurement and calculation of linearity | 21 |
| Figure 14 – Example of reproducibility test results | 22 |
| Figure 15 – Reproducibility test procedure | 23 |
| Figure 16 – Examples of measurements of reproducibility – Velocity dependence..... | 24 |
| Figure 17 – SNR definition concept..... | 25 |
| Figure 18 – Dragging direction for reporting time measurement | 26 |
| Figure 19 – Reporting time interval measurement | 27 |
| Figure 20 – Latency measurement | 27 |
| Figure 21 – Example of the effect of external noise..... | 28 |
| Figure 22 – External noise injection | 29 |
| Figure 23 – Report of external noise immunity | 29 |
| Figure 24 – Example of water drop effect..... | 30 |
| Figure 25 – Water droplet test procedure..... | 30 |
| Figure 26 – Perpendicular touch /hover distance measurement..... | 32 |
| Figure 27 – Point grid | 33 |
| Figure 28 – Accuracy definition for in-plane of XY coordinates on the target projection plane (l) of the active area | 33 |
| Figure 29 – Accuracy definition for Z coordinate on the target projection plane (l) of the active area..... | 34 |
| Figure 30 – Repeatability for in-plane of XY coordinates on the target projection plane (l) of the active area..... | 36 |
| Figure 31 – Repeatability for Z coordinate on the target projection plane (l) of the active area..... | 36 |
| Figure 32 – Dragging direction of in-plane for reporting time measurement..... | 39 |
| Figure 33 – Dragging direction of Z -axis for reporting time measurement..... | 39 |
| Figure 34 – Reporting time interval measurement | 40 |
| Figure A.1 – Diagrammatic representation of measurement of resistance | 42 |
| Figure A.2 – Diagrammatic representation of measurement of capacitance..... | 43 |
| Table 1 – Standard conditions for reference measurements and tests..... | 8 |
| Table A.1 – Specification of LCR impedance meter..... | 41 |

INTERNATIONAL ELECTROTECHNICAL COMMISSION

TOUCH AND INTERACTIVE DISPLAYS –

Part 12-10: Measurement methods of touch displays – Touch and electrical performance

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition IEC 62908-12-10:2017. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

IEC 62908-12-10 has been prepared by IEC technical committee 110: Electronic displays. It is an International Standard.

This second edition cancels and replaces the first edition published in 2017. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) added hovering performance measurement methods, especially in-plane characteristics at a constant distance from the touch sensor;
- b) added pen touch performance.

The text of this International Standard is based on the following documents:

| Draft | Report on voting |
|--------------|------------------|
| 110/1434/CDV | 110/1480A/RVC |

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 62908 series, published under the general title *Touch and interactive displays*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

TOUCH AND INTERACTIVE DISPLAYS –

Part 12-10: Measurement methods of touch displays – Touch and electrical performance

1 Scope

This part of IEC 62908 specifies the standard measuring conditions and measurement methods for determining touch and hovering performance of a touch sensor module. This document is applicable to touch sensor modules, where the structural relationship between touch sensor, touch controller, touch sensor module, display panel, touch display panel, and touch display module is defined in IEC 62908-1-2.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-1, *Environmental testing – Part 1: General and guidance*

IEC 62908-1-2⁴, *Touch and interactive displays – Part 1-2: Generic – Terminology and letter symbols*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60068-1 and IEC 62908-1-2 apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at <https://www.electropedia.org/>
- ISO Online browsing platform: available at <https://www.iso.org/obp>

4 Measuring conditions

4.1 Standard measuring environmental conditions

Measurements shall be carried out under the standard environmental conditions:

- temperature: 25 °C ± 3 °C,
- relative humidity: 25 % RH to 85 % RH,
- atmospheric pressure: 86 kPa to 106 kPa.

When different environmental conditions are used, they shall be noted in the measurement report.

⁴—Under preparation. Stage at the time of publication: IEC/AFDIS 62908-1-2:2017.

4.2 Standard atmospheric conditions for reference measurements and tests

If the parameters to be measured depend on temperature, pressure and humidity, and their dependence on temperature, pressure and humidity is unknown, the atmospheres to be specified shall be selected from the following values, as shown in Table 1. The selected values shall be noted in the relevant specifications.

Table 1 – Standard conditions for reference measurements and tests

| Temperature ^a °C | Relative humidity ^{a, b} % RH | Air pressure ^a kPa |
|--|---|----------------------------------|
| (20, 25, 30, and 35) ± 3 | 45 to 75 | 86 to 106 |
| ^a Including extreme values. ^b Absolute humidity ≤ 22 g/m ³ . | | |

4.3 Standard positioning equipment and setup

The standard positioning equipment for touch performance shall be the positioning machine equipped with a test bar, a moving arm, and a stage onto which the touch sensor module is placed, as shown in Figure 1. The positioning machine shall move its arm and stage to place the test bar on or over the touch sensor module.

There are three types of positions associated with a given test: target, actual and reported positions. The target position is a desired measurement location in physical space referenced to a fixed datum on or over the touch sensor module surface. The actual position is the actual location of contact or hovering during test, referenced to the same fixed datum, which may can differ from the target position due to test bar placement error. The reported position is the location reported by the touch controller.

As shown in Figure 2, the reported positions from the touch controller are analysed to define performance measures with respect to the target positions.

The touch sensor module and the stage shall be aligned correctly while setting up the measurement equipment, because a misalignment between them may can introduce coordinate shifts or rotation between the actual touch positions and target positions; each positioning machine has its inherent accuracy, which means that an actual touched position does not coincide with its target position. The performance measurements based on the target positions may can include errors due to the accuracy of the positioning machine. The touch sensor module under test shall be attached to the stage and connected to the electrical interface. The test bar of the selected diameter shall be attached to the moving arm. In case of measurement of the pen touch performance, instead of the test bar, a selected touch pen (stylus pen) shall be attached to the moving arm.




Figure 1 – Composition of test equipment




Figure 2 – Concept of performance measurement

4.4 Human operator alternative to standard positioning equipment

Under certain circumstances, for example if the display under test is too large for suitable positioning equipment to be available, a suitably designed test arm may be manually positioned to enable completion of a subset of the tests described in this document. In this situation, the test arm needs to be designed carefully to minimise the reasonable achievable error between actual and target positions when conducting measurements. An example of such a test arm **may** consist of a rod with a sliding tip (Figure 3, left), whose materials are chosen so that contact between the rod and the display does not trigger a touch event (Figure 3, middle), whereas contact between the sliding tip and the display does trigger a touch event (Figure 3, right). Such a test arm **may** be placed accurately and reliably by the human operator with the sliding tip away from the display, subsequent to which a measurement **may** be made by sliding the tip into contact with the display.

The human operator alternative is not recommended for hovering performance measurements because it is difficult to ensure the accuracy of positions, including the height.




Figure 3 – Example of manual test tool (left), positioning without triggering a touch event (middle) and recording a touch event (right)

4.5 Test bar ~~size, shape and material parameters~~ touch pen


The parameters of the test bar shall be size, shape, and material. Examples of suitable sizes and shapes of the test bar are shown in Figure 4. ~~Care shall be taken to ensure that~~ The material parameters for the test bar ~~are~~ shall be appropriately chosen given the device category under test.

When the touch sensor module is a capacitive touch system, the test bar shall be electrically conductive and shall additionally be grounded in order to avoid potential performance degradation due to electrical noise, unless otherwise stated. A test bar may have an insulating layer on the base to model the effect of a gloved finger.

<https://standards.iteh.ai/> For reflection-based optical systems, the reflectivity of the contact end of the test bar shall be chosen to be spectrally representative of human skin. IEC 62908-12-10:2023

In all cases, the appropriate properties (including size, shape and material) of the test bar shall be reported.

In case of measurement of the pen touch performance, the selected touch pen shall be applied instead of the test bar. The touch pen corresponding to the touch sensor module shall be selected, because there are several types of touch pens (see IEC TR 62908-1-3). The information of the selected touch pen and related properties (i.e., tilt angle of touch pen, pressure of touch pen, etc.) shall be reported.



NOTE \varnothing (test bar diameter) = 4 mm, 6 mm, 7 mm, 9 mm, or 12 mm.

Figure 4 – Examples of test bars

5 Touch performance-measuring measurement methods

5.1 General

Fundamental touch performance-measuring measurement methods are described in Clause 5. They shall be ~~taken into account~~ applied during the characterization of a touch sensor module to ~~realize~~ provide a good user experience. (See Annex A regarding electrical performance measurement methods of touch sensors.)

5.2 Accuracy test

5.2.1 Purpose

The purpose of this test is to measure the ability of touch sensors and modules to indicate how close touch positions are reported relative to their target positions.

5.2.2 Test procedure

5.2.2.1 General

For the accuracy measurement, one of the following two methods can be selected. The first method is a straightforward method to evaluate the distance between each target point and its corresponding reported point. The second method is an indirect method where target grid points are estimated from reported points. This method can tolerate coordinate shifts which are caused by a misalignment between the touch sensor module and the stage while setting up the measurement equipment.

5.2.2.2 Method 1

The active area is defined as the area where touch is recognized. The centre area is defined as the rest of the active area without the edge area as shown in Figure 5. The edge area is defined as an area with the width of W from the edge of the active area. The origin and axis direction shall be defined.

The touch sensor module under test shall be attached to the stage and connected to the electrical interface. The test bar of the selected diameter size, shape and material shall be attached to the moving arm. For a precise measurement of the accuracy, the test equipment should be set up properly. The measurement points in the test grid are evenly spaced along both X and Y axes, away from the origin and spanning the whole active area of the touch sensor panel as shown in Figure 6.





Figure 5 – Location of edge area and centre area



NOTE m, n : number of points in the X and Y direction.

Figure 6 – Point grid

At each target grid point (i, j) , lift the test bar down and up, and collect the touch reports p times. As shown in Figure 7, the accuracy is defined as the distance between the target coordinate and the mean reported coordinate.