

Edition 6.0 2024-04

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Maritime navigation and radiocommunication equipment and systems – Digital interfaces –

Part 1: Single talker and multiple listeners 10 S 11 e 11 21

Matériels et systèmes de navigation et de radiocommunication maritimes – Interfaces numériques –

Partie 1: Émetteur unique et récepteurs multiples

https://standards.iteh.ai/catalog/standards/iec/a8a93323-d5db-4f57-9388-3dfaa03bdd94/iec-61162-1-2024





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2024 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

Droits de reproduction réservés. Sauf indication contraire, aucune partie de cette publication ne peut être reproduite ni utilisée sous quelque forme que ce soit et par aucun procédé, électronique ou mécanique, y compris la photocopie et les microfilms, sans l'accord écrit de l'IEC ou du Comité national de l'IEC du pays du demandeur. Si vous avez des questions sur le copyright de l'IEC ou si vous désirez obtenir des droits supplémentaires sur cette publication, utilisez les coordonnées ci-après ou contactez le Comité national de l'IEC de votre pays de résidence.

IEC Secretariat Tel.: +41 22 919 02 11

3, rue de Varembé info@iec.ch CH-1211 Geneva 20 www.iec.ch

Switzerland

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished

Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

A propos de l'IEC

La Commission Electrotechnique Internationale (IEC) est la première organisation mondiale qui élabore et publie des Normes internationales pour tout ce qui a trait à l'électricité, à l'électronique et aux technologies apparentées.

A propos des publications IEC

Le contenu technique des publications IEC est constamment revu. Veuillez vous assurer que vous possédez l'édition la plus récente, un corrigendum ou amendement peut avoir été publié.

Recherche de publications IEC -

webstore.iec.ch/advsearchform

La recherche avancée permet de trouver des publications IEC en utilisant différents critères (numéro de référence, texte, comité d'études, ...). Elle donne aussi des informations sur les projets et les publications remplacées ou retirées.

IEC Just Published - webstore.iec.ch/justpublished

Restez informé sur les nouvelles publications IEC. Just Published détaille les nouvelles publications parues. Disponible en ligne et une fois par mois par email.

Service Clients - webstore.iec.ch/csc

Si vous désirez nous donner des commentaires sur cette publication ou si vous avez des questions contactez-nous: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Découvrez notre puissant moteur de recherche et consultez gratuitement tous les aperçus des publications, symboles graphiques et le glossaire. Avec un abonnement, vous aurez toujours accès à un contenu à jour adapté à vos besoins.

Electropedia - www.electropedia.org

Le premier dictionnaire d'électrotechnologie en ligne au monde, avec plus de 22 500 articles terminologiques en anglais et en français, ainsi que les termes équivalents dans 25 langues additionnelles. Egalement appelé Vocabulaire Electrotechnique International (IEV) en ligne.



Edition 6.0 2024-04

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Maritime navigation and radiocommunication equipment and systems – Digital interfaces –

Part 1: Single talker and multiple listeners

Matériels et systèmes de navigation et de radiocommunication maritimes – Interfaces numériques –

Partie 1: Émetteur unique et récepteurs multiples

https://standards.iteh.ai/catalog/standards/iec/a8a93323-d5dh-4f57-9388-3dfaa03bdd94/iec-61162-1-2024

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 47.020.70 ISBN 978-2-8322-7831-4

Warning! Make sure that you obtained this publication from an authorized distributor.

Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

CONTENTS

Г	JREWO	KU	δ
IN	ITRODU	CTION	10
1	Scop	e	11
2	Norm	ative references	11
3	Term	s and definitions	11
4	Manu	facturer's documentation	12
5	Hard	ware specification	12
	5.1	General	
	5.2	Interconnecting wire	
	5.3	Conductor definitions	
	5.4	Electrical connections/shield requirements	
	5.5	Connector	
	5.6	Electrical signal characteristics	
	5.6.1	General	
	5.6.2	Signal state definitions	
	5.6.3	Talker drive circuits	
	5.6.4	Listener receive circuits	13
	5.6.5	Electrical isolation	
	5.6.6	Maximum voltage on bus	
6	Data	transmission	14
7	Data	format protocol	15
	7.1	Characters	
	7.1.1	General	
	7.1.2		
	7.1.3		
	7.1.4	Undefined characters	
	7.1.5		
	7.1.6	Manufacturer's mnemonic code	
	7.2	Fields	
	7.2.1	String	
	7.2.2	Address field	
	7.2.3	Data fields	
	7.2.4		
	7.2.5	Sequential message identifier field	18
	7.3	Sentences	
	7.3.1	General structure	18
	7.3.2	Description of approved sentences	18
	7.3.3	Parametric sentences	19
	7.3.4	Encapsulation sentences	20
	7.3.5	Query sentences	22
	7.3.6	Proprietary sentences	23
	7.3.7	Command sentences	23
	7.3.8	Valid sentences	24
	7.3.9	Multi-sentence messages	24
	7.3.1	0 Sentence transmission timing	24
	7.3.1	1 Additions to approved sentences	25

	7.3.12	Message reception timeout for multi-sentence method	25
7.	4	Error detection and handling	25
7.	5	Handling of deprecated sentences	25
8	Data	content	25
8.	1	Character definitions	25
8.	2	Field definitions	28
8.		Approved sentences	
	8.3.1	General format	
	8.3.2	AAM – Waypoint arrival alarm	31
	8.3.3	ABK – AIS addressed and binary broadcast acknowledgement	
	8.3.4	ABM – AIS addressed binary and safety related message	
	8.3.5	ACA – AIS channel assignment message	
	8.3.6	ACK – Acknowledge alarm	
	8.3.7	ACN – Alert command	35
	8.3.8	ACS – AIS channel management information source	
	8.3.9	AGL – Alert group list	
	8.3.10		
	8.3.11	·	
	8.3.12	-	
	8.3.13	•	
	8.3.14	ALF – Alert sentence	41
	8.3.15	5 ALR – Set alarm state	44
	8.3.16	APB – Heading/track controller (autopilot) sentence B	44
	8.3.17	7 ARC – Alert command refused	45
	8.3.18	BBM – AIS broadcast binary message	45
	8.3.19		
	8.3.20		
nttps://stan	8.3.21		
	8.3.22		
	8.3.23	BWW – Bearing waypoint to waypoint	47
	8.3.24	CUR – Water current layer – Multi-layer water current data	48
	8.3.25	DBT – Depth below transducer	48
	8.3.26	DDC – Display dimming control	48
	8.3.27	7 DOR – Door status detection	51
	8.3.28	B DPT – Depth	53
	8.3.29	DSC – Digital selective calling information	53
	8.3.30	DSE – Expanded digital selective calling	54
	8.3.31	1 DTM – Datum reference	54
	8.3.32	EPM – Command or report long equipment property value	55
	8.3.33	B EPV – Command or report equipment property value	56
	8.3.34	ETL – Engine telegraph operation status	58
	8.3.35	5 EVE – General event message	59
	8.3.36	S FIR – Fire detection	59
	8.3.37	7 FSI – Frequency set information	60
	8.3.38	GBS – GNSS satellite fault detection	61
	8.3.39	GDC – GNSS differential correction	64
	8.3.40	GEN – Generic binary information	67
	8.3.41	GFA – GNSS fix accuracy and integrity	68
	8.3.42	GGA – Global positioning system (GPS) fix data	69

8.3.43	GLL – Geographic position – Latitude/longitude	69
8.3.44	GNS – GNSS fix data	70
8.3.45	GRS – GNSS range residuals	72
8.3.46	GSA – GNSS DOP and active satellites	75
8.3.47	GST – GNSS pseudorange error statistics	78
8.3.48	GSV – GNSS satellites in view	78
8.3.49	HBT – Heartbeat supervision sentence	81
8.3.50	HCR – Heading correction report	81
8.3.51	HDG – Heading, deviation and variation	82
8.3.52	HDT – Heading true	82
8.3.53	HMR – Heading monitor receive	82
8.3.54	HMS – Heading monitor set	83
8.3.55	HRM – Heel angle, roll period and roll amplitude measurement device.	83
8.3.56	HSC – Heading steering command	85
8.3.57	HSS – Hull stress surveillance systems	85
8.3.58	HTC – Heading/track control command; HTD – Heading /track control data	85
8.3.59		
8.3.60		
8.3.61	LR3 – AIS long-range reply sentence 3	88
8.3.62		
8.3.63	LRI – AIS long-range interrogation	89
8.3.64		
8.3.65	MSK – MSK receiver interface	91
8.3.66	MSS – MSK receiver signal status	92
8.3.67		
8.3.68	MWD – Wind direction and speed	92
https://standa.69	MWV – Wind speed and angle	92
8.3.70		
8.3.71	NLS – Navigation light status	94
8.3.72	NRM – NAVTEX receiver mask	95
8.3.73	NRX – MSI received message	96
8.3.74	NSR – Navigation status report	98
8.3.75	OSD – Own ship data	99
8.3.76	POS – Device position and ship dimensions report or configuration command	100
8.3.77		
8.3.78		
8.3.79	_	
8.3.80		
8.3.81	RMC – Recommended minimum specific GNSS data	104
8.3.82	·	
8.3.83	ROT – Rate of turn	106
8.3.84	RPM – Revolutions	106
8.3.85		
8.3.86	•	
8.3.87	-	
8.3.88	•	
8 3 89		109

	8.3.90	SFI – Scanning frequency information	110
	8.3.91	SLM – Steering location/mode	111
	8.3.92	SM1 – SafetyNET Message, All Ships/NavArea	112
	8.3.93	SM2 – SafetyNET Message, Coastal Warning Area	114
	8.3.94	SM3 – SafetyNET Message, Circular Area address	116
	8.3.95	SM4 – SafetyNET Message, Rectangular Area Address	118
	8.3.96	SMB – IMO SafetyNET Message Body	121
	8.3.97	SMV – SafetyNET Message, Vessel in distress information	122
	8.3.98	SPW – Security password sentence	124
	8.3.99	SSD – AIS ship static data	125
	8.3.100	STN – Multiple data ID	126
	8.3.101	THS – True heading and status	126
	8.3.102	TLB – Target label	126
	8.3.103	TLL – Target latitude and longitude	127
	8.3.104	TRC – Thruster control data	127
	8.3.105	TRD – Thruster response data	128
	8.3.106	TRL – AIS transmitter-non-functioning log	128
	8.3.107	TTD – Tracked target data	129
	8.3.108	TTM – Tracked target message	132
	8.3.109	TUT – Transmission of multi-language text	132
	8.3.110	TXT – Text transmission	133
	8.3.111	UID – User identification code transmission	
	8.3.112	VBC – Water-referenced and ground-referenced docking speed data	134
	8.3.113	VBW – Dual ground/water speed	
	8.3.114	VDM – AIS VHF data-link message	135
	8.3.115	VDO – AIS VHF data-link own-vessel report	136
	8.3.116	VDR – Set and drift	137
	8.3.117	VER - Version	137 _20
	8.3.118	VHW – Water speed and heading	
	8.3.119	VLW – Dual ground/water distance	
	8.3.120	VPW – Speed measured parallel to wind	138
	8.3.121	VSD – AIS voyage static data	
	8.3.122	VTG – Course over ground and ground speed	140
	8.3.123	WAT – Water level detection	
	8.3.124	WCV – Waypoint closure velocity	
	8.3.125	WNC – Distance waypoint to waypoint	
	8.3.126	WPL – Waypoint location	
	8.3.127	XDR – Transducer measurements	
	8.3.128	XTE – Cross-track error, measured	
	8.3.129	XTR – Cross-track error, dead reckoning	
	8.3.130	ZDA – Time and date	
	8.3.131	ZDL – Time and distance to variable point	
	8.3.132	ZFO – UTC and time from origin waypoint	
	8.3.133	ZTG – UTC and time to destination waypoint	
9		ons	
ę		mple parametric sentences	
	9.1.1	General	
	9.1.2	Example 1 – LORAN-C latitude/longitude	
	9.1.3	Example 2 – LORAN-C arrival alarm	147

	Example 3 – Proprietary sentence	140
9.1.5	Example 4 – RMA examples	148
9.1.6	Example 5 – FSI examples	149
9.1.7	Example 6 – MSK/MSS examples	149
9.1.8	Example 7 – DSC and DSE sentences	150
9.1.9	Example 8 – FIR, DOR and WAT sentences	150
9.2	Example encapsulation sentences	151
9.3	Examples of receiver diagrams	151
Annex A	(informative) Example encapsulation sentence	152
A.1	Example encapsulation sentence	152
A.2	AIS VHF data-link message VDM sentence encapsulation example	152
A.3	Background discussion – Encapsulation coding	152
A.4	Decoding the encapsulated string	156
A.5	Conversion from symbols to binary bits	156
A.6	Organising the binary message data	157
A.7	Interpreting the decoded binary strings	157
Annex B	(normative) Guidelines for methods of testing and required test results	158
B.1	General	158
B.2	Definition of environmental conditions for the tests	158
B.3	Examination of the manufacturer's documentation	158
B.4	Test of hardware	159
B.4.′	1 Interface units	159
B.4.2	2 Input circuit test	159
B.4.3		
B.4.4	Maximum input voltage test	159
B.4.5		
B.4.6		
s://starB.4.7	1 3	
B.4.8	•	
B.4.9		
Annex C	(normative) Six-bit binary field conversion	167
Annex D	(normative) Alarm system fields	170
Annex E	(informative) Example of use of FIR, DOR and WAT sentences	178
E.1	Example of the use of system status messages	178
E.2	Use of system division codes	178
E.3	Send complete status	179
E.4	Change measurement point status	180
E.5	Point status change during a status update	180
E.6	Failure in a sub-system	180
E.7	Status updates when a sub-system is in fault	181
E.8	Signal a correction of a sub-system fault	181
Bibliograp	phy	182
	- Listener receive circuit	14
Figure 1 -		
	- Data transmission format	14
Figure 2 -	Data transmission formatExample 1, J-FET, N channel, opto-isolator based listener circuit	

Figure A.1 – Message data format	154
Figure A.2 – Work sheet for decoding and interpreting encapsulated string	155
Figure C.1 – 6-bit binary code converted to valid IEC 61162-1 character	168
Figure C.2 – Valid IEC 61162-1 character converted to 6-bit binary code	169
Figure E.1 – Example system diagram	179
Table 1 – Reserved characters	26
Table 2 – Valid characters	26
Table 3 – Character symbol	27
Table 4 – Talker identifier mnemonics	28
Table 5 – Field type summary	30
Table A.1 – Example message from ITU-R M.1371	153
Table B.1 – Example – Special characters	160
Table B.2 – Example – Parsing	160
Table B.3 – Example – Future extensions	161
Table B.4 – Example – Data string GGA sent by the EUT to the test receiver (listener)	162
Table B.5 – Example – Checksum data sent	163
Table B.6 – Example – Data string GNS received by the EUT	164
Table B.7 – Example – Checksum data received	165
Table B.8 – Example – Break of data line	166
Table B.9 – Example – Receiving Interval	166
Table B.10 – Example – Talker ID	166
Table C.1 – Six-bit binary field conversion table	
Table D.1 – System alarm fieldsIEC.611.62.1.2024	170

https://standards.iteh.ai/catalog/standards/iec/a8a93323-d5db-4f57-9388-3dfaa03bdd94/iec-61162-1-2024

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – DIGITAL INTERFACES –

Part 1: Single talker and multiple listeners

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61162-1 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems. It is an International Standard.

This sixth edition cancels and replaces the fifth edition published in 2016. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) alternative hardware is given in 5.1 which may now be as specified in this document or as specified in IEC 61162-2;
- b) the data transmission rate given in Clause 6 is now configurable. The default remains as 4 800 (bits/s) but higher rates may be provided;

- c) new identifiers have been added to Table 4;
- d) new sentences AGL, EPM, GDC, NLS, SEL, SLM, SMV and VBC have been added;
- e) revisions have been made to ABK, ABM, ACN, ALC, ALF, ARC, BBM, DDC, DTM, EPV, FIR, GBS, GFA, GLL, GNS, GRS, GSA, GST, GSV, HRM, NRX, POS, RLM, ROR, RSA, TLB, TTD, VSD and XDR;
- f) the previous Annex A, Glossary, has been deleted as being of historical interest.

The text of this International Standard is based on the following documents:

Draft	Report on voting
80/1093/FDIS	80/1097/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 61162 series, published under the general title *Maritime navigation* and radiocommunication equipment and systems – Digital interfaces, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- https://st.reconfirmed.ai/catalog/standards/iec/a8a93323-d5db-4f57-9388-3dfaa03bdd94/iec-61162-1-2024
 - withdrawn, or
 - revised.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

The IEC 61162 series consists of 5 parts which specify digital interfaces for application in marine navigation, radiocommunication and system integration, as follows:

IEC 61162-1: Single talker and multiple listeners;

IEC 61162-2: Single talker and multiple listeners, high speed transmission;

IEC 61162-3: Serial data instrument network;

IEC 61162-450: Multiple talkers and multiple listeners – Ethernet interconnection;

IEC 61162-460: Multiple talkers and multiple listeners – Ethernet interconnection – Safety and security

IEC technical committee 80 interface standards are developed with input from manufacturers, private and government organisations and equipment operators. The information is intended to meet the needs of users at the time of publication, but users should recognise that as applications and technology change, interface standards should change as well. Users of this document are advised to immediately inform the IEC of any perceived inadequacies therein.

The first edition of IEC 61162-1 was published in 1995. The second edition published in 2000 removed some sentences which were no longer in use, added some new sentences and included details of the ship equipment defined in IMO resolutions together with appropriate sentences for communication between them. This information was subsequently removed from the third edition when it became the practice to specify the sentence formatters in the individual standards for equipment.

The third edition published in 2007 introduced a re-arrangement of the text and new sentences particularly to support the automatic identification system and the voyage data recorder. The third edition also introduced a further type of start of sentence delimiter. The conventional delimiter "\$" was retained for the conventional sentences which are now called "parametric sentences". The new delimiter "!" identifies sentences that conform to special purpose encapsulation.

The fourth edition removed some sentences which were not in use, added some new sentences for new applications and made some corrections and additions. In particular, the sentences of relevance to satellite navigation receivers were expanded to facilitate the description of new satellite systems.

The fifth edition also removed some sentences which were no longer in use, added some new sentences for new applications and made some corrections and additions.

This sixth edition adds some new sentences for new applications and makes some corrections and additions.

This edition has been aligned where appropriate and possible with NMEA 0183 version 4.10.

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – DIGITAL INTERFACES –

Part 1: Single talker and multiple listeners

1 Scope

This part of IEC 61162 contains the requirements for data communication between maritime electronic instruments, navigation and radiocommunication equipment when interconnected via an appropriate system.

This document is intended to support one-way serial data transmission from a single talker to one or more listeners. These data are in printable ASCII form and can include information such as position, speed, depth, frequency allocation, etc. Typical messages can be from about 11 to a maximum of 79 characters in length and generally require transmission no more rapidly than one message per second.

The electrical definitions in this document are not intended to accommodate high-bandwidth applications such as radar or video imagery, or intensive database or file transfer applications. Since there is no provision for guaranteed delivery of messages and only limited error checking capability, it is important this document is used with caution in all safety applications.

For applications where a faster transmission rate is necessary, IEC 61162-2 applies.

For applications to shore based equipment of the automatic identification system (AIS) the IEC 62320 series applies.

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, Maritime navigation and radiocommunication equipment and systems – General requirements - Methods of testing and required test results

ISO/IEC 8859-1:1998, Information technology - 8-bit single-byte coded graphic character sets - Part 1: Latin alphabet No. 1

ITU-T Recommendation X.27/V.11:1996, *Electrical characteristics for balanced double-current interchange circuits operating at data signalling rates up to 10 Mbit/s*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at https://www.electropedia.org/
- ISO Online browsing platform: available at https://www.iso.org/obp

3.1

listener

device which receives data from another device

3.2

talker

device which sends data to other devices

Note 1 to entry: The type of talker is identified by a 2-character mnemonic as listed in 8.2 (see Table 4).

4 Manufacturer's documentation

Installation manuals provided for equipment that is intended to meet the requirements of this document shall contain the following information:

- a) identification of the A and B signal lines (see Figure 1);
- b) the output drive capability as a talker;
- c) a list of approved sentences, noting unused fields, proprietary sentences transmitted as a talker and transmission interval for each sentence;
- d) the load requirements as a listener;
- e) a list of sentences and associated data fields that are required as a listener;
- f) the current software and hardware revision, if this is relevant to the interface;
- g) an electrical description or schematic of the listener/talker input/output circuits citing actual components and devices used, including connector type and part number;
- h) the version number and date of update of the standard for which compliance is sought;
- i) list of supported baud rates (bits/s) including any limitations per each baud rate supported.

5 Hardware specification

IEC 61162-1:2024

https: 5.1and General, ai/catalog/standards/iec/a8a93323-d5db-4f57-9388-3dfaa03bdd94/iec-61162-1-2024

NOTE Guidelines on methods of testing are given in Annex B.

One talker and multiple listeners may be connected in parallel over an interconnecting wire. The number of listeners depends on the output capability and input drive requirements of individual devices.

There are two alternatives for the hardware:

- 1) method based on 5.2 to 5.6;
- 2) method based on IEC 61162-2.

5.2 Interconnecting wire

Interconnection between devices may be by means of a two-conductor, shielded, twisted-pair wire.

5.3 Conductor definitions

The conductors referred to in this document are the signal lines A and B, and shield (see Figure 1).