INTERNATIONAL STANDARD

IEC 61158-5

Third edition
2003-05

Withdrawn

Digital data communications for measurement and control – Fieldbus for use in industrial control systems –

Part 5: Application layer service definition

iTeh Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-5:2003
https://standards.iteh.ai/catalog/standards/iec/4bbc9779-4a7d-4b4e-a2fe-009a7f236e8a/iec-61158-5-2003

Reference number
IEC 61158-5:2003(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site (www.iec.ch)**

- **Catalogue of IEC publications**

  The on-line catalogue on the IEC web site (http://www.iec.ch/searchpub/cur_fut.htm) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

- **IEC Just Published**

  This summary of recently issued publications (http://www.iec.ch/online_news/justpub/jp_entry.htm) is also available by email. Please contact the Customer Service Centre (see below) for further information.

- **Customer Service Centre**

  If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

  Email: custserv@iec.ch
  Tel: +41 22 919 02 11
  Fax: +41 22 919 03 00

Withdrawn
(https://standards.iteh.ai)
Document Preview
IEC 61158-5:2003
https://standards.iteh.ai/catalog/standards/sist/d-4b4e-a2fe-009a/f236e8a/iec-61158-5-2003

INTERNATIONAL STANDARD

IEC 61158-5

Third edition
2003-05

Withdrawn

Digital data communications for measurement and control – Fieldbus for use in industrial control systems –

Part 5: Application layer service definition

iTeh Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-5:2003
https://standards.iteh.ai/catalog/standards/iec/4bbe9779-4a7d-4b4e-a2fe-009a7f236e8a/iec-61158-5-2003

© IEC 2003 – Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch

Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE XH

For price, see current catalogue

CONTENTS

FOREWORD 24

0 Introduction 26
0.1 General 26
0.2 Nomenclature for references within this standard 26

1 Scope 27

2 Normative references 27

3 Terms and definitions 28
3.1 ISO/IEC 7498-1 terms 28
3.2 ISO/IEC 8822 terms 29
3.3 ISO/IEC 9545 terms 29
3.4 ISO/IEC 8824 terms 29
3.5 Fieldbus Data Link Layer terms 29
3.6 Fieldbus Application Layer specific definitions 30
3.7 Abbreviations and symbols 41
3.8 Conventions 42

4 Concepts 45
4.1 Overview 45
4.2 Architectural relationships 46
4.3 Fieldbus Application Layer structure 48
4.4 Fieldbus Application Layer naming and addressing 60
4.5 Architecture summary 60
4.6 FAL service procedures 61
4.7 Common FAL attributes 62
4.8 Common FAL service parameters 62
4.9 APDU size 63

5 Data type ASE 63
5.1 General 63
5.2 Formal definition of data type objects 66
5.3 FAL defined data types 67
5.4 Data type ASE service specification 102

6 Type 1 communication model specification 102
6.1 Concepts 102
6.2 ASEs 102
6.3 ARs 246
6.4 Summary of FAL classes 270
6.5 Permitted FAL services by AREP role 271

7 Type 2 communication model specification 273
7.1 Concepts 273
7.2 ASEs 281
7.3 AR 346
7.4 Summary of FAL classes 382
7.5 Permitted FAL services by AR type 383

8 Type 3 communication model specification 383

Withdrawn
iTeh Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-5:2003
https://standards.iteh.ai/catalog/standards/iec/6bbc9779-4a7d-4b4e-a2fe-009a7f236e8a/iec-61158-5-2003

8.1 DP concepts 383
8.2 ASEs 401
8.3 Summary of AL classes 734
8.4 Permitted AL services by AREP role 735
8.5 Conformance classes 739
8.6 Application characteristics 739

9 Type 4 communication model specification 740
9.1 Concepts 740
9.2 Variable ASE 747
9.3 Application relationship ASE 766

10 Type 5 communication model specification 772
10.1 Concepts 772
10.2 ASEs 793
10.3 FDA sessions 828
10.4 Summary of FAL Type 9 and Type 5 classes 837
10.5 Permitted FAL Type 9 and Type 5 services by AREP role 838

11 Type 6 communication model specification 840
11.1 Application relationship (AR) and Application relationship endpoint (AREP) characteristics 840
11.2 Relationship of Type 6 to Type 1 842
11.3 Permitted services by AREP role 846

12 Type 7 communication model specification 848
12.1 Concepts 848
12.2 ASEs 864
12.3 ARs 1033

13 Type 8 communication model specification 1053
13.1 Concepts 1053
13.2 ASEs 1055
13.3 Application relationships 1070
13.4 Permitted FAL services by AREP role 1071

14 Type 9 communication model specification 1072
14.1 Concepts 1072
14.2 Common parameters 1072
14.3 ASEs 1073
14.4 ARs 1163
14.5 Summary of classes 1166
14.6 Permitted services by AREP role 1166

15 Type 10 communication model specification 1168
15.1 Type 10 Concepts 1168
15.2 ASE Data Types 1174
15.3 ASEs 1175
15.4 ARs 1289
15.5 Summary of FAL classes 1292
15.6 Summary of FAL services 1292

Withdrawn
iTeh Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-5:2003

Figure 1 – Relationship of IEC 61158-3 to other fieldbus layers and to users of the fieldbus Application Service 26
Figure 2 – Relationship to the OSI basic reference model 46
Figure 3 – Architectural positioning of the fieldbus Application Layer 47
Figure 4 – Client/server interactions 49
Figure 5 – Pull model interactions 50
Figure 6 – Push model interactions 51
Figure 7 – APOs services conveyed by the FAL 52
Figure 8 – Application entity structure 54
Figure 9 – Example FAL ASEs 55
Figure 10 – FAL management of objects 56
Figure 11 – ASE service conveyance 57
Figure 12 – Defined and established AREPs 59
Figure 13 – FAL architectural components 61
Figure 14 – Data type class hierarchy example 64
Figure 15 – The AR ASE conveys APDUs between APs 133
Figure 16 – 1-to-1 AR establishment 145
Figure 17 – 1-to-many AR establishment 145
Figure 18 – Event model overview 185
Figure 19 – Residence timeliness 261
Figure 20 – Synchronized timeliness 262
Figure 21 – Residence timeliness 267
Figure 22 – Synchronized timeliness 268
Figure 23 – Overview of ASE's and object classes 275
Figure 24 – Addressing format using MAC, class, instance and attribute IDs 275
Figure 25 – Static Assembly state transition diagram 293
Figure 26 – Dynamic Assembly state transition diagram 294
Figure 27 – Example of Find_Next_Object_Instance service 323
Figure 28 – Context of transport services within the connection model 349
Figure 29 – Application–to–application view of data transfer 349
Figure 30 – Data flow diagram for a link producer 350
Figure 31 – Data flow diagram for a link consumer 351
Figure 32 – Triggers 352
Figure 33 – Binding transport instances to the producer and consumer of a transport connection that does not have a reverse data path 353
Figure 34 – Binding transport instances to the producers and consumers of a transport connection that does have a reverse data path 353
Figure 35 – Binding transport instances to the producer and consumers of a multipoint connection when the transport connection does not have a reverse data path 354
Figure 36 – Binding transport instances to the producers and consumers of a multipoint connection when the transport connection does have reverse data paths 354
Figure 37 – Example of DP communication with a single controlling device 386
Figure 38 – Example of DP communication with several controlling devices 386
Figure 39 – Example of DP communication between field devices 386
Figure 40 – DP-slave model (modular DP-slave) 389
Figure 41 – DP-slave model (compact DP-slave) 389
Figure 42 – Overview of application processes 390

Withdrawn
iTeh Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-5:2003
https://standards.iteh.ai/catalog/standards/sist/1e9f7c2-4a7d-4b4e-a2fe-009a7f236e8a/iec-61158-5-2003

Figure 43 – DP-slave model (modular DP-slave) ... 391
Figure 44 – Application Service Elements (ASEs) ... 393
Figure 45 – Application Process with application Objects (APOs) ... 394
Figure 46 – Access to a remote APO ... 395
Figure 47 – Access to a remote APO for publisher/subscriber association ... 396
Figure 48 – Example of one AR with two AREPs ... 397
Figure 49 – Relation of a simple process data object to the real object ... 402
Figure 50 – Relation of a combined process data object to the real objects ... 405
Figure 51 – Sequence of an isochronous DP cycle with one DP-master (class 1) ... 433
Figure 52 – Additional time relationships in a DP system operating in isochronous mode ... 434
Figure 53 – DP system with optimised isochronous DP cycle ... 436
Figure 54 – Buffered synchronised isochronous mode at the DP-master (class 1) ... 437
Figure 55 – Enhanced synchronised isochronous mode at the DP-master (class 1) ... 438
Figure 56 – Input, output and PLL state machine interaction ... 438
Figure 57 – PLL state diagram ... 444
Figure 58 – OUTPUT state diagram ... 448
Figure 59 – INPUT state diagram ... 452
Figure 60 – Treatment of an alarm in the DP system ... 481
Figure 61 – Load Region state diagram for erasable memory ... 568
Figure 62 – Load region state diagram for non erasable memory ... 568
Figure 63 – Function invocation state diagram ... 595
Figure 64 – System architecture ... 605
Figure 65 – Assignment of communication relationship to application relationship ... 612
Figure 66 – MS0 application relationship ... 618
Figure 67 – Output buffer model of a DP-slave without sync functionality ... 619
Figure 68 – Output buffer model of a DP-slave with sync functionality ... 619
Figure 69 – Input buffer model of a DP-slave without freeze functionality ... 620
Figure 70 – Input buffer model of a DP-slave with freeze functionality ... 620
Figure 71 – MS1 application relationship ... 621
Figure 72 – MS2 application relationship ... 622
Figure 73 – Example of inter-network communication ... 623
Figure 74 – Example without inter-network addressing ... 623
Figure 75 – First example with inter-network addressing ... 624
Figure 76 – Second example with inter-network addressing ... 624
Figure 77 – MS3 application relationship ... 625
Figure 78 – MM1 application relationship ... 626
Figure 79 – MM2 application relationship ... 627
Figure 80 – Cycle time of the DP system ... 740
Figure 81 – FAL AE ... 741
Figure 82 – Summary of the FAL architecture ... 744
Figure 83 – FAL service procedure overview ... 745
Figure 84 – Time sequence diagram for the confirmed services ... 746
Figure 85 – Time sequence diagram for unconfirmed services ... 747
Figure 86 – VCR initiation ... 778
Figure 87 – Misordered message handling ... 784
Figure 88 – FF SM port message processing order ... 785

Withdrawn
iTeh Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-5:2003
https://standards.iteh.ai/catalog/standards/iec/0abc9779-4a7d-4b4e-a2fe-009a7f236e8a/iec-61158-5-2003

Figure 89 – FF FDA port message processing order 785
Figure 90 – FF TCP connection message processing order 786
Figure 91 – Session endpoint message processing order 786
Figure 92 – FDA LAN redundancy port message processing order 786
Figure 93 – Message processing by receiving entity 787
Figure 94 – Organisation of the ASEs and ARs 848
Figure 95 – Object model of the MPS ASE 868
Figure 96 – Time-out evaluation net 881
Figure 97 – Asynchronous promptness status evaluation net 885
Figure 98 – Synchronous promptness status evaluation net 886
Figure 99 – Punctual promptness status evaluation net 888
Figure 100 – Asynchronous refreshment status evaluation net 891
Figure 101 – Synchronous refreshment status evaluation net 892
Figure 102 – Punctual refreshment status evaluation net 894
Figure 103 – A_Readloc service procedure 897
Figure 104 – A_Writeloc service procedure 898
Figure 105 – A_Update service procedure 900
Figure 106 – A_Readfar service procedure 902
Figure 107 – A_Writefar service procedure 904
Figure 108 – A_Sent service procedure 905
Figure 109 – A_Received service procedure 906
Figure 110 – A_Read service procedure 908
Figure 111 – A_Read service state machine 909
Figure 112 – A_Write service procedure 910
Figure 113 – A_Write service state machine 911
Figure 114 – Model of a resynchronised variable 914
Figure 115 – Principles for resynchronisation of a produced variable 915
Figure 116 – Resynchronisation mechanism state machine for a produced variable 917
Figure 117 – Asynchronous refreshment private mechanism evaluation net 918
Figure 118 – Asynchronous refreshment public mechanism evaluation net 919
Figure 119 – Synchronous refreshment private mechanism evaluation net 920
Figure 120 – Synchronous refreshment public mechanism evaluation net 921
Figure 121 – Punctual refreshment private mechanism evaluation net 922
Figure 122 – Punctual refreshment public mechanism evaluation net 923
Figure 123 – Principles for the resynchronisation of a consumed variable 924
Figure 124 – Resynchronisation mechanism state machine for consumed variable 926
Figure 125 – Asynchronous promptness public mechanism evaluation net 927
Figure 126 – Asynchronous promptness private mechanism evaluation net 928
Figure 127 – Synchronous promptness public mechanism evaluation net 929
Figure 128 – Synchronous promptness private mechanism evaluation net 931
Figure 129 – Punctual promptness public mechanism evaluation net 932
Figure 130 – Punctual promptness private mechanism evaluation net 933
Figure 131 – Spatial consistency list variables interchange mechanism 936
Figure 132 – Spatial consistency – consistency variable interchange mechanism 936
Figure 133 – Spatial consistency – list recovery mechanism 937
Figure 134 – Spatial consistency – validity of the spatial consistency status 937

Withdrawn
iTeh Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-5:2003
https://standards.iteh.ai/catalog/standards/iec/0bbc9779-4a7d-4b4e-a2fe-009a7f236e8a/iec-61158-5-2003

Figure 135 – Object model of a variable list 938
Figure 136 – A_Readlist service procedure 943
Figure 137 – Consistency variable value evaluation net 949
Figure 138 – Consistency interchange timing diagram 950
Figure 139 – Recovery mechanism evaluation net 951
Figure 140 – Recovery interchange timing diagram 951
Figure 141 – Flowchart of the sub-MMS environment management state 958
Figure 142 – Domain management state chart 988
Figure 143 – Domain upload flowchart 991
Figure 144 – Domain download sequence diagram 992
Figure 145 – Domain upload sequence diagram 992
Figure 146 – Program invocation state chart 1004
Figure 147 – A_Associate service procedure 1042
Figure 148 – A_Release service procedure 1045
Figure 149 – A_Abort service procedure 1046
Figure 150 – A_Data service procedure 1048
Figure 151 – A_Unidata service procedure 1051
Figure 152 – Associated mode service state chart 1052
Figure 153 – Non-associated mode service state chart 1053
Figure 154 – Architectural positioning of the fieldbus Application Layer 1053
Figure 155 – VFD model 1073
Figure 156 – Abstract model of an automation system (VFD) 1073
Figure 157 – Source OD/remote OD 1080
Figure 158 – Put OD state machine 1093
Figure 159 – Transaction object state machine 1100
Figure 160 – Context test of two features-supported with different bitstring length 1107
Figure 161 – Overview of event 1127
Figure 162 – Event state machine 1133
Figure 163 – Domain GenericDownload/Download state machine (server) 1147
Figure 164 – Domain Upload state machine (server) 1149
Figure 165 – State diagram 1161
Figure 166 — FAL ASEs Communication Architecture 1170
Figure 167 — Runtime object model 1171
Figure 168 — Relationship between Engineering and Runtime 1172
Figure 169 — Navigation in the runtime object model 1173
Figure 170 — Operating state block diagram 1198
Figure 171 — Device status model for the common diagnosis 1199
Figure 172 — ACCO ASE structure 1223
Figure 173 — Productive operation of data connections 1224
Figure 174 — Productive operation of event connections 1225
Figure 175 — Quality Code transfer – standard behavior 1233
Figure 176 — Quality Code with communication fault 1234
Figure 177 — Quality Code when an connection is cleared 1235
Figure 178 — Quality Code when an connection is deactivated 1235
Figure 179 — Quality Code during the transfer of "incorrect“ connection data 1236
Figure 180 — Quality Code for provider in "Ready“ state 1236

Withdrawn
iTeh Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-5:2003
https://standards.iteh.ai/catalog/standards/iec/6bbc9779-4a7d-4b4e-a2fe-009a7f236e8a/iec-61158-5-2003

Figure 181 — Quality Code when clearing an object from the provider 1237
Figure 182 — Quality Code when a connection is forced 1237
Figure 183 — Quality Code at QoS violation 1238
Figure 184 — Quality Code for initial value 1238
Figure 185 — Productive operation of data connections 1242
Figure 186 — Productive operation of event connections 1243
Figure 187 — Failure of the provider in productive operation 1246
Figure 188 — Failure of the consumer 1247
Figure 189 — Failure of the provider when changing the connection status 1248
Figure 190 – Failure of the provider when changing the interconnection status 1249
Figure 191 — Failure of the provider when clearing connections 1250
Figure 192 — Information levels 1250
Figure 193 — ACCO ASE status model for the common diagnosis 1251
Figure 194 — ACCO ASE status model for the detailed diagnosis 1251
Figure 195 — Structure of the transmitted connection data 1274

Table 1 – PERSISTDEF 72
Table 2 – VARTYPE 73
Table 3 – ITEMQUALITYDEF 74
Table 4 – STATEDEF 77
Table 5 – GROUPERRORDEF 77
Table 6 – ACCESSRIGHTSDEF 78
Table 7 – HRESULT 78
Table 8 – UUID 85
Table 9 – Data type names for value 100
Table 10 – UUID 102
Table 11 – Create service parameters 103
Table 12 – Delete service parameters 104
Table 13 – Get Attributes service parameters 106
Table 14 – Set Attributes service parameters 108
Table 15 – Begin Set Attributes 110
Table 16 – End Set Attributes 111
Table 17 – Subscribe service parameters 120
Table 18 – Identify 123
Table 19 – Get status 124
Table 20 – Status notification 125
Table 21 – Initiate 126
Table 22 – Terminate 129
Table 23 – Conclude 131
Table 24 – Reject 131
Table 25 – Conveyance of service primitives by AREP role 134
Table 26 – Valid combinations of AREP roles involved in an AR 134
Table 27 – AR-Unconfirmed Send 140
Table 28 – AR-Confirmed Send 142
Table 29 – AR-Establish service 144
Table 30 – Valid combinations of AREP classes to be related 146

Withdrawn
iTeh Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-5:2003
https://standards.iteh.ai/catalog/standards/iec/4bbc9779-4a7d-4b4e-a21e-009a7f236e8a/iec-61158-5-2003

Table 31 – AR-DeEstablish service 147
Table 32 – AR-Abort 148
Table 33 – AR-Compel service 149
Table 34 – AR-Get Buffered Message service 150
Table 35 – AR-Schedule Communication service 151
Table 36 – AR-Cancel Scheduled Sequence service 152
Table 37 – AR-Status 153
Table 38 – AR-XON-OFF 154
Table 39 – AR-Remote Read service 155
Table 40 – AR-Remote Write service 156
Table 41 – Read service parameters 165
Table 42 – Read List service parameters 168
Table 43 – Write service parameters 170
Table 44 – Write List service parameters 172
Table 45 – Information Report service 174
Table 46 – Information Report List service 176
Table 47 – Exchange service parameters 178
Table 48 – Exchange List service parameters 182
Table 49 – Acknowledge Event 194
Table 50 – Acknowledge Event List service parameters 195
Table 51 – Enable event 197
Table 52 – Event Notification service parameters 198
Table 53 – Enable Event List 200
Table 54 – Notification recovery service parameters 201
Table 55 – Get Event Summary service parameters 202
Table 56 – Get Event Summary List service parameters 204
Table 57 – Query Event Summary List service parameters 208
Table 58 – Initiate Load service parameters 216
Table 59 – Terminate Load service parameters 218
Table 60 – Push Segment service parameters 219
Table 61 – Pull Segment service parameters 220
Table 62 – Discard service parameters 221
Table 63 – Pull Upload Sequencing of service primitives 223
Table 64 – Pull Upload service parameter constraints 223
Table 65 – Pull Upload state table 224
Table 66 – Pull Download Sequencing of service primitives 225
Table 67 – Pull Download service parameter constraints 225
Table 68 – Pull Download state table 226
Table 69 – Push Download sequencing of service primitives 227
Table 70 – Push Download service parameter constraints 228
Table 71 – Push Download state table 228
Table 72 – Start service parameters 235
Table 73 – Stop service parameters 236
Table 74 – Resume service parameters 237
Table 75 – Reset service parameters 238
Table 76 – Kill service parameters 239

Withdrawn
iTeh Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-5:2003
https://standards.iteh.ai/catalog/standards/sist/4bb09779-4a7d-4b4e-a21e-009a7f236e8a/iec-61158-5-2003

Table 77 – Action Invoke service parameters 240
Table 78 – Action Return service parameters 241
Table 79 – State transitions for a function invocation object 243
Table 80 – FAL class summary 271
Table 81 – Services by AREP role 271
Table 82 – Common elements 278
Table 83 – ST language elements 279
Table 84 – Type conversion operations 279
Table 85 – Values of implementation-dependent parameters 280
Table 86 – Extensions to IEC 61131-3 281
Table 87 – Static Assembly state event matrix 293
Table 88 – Dynamic Assembly state event matrix 294
Table 89 – Message Router object Forward_Open parameters 297
Table 90 – Status codes 299
Table 91 – Format of extended status 301
Table 92 – Get_Attribute_All service parameters 302
Table 93 – Set_Attribute_All service parameters 303
Table 94 – Get_Attribute_List service parameters 305
Table 95 – Set_Attribute_List service parameters 307
Table 96 – Reset service parameters 309
Table 97 – Start service parameters 311
Table 98 – Stop service parameters 313
Table 99 – Create service parameters 315
Table 100 – Delete service parameters 317
Table 101 – Get_Attribute_Single service parameters 318
Table 102 – Set_Attribute_Single service parameters 320
Table 103 – Find_Next_Object_Instance service parameters 322
Table 104 – NOP service parameters 324
Table 105 – Apply_Attributes service parameters 325
Table 106 – Save service parameters 327
Table 107 – Restore service parameters 329
Table 108 – CM_Open service parameters 337
Table 109 – CM_Close service parameters 339
Table 110 – CM_ Unconnected_Send service parameters 340
Table 111 – CM_Get_Connection_Data service parameters 342
Table 112 – CM_Search_Connection_Data service parameters 344
Table 113 – CM_Get_Connection_Data service parameters 345
Table 114 – How production trigger, transport class, and CM_RPI determine when data is produced 348
Table 115 – Transport classes 358
Table 116 – UCMM_Create service parameters 375
Table 117 – UCMM_Delete service parameters 376
Table 118 – UCMM_Write service parameters 377
Table 119 – UCMM_Abort service parameters 379
Table 120 – TR_Write service parameters 379
Table 121 – TR_Trigger service parameters 380

Withdrawn
iTeh Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-5:2003
https://standards.iteh.ai/catalog/standards/sist/...-61158-5-2003

Table 122 – TR_Packet_arrived service parameters 380
Table 123 – TR_Ack_received service parameters 381
Table 124 – TR_Verify service parameters 381
Table 125 – TR_Status_updated service parameters 382
Table 126 – FAL class summary 382
Table 127 – FAL services by AR type 383
Table 128 – Requirements and features of fieldbus DP 385
Table 129 – Status values of the service primitives 401
Table 130 – Access Rights MS1 403
Table 131 – Access Rights MS2 404
Table 132 – Access Rights MS1 406
Table 133 – Access Rights MS2 406
Table 134 – SCL matching rules 407
Table 135 – Read 408
Table 136 – Write 409
Table 137 – Data transport 410
Table 138 – Format (simple input data description) 414
Table 139 – Consistency (simple input data description) 414
Table 140 – Format (simple output data) 416
Table 141 – Consistency (simple output data) 416
Table 142 – Format (extended input data) 417
Table 143 – Consistency (extended input data) 417
Table 144 – Format (extended output data) 419
Table 145 – Consistency (extended output data) 419
Table 146 – Set Input 420
Table 147 – Read Input 421
Table 148 – Get Input 422
Table 149 – New Input 422
Table 150 – Set Output 424
Table 151 – Final 424
Table 152 – Read Output 425
Table 153 – Get Output 426
Table 154 – Clear Flag 426
Table 155 – New Flag 426
Table 156 – New Output 426
Table 157 – Clear Flag 427
Table 158 – Global Control 427
Table 159 – Clear Command 428
Table 160 – Sync Command 428
Table 161 – Freeze Command 428
Table 162 – New publisher data 428
Table 163 – Get publisher data 429
Table 164 – New Flag 429
Table 165 – SYNCH 430
Table 166 – SYNCH Delayed 430
Table 167 – DX Finished 431

Withdrawn
iTeh Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-5:2003
https://standards.iteh.ai/catalog/standards/iec/4bbc9777-4a7d-4b4e-a21e-009a7f236e8a/iec-61158-5-2003

Table 168 – SYNCH Event 431
Table 169 – Status 431
Table 170 – Primitives issued by the AL to the PLL state machine 440
Table 171 – Primitives issued by the user to the PLL state machine 440
Table 172 – Allowed values of status 440
Table 173 – Primitives issued by the user to the input state machine 440
Table 174 – Primitives issued by the user to the output state machine 441
Table 175 – Primitives issued by the PLL to the output state machine 441
Table 176 – Primitives issued by the output to the PLL state machine 441
Table 177 – Primitives issued by the PLL to the input state machine 441
Table 178 – Primitives issued by the output to the input state machine 441
Table 179 – Primitives issued by the output state machine to the AL 442
Table 180 – Primitives issued by the AL to the output state machine 442
Table 181 – Primitives issued by the input state machine to the AL 442
Table 182 – Primitives issued by the AL to the input state machine 442
Table 183 – PLL state table 445
Table 184 – OUTPUT state table 449
Table 185 – INPUT state table 453
Table 186 – Identifier status 455
Table 187 – Channel type 456
Table 188 – IO type 456
Table 189 – Error type 457
Table 190 – Status type 457
Table 191 – Status specifier 458
Table 192 – Status specifier 459
Table 193 – Module status 459
Table 194 – Status specifier 460
Table 195 – Link status 460
Table 196 – Link error 461
Table 197 – Set Slave Diag 462
Table 198 – Ext Diag Flag 462
Table 199 – Get Slave Diag 464
Table 200 – Read Slave Diag 473
Table 201 – New Slave Diag 481
Table 202 – Alarm type 483
Table 203 – Add Ack 483
Table 204 – Alarm specifier 483
Table 205 – Alarm notification 484
Table 206 – Alarm Ack 485
Table 207 – Prm data type 490
Table 208 – Supported feature 499
Table 209 – Supported profile feature 499
Table 210 – Role 500
Table 211 – Check user Prm 502
Table 212 – Prm structure 503
Table 213 – MS1 Command 505

Withdrawn
iTeh Standards
(https://standards.iteh.ai)
Document Preview
IEC 61158-5:2003
https://standards.iteh.ai/catalog/standards/iec/4bbc9779-4a7d-4b4e-a21e-009a7f236e8a/iec-61158-5-2003