



SLOVENSKI STANDARD
SIST EN 300 903 V7.1.1:2003
01-december-2003

8 [[[HJb]`W] b]`hY`ca i b]_UW`g_]`g]ghYa `fZuU&ZL`E`J]X]_]`bU flrcj Ub`UcXXUUb`U
 [c] cfbY`ghcf]hj Y`j `Uj bYa `cdYbg_Ya `a cV]`bYa `ca fY`f`fD@ABL`g]ghYa U; GA
 fl GA `\$' ') \$zfUh`]]WU+`%`%`z]nXUU`%`-, Ł

Digital cellular telecommunications system (Phase 2+) (GSM); Transmission planning aspects of the speech service in the GSM Public Land Mobile Network (PLMN) system (GSM 03.50 version 7.1.1 Release 1998)

iteh STANDARD PREVIEW
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/2b07515c-cadc-46b3-8b79-c970b9f1da63/sist-en-300-903-v7-1-1-2003>

Ta slovenski standard je istoveten z: EN 300 903 Version 7.1.1

ICS:

33.070.50	Globalni sistem za mobilno telekomunikacijo (GSM)	Global System for Mobile Communication (GSM)
-----------	---------------------------------------------------	----------------------------------------------

SIST EN 300 903 V7.1.1:2003 **en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 903 V7.1.1:2003](https://standards.iteh.ai/catalog/standards/sist/2b07515c-cadc-46b3-8b79-c970b9f1da63/sist-en-300-903-v7-1-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/2b07515c-cadc-46b3-8b79-c970b9f1da63/sist-en-300-903-v7-1-1-2003>

ETSI EN 300 903 V7.1.1 (2000-11)

European Standard (Telecommunications series)

**Digital cellular telecommunications system (Phase 2+);
Transmission planning aspects
of the speech service in the GSM
Public Land Mobile Network (PLMN) system
(GSM 03.50 version 7.1.1 Release 1998)**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

GSM®
GLOBAL SYSTEM FOR
MOBILE COMMUNICATIONS

[SIST EN 300 903 V7.1.1:2003](https://standards.iteh.ai/catalog/standards/sist/2b07515c-cadc-46b3-8b79-c970b9f1da63/sist-en-300-903-v7-1-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/2b07515c-cadc-46b3-8b79-c970b9f1da63/sist-en-300-903-v7-1-1-2003>



Reference

REN/SMG-110350Q7R1

KeywordsDigital cellular telecommunications system,
Global System for Mobile communications (GSM)**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88**iTeh STANDARD PREVIEW**
(standards.iteh.ai)SIST EN 300 903 V7.1.1:2003<https://standards.iteh.ai/catalog/standards/sist/2b07515c-cadc-46b3-8b79-c970b9f1da63/sist-en-300-903-v7-1-1-2003>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:
editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Contents

Intellectual Property Rights	7
Foreword.....	7
1 Scope	8
1.1 References	8
1.2 Abbreviations	10
1.3 Introduction	10
2 Network configurations	11
2.1 General	11
2.2 Model of the PLMN	11
2.3 Interfaces	11
2.4 Configurations of connections	12
2.4.1 General configurations of connections.....	12
2.4.2 Reference configurations to illustrate delay and echo control issues.....	12
2.5 4-wire circuits in the PLMN.....	12
3 Transmission performance	13
3.1 Overall Loss/Loudness ratings	13
3.1.1 Connections with handset MSs.....	14
3.1.2 Connections with handsfree MSs.....	14
3.1.3 Connections with headset MSs.....	14
3.2 Stability Loss.....	15
3.3 Delay	15
3.3.1 General.....	15
3.3.2 Sources of delay	15
3.3.2.1 Elements of the PLMN that cause delay	15
3.3.2.2 Elements of the PSTN that cause delay.....	16
3.3.3 Effects of delay.....	16
3.3.4 Allocation of delay to the PLMN.....	16
3.3.4.1 Allocation of delay to the PLMN when using a full rate system.....	16
3.3.4.2 Allocation of delay to the PLMN when using a half rate system.....	16
3.3.5 Delay of various network configurations.....	17
3.3.5.1 National and international connections with no echo control in the PSTN (reference configurations A)	17
3.3.5.2 National and international connections with echo control in the PSTN (reference configurations B).....	17
3.3.5.3 Connections where re-routing leads to a significant increase in transmission path length (reference configurations C).....	17
3.3.6 Delay related requirements on the MS.....	17
3.3.6.1 Full rate MS.....	17
3.3.6.2 Half rate MS.....	17
3.3.6.3 Handsfree MS.....	17
3.4 Echo.....	18
3.4.1 General.....	18
3.4.2 Electrical echo control in the PLMN (Reference configurations A).....	18
3.4.3 Acoustic echo control in the PLMN	18
3.4.3.1 Acoustic echo control in a handsfree MS.....	19
3.4.3.2 Acoustic echo control in a handset MS	19
3.4.3.3 Acoustic echo control in a headset MS	19
3.4.4 Interaction between tandem echo control devices (reference configurations B & C).....	19
3.5 Clipping.....	19
3.5.1 General.....	19
3.5.2 Properties of voice switches in the PLMN.....	19
3.5.3 Problems of tandem voice switching	20
3.6 Idle channel noise (handset and headset MS).....	20
3.6.1 Sending	20
3.6.2 Receiving	20

3.7	Noise contrast	20
3.7.1	General	20
3.7.2	Elements of a PLMN which can cause noise contrast impairment	21
3.7.3	Reduction of noise contrast	21
3.7.3.1	Reduction of noise contrast by limiting the noise received by the microphone	21
3.7.3.1.1	Headset MS	21
3.7.3.1.2	Handset MS	22
3.7.3.1.3	Handsfree MS	22
3.7.3.2	Reduction of noise contrast by insertion of comfort noise	22
3.7.4	Consequence of the introduction of high comfort noise levels on other voice-operated devices	22
3.8	Sensitivity/frequency characteristics	22
3.8.1	Headset and Handset MSs	22
3.8.1.1	Sending	22
3.8.1.2	Receiving	23
3.8.2	Handsfree MS	23
3.8.2.1	Sending	23
3.8.2.2	Receiving	24
3.9	Distortion (handset and headset MS)	24
3.9.1	Sending	24
3.9.2	Receiving	25
3.10	Sidetone (handset and headset MS)	26
3.10.1	Sidetone loss	26
3.10.2	Sidetone distortion	26
3.11	Out-of-band signals	26
3.11.1	Discrimination against out-of-band input signals	26
3.11.1.1	Handset and headset MS	26
3.11.1.2	Handsfree MS	26
3.11.2	Spurious out-of-band signals	27
3.11.2.1	Handset and headset MS	27
3.11.2.2	Handsfree MS	27
3.12	Requirements for information tones	27
3.13	Crosstalk	27
3.13.1	Near and far end crosstalk	27
3.13.2	Go/return crosstalk	28
3.14	MS Ambient Noise Rejection	28
3.14.1	Full-Rate, (TCH-FS) MS Ambient Noise Rejection (handset MS)	28
3.14.2	Full-Rate, (TCH-FS) MS Ambient Noise Rejection (handsfree MS)	28
3.14.3	Half-Rate, (TCH-HS) MS and Dual-Rate (TCH-FS and TCH-HS) MS Ambient Noise Rejection	28
Annex A (informative): Considerations on the Acoustic Interface of the Mobile Station		37
A.1	Handsfree MS	37
A.2	Handset MS	37
A.3	Headset MS	37
A.4	Inter-reaction with DTX	37
Annex B (normative): Test considerations		38
B.1	Test signals	38
B.1.1	Sinusoidal signals	38
B.1.2	Artificial voice	38
B.2	Test signal levels	38
B.2.1	Sending	38
B.2.1.1	Handset and headset MSs	38
B.2.1.2	Office type Handsfree MS	38
B.2.1.3	Car type Handsfree MS	39
B.2.2	Receiving	39
B.3	Test rooms	39
B.3.1	Anechoic room	39

B.4	Test arrangement	40
B.4.1	Electro-acoustic equipment	40
B.4.2	Test arrangement for handsfree MS	41
B.4.2.1	Office type handsfree MS	41
B.4.2.2	Car type handsfree MS.....	41
B.4.2.3	Use of HATS for testing the receive characteristics of the car type handsfree MS	42
B.4.2.3.1	Equalization of HATS.....	42
B.4.2.3.2	Combination of ear signals.....	43
Annex C (normative):	Transmission requirements testing	44
C.1	Loudness ratings.....	44
C.1.1	Sending Loudness Rating (SLR) - Handset MS	44
C.1.2	Sending Loudness Rating (SLR) - Handsfree MS	44
C.1.3	Receiving Loudness Rating (RLR) - Handset MS.....	44
C.1.4	Receiving Loudness Rating (RLR) - Handsfree MS	45
C.2	Idle Channel Noise	45
C.2.1	Sending.....	45
C.2.2	Receiving.....	45
C.3	Sensitivity/frequency characteristics	45
C.3.1	Sending - Handset MS.....	45
C.3.2	Sending - Handsfree MS	46
C.3.3	Receiving - Handset	46
C.3.4	Receiving - Handsfree	47
C.4	Distortion.....	47
C.4.1	Sending.....	47
C.4.2	Receiving.....	47
C.5	Variation of gain with input level.....	48
C.5.1	Sending.....	48
C.5.2	Receiving.....	48
C.6	Sidetone.....	48
C.6.1	Talker sidetone (STMTR).....	48
C.6.2	Listener sidetone (LSTR)	48
C.7	Sidetone distortion.....	49
C.8	Out-of-band signals	49
C.8.1	Discrimination against out-of-band input signal for handset and headset MS	49
C.8.2	Spurious out-of-band signals for handset and headset MS	49
C.8.3	Discrimination against out-of-band signals for handsfree MS	49
C.8.4	Spurious out-of-band emissions for handsfree MS.....	49
C.9	Acoustic echo loss	50
C.9.1	Acoustic echo loss - Handset MS	50
C.9.2	Acoustic echo loss - Handsfree MS.....	50
C.10	Delay for handsfree MS.....	51
C.10.1	Uplink.....	51
C.10.2	Downlink	51
C.10.3	Result.....	51
C.11	Ambient noise rejection.....	51
C.11.1	Full-Rate, (TCH-FS) MS Ambient Noise Rejection (handset MS).....	53
C.11.2	Full-Rate, (TCH-FS) MS Ambient Noise Rejection (handsfree MS).....	53
C.11.3	Half-Rate, (TCH-HS) MS and Dual-Rate (TCH-FS and TCH-HS) MS Ambient Noise Rejection.....	53

iTech STANDARD PREVIEW
(standards.itech.ai)

SIST EN 300 903 V7.1.1:2003

[https://standards.itech.ai/catalog/standards/sist/2b07515c-cadc-46b3-8b79-](https://standards.itech.ai/catalog/standards/sist/2b07515c-cadc-46b3-8b79-c970b9f1da63/sist-en-300-903-v7-1-1-2003)

[c970b9f1da63/sist-en-300-903-v7-1-1-2003](https://standards.itech.ai/catalog/standards/sist/2b07515c-cadc-46b3-8b79-c970b9f1da63/sist-en-300-903-v7-1-1-2003)

Annex D (normative):	MS delay requirement definition.....	54
D.1	Full rate MS delay requirement definition	54
D.2	Half rate MS delay requirement definition.....	55
Annex E (informative):	Adaptive gain control	56
Annex F (informative):	Change Request History.....	57
History		58

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 903 V7.1.1:2003](https://standards.iteh.ai/catalog/standards/sist/2b07515c-cadc-46b3-8b79-c970b9f1da63/sist-en-300-903-v7-1-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/2b07515c-cadc-46b3-8b79-c970b9f1da63/sist-en-300-903-v7-1-1-2003>

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Special Mobile Group (SMG).

The present document describes the transmission planning aspects pertaining to the speech service within the digital cellular telecommunications system (Phase 2+).

The contents of the present document is subject to continuing work within SMG and may change following formal SMG approval. Should SMG modify the contents of the present document it will be re-released with an identifying change of release date and an increase in version number as follows:

Version 7.x.y

where:

- 7 indicates Release 1998 of GSM Phase 2+.
- x the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- y the third digit is incremented when editorial only changes have been incorporated in the specification.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

National transposition dates

Date of adoption of this EN:	17 November 2000
Date of latest announcement of this EN (doa):	28 February 2001
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 August 2001
Date of withdrawal of any conflicting National Standard (dow):	31 August 2001

1 Scope

The present document describes the transmission planning aspects pertaining to the speech service in the GSM PLMN system. Due to technical and economic factors, there cannot be full compliance with the general characteristics of international telephone connections and circuits recommended by the ITU-T.

The present document gives guidance as to the precautions, measures and minimum requirements needed for successful interworking of the PLMN with the national and international PSTN. The present document identifies a number of routing and network configurations. The objective is to reach a quality as close as possible to ITU-T standards in order to safeguard the performance seen by PSTN customers.

1.1 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- A non-specific reference to an ETS shall also be taken to refer to later versions published as an EN with the same number.
- For this Release 1998 document, references to GSM documents are for Release 1998 versions (version 7.x.y).

- iTeh STANDARD PREVIEW**
(standards.iteh.ai)
- [1] GSM 01.04: "Digital cellular telecommunications system (Phase 2+); Abbreviations and acronyms". [SIST EN 300 903 V7.1.1:2003](https://standards.iteh.ai/catalog/standards/sist/2b07515c-cadc-46b3-8b79-9740211da65/sist-en-300-903-v7-1-1-2003)
- [2] GSM 03.04: "Digital cellular telecommunications system (Phase 2+); Signalling requirements relating to routing of calls to mobile subscribers". <https://standards.iteh.ai/catalog/standards/sist/2b07515c-cadc-46b3-8b79-9740211da65/sist-en-300-903-v7-1-1-2003>
- [3] GSM 06.01: "Digital cellular telecommunications system (Phase 2+); Full rate speech processing functions".
- [4] GSM 06.10: "Digital cellular telecommunications system (Phase 2+); Full rate speech; Transcoding".
- [5] GSM 06.11: "Digital cellular telecommunications system (Phase 2+); Full rate speech; Substitution and muting of lost frames for full rate speech channels".
- [6] GSM 06.12: "Digital cellular telecommunications system (Phase 2+); Full rate speech; Comfort noise aspect for full rate speech traffic channels".
- [7] GSM 06.31: "Digital cellular telecommunications system (Phase 2+); Full rate speech; Discontinuous Transmission (DTX) for full rate speech traffic channels".
- [8] GSM 06.32: "Digital cellular telecommunications system (Phase 2+); Voice Activity Detection (VAD)".
- [9] GSM 06.02: "Digital cellular telecommunications system (Phase 2+); Half rate speech; Half rate speech processing functions".
- [10] GSM 06.20: "Digital cellular telecommunications system (Phase 2+); Half rate speech; Half rate speech transcoding".
- [11] GSM 06.21: "Digital cellular telecommunications system (Phase 2+); Half rate speech; Substitution and muting of lost frames for half rate speech traffic channels".

- [12] GSM 06.22: "Digital cellular telecommunications system (Phase 2+); Half rate speech; Comfort noise aspects for half rate speech traffic channels".
- [13] GSM 06.41: "Digital cellular telecommunications system (Phase 2+); Half rate speech; Discontinuous Transmission (DTX) for half rate speech traffic channels".
- [14] GSM 06.42: "Digital cellular telecommunications system (Phase 2+); Half rate speech; Voice Activity Detection (VAD) for half rate speech traffic channels".
- [15] I-ETS 300 245-2: "Integrated Services Digital Network (ISDN): Technical characteristics of telephony terminals: Part 2: PCM A-Law handset telephony".
- [16] ITU-T Recommendation G.103 (1998): "Hypothetical reference connections".
- [17] ITU-T Recommendation G.111 (1993): "Loudness ratings (LRs) in an international connection".
- [18] ITU-T Recommendation G.113 (1993): "Transmission impairments".
- [19] ITU-T Recommendation G.114 (1993): "Mean one-way propagation time".
- [20] ITU-T Recommendation G.121 (1993): "Loudness ratings (LRs) of national systems".
- [21] ITU-T Recommendation G.122 (1993): "Influence of national systems on stability, talker echo, and listener echo in international connections".
- [22] ITU-T Recommendation G.131 (1988): "Stability and echo".
- [23] ITU-T Recommendation G.165 (1993): "Echo cancellers".
- [24] ITU-T Recommendation G.223 (1988): "Assumptions for the calculation of noise on hypothetical reference circuits for telephony".
- [25] ITU-T Recommendation G.703 (1991): "Physical/electrical characteristics of hierarchical digital interfaces".
- [26] ITU-T Recommendation G.711 (1988): "Pulse code modulation (PCM) of voice frequencies".
- [27] ITU-T Recommendation G.712 (1992): "Transmission performance characteristics of pulse code modulation".
- [28] ITU-T Recommendation G.167 (1993): "Acoustic Echo Controllers".
- [29] ITU-T Recommendation M.1020 (1993): "Characteristics of special quality international leased circuits with special bandwidth conditions".
- [30] ITU-T Recommendation M.1025 (1993): "Characteristics of special quality international leased circuits with basic bandwidth conditioning".
- [31] ITU-T Recommendation M.1030 (1988): "Characteristics of ordinary quality international leased circuits forming part of private switched telephone networks".
- [32] ITU-T Recommendations M.1040 (1988): "Characteristics of ordinary quality international leased circuits".
- [33] ITU-T Recommendation O.132 (1988): "Specification for a quantizing distortion measuring apparatus using a sinusoidal test signal".
- [34] ITU-T Recommendation P.11 (1993): "Effect of transmission impairments".
- [35] ITU-T Recommendation P.34 (1993): "Transmission characteristics of hands-free telephones".
- [36] ITU-T Recommendation P.38 (1993): "Transmission characteristics of operator telephone systems (OTS)".
- [37] ITU-T Recommendation P.50 (1993): "Artificial voices".
- [38] ITU-T Recommendation P.51 (1993): "Artificial mouths".

- [39] ITU-T Recommendation P.64 (1993): "Determination of sensitivity/frequency characteristics of local telephone".
- [40] ITU-T Recommendation P.76 (1988): "Determination of loudness ratings; fundamental principles".
- [41] ITU-T Recommendation P.79 (1993): "Calculation of loudness ratings".
- [42] ITU-T Recommendation Q.35 (1988): "Technical characteristics of tones for the telephone service".
- [43] ITU-T Recommendation Q.551 (1994): "Transmission characteristics of digital exchanges".
- [44] ITU-T Blue Book (1988): "Volume V, Supplement 13: Noise spectra".
- [45] ISO 3 - 1973: "Preferred numbers - series of preferred numbers".
- [46] ITU-T Recommendation P.57 (1996): "Artificial Ears".
- [47] ITU-T Recommendation P.58 (1993): "Head and Torso Simulator for Telephonometry".
- [48] I-ETS 300 245-3: "Integrated Services Digital Network (ISDN): Technical characteristics of telephony terminal: Part 3: PCM A-law loudspeaking and handsfree telephony".

1.2 Abbreviations

In addition to those below, the abbreviations used in the present document are listed in GSM 01.04.

ADC	Analogue to Digital Converter
ADPCM	Adaptive Differential Pulse Code Modulation
AEC	Acoustic Echo Control
BSC	Base Station Controller (excluding transmission systems)
BTS	Base Transceiver Station (excluding transmission systems)
DAC	Digital to Analogue Converter
DMR	Digital Mobile Radio
DSI	Digital Speech Interpolation
EEC	Electric Echo Control
EL	Echo Loss
ERP	Ear Reference Point
FDM	Frequency Division Multiplex
ISC	International Switching
LE	Local Exchange
LSTR	Listener Sidetone Rating
MRP	Mouth Reference Point
OLR	Overall Loudness Rating
PCM	Pulse Code Modulation
POI	Point of Interconnection (with PSTN)
RLR	Receiver Loudness Rating
SLR	Send Loudness Rating
STMR	Sidetone Masking Rating
UPCMI	13-bit Uniform PCM Interface

1.3 Introduction

Since the transmission quality and the conversational quality of the PLMN will in general be lower than the quality of the PSTN connection due to coding distortion, delay, etc., only some transmission aspects can be brought in line with ITU-T Recommendations. It is therefore necessary to improve the overall quality as much as possible by implementing proper routing and network configurations.

It should be recognized that the transmission plan for the GSM PLMN cannot lead to major changes in the PSTN. However, it is important to use the improvements in the evolving PSTN (e.g. digitalization, introduction of echo cancellers) in an effective way.

The transmission requirements are in the first place based on international connections. When the quality is sufficient for international connections, it can be assumed that the national connections will have the same or better quality.

In order to obtain a sufficient quality in the connection, it is preferable to have digital connectivity between the Base Station System (BSS) and the international exchange. The PLMN requirements are based on this assumption. When this situation cannot be provided, a lower quality must temporarily be accepted.

The present document consists of two parts: one will deal with network configurations, the other with transmission performance.

The part about network configurations gives information about the reference connections, on which the transmission plan is based. Furthermore, some guidelines are presented for improvement of the transmission quality in the evolving (digital) PSTN.

The part about transmission performance gives mainly characteristics of the transmission between MS acoustic interface (MRP/ERP) and the interface between the PLMN and the PSTN (POI). For transmission aspects where it is impossible to give overall characteristics, it is in some cases necessary to make recommendations for individual parts of the equipment.

Annex A considers the effects of the type of acoustic interfaces of the MS.

2 Network configurations

2.1 General

The basic configuration for the interworking with the PSTN is shown in figure 1.

2.2 Model of the PLMN

A more detailed model of the PLMN used for the consideration of transmission planning issues for speech is shown in figure 2. This model represents the main functions required and does not necessarily imply any particular physical realization. Routeing of calls is given in GSM 03.04.

Any acoustic echo control is not specifically shown as it will be provided by analogue processing of digital processing or a combination of both techniques.

2.3 Interfaces

The main interfaces identified within the GSM specifications are shown in figure 1. For the purposes of the present document, the Air Interface and the Point of Interconnect (POI) are identified along with two other interfaces, Interface Z and a 13-bit Uniform PCM Interface (UPCMI). These interfaces are needed to define the PLMN transmission characteristics and the overall system requirements.

The Air Interface is specified by GSM 05 series specifications and is required to achieve MS transportability. Analogue measurements can be made at this point by using the appropriate radio terminal equipment and speech transcoder. The losses and gains introduced by the test speech transcoder will need to be specified.

The POI with the PSTN will generally be at the 2 048 kbits/s level at an interface, in accordance with ITU-T Recommendation G.703. At the point, which is considered to have a relative level of 0 dBr, the analogue signals will be represented by 8-bit A-law, according to ITU-T Recommendation G.711. Analogue measurements may be made at this point using a standard send and receive side, as defined in ITU-T Recommendations.

Interface Z might be used in the case of direct MSC to MSC connections. Interface Z is of the same nature as the POI.

The UPCMI is introduced for design purposes in order to separate the speech transcoder impairments from the basic audio impairments of the MS.

2.4 Configurations of connections

2.4.1 General configurations of connections

Figure 3 shows a variety of configurations of connections. There are a number of PSTN features which should be avoided from such connections. These include:

- echo control devices in the international network. If present, and not disabled, these devices will be in tandem with PLMN echo cancellers and may introduce degradation;
- satellite routings. The delay inherent in the connections when added to the PLMN delay, may result in conversational difficulties. Double satellite links are likely to cause severe difficulties and special precautions should be taken to avoid this situation under call forwarding arrangements;
- Digital Speech Interpolation systems (DSI). There is likely to be an adverse interaction between DSI and DTX;
- ADPCM. The distortion introduced by ADPCM on routes where PSTN echo control is not provided is likely to reduce the echo cancellation provided by the PLMN electric echo canceller;
- significant differences in clock rates on non-synchronized digital network components. The resulting phase roll and slips are likely to degrade the performance of the PLMN echo canceller;
- those analogue FDM routings which exhibit phase roll. Any phase roll due to the absence of synchronization between the carrier frequencies on the two directions of transmission is likely to degrade the performance of the PLMN echo canceller;
- tandem connections of sources of quantization distortion. The PLMN speech transcoder is estimated to be equivalent to 7 QDUs between uniform PCM interfaces (see ITU-T Recommendation G.113).

It is recognized that on some connections it may not be feasible to avoid these features, but in many cases, especially if taken into account at the planning stage, this should be possible.

2.4.2 Reference configurations to illustrate delay and echo control issues

Three basic reference configuration types shown in figures 4 to 6 are defined to illustrate delay and echo control issues. Intermediate echo control devices as shown in the figures are disabled by appropriate signalling between the MSC and ISC or MSC and MSC.

Reference configurations A (see figure 4) represent national or international connections where there is no echo control device in the PSTN. These reference configurations include re-routings configurations where the overall delay of the transmission path has not been extended.

Reference configurations B (see figure 5) represent national or international connections where echo control is provided in the PSTN. These reference configurations include re-routings configurations where the overall delay of the transmission path has not been extended.

Reference configurations C (see figure 6) represent national or international connections where re-routings has led to an increase in the overall delay of the transmission path beyond recommended limits.

2.5 4-wire circuits in the PLMN

As shown in figure 2, the PLMN will usually contain transmission systems. Where present, they should provide 4-wire circuits.

In the case of digital circuits which do not include any speech processing devices, the overall system requirements of the PLMN will not be affected by the presence of the link.

In the case of analogue links, the transmission characteristics (e.g. attenuation, attenuation distortion, noise) will affect the overall system requirements of the PLMN. ITU-T Recommendations M.1020, M.1025, M.1030 and M.1040 describe several transmission characteristics for leased circuits. In cases where the analogue link introduces loss, provision will have to be made at the interface to restore the loss.

3 Transmission performance

The overall transmission performance of connections in alternate conversation mode can be considered as a summation of the effects of:

- the audio part between the MRP/ERP and the UPCMI interface;
- the speech transcoder part including the effects of radio transmission, and speech processing between the UPCMI and the POI;
- the overall characteristics of the connection between POI and the other user.

There is not only a linear addition of these effects but there is also an influence from different parts of the connection on the performance of the speech transcoder and other speech processing devices.

Where possible, the transmission performance is specified between the MRP/ERP and the POI. Where this is not possible, the transmission aspects of the audio part mentioned above have been specified. The transmission aspects of the speech transcoder are specified in GSM 06 series specifications. In the following paragraphs, requirements are specified for the UPCMI, the Air Interface or the POI as appropriate.

The transmission requirements of the MS have been derived from the requirements of digital telephones stated in I-ETS 300 245-2 and 3.

MSs will have to work in a variety of environments ranging from quiet office locations to very noisy environments as found in moving cars. In noisy conditions, different values for the sending and receiving sensitivities relative to the nominal values can increase the performance of the terminal. Some guidance is given in annex E.

The overall transmission performance in full duplex conversation mode will also greatly depend on the performance of the echo control devices which may be included in the connection.

The handsfree requirements in the present document are designed to provide a basic level of performance and to avoid adverse interactions with other networks. Testing is carried out in one configuration in a vehicle, whilst this gives some confidence that the system can work in a typical environment, the testing is by no means complete. It is assumed that the manufacturer submits the handsfree system with the transducers fitted in reasonable locations within the vehicle (the transducers should not impede the normal operation of the vehicle or its fittings). Unusual installations should be agreed for suitability with the relevant Type Approval Authority before testing.

In a real vehicle installation, care should be taken to allow for the acoustic properties of that vehicle and the likely acoustic environment. It is important that the best possible coupling between the microphone and the MS user is achieved. Hence the microphone should be directional and mounted as close to the user's mouth as practical. The loudspeakers should be mounted in such a way that the maximum receive signal is directed at the user, rather than dissipated by the various obstacles in that vehicle, such as the seats.

Proper consideration for the noise environment and the direct coupling between the microphone and loudspeakers is necessary. Excessive noise coupled into the microphone can mask the MS user's send speech and potentially affect the operation of DTX. The vehicle noise environment can potentially mask the received speech, unless sufficient volume is provided. However, direct coupling between the transducers can cause annoying echo to be heard by the far end user.

Primary factors affecting the coupling between the loudspeaker(s) and microphone(s) include:

- directionality of the microphone(s);
- directionality of the loudspeaker(s);
- location of the transducers in relation to each other and reflecting surfaces such as the windows and windscreen.

3.1 Overall Loss/Loudness ratings

The overall international connection involving PLMNs and the PSTN should meet the overall loudness rating (OLR) limits in ITU-T Recommendation G.111. The national parts of the connection should therefore meet the send and receive loudness rating (SLR, RLR) limits in ITU-T Recommendation G.121.