



Designation: **D5967—19** **D5967 – 21**

Standard Test Method for Evaluation of Diesel Engine Oils in T-8 Diesel Engine¹

This standard is issued under the fixed designation D5967; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This test method covers an engine test procedure for evaluating diesel engine oils for performance characteristics, including viscosity increase and soot concentrations (loading).² This test method is commonly referred to as the Mack T-8.

1.2 This test method also provides the procedure for running an extended length T-8 test, which is commonly referred to as the T-8E and an abbreviated length test, which is commonly referred to as T-8A. The procedures for the T-8E and the T-8A are identical to the T-8 with the exception of the items specifically listed in [Annex A8](#) and [Annex A9](#) respectively. Additionally, the procedure modifications listed in [Annex A8](#) and [Annex A9](#) refer to the corresponding section of the T-8 procedure.

1.3 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.3.1 *Exceptions*—Where there is no direct SI equivalent such as the units for screw threads, National Pipe Threads/diameters, tubing size, sole source equipment suppliers, and oil consumption in grams per kilowatt-hour.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use. See [Annex A6](#) for specific safety precautions.*

1.5 A Table of Contents follows:

Scope	1
Referenced Documents	2
Terminology	3
Summary of Test Method	4
Significance and Use	5
Apparatus	6
General Description	6.1
The Test Engine	6.2
Mack Test Engine	6.2.1
Engine Cooling System	6.2.2
Engine Oil System	6.2.3
Auxiliary Oil System	6.2.4
Crankcase Aspiration	6.2.5
Blowby Meter	6.2.6
Air Supply and Filtration	6.2.7

¹ This test method is under the jurisdiction of ASTM Committee D02 on Petroleum Products, Liquid Fuels, and Lubricants and is the direct responsibility of Subcommittee D02.B0.02 on Heavy Duty Engine Oils.

Current edition approved Nov. 1, 2019/July 1, 2021. Published November 2019/July 2021. Originally approved in 1996. Last previous edition approved in 2017/2019 as [D5967—17](#)/[D5967 – 19](#). DOI: [10.1520/D5967-19.1520/D5967-21](#).

² The ASTM Test Monitoring Center will update changes in this test method by means of Information Letters. This edition incorporates revisions contained in all information letters through [19-1-21-1](#). Information letters may be obtained from the ASTM Test Monitoring Center, 6555 Penn Avenue, Pittsburgh, PA 15206-4489, Attention: Administrator.

*A Summary of Changes section appears at the end of this standard

Fuel Supply	6.2.8
Intake Manifold Temperature Control	6.2.9
Engine Fluids	7
Test Oil	7.1
Test Fuel	7.2
Engine Coolant	7.3
Cleaning Materials	7.4
Preparation of Apparatus at Rebuild	8
Cleaning of Parts	8.1
Valves, Seats, Guides, and Springs	8.2
Cylinder Liner, Piston, and Piston Ring Assembly	8.3
Injectors and Injection Pump	8.4
Assembly Instructions	8.5
Measurements	8.6
Laboratory and Engine Test Stand Calibration/Non-Reference Requirements	9
Calibration Frequency	9.1
Calibration Reference Oils	9.2
Test Numbering	9.3
New Laboratories and New Test Stands	9.4
Calibrated Laboratories and Test Stands	9.5
Calibration Test Acceptance	9.6
Failing Calibration Tests	9.7
Non-Reference Oil Test Requirements	9.8
Procedure	10
Pretest Procedure	10.1
Engine Start-Up	10.2
Engine Shutdown	10.3
Test Cycle	10.4
Oil Addition/Drain	10.5
Oil Samples	10.6
Oil Consumption Calculations	10.7
Fuel Samples	10.8
Periodic Measurements	10.9
Blowby	10.10
Centrifugal Oil Filter Mass Gain	10.11
Oil Filter ΔP Calculation	10.12
Post Test	10.13
Inspection of Fuel and Oil During Test	11
Oil Inspection	11.1
Fuel Inspections	11.2
Oil Consumption	11.3
Report	12
Reporting Test Results	12.1
Deviations from Test Operational Limits	12.2
Electronic Transmission of Test Results	12.3
Plots of Operational Data	12.4
Precision and Bias	13
Precision	13.1
Bias	13.2
Keywords	14
Annexes	
Report Forms	Annex A1
Sensor Locations	Annex A2
Kinematic Viscosity At 100°C For Test Method D5967 Samples	Annex A3
Kinematic Viscosity At 100 °C For Test Method D5967 Samples	Annex A3
Enhanced Thermal Gravimetric Analysis (TGA) Procedure	Annex A4
Procurement of Test Materials	Annex A5
Safety Precautions	Annex A6
Data Dictionary	Annex A7
T-8E Extended Length Test Requirements	Annex A8
T-8A Abbreviated Length Test Requirements	Annex A9
Mack T-8A, T-8, and T-8E Fuel Requirements	Annex A10

1.6 This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.

2. Referenced Documents

2.1 ASTM Standards:³

D86 Test Method for Distillation of Petroleum Products and Liquid Fuels at Atmospheric Pressure

³ For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For Annual Book of ASTM Standards volume information, refer to the standard's Document Summary page on the ASTM website.

- D93 Test Methods for Flash Point by Pensky-Martens Closed Cup Tester
- D97 Test Method for Pour Point of Petroleum Products
- D130 Test Method for Corrosiveness to Copper from Petroleum Products by Copper Strip Test
- D235 Specification for Mineral Spirits (Petroleum Spirits) (Hydrocarbon Dry Cleaning Solvent) (Withdrawn 2021)⁴
- D287 Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method)
- D445 Test Method for Kinematic Viscosity of Transparent and Opaque Liquids (and Calculation of Dynamic Viscosity)
- D446 Specifications and Operating Instructions for Glass Capillary Kinematic Viscometers
- D482 Test Method for Ash from Petroleum Products
- D524 Test Method for Ramsbottom Carbon Residue of Petroleum Products
- D613 Test Method for Cetane Number of Diesel Fuel Oil
- D664 Test Method for Acid Number of Petroleum Products by Potentiometric Titration
- D976 Test Method for Calculated Cetane Index of Distillate Fuels
- D1319 Test Method for Hydrocarbon Types in Liquid Petroleum Products by Fluorescent Indicator Adsorption
- D2274 Test Method for Oxidation Stability of Distillate Fuel Oil (Accelerated Method)
- D2500 Test Method for Cloud Point of Petroleum Products and Liquid Fuels
- D2622 Test Method for Sulfur in Petroleum Products by Wavelength Dispersive X-ray Fluorescence Spectrometry
- D2709 Test Method for Water and Sediment in Middle Distillate Fuels by Centrifuge
- D4052 Test Method for Density, Relative Density, and API Gravity of Liquids by Digital Density Meter
- D4175 Terminology Relating to Petroleum Products, Liquid Fuels, and Lubricants
- D4294 Test Method for Sulfur in Petroleum and Petroleum Products by Energy Dispersive X-ray Fluorescence Spectrometry
- D4485 Specification for Performance of Active API Service Category Engine Oils
- D4737 Test Method for Calculated Cetane Index by Four Variable Equation
- D5185 Test Method for Multielement Determination of Used and Unused Lubricating Oils and Base Oils by Inductively Coupled Plasma Atomic Emission Spectrometry (ICP-AES)
- D5453 Test Method for Determination of Total Sulfur in Light Hydrocarbons, Spark Ignition Engine Fuel, Diesel Engine Fuel, and Engine Oil by Ultraviolet Fluorescence
- D6278 Test Method for Shear Stability of Polymer Containing Fluids Using a European Diesel Injector Apparatus
- D7422 Test Method for Evaluation of Diesel Engine Oils in T-12 Exhaust Gas Recirculation Diesel Engine
- E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications
- 2.2 SAE Standard:⁵
- SAE J1995 Engine Power Test Code—Spark Ignition and Compression Ignition—Gross Power Rating

3. Terminology

3.1 Definitions:

- <https://standards.iteh.ai/catalog/standards/sist/331e21ee-df00-4ed3-9c29-6e7597ad1fd7/astm-d5967-21>
- 3.1.1 *blind reference oil, n*—a reference oil, the identity of which is unknown by the test facility. **D4175**
- 3.1.2 *blowby, n*—in internal combustion engines, that portion of the combustion products and unburned air/fuel mixture that leaks past piston rings into the engine crankcase during operation.
- 3.1.3 *calibrate, v*—to determine the indication or output of a device (e.g., thermometer, manometer, engine) with respect to that of a standard.
- 3.1.4 *heavy-duty, adj*—in internal combustion engine operation, characterized by average speeds, power output, and internal temperatures that are close to the potential maximums. **D4485**
- 3.1.5 *heavy-duty engine, n*—in internal combustion engine types, one that is designed to allow operation continuously at or close to its peak output.
- 3.1.6 *non-reference oil, n*—any oil other than a reference oil; such as a research formulation, commercial oil, or candidate oil. **D4175**
- 3.1.7 *non-standard test, n*—a test that is not conducted in conformance with the requirements in the standard test method, such

⁴ The last approved version of this historical standard is referenced on www.astm.org.

⁵ Available from Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096-0001.

as running on an uncalibrated test stand, using different test equipment, applying different equipment assembly procedures, or using modified operating conditions. **D4175**

3.1.8 *oxidation, n—of engine oil*, the reaction of the oil with an electron acceptor, generally oxygen, that can produce deleterious acidic or resinous materials often manifested as sludge formation, varnish formation, viscosity increase, or corrosion, or a combination thereof.

3.1.9 *reference oil, n*—an oil of known performance characteristics, used as a basis for comparison. **D4175**

3.1.9.1 *Discussion*—

Reference oils are used to calibrate testing facilities, to compare the performance of other oils, or to evaluate other materials (such as seals) that interact with oils.

3.1.10 *sludge, n—in internal combustion engines*, a deposit, principally composed of insoluble resins and oxidation products from fuel combustion and the lubricant, that does not drain from engine parts but can be removed by wiping with a cloth. **D4175**

3.1.11 *standard test, n*—a test on a calibrated test stand, using the prescribed equipment that is assembled according to the requirements in the test method, and conducted according to the specified operating conditions.

3.1.12 *varnish, n—in internal combustion engines*, a hard, dry, generally lustrous deposit that can be removed by solvents but not by wiping with a cloth. **D4175**

3.1.13 *wear, n*—the loss of material from a surface, generally occurring between two surfaces in relative motion, and resulting from mechanical or chemical action, or a combination of both. **D7422**

4. Summary of Test Method

4.1 The test operation involves use of a Mack E7-350 diesel engine with a warm-up, a 2 h flush for each test, and then a constant speed and torque conditions that are held for the remainder of the test. Reference oil test length is 300 h. Non-reference oil test length is 250 h.

4.2 Oil samples are taken periodically and analyzed for viscosity increase.

4.3 Engine rebuild frequency is based on the degradation of test parameters and is left to the discretion of the test laboratory. At rebuild, the power section of the engine is disassembled, solvent-cleaned, measured, and rebuilt, using all new pistons, rings, cylinder liners, and valve guides, in strict accordance with furnished specifications.

4.4 The engine crankcase is solvent-cleaned, and worn or defective parts are replaced.

4.5 The test stand is equipped with appropriate accessories for controlling speed, load, and various engine operating conditions.

5. Significance and Use

5.1 This test method was developed to evaluate the viscometric performance of engine oils in turbocharged and intercooled four-cycle diesel engines. Results are obtained from used oil analysis.

5.2 The test method is used for engine oil specification acceptance when all details of the procedure are followed.

6. Apparatus

6.1 *General Description:*

6.1.1 The test engine is a Mack E7-350 mechanically governed engine, P/N 11GBA77623 (see **Annex A5**). It is an open-chamber, in-line, six-cylinder, four-stroke, turbocharged, charge air-cooled, compression ignition engine. The bore and stroke are 124 mm by 165 mm, and the displacement is 12 L. The engine is rated at 261 kW at 1800 r/min governed speed (see SAE J1995).

6.1.2 The ambient laboratory atmosphere should be relatively free of dirt, dust, and other contaminants as required by good laboratory standards. Additionally, it is recommended that the atmosphere in the engine buildup area be filtered and controlled for temperature and humidity to prevent accumulation of dirt or dust on engine parts. Uniform temperature control will also aid in measuring and selecting parts for assembly.

6.1.3 Use the low sulfur reference diesel fuel shown in the “PC-9-HS Fuel Specification” section of the TMC-Monitored Test Fuel Specifications” document maintained by the TMC.

6.2 *The Test Engine:*

6.2.1 *Mack Test Engine*—The engine is available from Mack Trucks, Inc. A complete parts list is shown in [Table A5.1](#).

6.2.2 *Engine Cooling System:*

6.2.2.1 A new Mack coolant conditioner shown in [Table A5.1](#) is required every test to limit scaling in the cooling system. Pressurize the system at the expansion tank to 103 kPa.

6.2.2.2 Use a closed-loop, pressurized external engine cooling system composed of a nonferrous core heat exchanger, reservoir, and water-out temperature control valve. The system should prevent air entrainment and control jacket temperatures within the specified limit. Install a sight glass between the engine and the cooling tower to check for air entrainment and uniform flow in an effort to prevent localized boiling. Block the thermostat wide open.

6.2.3 *Engine Oil System*—A schematic of the engine oil system is shown in [Fig. A2.9](#).

6.2.4 *Auxiliary Oil System*—To maintain a constant oil level in the pan, a separate closed tank is connected to the sump that provides an additional 9.5 L sump. Circulate oil through the tank with an auxiliary pump at a rate of 5.7 L/min \pm 1.9 L/min. A typical auxiliary oil system is shown in [Fig. A2.9](#). The No. 6 and No. 8 Aeroquip⁶ lines should have inside diameters of 10 mm and 13 mm, respectively. The vent line size is specified as a minimum No. 8 line size. Equivalent lines may be substituted for Aeroquip lines provided they have the proper inside diameters.

6.2.5 *Crankcase Aspiration*—A simple squirrel cage blower will suffice to control crankcase pressure within the test limits.

6.2.6 *Blowby Meter*—Use a displacement type gas meter, or equivalent, to measure blowby.

6.2.7 *Air Supply and Filtration*—Use an intake air filter with an initial efficiency of 99.2 %. Replace filter cartridge when 2.5 kPa ΔP is reached. Install an adjustable valve (flapper) in the inlet air system at least two pipe diameters before any temperature, pressure, and humidity measurement devices. Use the valve to maintain inlet air restriction within required specifications.

6.2.8 *Fuel Supply*—Heating or cooling, or both, of the fuel supply may be required and a recommended system is shown in [Fig. A2.11](#).

6.2.9 *Intake Manifold Temperature Control*—Control intake manifold temperature with the use of a slave intercooler.

7. Engine Fluids

7.1 *Test Oil*—Approximately 151 L of test oil are required for the test.

7.2 *Test Fuel*—Use PC-9-HS test fuel: from Chevron-Phillips, an approved supplier. The fuel shall have the properties and tolerances shown in the “PC-9-HS Fuel Specification” section of the “TMC-Monitored Test Fuel Specifications” document maintained by the TMC.⁷ See [Annex A10](#) for more information.

7.3 *Engine Coolant*—Use demineralized water with less than 0.03 g/L of salts or distilled water (do not use antifreeze solutions or other coolant additives).

⁶ Aeroquip lines are available at local industrial hose suppliers.

⁷ Available at <https://www.astmtmc.org/ftp/docs/fuel/tmc-monitored%20test%20fuel%20specifications.pdf>.

7.4 *Solvent*—Use only mineral spirits meeting the requirements of Specification **D235**, Type II, Class C for Aromatic Content 0 % vol to 2 % vol, Flash Point (61 °C, min), and Color (not darker than +25 on Saybolt Scale or 25 on Pt-Co Scale). (**Warning**—Combustible. Health hazard.) Obtain a Certificate of Analysis for each batch of solvent from the supplier.

8. Preparation of Apparatus at Rebuild

8.1 *Cleaning of Parts:*

8.1.1 *Engine Block*—Thoroughly spray the engine with solvent (see 7.4) to remove any oil remaining from the previous test, and air dry.

8.1.2 *Rocker Covers and Oil Pan*—Remove all sludge, varnish, and oil deposits. Rinse with solvent, and air dry.

8.1.3 *Auxiliary Oil System*—Flush all oil lines, galleries, and external oil reservoirs with solvent to remove any previous test oil, and air dry.

8.1.4 *Oil Cooler and Oil Filter*—If heavy deposits are present or suspected, flush the oil cooler and filter lines with solvent to remove any previous test oil, and air dry.

8.1.5 *Cylinder Head*—Clean the cylinder heads using a wire brush to remove deposits and rinse with solvent to remove any sludge and oil, and air dry.

8.2 *Valves, Seats, Guides, and Springs*—Visually inspect valves, seats, and springs for defects and replace, if defective.

8.2.1 Replace and ream guides to $0.9525 \text{ cm} \pm 0.0013 \text{ cm}$.

8.3 *Cylinder Liner, Piston, and Piston Ring Assembly:*

8.3.1 *Cylinder Liner Fitting*—To ensure proper heat transfer, fit cylinder liners to the block in accordance with the procedure outlined in the Mack Service Manual (see **Annex A5**).

8.3.2 *Piston and Rings*—Cylinder liners, pistons, and rings are provided as a set and should be used as a set. Examine piston rings for any handling damage. Measure piston ring end gaps for conformance with Mack specifications and record.

8.4 *Injectors and Injection Pump:*

8.4.1 *Injectors*—Servicing of injectors is recommended every 1000 h. Resetting of injector opening pressure is allowed if pressure is below specification.

8.4.2 *Injection Pump*—The removal of the injection pump is not recommended unless a problem is noted during a test. Removing the injection pump invalidates the test stand calibration. Replacing injection pumps at each calibration is recommended. New or rebuilt injection pumps may be used and should be obtained from the supplier shown in **A5.3**. High pressure flow calibration equipment, such as a Bacharach No. 72-7010 standard injector tester, is available from Mack approved dealers. Kent-Moore^{8,9} tool numbers J29539 top dead center indicator and J37077 position sensor are recommended for setting the injection timing.

8.5 *Assembly Instructions:*

8.5.1 *General*—The test parts specified for this test method are intended to be used without material or dimensional modification. Exceptions, for example, is approval of a temporary parts supply problem by the Test Monitoring Center (TMC), and noting of this approval in the test report. All replacement test engine parts shall be genuine Mack Trucks, Inc. parts. Assemble all parts as

⁸ The sole source of supply for test fuel of the tools known to the committee at this time is PC-9 HS Reference Diesel Fuel from Chevron-Phillips Chemical Company LP, 10001 Six Pines Drive, The Woodlands, TX 77380; Kent-Moore Corp., 29784 Little Mack, Roseville, MI 48066.

⁹ If you are aware of alternative suppliers, please provide this information to ASTM Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee,¹ which you may attend.

illustrated in the Mack Service Manual (see [A5.2](#)), except where otherwise noted. Target all dimensions for the means of the specifications. Use the buildup oil (see [Annex A5](#)) for lubricating parts during assembly.

8.5.1.1 *Thermostat*—Block the thermostat wide open using an all thread rod.

8.5.1.2 *Rod Bearings*—Check the condition of the connecting rod bearings. Replacement of the connecting rod bearings is at the laboratory’s discretion.

8.5.1.3 *Main Bearings*—Check the condition of the main bearings. Replacement of the main bearings is at the laboratory’s discretion.

8.5.1.4 *Piston Undercrown Cooling Nozzles*—Take particular care in assembling the piston undercrown cooling nozzles to ensure proper piston cooling (as outlined in the Mack Service Manual).

NOTE 1—Proper oil pressure is also important to ensure sufficient oil volume for proper cooling.

8.5.2 *New Parts*—Install the following new parts for each rebuild (see [Table A5.1](#), [Annex A5](#), for part numbers):

8.5.2.1 Cylinder liners,

8.5.2.2 Pistons,

8.5.2.3 Piston rings,

8.5.2.4 Overhaul gasket set,

8.5.2.5 Oil filters (also after each test),

8.5.2.6 Engine coolant conditioner (also every test),

8.5.2.7 Primary fuel filter (also every test),

8.5.2.8 Secondary fuel filter (also every test),

8.5.2.9 Valve guides, and

8.5.2.10 Valve stem seals.

8.6 *Measurements:*

8.6.1 *Calibrations*—Calibrate thermocouples, pressure gages, speed, and fuel flow measuring equipment prior to each reference test or at any time readout data indicates a need. Conduct calibrations with at least two points that bracket the normal operating range. Make these calibrations part of the laboratory record. During calibration, connect leads, hoses, and read-out systems in the normally used manner and calibrate with necessary standards. Immerse thermocouples in calibration baths. Calibrate standards with instruments traceable to the National Institute of Standards and Technology on a yearly basis.

8.6.2 *Temperatures:*

8.6.2.1 *General*—Measure temperatures with thermocouples and conventional readout equipment or equivalent. For 0 °C to 150 °C range, calibrate temperature measuring systems to ± 0.5 °C at 100 °C ± 1 °C and to ± 0.5 °C at 0 °C ± 1 °C. Insert all thermocouples so that the tips are located midstream of the flow unless otherwise indicated.

8.6.2.2 *Ambient Air*—Locate thermocouple in a convenient, well-ventilated position between 2 m and 3 m from the engine and hot accessories.

8.6.2.3 *Coolant*—Locate thermocouple in water manifold prior to thermostat housing. Locate in center of water stream (refer to [Fig. A2.5](#)).

- 8.6.2.4 *Oil*—Locate thermocouple on the right side of the engine on the top of the accessory drive, as shown in Fig. A2.5.
- 8.6.2.5 *Intake Air*—Locate sensors for dry bulb temperature measurement and humidity in center of air stream at the turbocharger inlet as shown in Fig. A2.3. It is not necessary to control intake air humidity, but measurements are recommended.
- 8.6.2.6 *Fuel In*—Locate thermocouple in center of fuel line between secondary filter and injection pump, as shown in Fig. A2.4.
- 8.6.2.7 *Pre-Turbine Temperatures*—Locate one thermocouple in each side of exhaust manifold tee section (see Fig. A2.3). The exhaust manifold (pre-turbine) thermocouples and pressure taps are located on the same tee.
- 8.6.2.8 *Exhaust (Tailpipe) Temperature*—Locate thermocouple in exhaust pipe downstream of turbine in accordance with Fig. A2.7.
- 8.6.2.9 *Intake Manifold*—Locate thermocouple at tapped fitting on intake air manifold, as shown in Fig. A2.6.
- 8.6.2.10 *Additional*—Monitor any additional temperatures the test lab regards as helpful in providing a consistent test procedure.
- 8.6.3 *Pressures:*
- 8.6.3.1 *Before Filter Oil Pressure*—Locate pickup at tapped hole on oil cooler fitting (see Fig. A2.2).
- 8.6.3.2 *After Filter/Main Gallery Oil Pressure*—Locate pickup at tapped hole on top of oil filter pad above centrifugal oil filter (see Fig. A2.2).
- NOTE 2—The E7 engine has only one oil gallery, which serves as both a main gallery and a piston cooling gallery.
- 8.6.3.3 *Pre-Turbine Exhaust Pressure*—Locate pickup in each side of exhaust manifold tee section (same tap as pre-turbine pressure), Fig. A2.3.
- 8.6.3.4 *Intake Air Boost*—Take measurement at tapped fitting provided on intake manifold, as illustrated in Fig. A2.6.
- 8.6.3.5 *Intake Air Total Pressure*—Measure with a Keil Probe^{9,10} (p/n No. KDF-8-W recommended) located at the turbo inlet (see Fig. A2.3).
<https://standards.iteh.ai/catalog/standards/sist/331e21ee-df00-4ed3-9c29-6e7597ad16d7/astm-d5967-21>
- 8.6.3.6 *Exhaust Back Pressure*—Locate pickup in exhaust pipe after turbocharger in center of exhaust stream. Measure exhaust back pressure in a straight section of pipe, 30.5 cm to 40.6 cm downstream of the turbo with a 1/16 NPT tread pressure tap hole, as shown in Fig. A2.3.
- 8.6.3.7 *Crankcase Pressure*—Locate pickup at dipstick tube fitting or other suitable opening direct to the crankcase.
- 8.6.3.8 *Barometric Pressure*—Locate barometer approximately 1.2 m above ground level in convenient location in the lab.
- 8.6.4 *Engine Blowby*—Connect the metering instrument to the blowby line coming from the valve cover crossover tube (P/N 191GC418A).
- 8.6.5 *Fuel Consumption Measurements*—Place the measuring equipment in the fuel line before the primary fuel filter. Install the primary fuel filter before the fuel transfer pump and install the secondary filter before the injection pump. Accurate fuel consumption measurements require proper accounting of return fuel. (**Warning**—Fuel return lines should never be plugged.)
- 8.6.6 *Humidity*—Place the measurement equipment between the inlet air filter and compressor in such a manner so as not to affect temperature and pressure measurements. Measure humidity at 8 h intervals and report (see Annex A1).

9. Laboratory and Engine Test Stand Calibration/Non-Reference Requirements

9.1 Calibration Frequency:

¹⁰ The sole source of supply of Keil Probes known to the committee at this time is United Sensor Corp., 3 Northern Blvd., Amherst, NH 03031.

9.1.1 To maintain test consistency and severity levels, engine test stand calibration is required at regular intervals. The frequency of calibration is dependent on the laboratories' previous calibration experience or at the discretion of the TMC.

9.1.2 Engine test stand calibration is required when the injection pump is removed from the engine, when the front or rear gear train timing is changed, or when cylinder heads are replaced. Cylinder heads and power cylinder components (pistons, rings, and liners) can be rebuilt without re-calibrating. Any rebuild requires a new break-in sequence to be run on the engine prior to testing. Rear gear train timing changes to meet soot targets are only allowed for reference oil tests. Timing changes are limited to a maximum of two changes in the first 100 h of the test. No single timing change can be greater than 1° and the cumulative change shall be $\pm 1^\circ$ from the initial timing.

9.2 Calibration Reference Oils:

9.2.1 The reference oils used to calibrate test stands have been formulated or selected to represent specific chemical types or performance levels, or both. They can be obtained from the TMC. The TMC assigns reference oils for calibration tests. These oils are supplied under code numbers (blind reference oils).

9.2.2 *Reference Oils Analysis*—Reference oils are not to be submitted to either physical or chemical analysis, for identification purposes. Identifying the oils by analysis could undermine the confidentiality required to operate an effective blind reference oil system. Therefore, reference oils are supplied with the explicit understanding that they will not be subjected to analysis other than those specified within this procedure unless specifically authorized by the TMC. In such cases in which analysis is authorized, written confirmation of the circumstances involved, the data obtained, and the name of the person authorizing the analysis shall be supplied to the TMC.

9.3 *Test Numbering*—Number each test to identify the test stand number, the test stand run number, engine serial number, and engine block hours at the start of the test. The sequential stand run number remains unchanged for reruns of aborted, invalid, or unacceptable calibration tests. However, the sequential stand run number shall be followed by the letter A for the first rerun, B for the second, and so forth. For calibration tests, engine block hours are the test hours since last engine rebuild. For non-reference tests, engine block hours are the test hours accumulated since last reference. For example, 58-12A-2H0380-500 defines a test on stand 58 and stand run 12 as a calibration test that was run twice on engine 2H0380 (serial number), which has run 500 h since the last engine rebuild.

[ASTM D5967-21](https://standards.iteh.ai/catalog/standards/sist/331e21ee-df00-4ed3-9c29-6e7597ad16d7/astm-d5967-21)

9.4 New Laboratories and New Test Stands:

9.4.1 A new stand is defined as an engine, dynamometer/cell and support hardware that has never been previously calibrated under this test procedure. On both new and existing stands the test engine is part of the stand calibration. A new engine in a existing test stand only requires one successful calibration test.

9.4.2 Calibrate a new test stand in accordance with the Lubricant Test Monitoring System (LTMS). Generally, new test stands require two successful calibration tests. However, provisions do exist within the LTMS to allow new stands to calibrate with one test, based upon previous test experience within the laboratory.

9.4.3 A laboratory not running a test for 12 months from the start of the last test is considered a new laboratory. Under special circumstances (that is, extended downtime due to industry-wide parts shortage or fuel outages) the TMC may extend the lapsed time requirement. Non-reference tests conducted during an extended time allowance shall be annotated (see [Annex A1](#)), Downtime and Comments Summary.

9.5 Calibrated Laboratories and Test Stands:

9.5.1 A calibration test on a reference oil assigned by the TMC is required after 3000 h of non-reference test time, ten operationally valid non-reference oil tests, or nine months, whichever comes first, have elapsed since the starting date of the last calibration test. A non-reference test may be started in a test stand provided at least 1 h remains in its calibration period.

9.6 Calibration Test Acceptance:

9.6.1 Use the TMC's Lubricant Test Monitoring System (LTMS)¹¹ for calibration test targets and acceptance criteria.

9.6.2 The specified test parameter for determination of test acceptance is Viscosity Increase in mm²/s, at 100 °C and 3.8 % Thermal Gravimetric Analysis (TGA) soot, as shown in [Annex A3](#) and [Annex A4](#).

9.6.2.1 Calculate Viscosity Increase at 3.8 % TGA, using linear interpolation from the minimum viscosity that occurs during the test. Do not use the 25 h, 75 h, and 125 h oil sample results to calculate Viscosity Increase at 3.8 % TGA soot.

9.6.2.2 *Correction Factor for Viscosity Increase at 3.8% TGA Soot*—For all tests completing on or after September 17, 2011, add +0.40 to the value calculated in [9.6.2.1](#).

9.6.3 *Soot Requirements:*

9.6.3.1 All operationally valid calibration tests on TMC oil 1004-1 shall produce a TGA soot level between 4.0 % to 4.6 % at 250 h.

9.6.3.2 All operationally valid calibration tests on TMC oil 1004-2 shall produce a TGA soot level between 4.0 % to 4.8 % at 250 h.

9.6.3.3 All operationally valid calibration tests on TMC oil 1004-3 completed on or before Dec. 31, 2006 shall produce a TGA soot level between 4.0 % to 4.8 % at 250 h.

9.6.3.4 All operationally valid calibration tests on TMC oil 1004-3 completed on or after Jan. 1, 2007 and all operationally valid calibration tests on TMC oil 1005-2 shall produce a TGA soot level between 4.0 % to 5.0 % at 250 h.

9.6.3.5 A laboratory may terminate a calibration test that is projected to miss the 250 h test soot window. Calibration tests with soot levels outside the 250 h soot window are considered operationally invalid.

9.7 *Failing Calibration Tests:*

9.7.1 Failure of a reference oil test to meet test acceptance bands can be indicative of a false alarm, testing stand, testing laboratory, or industry-related problem. When this occurs, the laboratory, in conjunction with the TMC, shall attempt to determine the problem source.

<https://standards.iteh.ai/catalog/standards/sist/331e21ee-df00-4ed3-9c29-6e7597ad16d7/astm-d5967-21>

9.7.2 The TMC decides, with input as needed from industry expertise (testing laboratories, test developer, ASTM Technical Guidance Committee, Surveillance Panel, and so forth), if the reason for any unacceptable blind reference oil test is isolated to one particular stand or related to other stands. If it is decided that the problem is isolated to an individual stand, calibrated testing on other stands can continue throughout the laboratory. Alternatively, if it is decided that more than one stand may be involved, the involved stands will not be considered calibrated until the problem is identified, corrected, and an acceptable reference oil test completed in one of the involved stands.

9.7.3 If nonstandard tests are conducted on the referenced test stand, the stand may be required to be recalibrated prior to running standard tests at the discretion of the TMC.

9.8 *Non-Reference Oil Test Requirements*—Non-reference oil tests shall produce a minimum 3.8 % TGA soot level at 250 h. Tests shall run to 250 h regardless of meeting the 3.8 % soot level prior to 250 h. Tests that do not reach 3.8 % soot at 250 h are deemed not interpretable.

NOTE 3—Fixed non-reference oil pass criteria are published in Specification [D4485](#).

9.8.1 *Non-Reference Oil Test Result Severity Adjustments*—This test method incorporates the use of a severity adjustment (SA) for non-reference oil test results. A control chart technique, described in the LTMS, has been selected for the purpose of identifying when a bias becomes significant for viscosity increase at 3.8 % TGA soot. When calibration test results identify a significant bias,

¹¹ The lubricant test monitoring system may be obtained from the ASTM Test Monitoring Center, 6555 Penn Ave., Pittsburgh, PA 15206-4489. Attention: Administrator.

a SA value is determined in accordance with the LTMS. Report the SA value (see [Annex A1](#)), Test Result Summary, under the non-reference oil test block in the space for SA. Add this SA value to non-reference oil test results, and enter the adjusted viscosity increase at 3.8 % TGA soot value in the appropriate space. The SA remains in effect until a new SA is determined from subsequent calibration tests, or the test results indicate the bias is no longer significant.

9.9 Donated Reference Oil Test Programs—The surveillance panel is charged with maintaining effective reference oil test severity and precision monitoring. During times of new parts introductions, new or re-blended reference oil additions, and procedural revisions, it may be necessary to evaluate the possible effects on severity and precision levels. The surveillance panel may choose to conduct a program of donated reference oil tests in those laboratories participating in the monitoring system, in order to quantify the effect of a particular change on severity and precision. Typically, the surveillance panel requests its panel members to volunteer enough reference oil test results to create a robust data set. Broad laboratory participation is needed to provide a representative sampling of the industry. To ensure the quality of the data obtained, donated tests are conducted on calibrated test stands. The surveillance panel shall arrange an appropriate number of donated tests and ensure completion of the test program in a timely manner.

9.10 *Adjustments to Reference Oil Calibration Periods:*

9.10.1 Procedural Deviations—On occasions when a laboratory becomes aware of a significant deviation from the test method, such as might arise during an in-house review or a TMC inspection, the laboratory and the TMC shall agree on an appropriate course of action to remedy the deviation. This action may include the shortening of existing reference oil calibration periods.

9.10.2 Parts and Fuel Shortages—Under special circumstances, such as industry-wide parts or fuel shortages, the surveillance panel may direct the TMC to extend the time intervals between reference oil tests. These extensions shall not exceed one regular calibration period.

9.10.3 Reference Oil Test Data Flow—To ensure continuous severity and precision monitoring, calibration tests are conducted periodically throughout the year. There may be occasions when laboratories conduct a large portion of calibration tests in a short period of time. This could result in an unacceptably large time frame when very few calibration tests are conducted. The TMC can shorten or extend calibration periods as needed to provide a consistent flow of reference oil test data. Adjustments to calibration periods are made such that laboratories incur no net loss (or gain) in calibration status.

9.10.4 Special Use of the Reference Oil Calibration System—The surveillance panel has the option to use the reference oil system to evaluate changes that have potential impact on test severity and precision. This option is only taken when a program of donated tests is not feasible. The surveillance panel and the TMC shall develop a detailed plan for the test program. This plan requires all reference oil tests in the program to be completed as close to the same time as possible, so that no laboratory/stand calibration is left in an excessively long pending status. In order to maintain the integrity of the reference oil monitoring system, each reference oil test is conducted so as to be interpretable for stand calibration. To facilitate the required test scheduling, the surveillance panel may direct the TMC to lengthen and shorten reference oil calibration periods within laboratories such that the laboratories incur no net loss (or gain) in calibration status.

10. Procedure

10.1 *Pretest Procedure:*

10.1.1 Initial Oil Fill for Flush—The initial oil fill is 45.4 L of test oil: 26.5 L for the pan, 3.8 L for the filters, 1.9 L for the engine oil cooler, and 13.2 L for the auxiliary oil reservoir and lines. Add the first 3.8 L of fresh test oil to the oil filters (1.9 L per filter), then turn on the auxiliary oil pumps and add an additional 41.6 L of test oil to the engine. This oil can be added directly through the engine oil fill tube.

10.1.2 *Pretest Oil Flush and Break-In:*

10.1.2.1 Start the engine, as described in [11.2](#). For a new or rebuilt engine, run the break-in sequence described in [Table 1](#). For non-reference oil tests only a pretest oil flush procedure is required. A post test flush should be done prior to a pretest, as described in [10.13.1](#) and [10.13.2](#).

10.1.2.2 Shutdown the engine (as shown in [11.3](#)) and drain the test oil from the oil pan, external oil reservoir, and change the oil filters.

TABLE 1 Break-in and Flush Operating Conditions

Conditions	New or Rebuild Break-in		Pretest Flush
Time, min	30	30	120
Speed, r/min	1250	1800	1800
Torque, N·m ^A ± 1 % ^B	1731 (1277)	1384 (1021)	1384 (1021)

^A At 98.2 kPa and 29.5 °C dry air.

^B When engine performance falls outside these limits, corrective action should be taken.

10.1.2.3 Install new oil filters and add 3.8 L of fresh test oil to the filters (1.9 L per filter). Start the auxiliary oil pumps and add an additional 41.6 L of new oil to the engine. This oil can be added directly through the engine oil fill tube.

10.2 *Engine Start-Up*—Each time the engine is started, work up to 20 % to 30 % of full load at 1000 r/min to 1400 r/min and hold until the oil sump temperature reaches approximately 66 °C to 77 °C. This takes about 10 min for a cold engine; then go to test conditions. Start-ups are not included as test time. Test time starts as soon as the engine returns to the test cycle. The start date and time of a test, is defined as when the test reaches test conditions (after a flush). (**Warning**—The engine should be cranked prior to start-up to fill the engine oil passages. This practice will enhance engine durability significantly.)

10.3 *Engine Shutdown*—The engine may be shut down for periods of time. Before each shutdown, operate the engine at 1000 r/min to 1400 r/min no-torque for 10 min, then close the fuel rack. The shutdown operation does not count as test time. Record the length and reason of each shutdown (see **Annex A1**).

10.4 *Test Cycle*—The test cycle includes a pretest oil flush at the conditions shown in **Table 1**. For new and rebuilt engines, a break-in procedure is also required. Conduct the test at 1800 r/min full-torque conditions as described in **Table 2**. Reference oil test length is 300 h. Non-reference oil test length is 250 h.

10.4.1 At EOT (end of test), the average results for all controlled operational parameters shall be within the stated specifications for the test to be declared operationally valid. For calibration tests, investigate any uncontrolled operational parameters outside the stated specifications jointly by the laboratory and the TMC. Base a validity judgment on the joint agreement between the laboratory and the TMC.

TABLE 2 Test Conditions

Parameter	Limits
Time, h	250 (300 for reference oils)
Controlled Parameters ^A	
Speed, r/min	1800 ± 5
Fuel flow, kg/h	63.3 ± 1 %
Inlet manifold temperature, °C	43 ± 3
Coolant out, °C	85 ± 3
Fuel in, °C	40 ± 1
Intake air, °C	25 ± 3
Crankcase pressure, kPa	0.50 ± 0.25
Inlet air restriction, kPa	2.50 ± 0.25
Exhaust back pressure, kPa	3.1 ± 0.4
Uncontrolled Parameters	
Torque, N·m ^B	1369/1398 ^C
Exhaust temperature, °C	
Pre-turbine	602/632
Tailpipe	455/474
Inlet manifold pressure, kPa	186/199 ^C
Oil, °C	100/107
Main gallery oil pressure, kPa	372/441 ^D
Intercooler Δ <i>P</i> , kPa	Not to exceed 13.6
Oil filter Δ <i>P</i> , kPa	Not to exceed 138 ^E

^A All control parameters are to be held at the mean indicated.

^B At 98.2 kPa and 29.5 °C dry air.

^C When engine performance falls outside these limits, corrective action should be taken. Fuel flow is the primary control parameter.

^D Note pressures are typical of SAE 15W40 oils; other oil grades may show different results.

^E If oil filter Δ*P* exceeds 138 kPa, change the two full flow filters.