



# SLOVENSKI STANDARD SIST EN 301 486-6 V1.1.1:2005

01-januar-2005

ü]fc\_cdUgcj bc`X][ ]HJbc`ca fYÿ`Y`n`]bhY[ f]fUb]a ]`gfcf]hj Ua ]`f6 !-G8 BŁĚ`Dfcfc\_c`  
X][ ]HJbY`bUfc b]ý\_Y`g][ bU]nUWY`Y`ýH`&fB GG&ŁĚ`? UfU\_hYf]gh\_Y`nj YnY`Ě`GdfYa Ya VU  
dfca YfbY[ UXyg\_f]dHcf`U5 HA `g`dc[ U`Ub`Ya `n`Ugfb]\_ca `nj YnY`Ě`\* "XY.`5 VgHfU`fb]  
dfYg\_i ýUb]`b]n`f5 HGL`b`XY`bUXcXUfbU]bZ`fa UWY`UnUdfYg\_i ýUb`Y`nj YXVY  
dfcfc\_c`UfD`L`+ŁĚ`DfcZ`fa UgdYWZ]\_UWY`UnUca fYÿ`Y`

Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Connection characteristics; ATM traffic descriptor modification with negotiation by the connection owner; Part 6: Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the network

<https://standards.iteh.ai/catalog/standards/sist/15d87720-6ab0-4d19-9aba-30ff9704f0d0/sist-en-301-486-6-v1-1-1-2005>

**Ta slovenski standard je istoveten z: EN 301 486-6 Version 1.1.1**

**ICS:**

33.080	Digitalno omrežje z integriranimi storitvami (ISDN)	Integrated Services Digital Network (ISDN)
--------	---	--

**SIST EN 301 486-6 V1.1.1:2005 en**

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 301 486-6 V1.1.1:2005

<https://standards.iteh.ai/catalog/standards/sist/15d87720-6ab0-4d19-9aba-30ff9704f0d0/sist-en-301-486-6-v1-1-1-2005>

# ETSI EN 301 486-6 V1.1.1 (2002-02)

*European Standard (Telecommunications series)*

**Broadband Integrated Services Digital Network (B-ISDN);  
Digital Subscriber Signalling System No. two (DSS2) protocol;  
Connection characteristics;  
ATM traffic descriptor modification with negotiation  
by the connection owner;  
Part 6: Abstract Test Suite (ATS) and partial Protocol  
Implementation eXtra Information for Testing (PIXIT)  
proforma specification for the network**

**iTeh STANDARD PREVIEW  
(standards.iteh.ai)**

[SIST EN 301 486-6 V1.1.1:2005](https://standards.iteh.ai/catalog/standards/sist/15d87720-6ab0-4d19-9aba-30ff9704f0d0/sist-en-301-486-6-v1-1-1-2005)

<https://standards.iteh.ai/catalog/standards/sist/15d87720-6ab0-4d19-9aba-30ff9704f0d0/sist-en-301-486-6-v1-1-1-2005>



---

**Reference**

DEN/SPAN-130202-6

---

**Keywords**ATM, ATS, B-ISDN, broadband, DSS2, layer 3,  
network, PIXIT**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

SIST EN 301 486-6 V1.1.1:2005<https://standards.iteh.ai/catalog/standards/sist/15d87720-6ab0-4d19-9aba-30ff9704f0d0/sist-en-301-486-6-v1-1-1-2005>

---

**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

[editor@etsi.fr](mailto:editor@etsi.fr)

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2002.  
All rights reserved.

# Contents

Intellectual Property Rights .....	5
Foreword.....	5
1 Scope .....	6
2 References .....	6
3 Definitions and abbreviations.....	7
3.1 Definitions .....	7
3.2 Abbreviations .....	7
4 Abstract Test Method .....	8
4.1 Description of ATM used.....	8
4.2 Conventions for test components and PCOs .....	8
5 Untestable test purposes .....	9
6 ATS to TP map.....	9
7 PCTR conformance .....	10
8 PIXIT conformance.....	10
9 ATS conformance .....	10
<b>Annex A (normative): Protocol Conformance Test Report (PCTR) proforma.....</b>	<b>11</b>
A.1 Identification summary.....	11
A.1.1 Protocol conformance test report.....	11
A.1.2 IUT identification.....	11
A.1.3 Testing environment.....	11
A.1.4 Limits and reservations .....	12
A.1.5 Comments.....	12
A.2 IUT conformance status .....	12
A.3 Static conformance summary .....	12
A.4 Dynamic conformance summary.....	13
A.5 Static conformance review report.....	13
A.6 Test campaign report.....	13
A.7 Observations.....	14
<b>Annex B (normative): Partial PIXIT proforma .....</b>	<b>15</b>
B.1 Identification summary.....	15
B.2 Abstract test suite summary .....	15
B.3 Test laboratory.....	15
B.4 Client (of the Test Laboratory).....	16
B.5 SUT .....	16
B.6 Protocol information.....	17
B.6.1 Protocol identification .....	17
B.6.2 Configuration to be tested .....	17
B.6.3 Test management timers.....	17
B.6.4 Parameter values .....	18
<b>Annex C (normative): Abstract Test Suite (ATS) .....</b>	<b>19</b>

C.1	The TTCN Graphical form (TTCN.GR) .....	19
C.2	The TTCN Machine Processable form (TTCN.MP) .....	19
History	.....	20

## **iTeh STANDARD PREVIEW** **(standards.iteh.ai)**

[SIST EN 301 486-6 V1.1.1:2005](https://standards.iteh.ai/catalog/standards/sist/15d87720-6ab0-4d19-9aba-30ff9704f0d0/sist-en-301-486-6-v1-1-1-2005)

<https://standards.iteh.ai/catalog/standards/sist/15d87720-6ab0-4d19-9aba-30ff9704f0d0/sist-en-301-486-6-v1-1-1-2005>

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Services and Protocols for Advanced Networks (SPAN).

The present document is part 6 of a multi-part deliverable covering the Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Connection characteristics; ATM traffic descriptor modification with negotiation by the connection owner, as identified below:

- Part 1: "Protocol specification [ITU-T Recommendation Q.2963.3, modified]";
- Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";
- Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification for the user";
- Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user";
- Part 5: "Test Suite Structure and Test Purposes (TSS&TP) specification for the network";
- Part 6: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the network".**

National transposition dates	
Date of adoption of this EN:	1 February 2002
Date of latest announcement of this EN (doa):	31 May 2002
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	30 November 2002
Date of withdrawal of any conflicting National Standard (dow):	30 November 2002

## 1 Scope

The present document specifies the network Abstract Test Suite (ATS) for the  $T_B$  reference point or coincident  $S_B$  and  $T_B$  reference point (as defined in ITU-T Recommendation I.413 [9]) of implementations conforming to the standards for the signalling user-network layer 3 specification for ATM traffic descriptor modification with negotiation by the connection owner of the Digital Subscriber Signalling System No. two (DSS2) protocol for the pan-European Broadband Integrated Services Digital Network (B-ISDN), EN 301 486-1 [1].

A further part of the present document specifies the Test Suite Structure and Test Purposes (TSS&TP) related to this ATS and partial PIXIT proforma. Other parts specify the TSS&TP and the ATS and partial PIXIT proforma for the User side of the  $T_B$  reference point or coincident  $S_B$  and  $T_B$  reference point of implementations conforming to EN 301 486-1 [1].

## 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

- STANDARD PREVIEW**  
(standards.iteh.ai)
- [1] ETSI EN 301 486-1: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Connection characteristics; ATM traffic descriptor modification with negotiation by the connection owner; Part 1: Protocol specification [ITU-T Recommendation Q.2963.3, modified]"  
<https://standards.iteh.ai/catalog/standards/sist/15d87720-6ab0-4d19-9aba-3089704f0d0/sist-en-301-486-6-v1-1-1-2005>
- [2] ETSI EN 301 486-2: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Connection characteristics; ATM traffic descriptor modification with negotiation by the connection owner; Part 2: Protocol Implementation Conformance Statement (PICS) proforma specification".
- [3] ETSI EN 301 486-5: "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; Connection characteristics; ATM traffic descriptor modification with negotiation by the connection owner; Part 5: Test Suite Structure and Test Purposes (TSS&TP) specification for the network".
- [4] ISO/IEC 9646-1 (1994): "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts".
- [5] ISO/IEC 9646-2 (1994): "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 2: Abstract Test Suite specification".
- [6] ISO/IEC 9646-3 (1998): "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 3: The Tree and Tabular Combined Notation (TTCN)".
- [7] ISO/IEC 9646-4 (1994): "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 4: Test realization".
- [8] ISO/IEC 9646-5 (1994): "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 5: Requirements on test laboratories and clients for the conformance assessment process".
- [9] ITU-T Recommendation I.413 (1993): "B-ISDN user-network interface".



## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

**Abstract Test Suite (ATS):** See ISO/IEC 9646-1 [4].

**Implementation Under Test (IUT):** See ISO/IEC 9646-1 [4].

**Lower Tester (LT):** See ISO/IEC 9646-1 [4].

**Point of Control and Observation (PCO):** See ISO/IEC 9646-1 [4].

**Protocol Implementation Conformance Statement (PICS):** See ISO/IEC 9646-1 [4].

**PICS proforma:** See ISO/IEC 9646-1 [4].

**Protocol Implementation eXtra Information for Testing (PIXIT):** See ISO/IEC 9646-1 [4].

**PIXIT proforma:** See ISO/IEC 9646-1 [4].

**System Under Test (SUT):** See ISO/IEC 9646-1 [4].

**Upper Tester (UT):** See ISO/IEC 9646-1 [4].

### 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

ATM	Abstract Test Method
ATS	Abstract Test Suite
B-ISDN	Broadband Integrated Services Digital Network
CM	Co-ordination Message
CP	Co-ordination Point
DSS2	Digital Subscriber Signalling System No. two
ExTS	Executable Test Suite
ISDN	Integrated Services Digital Network
IUT	Implementation Under Test
LT	Lower Tester
MOT	Means Of Testing
MTC	Main Test Component
PCO	Point of Control and Observation
PCTR	Protocol Conformance Test Report
PDU	Protocol Data Unit
PICS	Protocol Implementation Conformance Statement
PIXIT	Protocol Implementation eXtra Information for Testing
PTC	Parallel Test Component
SUT	System Under Test
TP	Test Purpose
TTCN	Tree and Tabular Combined Notation
UT	Upper Tester

## 4 Abstract Test Method

### 4.1 Description of ATM used

The requirement for testing the network IUT is to focus on the behaviour of the network IUT at the user-network interface where a  $T_B$  reference point or coincident  $S_B$  and  $T_B$  reference point applies. Thus the IUT is the network DSS2 protocol entity at a particular user-network interface and is not the whole network.

It is possible to specify an ATS based on a single party (remote) test method for such an IUT. However, it is considered that an ATS based on such an approach is of limited use as the only way to specify IUT generated PDUs is to use the "implicit send" statement. Many users of such an ATS would replace the "implicit send" statements with descriptions of the behaviour at other interfaces.

An ATS based on a multi-party test method is considered to be more useful in that it is closer to how a real test suite would be constructed. Such a test method specifies behaviour at multiple network interfaces. One very important limitation here is that tests are focussed on one particular interface. Thus the test system is made up one Main Test Component (MTC) and one or more Parallel Test Components (PTC), see figure 1.

### 4.2 Conventions for test components and PCOs





Figure 1: Multi-party test method

In a master/slave arrangement, the MTC is considered to be the master while the PTCs are the slaves. The "slave" testers are only an explicit description of how to deal with the remote interfaces during the testing process, i.e. "how to make the IUT send the required message".

This means, in particular, that the verdict will only be assigned from the protocol aspects observed on the interface under test (i.e. by the "master" tester), as it would be observed by a terminal connected to this interface. A failure in the correlation between the protocol at the different interfaces to which the different testers are connected, i.e. in the mechanism of the functional service itself, will not cause a FAIL verdict. For instance, if the IUT fails to send a message on the tested interface after another interface has received the proper stimulus, the verdict will be INCONCLUSIVE.

The MTC MTCAs has two functions in this configuration. Firstly, it has the MTC function of controlling the one or more PTCs. Thus it is responsible for starting the PTCs and afterwards co-ordinates activities by exchanging Co-ordination Messages (CM) with the PTCs. Secondly it is responsible for the behaviour of the Lower Tester (LT) at PCO L0.

A combination of the remote and multi-party test methods is applied. As can be seen from figure 1, several PCOs are used. All PCOs reside at the service access points between layers 2 and 3.



**Figure 2: Combination of the remote and multi-party test methods**

SIST EN 301 486-6 V1.1.1:2005

The MTC PCO is named "L0" ("L" for Lower). The L0 PCO is used to control and observe the behaviour of the IUT and test case verdicts are assigned depending on the behaviour observed at this PCO. The PTC PTC1 uses PCOs L1. These PCO is used to control and, in a limited way, observe the behaviour of the network equipment at interface other than the one under test. No verdicts are assigned at this PCO.

As stated in a previous paragraph, the non-receipt of network generated messages at L0, which are stimulated by events at the L1, will result in INCONCLUSIVE rather than FAIL verdicts being assigned.

In test cases which verify that the IUT rejects invalid or unacceptable SETUP messages and in the majority of the test cases for the restart procedures, no PTC is activated at all, as these procedures are considered local to the access between IUT and MTC.

---

## 5 Untestable test purposes

There are no untestable test purposes associated with this ATS.

---

## 6 ATS to TP map

The identifiers used for the TPs (see EN 301 486-5 [3]) are reused as test case names. Thus there is a straightforward one-to-one mapping.