

INTERNATIONAL STANDARD

IEC
62272-2

First edition
2007-03

Digital radio mondiale (DRM) –

Part 2:

**Digital radio in the bands below 30 MHz –
Methods of measurement for DRM transmitters**

iTeh Standards

(<https://standards.iteh.ai>)

Document Preview

[IEC 62272-2:2007](#)

<https://standards.iteh.ai/catalog/standards/iec/83453a31-2cae-4de6-beff-84eac35c1c59/iec-62272-2-2007>



Reference number
IEC 62272-2:2007(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- **IEC Web Site** (www.iec.ch)
- **Catalogue of IEC publications**
The on-line catalogue on the IEC web site (www.iec.ch/searchpub) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.
- **IEC Just Published**
This summary of recently issued publications (www.iec.ch/online_news/justpub) is also available by email. Please contact the Customer Service Centre (see below) for further information.
- **Customer Service Centre**
If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: custserv@iec.ch
Tel: +41 22 919 02 11
Fax: +41 22 919 03 00

INTERNATIONAL STANDARD

IEC 62272-2

First edition
2007-03

Digital radio mondiale (DRM) –

Part 2:

**Digital radio in the bands below 30 MHz –
Methods of measurement for DRM transmitters**

iTeh Standards

(<https://standards.iteh.ai>)

Document Preview

[IEC 62272-2:2007](#)

<https://standards.iteh.ai/catalog/standards/iec/83453a31-2cae-4de6-beff-84eac35c1c59/iec-62272-2-2007>

© IEC 2007 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE

R

For price, see current catalogue

CONTENTS

FOREWORD.....	3
1 Scope.....	5
2 Normative references.....	5
3 Terms, definitions and abbreviations	6
3.1 Terms and definitions	6
3.2 Abbreviations.....	6
4 General conditions of operation.....	7
5 General conditions of measurement.....	7
5.1 Input and output measurement arrangements	7
5.2 Temperature and humidity	8
5.3 Conditions for primary power supply.....	8
5.4 Output power	8
6 General characteristics	8
6.1 Output power.....	8
6.2 Frequency	9
7 Transmission performance characteristics	11
7.1 Spurious emissions.....	11
7.2 Out-of-band emissions (spectrum mask).....	12
7.3 Modulation error ratio (MER).....	13
7.4 Bit error ratio (BER).....	13
8 Protection against atmospheric discharge	14
9 Acoustic noise	15
10 Safety.....	15
Annex A (informative) Measuring arrangements.....	16
Annex B (informative) Out-of-band emission limits for DRM transmitters.....	18
Annex C (informative) Additional measuring details	20
Figure 1 – Spectrum occupancy for 9 kHz channels.....	10
Figure 2 – Spectrum occupancy for 10 kHz channels.....	10
Figure 3 – PRBS generator	14
Figure A.1 – Arrangement A	16
Figure A.2 – Arrangement B	16
Figure A.3 – Arrangement C.....	17
Figure A.4 – Arrangement D.....	17
Figure B.1 – Out-of-band emission limits (upper half only of a symmetrical spectrum mask shown).....	18
Table B.1 – Out-of-band emission limits	18

INTERNATIONAL ELECTROTECHNICAL COMMISSION

DIGITAL RADIO MONDIALE (DRM) –**Part 2: Digital radio in the bands below 30 MHz –
Methods of measurement for DRM transmitters**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62272-2 has been prepared by IEC technical committee 103: Transmitting equipment for radiocommunication.

The text of this standard is based on the following documents:

FDIS	Report on voting
103/64/FDIS	103/66/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[IEC 62272-2:2007](#)

<https://standards.iteh.ai/catalog/standards/iec/83453a31-2cae-4de6-beff-84eac35c1c59/iec-62272-2-2007>

DIGITAL RADIO MONDIALE (DRM) –

Part 2: Digital radio in the bands below 30 MHz – Methods of measurement for DRM transmitters

1 Scope

This part of IEC 62272 describes the methods of measurement to assess the performance characteristics of digital modulated radio transmitters in the bands below 30 MHz for sound and/or data broadcasting in the LF, MF and HF bands, and to facilitate the comparison of measurements which are carried out by different personnel.

It contains details of specially selected methods for determining the most important performance parameters of digital radio transmitters. The measurement methods described apply to a limited number of performance parameters, i.e. those which can give rise to ambiguous interpretation due to the use of different methods and conditions. They are neither restrictive nor mandatory: measurements can be chosen for each particular case.

The measurement methods described in this standard are intended to be used for type approval tests, quality control tests or acceptance test measurements in factories and on site.

Fewer or additional measurements may be carried out by agreement between customer and supplier. Any additional test should comply with standards which have been established by other study groups, subcommittees of the IEC or other international or suitably accredited organizations.

This standard does not specify limiting values for acceptable performance as these are usually given in the equipment specification or in requirements laid down by the responsible regulation bodies. However, some values are quoted, where appropriate, for guidance in the presentation of the results.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60244-1, *Methods of measurement for radio transmitters – Part 1: General characteristics for broadcast transmitters*

IEC 60244-15, *Methods of measurement for radio transmitters – Part 15: Amplitude-modulated transmitters for sound broadcasting*

IEC 60215, *Safety requirements for radio transmitting equipment*

ITU *Radio Regulations*

ITU-R Recommendation V.663, *Use of certain terms linked with physical quantities*

3 Terms, definitions and abbreviations

3.1 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1.1

DRM standard

digital modulation standard for frequencies in the bands below 30 MHz for the purposes of audio and data broadcasting

3.1.2

DRM transmitters

sound broadcasting transmitters operating in the bands below 30 MHz and incorporating digital modulation in accordance with IEC 62272-1¹

3.1.3

power definitions

nominal output power is the continuous DRM mean power for which the transmitter is designed

maximum output power is the maximum possible continuous DRM mean power which the transmitter can deliver. The maximum output power might be concordant with the nominal output power

minimum output power is the minimum possible continuous DRM mean power for which the transmitter is designed

3.1.4

necessary bandwidth

for a given class of emission, the width of a frequency band which is just sufficient to ensure the transmission of information at the rate and with the quality required under specified conditions (ITU definition)

For the practical purposes of this standard, the necessary bandwidth for a DRM signal can be considered to be the same as the allocated channel bandwidth, for example, 10 kHz for a standard HF channel.

3.2 Abbreviations

BER	Bit Error Ratio
BS	Broadcasting Service
DRM	Digital Radio Mondiale
FAC	Fast Access Channel
HF	High Frequency
IEC	International Electrotechnical Commission
ISO	International Organization for Standardization
ITU	International Telecommunications Union
ITU-R	International Telecommunications Union – Radiocommunications Sector
LF	Low Frequency
MER	Modulation Error Ratio
MF	Medium Frequency
MLC	Multi-Level Coding
MSC	Main Service Channel

¹ IEC 62272-1, *Digital radio mondiale – Part 1: System specification*

OFDM	Orthogonal Frequency Division Multiplex
PRBS	Pseudo-Random Bit Sequence
QAM	Quadrature Amplitude Modulation
RF	Radiofrequency
SDC	Service Description Channel
SM	Spectrum Management
Tx	Transmitter

4 General conditions of operation

Any device for the suppression of unwanted signals, irrespective of whether or not the device is located inside the transmitter, shall be considered as part of the transmitter for the purposes of this standard.

Feeders and antennas to which the transmitter might be connected are not considered part of the transmitter and therefore excluded.

Unless otherwise specified, the measurements shall be made under normal operating and environmental conditions and at the nominal output power. If required, they shall be repeated under extreme operating and environmental conditions and at any lower output power in accordance with the equipment specification.

The transmitting mode and the measured output power of the transmitter under test shall be stated.

The mains supply and the environmental conditions shall be stated with the measurement results.

The transmitter shall be connected to a test load having a VSWR relative to the nominal load impedance of the transmitter not greater than

- 1,2:1 at frequencies within the designated broadcast band;
- 1,5:1 at all frequencies outside the designated broadcast band up to a frequency of 10 times the highest frequency in the designated band.

If the transmitter includes devices to control the frequency band transmitted, all the characteristics shall be measured with the devices in the circuit.

Measurement uncertainty should be calculated and techniques employed to minimize its range. This uncertainty should be applied to the limit and any measurement falling below the range is deemed acceptable.

If a digital transmitter can also operate in analogue mode, the requirements of IEC 60244-1 and IEC 60244-15 shall also apply, in addition to the requirements of this standard.

5 General conditions of measurement

5.1 Input and output measurement arrangements

For the purposes of measurement, the input and output signal arrangements are given in the form of diagrams.

Where required, the impedance of the test equipment of the transmitter under test and of all the connections between them shall be appropriately terminated, taking into account the transmitter's specification and the termination impedance of any test equipment.

These test procedures for DRM transmitters require that the test signals used shall conform to the DRM standard and that the measuring equipment is sufficiently accurate and has the necessary performance and dynamic range to provide error-free measurements of transmitter performance parameters.

5.2 Temperature and humidity

Equipment to be measured shall be operated in an environment which meets the temperature and humidity requirements as defined in their technical specifications. Temperature and humidity must never be such as to cause condensation in or on the equipment during measurements. In the absence of temperature and humidity requirements in the technical specifications, the provisions of IEC 60244-1 shall apply.

5.3 Conditions for primary power supply

The measurements are carried out at the nominal voltage and the nominal frequency of the power supply given in the relevant equipment specification.

During a series of measurements carried out as part of one test on one equipment, the voltage and frequency of the power supply shall be set at the nominal values indicated in the equipment specification.

If called for in the specification and if the power source is able to be adjusted, the test shall be repeated at the extremes of voltage and frequency stipulated in the specification.

The conditions for primary power voltage and frequency shall be specified in the equipment specification. If no voltage or frequency range is specified, the tests shall be carried out with voltage within $\pm 5\%$ of nominal and frequency within $\pm 2\%$ of nominal.

5.4 Output power

The tests shall be carried out with the transmitter set to its nominal output power and, if required, also at any other output power within the equipment specification.

<https://standards.iteh.ai/catalog/standards/iec/83453a31-2cae-4de6-bef1-84eac35c1c59/iec-62272-2-2007>

6 General characteristics

6.1 Output power

6.1.1 Definition

For a digital signal with the OFDM modulation process the power is distributed evenly throughout the transmission channel. Hence, when taking power measurements on such a signal, the total bandwidth occupied by the modulated signal shall be taken into account.

The output power of a digital modulated transmitter is defined as the mean power (thermal power) delivered at its output port, measured during an interval of time sufficiently long compared with the lowest frequency encountered in the modulation envelope, taken under normal operating condition (continuous mean power).

6.1.2 Measuring arrangement

Figure A.1 shows the measuring set-up to be used.

In general, quantifying output power relies on measuring either the thermal effects of the power dissipated in the test load or the RF voltage across it. The method chosen will depend largely on power output.

Examples are as follows: