

Designation: E2043 - 99 (Reapproved 2021)

Standard Test Method for Nonvolatile Matter of Agricultural Adjuvant Solutions by Thermogravimetry¹

This standard is issued under the fixed designation E2043; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method covers the determination of the nonvolatile matter of agricultural tank mix adjuvant solutions by thermogravimetry.

1.2 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.3 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.

1.4 This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.

2. Referenced Documents

2.1 ASTM Standards:²

- E473 Terminology Relating to Thermal Analysis and Rheology
- E1131 Test Method for Compositional Analysis by Thermogravimetry
- E1519 Terminology Relating to Agricultural Tank Mix Adjuvants

3. Terminology

3.1 Definitions:

3.1.1 *nonvolatile matter, n*—the matter remaining after heating an agricultural adjuvant solution at 50 °C \pm 2.5 °C for 16 h.

4. Summary of Test Method

4.1 This test method is an empirical technique using thermogravimetry in which the mass of an agricultural adjuvant, heated at a controlled rate in an appropriate environment, is recorded as a function of time and temperature. Nonvolatile matter is the mass remaining after heating at a specific time and temperature.

5. Significance and Use

5.1 This test method is intended for use in quality control, material screening, and related problem solving where a nonvolatile content is desired or a comparison can be made with a known material of the same type.

5.2 The parameters described may be altered to suit a particular analysis, provided the changes are noted in the report.

6. Apparatus

6.1 Aluminum Weighing Dishes, flat bottom, 70 mL capacity.

6.2 Analytical Balance, with a sensitivity of 0.01 g.

6.3 Desiccator.

6.4 Drying Oven, gravity convection-type, capable of maintaining a temperature of 50 °C \pm 2.5 °C. If many determinations of solvent-based adjuvants are being made at the same time, an explosion-proof oven should be used.

7. Procedure

7.1 Bring the material to be tested to equilibrium temperature at 25 °C \pm 5 °C.

7.2 Dry two flat-bottomed aluminum weighing dishes in an oven at 50 °C \pm 2.5 °C for 1 h. Allow the dishes to return to ambient temperature in a desiccator.

7.3 Weigh each dish, making the determination in duplicate. Record the weight of the weighing dish to the nearest 0.01 g.

¹This test method is under the jurisdiction of ASTM Committee E35 on Pesticides, Antimicrobials, and Alternative Control Agents and is the direct responsibility of Subcommittee E35.22 on Pesticide Formulations and Delivery Systems.

Current edition approved Oct. 1, 2021. Published October 2021. Originally approved in 1999. Last previous edition approved in 2017 as E2043 – 99 (2017). DOI: 10.1520/E2043-99R21.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

7.4 Add approximately 2.0 g \pm 0.1 g of agricultural adjuvant solution to the aluminum weighing dish. Record the total weight of the sample and dish to the nearest 0.01 g.

7.5 Place the dish in an oven at 50 °C \pm 2.5 °C. Maintain this temperature for 16 h \pm 5 min. Begin timing when the oven has returned to temperature after loading.

7.6 After heating is complete, place the dish in a desiccator and allow it to return to ambient temperature.

7.7 Weigh the dish and sample to the nearest 0.01 g.

8. Calculation

8.1 Calculate the percent nonvolatile matters, using the following equation:

$$S = \frac{R - T}{W - T} \times 100 \tag{1}$$

where:

E2043 – 99 (2021)

R =final weight of residue and pan, g,

T =tare weight of pan, g, and

W = initial weight of sample and pan, g.

9. Precision and Bias

9.1 Duplicate determination should not differ by more than 0.5 % of the mean value.

10. Keywords

10.1 adjuvant; agriculture; nonvolatile matter; pesticide; solids; thermogravimetry

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; http://www.copyright.com/

ASTM E2043-99(2021)

https://standards.iteh.ai/catalog/standards/sist/e42c8138-831e-459b-at84-567cfb57ba15/astm-e2043-992021