



Designation: E3036 – 15 (Reapproved 2021)

Standard Guide for Notating Facade Conditions in the Field¹

This standard is issued under the fixed designation E3036; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This guide consists of symbols and notations pertaining to documenting deficient conditions observed during facade inspections.

1.2 The purpose of this guide is to provide a quick shorthand, notation system that will serve as a uniform system for facade inspectors to record their observations on existing elevation drawings or photographs, or both, of existing building facades.

1.3 This guide is not intended to be used to record or document a diagnosis for the particular symptom.

1.4 Notations are listed in alphabetical order. Compound terms appear as per the first word as spoken.

1.5 The values stated in inch-pound units are to be regarded as standard. No other units of measurement are included in this standard.

1.6 *This international standard was developed in accordance with internationally recognized principles on standard-*

ization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.

2. Referenced Documents

2.1 *ASTM Standards*:²
E631 [Terminology of Building Constructions](#)

3. Symbols³

3.1 See [Fig. 1](#).

4. Modifying Syntax

4.1 See [Fig. 2](#).

5. Notation Examples

5.1 See [Fig. 3](#).

6. Keywords

6.1 condition; facade; notation; survey

¹ This guide is under the jurisdiction of ASTM Committee E06 on Performance of Buildings and is the direct responsibility of Subcommittee E06.55 on Performance of Building Enclosures.

Current edition approved Oct. 1, 2021. Published October 2021. Originally approved in 2015. Last previous edition approved in 2015 as E3036–15. DOI: 10.1520/E3036-15R21.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ The selection of these symbols was based on availability across computing platforms and ease to hand draw for both types of applications in the field.


















<u>Notable Facade Condition</u>	<u>Symbol</u>
Crack	
Spall	
Incipient Spall	
Stain	
Hole or Void	
Deterioration	
Joint Failure	
Previous Repair	
Loose or Unsecured Item	
Coating Failed	
Corrosion	
Surface Loss	
Failed Anchor or Connection	
Weathered	
Unbonded	
Removed	
Missing	

FIG. 1 Symbols

Modifier	Symbol
Width	//
Quantity	○
Area	□
Length	=
Out of Plane	△
Time or Duration	⌘
Location	@
Photo Reference	*
Dangerous Condition	!

FIG. 2 Modifying Syntax







Modified Notation	Observed Condition
	Quarter inch wide crack
	Quarter inch wide crack that is one inch long
	Three spalls in one location
	Incipient spall that is six square inches in size
	Stain that is three inches long
	Loose item that is out-of-plane by two inches

FIG. 3 Notation Examples