

Edition 1.0 2022-11

PUBLICLY AVAILABLE SPECIFICATION



Conductive charging of electric vehicles - DC vehicle coupler configuration GG

(standards.iteh.ai)

IEC PAS 63454:2022

https://standards.iteh.ai/catalog/standards/sist/28fdd4ed-f5c1-421b-a897-5ef671b4e7d5/iec-pas-63454-2022





THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2022 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Secretariat 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Tel.: +41 22 919 02 11 info@iec.ch

www.iec.ch

About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublishedStay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews. With a subscription you will always have access to up to date content tailored to your needs.

Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 300 terminological entries in English and French, with equivalent terms in 19 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.



Edition 1.0 2022-11

PUBLICLY AVAILABLE SPECIFICATION



Conductive charging of electric vehicles – DC vehicle coupler configuration GG

https://standards.iteh.ai/catalog/standards/sist/28fdd4ed-f5c1-421b-a897-5ef671b4e7d5/iec-pas

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.120.30; 43.120 ISBN 978-2-8322-6008-1

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOF	REWORD	3
1	Scope	6
2	Normative references	6
3	Terms and definitions	6
4	General	6
5	Ratings	6
6	Connection between the power supply and the electric vehicle	7
7	Classification of accessories	8
8	Marking	8
9	Dimensions	8
10	Protection against electric shock	9
11	Size and colour of earthing conductors	9
12	Provisions for earthing	9
13	Terminals	9
14	Interlocks	9
15	Resistance to ageing of rubber and thermoplastic material	9
16	General construction	9
17	Construction of socket-outlets	
18	Construction of plugs and vehicle connectors	9
19	Construction of vehicle inlets	
20	Degrees of protectionIEC PAS 63454:2022	
21	Insulation resistance and dielectric strength 4ed-5c 421b-4897-5el671b4e7d5	
22	Breaking capacity	10
23	Normal operation	10
24	Temperature rise	10
25	Flexible cables and their connection	10
26	Mechanical strength	10
27	Screws, current-carrying parts and connections	10
28	Creepage distances, clearances and distances through sealing compound	10
29	Resistance to heat, to fire and to tracking	10
30	Corrosion and resistance to rusting	10
31	Conditional short-circuit current	10
32	Electromagnetic compatibility	10
33	Vehicle driveover	11
34	Thermal cycling	11
35	Humidity exposure	11
36	Misalignment test	11
37	Contact endurance test	11
STA	NDARD SHEETS	12
T-1	lo 201 . Overview of the DC yelliele interfere	-
	le 201 – Overview of the DC vehicle interfacele 202 – Interface overview	
าสม		0

INTERNATIONAL ELECTROTECHNICAL COMMISSION

CONDUCTIVE CHARGING OF ELECTRIC VEHICLES – DC VEHICLE COUPLER CONFIGURATION GG

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

A PAS is an intermediate specification made available to the public and needing a lower level of consensus than an International Standard to be approved by vote (simple majority).

IEC PAS 63454 has been processed by subcommittee 23H: Plugs, Socket-outlets and Couplers for industrial and similar applications, and for Electric Vehicles, of IEC technical committee TC 23: Electrical accessories.

The text of this PAS is based on the following document:

This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document:

Draft PAS	Report on voting		
23H/509/DPAS	23H/514A/RVDPAS		

Following publication of this PAS, which is a pre-standard publication, the technical committee or subcommittee concerned may transform it into an International Standard.

This PAS shall remain valid for an initial maximum period of 2 years starting from the publication date. The validity may be extended for a single period up to a maximum of 2 years, at the end of which it shall be transformed, with or without changes, into another type of normative document, or shall be withdrawn.

This PAS is to be read in conjunction with IEC 62196-1:2022 and IEC 62196-3:2022.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

iTeh STANDARD PREVIEW (standards.iteh.ai)

IEC PAS 63454:2022

https://standards.iteh.ai/catalog/standards/sist/28fdd4ed-f5c1-421b-a897-5ef671b4e7d5/iec-pas-63454-2022

INTRODUCTION

A total of four widely used DC charging interfaces is defined in IEC 62196-3:2022 as follows:

- · configuration AA proposed by Japan,
- · configuration BB proposed by China,
- · configuration EE proposed by North America, and
- configuration FF proposed by Europe.

This PAS introduces the charging interface (configuration GG), a new electric vehicle DC charging system jointly developed by some Chinese, Japanese and European companies. This interface is currently included in the Chinese draft national standard and in the Japanese standard and has considerable potential for future applications.

After consideration within SC 23H/MT 8 (in charge of the maintenance of the IEC 62196 series) and noting that the next revision of IEC 62196-3:2022 will come up after a longer period, it was agreed to issue configuration GG in a first stage in the form of an IEC PAS. The addition of configuration GG into IEC 62196-3 will be considered in the frame of the next revision of IEC 62196-3.

iTeh STANDARD PREVIEW (standards.iteh.ai)

IEC PAS 63454:2022

https://standards.iteh.ai/catalog/standards/sist/28fdd4ed-f5c1-421b-a897-5ef671b4e7d5/iec-pas-63454-2022

CONDUCTIVE CHARGING OF ELECTRIC VEHICLES – DC VEHICLE COUPLER CONFIGURATION GG

1 Scope

This document is applicable to vehicle couplers with pins and contact-tubes of standardized configuration (GG), herein also referred to as "accessories", intended for use in electric vehicle conductive charging systems which incorporate control means, with rated operating voltage and current in accordance with IEC 62196-1:2022.

The DC vehicle connectors and inlets covered by this document are used only in charging mode 4, according to IEC 61851-1:2017, 6.2.4, and case C, as shown in IEC 61851-1:2017, Figure 3.

These vehicle couplers are intended to be used for circuits specified in IEC 61851-23 which operate at different voltages and which can include extra-low voltage (ELV) and communication signals.

This document applies to the vehicle couplers to be used in an ambient temperature of between -30 °C and +40 °C.

NOTE 1 In some countries, other requirements may apply.

NOTE 2 In the following country, -35 °C applies: SE.

These vehicle couplers are intended to be connected only to cables with copper or copper-alloy conductors.

2 Normative references

https://standards.iteh.ai/catalog/standards/sist/28fdd4ed-f5c1-421b-a897-5ef671b4e7d5/iec-pas-Clause 2 of IEC 62196-3:2022 applies. 63454-2022

3 Terms and definitions

Clause 3 of IEC 62196-1:2022 applies.

4 General

Clause 4 of IEC 62196-3:2022 applies.

5 Ratings

Clause 5 of IEC 62196-3:2022 applies, except as follows:

5.1 Replacement:

The preferred rated operation voltage ranges are:

0 V to 60 V (signal or control purposes only)

480 V DC

600 V DC

750 V DC

1 000 V DC

1 500 V DC

6 Connection between the power supply and the electric vehicle

Clause 6 of IEC 62196-3:2022 applies, except as follows:

6.3 DC interface

Replacement:

Replace the existing text of IEC 62196-3:2022, 6.3 with the following:

The DC interface may contain up to 12 power or signal contacts, with only one physical configuration of contact positions. The electrical ratings and contact functions are described in Table 201.

Table 201 - Overview of the DC vehicle interface

	Configuration							
Position	AA		ВВ		GG		Symbol	Function
Number ^a	U _{max}	I _{max}	U _{max}	I _{max}	U _{max}	I _{max}	Symbol	runction
	V	Α	V	Α	V	Α		
1	1 000	400	950	250	1 500	·	DC+	DC+
2	1 000	400	950	250	1 500	KU	DC-	DC-
3	30	10	30	2	60	2	СР	Control Pilot 1
4	30	10	30	21	60	2	CP2	Control Pilot 2
5	30	10	-	-	-	-	CP3	Control Pilot 3
6	30	2	30	2 <u>IEC</u>	P608 6	34.24:20	122 COM1	Communication1(+)
http://star	daads.i	eh.2i/ca	tal30/st	and2rds	sis60 8f	1d42d-1	501 сом2-а8	Communication1(-)
8	30	2	-	-	63454	-2022	IM	Isolation Monitor
9	-	-	950	Rated for fault ^b	-	-	PE	Protective earth
10	30	2	-	-	-	-	PP or CS	Proximity detection or connection switch
11	30°	10 ^c -	30	20	-	-	AUX1	Auxiliary Power Supply 1(+)
12	-	-	30	20	-	-	AUX2	Auxiliary Power Supply 1(-)

^a Position number does not refer to the location and/or identification of the contact in the accessory.

For use with non-isolated DC EV supply equipment, the interface shall be provided with a contact for protective earthing conductors.

For use with isolated DC EV supply equipment, the interface may be provided with a contact for protective earthing conductors.

b "Rated for fault" means "rated for the highest fault current".

^c For configuration AA, position 11 is optional.

Classification of accessories

Clause 7 of IEC 62196-3:2022 applies, except as follows:

7.301 Replacement:

According to the Standard Sheet used:

- Configuration AA
- Configuration BB
- Configuration EE and AC corresponding to Type 1 in IEC 62196-2:2022
- Configuration FF and AC corresponding to Type 2 in IEC 62196-2:2022
- Configuration GG.

Marking

Clause 8 of IEC 62196-1:2022 applies.

Dimensions

Clause 9 of IEC 62196-3:2022 applies, except as follows:

9.1 Replacement:

GG

The vehicle connector and vehicle inlet shall comply with the relevant configuration shown in Table 202:

Table 202 - Interface overview

Configuration	Dimensions described in:	Max. rated voltage V DC	Max. rated current	Shall only be used with DC charging station according to the following annexes in IEC 61851-23:— ¹
AA	IEC 62196-3:2022, Standard Sheets 3-I	1 000	400	Annex AA
ВВ	IEC 62196-3:2022, Standard Sheets 3-II	950	250	Annex BB
EE ^a	IEC 62196-3:2022, Standard Sheets 3-III	1 000	400	Annex CC
FFb	IEC 62196-3:2022, Standard Sheets 3-IV	1 000	400	Annex CC

1 500

Standard Sheets 3-V

AC ratings are in accordance with IEC 62196-2:2022, 6.5, type 1

AC ratings are in accordance with IEC 62196-2:2022, 6.5, type 2

To be proposed in the future third edition of IEC 61851-23.

¹ Edition 2 under preparation. Stage at the time of publication: IEC CDV 61851-23:2022.

10 Protection against electric shock

Clause 10 of IEC 62196-3:2022 applies.

11 Size and colour of earthing conductors

Clause 11 of IEC 62196-3:2022 applies.

12 Provisions for earthing

Clause 12 of IEC 62196-1:2022 applies.

13 Terminals

Clause 13 of IEC 62196-1:2022 applies.

14 Interlocks

Clause 14 of IEC 62196-3:2022 applies.

15 Resistance to ageing of rubber and thermoplastic material

Clause 15 of IEC 62196-1:2022 applies.

16 General construction

https://standards.iteh.ai/catalog/standards/sist/28ldd4ed-15c1-421b-a897-5el671b4e7d5/iec-past Clause 16 of IEC 62196-3:2022 applies. 63454-2022

17 Construction of socket-outlets

Clause 17 of IEC 62196-1:2022 does not apply.

18 Construction of plugs and vehicle connectors

Clause 18 of IEC 62196-3:2022 applies.

19 Construction of vehicle inlets

Clause 19 of IEC 62196-3:2022 applies.

20 Degrees of protection

Clause 20 of IEC 62196-1:2022 applies.

21 Insulation resistance and dielectric strength

Clause 21 of IEC 62196-1:2022 applies.