



SLOVENSKI STANDARD

SIST EN 300 290 V1.2.1:2004

01-oktober-2004

Dostop in terminali (AT) - Digitalni zakupljeni vodi za prenosno hitrost 64 kbit/s brez omejitev za prenašane signale in z ohranjanjem oktetov (D64U) - Vmesnik terminalske opreme

Access and Terminals (AT); 64 kbit/s digital unrestricted leased line with octet integrity (D64U); Terminal equipment interface

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 290 V1.2.1:2004](https://standards.iteh.ai/catalog/standards/sist/d7b82ee8-8cd4-4ba4-846e-125268886608/sist-en-300-290-v1-2-1-2004)

Ta slovenski standard je istoveten z: EN 300 290 Version 1.2.1

ICS:

33.040.50	Vodi, zveze in tokokrogi	Lines, connections and circuits
-----------	--------------------------	---------------------------------

SIST EN 300 290 V1.2.1:2004	en
------------------------------------	-----------

iTeh STANDARD PREVIEW **(standards.iteh.ai)**

SIST EN 300 290 V1.2.1:2004

<https://standards.iteh.ai/catalog/standards/sist/d7b82ee8-8cd4-4ba4-846e-f232b888b808/sist-en-300-290-v1-2-1-2004>

ETSI EN 300 290 V1.2.1 (2001-07)

European Standard (Telecommunications series)

**Access and Terminals (AT);
64 kbit/s digital unrestricted leased line
with octet integrity (D64U);
Terminal equipment interface**

**iTeh STANDARD PREVIEW
(standards.iteh.ai)**

[SIST EN 300 290 V1.2.1:2004](https://standards.iteh.ai/catalog/standards/sist/d7b82ee8-8cd4-4ba4-846e-f232b888b808/sist-en-300-290-v1-2-1-2004)

<https://standards.iteh.ai/catalog/standards/sist/d7b82ee8-8cd4-4ba4-846e-f232b888b808/sist-en-300-290-v1-2-1-2004>



ReferenceREN/AT-020005

Keywordsdigital, interface, leased line, ONP, terminal
testing

ETSI650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 290 V1.2.1:2004

<https://standards.iteh.ai/catalog/standards/sist/d7b82ee8-8cd4-4ba4-846e-f232b888b808/sist-en-300-290-v1-2-1-2004>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:
editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2001.
All rights reserved.

Contents

Intellectual Property Rights	4
Foreword	4
Introduction	5
1 Scope	6
2 References	6
3 Definitions	6
4 Abbreviations	7
5 Requirements	7
5.1 Physical characteristics	7
5.1.1 Hardwired connection	8
5.1.2 Alternative means of connection	8
5.2 Electrical characteristics	8
5.2.1 Output port	8
5.2.1.1 Signal coding	8
5.2.1.2 Waveform shape	8
5.2.1.3 Output timing	10
5.2.1.4 Output jitter	10
5.2.1.5 Output return loss	10
5.2.1.6 Impedance towards ground	10
5.2.1.7 Longitudinal conversion loss	11
5.2.2 Input port	11
5.2.2.1 Signal coding	11
5.2.2.2 Input clock tolerance	11
5.2.2.3 Input jitter tolerance	11
5.2.2.4 Input return loss	12
5.2.2.5 Input loss tolerance	13
5.2.2.6 Immunity against reflections	13
5.2.2.7 Impedance towards ground	13
5.2.2.8 Longitudinal conversion loss	13
5.3 Safety	14
5.4 Overvoltage	14
5.5 Electro-magnetic compatibility	14
Annex A (normative): Test methods	15
A.1 General	15
A.1.1 Additional information to support the test	15
A.1.2 Equipment connection	15
A.2 Test methods	16
A.2.1 Signal coding at output port	16
A.2.2 Waveform shape at output port	16
A.2.3 Input coding, loss tolerance and immunity against reflections	17
A.2.4 Return loss at input port	18
A.2.5 Input and output jitter	19
A.2.6 Longitudinal conversion loss	20
A.2.7 Impedance towards ground	21
Annex B (normative): Code conversion rules	22
Annex C (informative): Bibliography	23
History	24

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Technical Committee Access and Terminals (AT).

The present document results from a mandate from the Commission of the European Community (CEC) to provide standards for the support of the Directive on Open Network Provision (ONP) of leased lines (92/44/EEC).

There are two other standards directly related to the present document:

- EN 300 288: "Access and Terminals (AT); 64 kbit/s digital unrestricted leased line with octet integrity (D64U); Network interface presentation";
- EN 300 289: "Access and Terminals (AT); 64 kbit/s digital unrestricted leased line with octet integrity (D64U); Connection characteristics".

The present document is based on information from ITU-T Recommendations and ETSI publications and the relevant documents are quoted where appropriate.

[SIST EN 300 290 V1.2.1:2004](https://standards.iteh.ai/catalog/standards/sist/d7b82ee8-8cd4-4ba4-846e-1232b888b808/sist-en-300-290-v1-2-1-2004)

[https://standards.iteh.ai/catalog/standards/sist/d7b82ee8-8cd4-4ba4-846e-](https://standards.iteh.ai/catalog/standards/sist/d7b82ee8-8cd4-4ba4-846e-1232b888b808/sist-en-300-290-v1-2-1-2004)

[1232b888b808/sist-en-300-290-v1-2-1-2004](https://standards.iteh.ai/catalog/standards/sist/d7b82ee8-8cd4-4ba4-846e-1232b888b808/sist-en-300-290-v1-2-1-2004)

National transposition dates

Date of adoption of this EN:	29 June 2001
Date of latest announcement of this EN (doa):	30 September 2001
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 March 2002
Date of withdrawal of any conflicting National Standard (dow):	31 March 2002

Introduction

The Council Directive on the application of Open Network Provision (ONP) to leased lines (92/44/EEC) concerns the harmonization of conditions for open and efficient access to, and use of, the leased lines provided over public telecommunications networks and the availability throughout the Community (EEC) of a minimum set of leased lines with harmonized technical characteristics.

The consequence of the Directive is that Telecommunications Organizations within the EEC shall make available a set of leased lines between points in these countries with specified connection characteristics and specified interfaces.

Two categories (voluntary and regulatory) of standard were used for the interfaces of terminal equipment designed for connection to the ONP leased lines. Technical Basis for Regulations (TBRs) gave the earlier essential requirements under the Directive 91/263/EEC, later replaced by 98/13/EC, for attachment to the leased lines, whereas other voluntary standards (ETSS or ENs) gave the full technical specifications for these interfaces. The present document, which is based on an earlier ETS, belongs to the second category.

The requirements of TBR 14 are a subset of the present document.

The present version of the present document has been produced to introduce some necessary changes.

ETS 300 166 and ITU-T Recommendation G.703 [1] were used as the basis for the terminal interface.

iTeh STANDARD PREVIEW (standards.iteh.ai)

[SIST EN 300 290 V1.2.1:2004](https://standards.iteh.ai/catalog/standards/sist/d7b82ee8-8cd4-4ba4-846e-f232b888b808/sist-en-300-290-v1-2-1-2004)

<https://standards.iteh.ai/catalog/standards/sist/d7b82ee8-8cd4-4ba4-846e-f232b888b808/sist-en-300-290-v1-2-1-2004>

1 Scope

The present document specifies the physical and electrical characteristics (except safety, overvoltage and EMC aspects) and corresponding test principles for a terminal equipment interface for connection to the network termination points of ONP 64 kbit/s digital unrestricted leased lines with octet integrity.

The present document is to ensure that the interface of the terminal equipment is compatible with the ONP 64 kbit/s digital unrestricted leased line with octet integrity. It is applicable to all interfaces designed for connection to the leased line, however in the cases of apparatus that carries a particular service, of complex apparatus and of apparatus in private networks, other requirements may apply in addition to the present document.

Customer premises wiring and installation between the terminal equipment and the Network Termination Point (NTP) are outside the scope of the present document.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

[1] ITU-T Recommendation G.703 (1998): "Physical/electrical characteristics of hierarchical digital interfaces".

[2] ITU-T Recommendation O.152 (1992): "Error performance measuring equipment for bit rates of 64 kbit/s and N x 64 kbit/s".

3 Definitions

For the purposes of the present document, the following definitions apply:

leased lines: telecommunications facilities provided by a public telecommunications network that provide defined transmission characteristics between network termination points and that do not include switching functions that the user can control, (e.g. on-demand switching)

Network Termination Point (NTP): all physical connections and their technical access specifications which form part of the public telecommunications network and are necessary for access to and efficient communication through that public network

Terminal Equipment (TE): equipment intended to be connected to the public telecommunications network, i.e.:

- a) to be connected directly to the termination of a public telecommunication network; or
- b) to interwork with a public telecommunications network being connected directly or indirectly to the termination of a public telecommunications network;

in order to send, process, or receive information.

4 Abbreviations

For the purposes of the present document, the following abbreviations apply:

D64U	64 kbit/s digital unrestricted ONP leased line with octet integrity
dc	direct current
EMC	Electro-Magnetic Compatibility
NTP	Network Termination Point
ONP	Open Network Provision
ppm	parts per million
PRBS(2 ¹¹ -1)	Pseudo Random Bit Sequence (as defined in clause 2.1 of ITU-T Recommendation O.152 [2])
rms	root mean square
RX	Receive (a signal input at either the leased line interface or the test equipment, see figure 1)
TE	Terminal Equipment
TX	Transmit (a signal output at either the leased line interface or the test equipment, see figure 1)
UI	Unit Interval

5 Requirements

The terminal equipment interface is for use with 64 kbit/s unrestricted leased lines with octet integrity, which provide bidirectional, point-to-point digital connections with a usable bit rate of 64 kbit/s where the leased line output timing is provided from the network. The interface timing arrangements are codirectional.

5.1 Physical characteristics

Currently no standardized connector is readily available. Consequently, the only method of connection that can be specified in the present document is the use of solid conductors of 0,4 mm to 0,6 mm. The present document requires the TE to be capable of presenting either a point for the attachment of unterminated solid conductors, or solid conductors themselves (see clause 5.1.1). It is a requirement that such a connection method be available to be provided for use with the TE if necessary.

In order to allow connection to be made using other methods (e.g. connectors), the TE is permitted to be supplied with a connection method suitable for use with those methods (see clause 5.1.2).

NOTE 1: The following are examples of arrangements that comply with the requirements. The list below should not be regarded as an exhaustive list of all permitted arrangements:

- a cord, permanently connected to the terminal equipment at one end and unterminated at the other end, with wires that are solid conductors with diameters in the range 0,4 mm to 0,6 mm;
- a cord, connected via a plug and socket to the terminal equipment at one end and unterminated at the other end, with wires that are solid conductors with diameters in the range 0,4 mm to 0,6 mm;
- an insulation displacement connector, designed to accept wires with solid conductors with diameters in the range 0,4 mm to 0,6 mm, but with no cord;
- a screw connector, designed to accept wires with solid conductors with diameters in the range 0,4 mm to 0,6 mm, but with no cord;
- the arrangement in b) plus one or more additional alternative cords with the same plug or socket arrangement at the terminal end and any plug or socket at the other end;
- the arrangement in c) or d) plus one or more cords suitable for connection to the terminal equipment at one end and any plug or socket at the other end.

The transmit pair is the output from the terminal equipment interface. The receive pair is the input to the terminal equipment interface, as shown in figure 1. Where the terms "output" and "input" are used without qualification in the present document, they refer to the terminal equipment interface.




Figure 1

NOTE 2: The use of a shielded cord or cable may be necessary to meet radiation and immunity requirements defined in Electro-Magnetic Compatibility (EMC) standards.

5.1.1 Hardwired connection

Requirement: The terminal equipment shall provide:

- a set of connection contacts (e.g. an insulation displacement connector or a screw terminal block) to which solid wire conductors with diameters in the range 0,4 mm to 0,6 mm may be connected; or
- a wiring arrangement connected by any means to the terminal equipment, with unterminated solid wire conductors with diameters in the range 0,4 mm to 0,6 mm at the end distant from the terminal equipment.

Test: There is no test. All subsequent tests are carried out via the specified connection method.

5.1.2 Alternative means of connection

Any alternative means of connection may be provided in addition to the connection arrangements under clause 5.1.1.

5.2 Electrical characteristics

5.2.1 Output port

<https://standards.iteh.ai/catalog/standards/sist/d7b82ee8-8cd4-4ba4-846e-f232b888b808/sist-en-300-290-v1-2-1-2004>

5.2.1.1 Signal coding

Requirement: The signal transmitted at the output port shall comply with the encoding rules given in annex B.

Test: The test shall be conducted according to annex A, clause A.2.1.

5.2.1.2 Waveform shape

Requirement: The pulse at the output port shall comply with the requirements given in table 2 and figures 2 and 3, taken from ITU-T Recommendation G.703 [1].

Table 2: Waveform shape at output port

Pulse shape (nominally rectangular)	All pulses of a valid signal shall conform with the masks (see figures 2 and 3) irrespective of the polarity.
Test load impedance	120 Ω non-reactive
Nominal peak voltage V of a mark (pulse)	1 V
Peak voltage of a space (no pulse)	0 V \pm 0,1 V
Nominal pulse width	3,9 μ s for a single pulse 7,8 μ s for a double pulse
Ratio of the amplitudes of positive and negative pulses at the centre of the pulse interval	0,95 to 1,05
Ratio of the widths of positive and negative pulses at the nominal half amplitude	0,95 to 1,05




Figure 2: Pulse mask for single pulse

STANDARD PREVIEW
(standards.itech.ai)




Figure 3: Pulse mask for double pulse

Test: The test shall be according to annex A, clause A.2.2.