



Designation: E1133 – 86 (Reapproved 2022)

Standard Practice for Performance Testing of Packaged Laboratory Apparatus for United States Government Procurements¹

This standard is issued under the fixed designation E1133; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This practice describes the procedures for testing loaded shipping containers that would be sold to the United States government. The following tests are performed to measure the ability of the shipping container to protect the contents from the environment, shock, and vibration during wartime conditions. This practice is not intended to supplant material specifications or existing pre-shipment test procedures. The suitability of this practice for use with hazardous materials has not been determined.

1.2 The procedures covered in this practice are suitable for all types of laboratory apparatus including reusable and disposable macro and micro products.

1.3 The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.5 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*²

¹ This practice is under the jurisdiction of ASTM Committee E41 on Laboratory Apparatus and is the direct responsibility of Subcommittee E41.01 on Laboratory Ware and Supplies.

Current edition approved Jan. 1, 2022. Published February 2022. Originally approved in 1986. Last previous edition approved in 2016 as E1133 – 86 (2016). DOI: 10.1520/E1133-86R22.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

D685 Practice for Conditioning Paper and Paper Products for Testing

D951 Test Method for Water Resistance of Shipping Containers by Spray Method

D1083 Test Methods for Mechanical Handling of Unitized Loads and Large Shipping Cases and Crates (Withdrawn 2001)³

D4169 Practice for Performance Testing of Shipping Containers and Systems

D4332 Practice for Conditioning Containers, Packages, or Packaging Components for Testing

2.2 *Military Standard:*

MIL-STD-810D Environmental Test Method⁴

3. Significance and Use

3.1 The test procedure in this practice is proposed as a package performance test to be met for items shipped for United States government procurements. This practice will apply only when requested by the buyer.

4. Requirements

4.1 Three individual shipping containers, or one unit consisting of two or more overpackaged individual units are required. Each specimen shall be run through the sequence of tests, in the order given.

4.2 Condition the test specimens in accordance with Method D685 for 72 h at 50 % \pm 2 % relative humidity and 23 °C \pm 1 °C.

5. Procedure

5.1 Expose the specimens to a salt spray for 2 h in accordance with Test Method D951.

5.2 *Drop Test Procedures:*

5.2.1 Items less than 100 lb shall be drop tested in accordance with Practice D4169 Element A, Assurance Level I, (see Table 1). The drop sequence shall be conducted as follows:

³ The last approved version of this historical standard is referenced on www.astm.org.

⁴ Available from Standardization Documents Order Desk, DODSSP, Bldg. 4, Section D, 700 Robbins Ave., Philadelphia, PA 19111-5098, http://dodssp.daps.dla.mil.

TABLE 1 Drop Test Conditions for Items Less Than 100 lb

Gross Weight, lb (Kg)	Drop Height, in. (mm)
0 to 20 (0 to 9.1)	24 (610)
20 to 40 (9.1 to 18.2)	21 (533)
40 to 60 (18.2 to 27.3)	18 (457)
60 to 80 (27.3 to 36.4)	15 (381)
80 to 100 (36.4 to 45.5)	12 (305)

bottom at twice specified height; bottom long edge at specified height; bottom adjacent short edge at specified height; bottom corner at specified height; bottom diagonal opposite corner at specified height; and top at specified height.

5.2.2 Items more than 100 lb (see Methods **D1083**) shall be drop tested in accordance with Practice **D4169** Element B, Assurance Level I, (see **Table 2**). The drop sequence shall be conducted as follows: one drop on each bottom edge; and the total number of drops shall be four.

5.3 *Compression Test Level*—Conduct the compression test in accordance with Practice **D4169** using the following equation.

$$L = W \frac{(H - h)}{(h)} \times 8.0 \quad (1)$$

where:

- L = load,
- W = weight of one shipping container, lb,
- h = height of one shipping container, in., and
- H = 120 in.

TABLE 2 Drop Test Conditions for Items Over 100 lb

Gross Weight, lb (Kg)	Drop Height, in. (mm)
100 to 500 (45.5 to 227.5)	12 (305)
500 and over (227.5 and over)	9 (228)

5.4 *Storage Test*—Subject the package to three cycles in accordance with Practice **D4332**. Each cycle shall consist of one week under each of the following environments in sequence, desert, tropical, and cryogenic. Drop test as outlined in **5.2**.

5.5 *Vibration Test*—Conduct the vibration test in accordance with Practice **D4169** Element E, Assurance Level I.

5.6 *Bounce, Loose Cargo Test*—Conduct the bounce, loose cargo test in accordance with MIL-STD-810D Method 5.6.12, Procedure XI, Part 2. Drop test as outlined in **5.2**.

6. Inspection

6.1 The packages shall be considered successful in passing the tests if, upon inspection, the following condition(s) are met:

6.1.1 *Disposable Glass*—Completion of testing without breakage occurring in any of the three units tested or in the case of bulk packed items with more than fifty in a shipping container, less than 3 % breakage in each of the three units tested.

6.1.2 *All Others*—Completion of testing without breakage occurring and the packaged item remaining 100 % functional.

6.2 Outer package must contain product and provide a degree of protection to contents.

7. Certification

7.1 Each supplier shall maintain on file laboratory test reports verifying successful testing as outlined in this practice and, if required, issue a written certification that the packaging complies with this practice.

8. Keywords

8.1 apparatus; government; packaging; procurement

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; http://www.copyright.com/