



Designation: ~~F2598 – 09 (Reapproved 2017)~~<sup>ε1</sup> F2598 – 22

## Standard Consumer Safety Specification for ~~Clothing Storage Chests~~ Sealed Storage Chests such as Cedar Chests, Hope Chests, Blanket Chests, Keepsake Chests<sup>1</sup>

This standard is issued under the fixed designation F2598; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

<sup>ε1</sup> NOTE—Editorially updated Referenced Documents in Section 2 in June 2017.

### INTRODUCTION

This consumer safety specification addresses chest accidents that have been identified by the U.S. Consumer Product Safety Commission (CPSC).

Products commonly referred to as cedar chests, hope chests, blanket chests, and keepsake chests have been in use for well over a century. A design characteristic of these products involves the necessity of a tight lid closure to create a sealed storage space for the prevention of insect infestation and dust or dirt contamination.

Many of these products were originally equipped with locks or latching mechanisms that automatically engage when the lid is closed. These locks or latching mechanisms can only be released from outside the product. Children playing in these original products can be inadvertently trapped and suffocate.

A CPSC Product Recall was issued as early as 1996 for products involving a major historical product brand. This recall involved modifying the locking/latching mechanisms to prevent automatic engagement when the lid is closed. This recall continues, and has expanded to include other brands that utilized similar locks or latches, as well as the risk of child entrapment resulting from unexpected lid closure.

This consumer safety specification attempts to minimize the following: (1) possible entrapment, entrapment, suffocation, and strangulation hazards associated with sudden lid closing or dropping and (2) possible crushing, pinching, and laceration hazards associated with folding mechanisms, hinges, and lid supports.

### 1. Scope

1.1 This consumer safety specification covers the performance requirements and test methods to ensure the safety of chests.

1.2 This consumer safety specification is intended to minimize the incidents and injuries to children resulting from normal use and reasonably foreseeable misuse or abuse of these chests.

1.3 This consumer safety specification applies to products ~~known as clothes chests or other single-compartment closed rigid boxes~~

<sup>1</sup> This consumer safety specification is under the jurisdiction of ASTM Committee F15 on Consumer Products and is the direct responsibility of Subcommittee F15.42 on Furniture Safety.

Current edition approved June 15, 2017; Jan. 15, 2022. Published July 2017; February 2022. Originally approved in 2009. Last previous edition approved in 2009 as F2598 – 09; F2598 – 09 (2017)<sup>ε1</sup>. DOI: 10.1520/F2598-09R17E01-10.1520/F2598-22.

(sometimes referred to as “cedar chests”) that are commonly known as cedar chests, hope chests, blanket chests, and keepsake chests, or other similar closed rigid boxes designed and marketed as sealed storage containers for clothes, blankets, or linens. The products subject to the requirements are those with a single volume of 1.1 ft<sup>3</sup> (0.031 m<sup>3</sup>) or more. Products subject to these requirements are: <sup>3</sup>(0.031 m<sup>3</sup>) or more.

1.3.1 Those with a single volume of 1.1 ft<sup>3</sup> (0.031 m<sup>3</sup>) or more measured with all removable shelves or compartments removed from the product, and

1.3.2 Those intended to create a tightly sealed storage space when the lid is closed for purposes such as the prevention of insect infestation and dust or dirt contamination.

1.4 No chest produced after the approval date of this consumer safety specification shall, either by label or other means, indicate compliance with this specification unless it conforms to all requirements contained herein.

1.5 The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.

1.6 The following precautionary caveat pertains only to the test methods portion, Section 5, of this specification: *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.7 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

## 2. Referenced Documents

### 2.1 ASTM Standards:<sup>2</sup>

**F963 Consumer Safety Specification for Toy Safety**

### 2.2 ANSI Standard:<sup>3</sup>

**ANSI Z535.4 Product Safety Signs and Labels**

### 2.3 Federal Standard:<sup>4</sup>

**Title 16 Code of Federal Regulations--Commercial Practices**

**16 CFR 1303 Ban on Lead-Containing Paint and Certain Consumer Products Bearing Lead-Containing Paint**

## 3. Performance Requirements

### 3.1 Lid Support:

3.1.1 Chests with vertically opening hinged lids shall be provided with lid-support mechanisms to prevent sudden collapse or dropping of the lid.

3.1.2 The lid-support mechanism shall support the lid so that at no position in the arc of travel of the lid from within 2.0 in. (50.8 mm) of the fully closed position through an arc not to exceed 60° from the fully closed position shall it drop more than 0.50 in. (12.7 mm) under the influence of its own weight, except in the last 2.0 in. (50.8 mm) of travel. The test shall be conducted in accordance with 5.1.

3.1.3 The chest lid shall comply with this requirement before and after being subjected to 3500 opening and closing cycles, as described in Section 5.

3.1.4 The lid-support mechanism shall not require adjustment by the consumer to ensure adequate lid support, nor shall it require adjustment to comply with 3.1.2 after being cycled according to 5.1.2.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

<sup>3</sup> Available from American National Standards Institute (ANSI), 25 W. 43rd St., 4th Floor, New York, NY 10036, <http://www.ansi.org>.

<sup>4</sup> Available from U.S. Government Printing Office Superintendent of Documents, 732 N. Capitol St., NW, Mail Stop: SDE, Washington, DC 20401, <http://www.access.gpo.gov>.

3.1.5 Lid-support mechanisms shall be designed so as to prevent pinching, crushing, or laceration injuries to fingers. Clearances or gaps produced by the action of such mechanisms (between components of the mechanism or between the mechanism and the chest lid) shall be constructed so that if the gap admits a 0.19-in. (4.8-mm) diameter rod it will also admit a 0.50-in. (12.7-mm) diameter rod at all positions of the arc of travel of the lid. This requirement does not apply to lid-support mechanisms installed on the inside of the chest that are at least 12 in. (305 mm) from the front and side edges of the chest or its lid.

3.2 *Closures*—Chest closures such as lids, covers, and doors shall not be fitted with automatic locking devices.

3.3 Closures and lids shall be of a type that can be opened with a force of 10 lbf (45 N) or less when tested in accordance with 5.2.

3.4 *Locks*—Locks shall be safety locks that do not automatically engage.

3.5 Chest shall withstand a load of  $250 \pm 5$  lb ( $113 \pm 2$  kg) applied to the center 8 by 8-in. (20 by 20-cm) area of the lid without permanent damage.

NOTE 1—Simulating an adult sitting on top of the chest.

#### **4. Labeling**

4.1 The name and address (city, state, and zip code) of either the manufacturer, distributor, or seller of the chest shall either be permanently and conspicuously labeled on the product or conspicuously marked in collateral information provided to each user that includes information on assembly, proper use, safety and product care.

4.2 Only those chests that meet the requirements of this safety specification may be marked or labeled on the product or its collateral materials with the phrase “Meets ASTM Safety Specification F2598.”

4.3 If the product does not comply with Consumer Safety Specification F963, the chest shall be permanently and conspicuously labeled inside on the lid with the words: “WARNING—This chest is not intended or suitable for use as a toy chest” and “Risk of Child Suffocation.” Labels shall meet the guidelines of ANSI Z535.4.

#### **5. Test Methods**

##### *5.1 Lid Support Mechanisms:*

5.1.1 Assemble the chest in accordance with manufacturer’s instructions.

5.1.2 Lift the lid to any position in its arc of travel to a distance greater than 2.0 in. (50.8 mm) but not to cause the lid to move through an arc of more than 60° from the lid’s fully closed position measured at the outermost edge of the lid. Release the lid and observe any dropping motion of a point in the approximate center of the outermost edge of the lid.

5.1.3 Subject the lid to 3500 opening and closing cycles. One cycle consists of raising the lid from its fully closed position to a fully open position and returning it to fully closed.

5.1.4 To prevent undue stress on screws or other fasteners used to attach lid support mechanisms, take care not to force the lid beyond its normal arc of travel.

5.1.5 Complete one cycle in approximately 10 to 15 s. Complete the 3500 cycles, then repeat the test described in 5.1.2.

##### *5.2 Closures and Lids:*

5.2.1 *Hinged Lids*—With the lid in a closed position, apply a gradually increasing force in an upward direction perpendicular to the plane of the lid at a point within 1 in. (25.4 mm) from its geometric center. Note the maximum force to cause the lid to begin to open.