

SLOVENSKI STANDARD SIST ISO 5211-2:2000

01-september-2000

Df]_`1 Yj Ub^Y'nUgi bY[U'U_hi Urcf'U'j Ybh]`U'!`&"XY'. NbU]`bcgh]'df]fcVb]W]b'gdc^_

Part-turn valve actuator attachment -- Part 2: Flange and coupling performance characteristics

Raccordement des servomoteurs à fraction de tour aux appareils de robinetterie -- Partie 2: Caractéristiques d'utilisation de l'embase et de l'accouplement

Ta slovenski standard je istoveten z: ISO 5211-2:1979 https://standards.iien.av.catalog/standards/sis/32baa44b-e0d0-4b7d-8c06-

e3e243a0b311/sist-iso-5211-2-2000

ICS:

23.060.01 Ventili na splošno Valves in general

SIST ISO 5211-2:2000 en

SIST ISO 5211-2:2000

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ISO 5211-2:2000

https://standards.iteh.ai/catalog/standards/sist/52baa44b-e0d0-4b7d-8c06-e3e243a0b311/sist-iso-5211-2-2000

International Standard



INTERNATIONAL ORGANIZATION FOR STANDARDIZATION•MEЖДУНАРОДНАЯ OPFAHU3ALUNЯ ПО CTAHDAPTU3ALUNG-ORGANISATION INTERNATIONALE DE NORMALISATION

Part-turn valve actuator attachment — Part 2: Flange and coupling performance characteristics

Raccordement des servomoteurs à fraction de tour aux appareils de robinetterie — Partie 2 : Caractéristiques d'utilisation de l'embase et de l'accouplement

First edition - 1979-12-15 iTeh STANDARD PREVIEW (standards.iteh.ai)

<u>SIST ISO 5211-2:2000</u> https://standards.iteh.ai/catalog/standards/sist/52baa44b-e0d0-4b7d-8c06-e3e243a0b311/sist-iso-5211-2-2000

UDC 621.646 : 62-526 Ref. No. ISO 5211/2-1979 (E)

Descriptors: industrial valves, servomotors, junctions, base plates, couplings, torque.

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO member bodies). The work of developing International Standards is carried out through ISO technical committees. Every member body interested in a subject for which a technical committee has been set up has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council.

iTeh STANDARD PREVIEW

International Standard ISO 5211/2 was developed by Technical Committee ISO/TC 153, General purpose industrial valves, and was circulated to the member bodies in August 1978.

SIST ISO 5211-2:2000

It has been approved by the member bodies of the following countries: \(\frac{152baa44b}{52baa44b} = \frac{000}{600} - \frac{457d}{600} - \frac{8006}{600} - \frac{1000}{600} - \frac{1

Australia India Romania Austria Ireland South Africa, Rep. of Belgium Italy Sweden Japan Canada Switzerland Chile Korea, Rep. of United Kingdom Finland Mexico USA France Netherlands **USSR**

Germany, F. R. Norway

The member body of the following country expressed disapproval of the document on technical grounds :

Czechoslovakia

Torque

N·m

125

250

500

1 000

2 000

4 000

8 000

16 000

32 000

63 000

125 000

INTERNATIONAL STANDARD

Part-turn valve actuator attachment — Part 2: Flange and coupling performance characteristics

Scope and field of application

This International Standard specifies reference values for torque for flanges having the dimensions specified in ISO 5211/1.

2 R	efere	nce
-----	-------	-----

ISO 5211/1, Part-turn valve actuator attachment — Part 1: Flange dimensions.

iTeh STANDARD PR F30 (standards.iteh F35 F40

Definition

torque: A turning moment transmitted through the mounting flagges and couplings. It is expressed in newton metres and couplings. It is expressed in newton metres. flanges and couplings. It is expressed in newton metres.

F48

Flange type

F05

F07

F10

F12

F14

F16

Maximum torques

The torque values listed in the table represent the maximum torques which can be transmitted through the mounting flanges and couplings, and are based upon specified criteria.

- 1 All values have been selected on the basis of the following assump
 - bolt material: ISO class 8.8; yield stress 628 N/mm²;
 - allowable stress: 200 N/mm²;
 - bolts in tension only; no allowance is made for stresses induced by tightening the bolts;
 - coefficient of friction between the mounting flanges: 0,3.
- $2 \ 1 \ N/mm^2 = 1 \ MPa.$