

---

8 [[ ]HJbc`ca fYy`Y`n`]bhY[ f]fUb]a ]`g]c]f]h]j Ua ]`f]G8 Bk!`Df]c]c`\_c`X]] [ ]HJbY`bU]c b]y`\_Y  
g]] bU]nUW]Y`y]h`r`%f]B GG%k!`G]] bU]nUW]g\_ U]ca fY]bU]d`U]g]h]n]U`\_]fa ]`Y]b`Y`j]c]X]c]j]b]Y] U  
c]g]b]c]j]b]Y] U`\_]W]U]!`%`r`X]Y.`G]d]Y]W]Z\_ U]W]U]d]f]c]c`\_c`U`f]t]f]Y]c]V`]\_]c]j]U]b]c]d]f]d]c]f]c ]`c`#]H ]!H  
E`"`. ` %f]l% - ` kL

Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 1: Protocol specification [ITU-T Recommendation Q.931 (1993), modified]

**ITeH STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ETS 300 403-1:1999](https://standards.iteh.ai/catalog/standards/sist/68dc65ce-bf78-4910-b556-ecf483b617cc/sist-ets-300-403-1-1999)

<https://standards.iteh.ai/catalog/standards/sist/68dc65ce-bf78-4910-b556-ecf483b617cc/sist-ets-300-403-1-1999>

**Ta slovenski standard je istoveten z: ETS 300 403-1 Edition 1**

---

**ICS:**

33.080	Digitalno omrežje z integriranimi storitvami (ISDN)	Integrated Services Digital Network (ISDN)
35.100.30	Omrežni sloj	Network layer

**SIST ETS 300 403-1:1999** en

**iTeh STANDARD PREVIEW**  
**(standards.iteh.ai)**

[SIST ETS 300 403-1:1999](#)

<https://standards.iteh.ai/catalog/standards/sist/68dc65ce-bf78-4910-b556-ecf483b617cc/sist-ets-300-403-1-1999>



**E**UROPEAN  
**T**ELECOMMUNICATION  
**S**TANDARD

**ETS 300 403-1**

November 1995

Source: ETSI TC-SPS

Reference: DE/SPS-05034-1

ICS: 33.080, 35.100.30

**Key words:** ISDN, DSS1, layer 3

**Integrated Services Digital Network (ISDN);  
Digital Subscriber Signalling System No. one (DSS1) protocol;  
Signalling network layer for circuit-mode basic call control;  
Part 1: Protocol specification**

STANDARD PREVIEW  
(standards.iteh.ai)  
SIST ETS 300 403-1:1999  
<https://standards.iteh.ai/catalog/standards/sist/68dc65ce-bf78-4910-b556-ecf483b617cc/sist-ets-300-403-1-1999>

**[ITU-T Recommendation Q.931 (1993), modified]**

**ETSI**

European Telecommunications Standards Institute

**ETSI Secretariat**

**Postal address:** F-06921 Sophia Antipolis CEDEX - FRANCE

**Office address:** 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

**X.400:** c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

\*

**Copyright Notification:** No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1995. All rights reserved.

## Foreword

This European Telecommunication Standard (ETS) has been produced by the Signalling Protocols and Switching (SPS) Technical Committee of the European Telecommunications Standards Institute (ETSI).

This ETS which is based on ITU-T Recommendation Q.931 (1993) is an extended and updated version of ETS 300 102-1 (1990) which was based on CCITT Recommendation Q.931 (1988). Annex ZA identifies the relevant differences between this ETS and ETS 300 102-1.

This ETS is part 1 of a multi-part standard covering the Digital Subscriber Signalling System No. one (DSS1) protocol specification for the Integrated Services Digital Network (ISDN) signalling network layer for circuit-mode basic call control, as described below:

**Part 1:** "Protocol specification";

Part 2: "Specification and Description Language (SDL) diagrams";

Part 3: "Protocol Implementation Conformance Statement (PICS) proforma specification";

Part 4: "Test Suite Structure and Test Purposes (TSS&TP) specification for the user";

Part 5: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user";

Part 6: "TSS&TP specification for the network";

Part 7: "ATS and partial PIXIT proforma specification for the network".

**iTeh STANDARD PREVIEW**  
(standards.iteh.ai)

(standards.iteh.ai)	
Date of adoption of this ETS:	10 November 1995
Date of latest announcement of this ETS (doa):	28 February 1996
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	31 August 1996
Date of withdrawal of any conflicting National Standard (dow):	31 August 1996

## Endorsement notice

The text of ITU-T Recommendation Q.931 (1993) was approved by ETSI as an ETS with agreed modifications as given below.

**NOTE:** New or modified text is indicated using sidebars. In addition, underlining and/or strike-out are used to highlight detailed modifications where necessary.

**Page 1, clause 1**

Delete clause 1 (General) and subclause 1.1 (Scope of the Recommendation).

Insert the following three clauses (Scope, Normative references, Definitions) at the start of the text:

**Scope**

This European Telecommunication Standard (ETS) specifies the stage three of circuit-mode on-demand basic telecommunication services for the pan-European Integrated Services Digital Network (ISDN) as provided by European telecommunications operators at the T reference point or coincident S and T reference point (as defined in ITU-T Recommendation I.411 [91] by means of the Digital Subscriber Signalling System No. one (DSS1). Stage three identifies the protocol procedures and switching functions needed to support a telecommunication service (see CCITT Recommendation I.130 [88]).

In addition, this ETS specifies the protocol requirements at the T reference point where the service is provided to the user via a private ISDN.

NOTE 1: Procedures at the T reference point, to support the access of a private ISDN to the public ISDN, are not explicitly identified in this ETS, however some procedures are applicable only to the T reference point.

This ETS does not specify the additional protocol requirements where the service is provided to the user via a telecommunication network that is not an ISDN.

A basic telecommunication service is a fundamental type of service. It forms the basis on which supplementary services may be added.

NOTE 2: Specific requirements of individual circuit-mode basic telecommunication services are not covered in this ETS. However, ETR 018 gives guidance on the use of service specific information elements to implement individual basic telecommunication services.

Further parts of this ETS specify the Specification and Description Language (SDL) diagrams, the method of testing and detailed application specific requirements to determine conformance based on this ETS.

This ETS is applicable to equipment supporting circuit-mode on-demand basic telecommunication services, to be attached at either side of a T reference point or coincident S and T reference point when used as an access to the public ISDN.

**Normative references**

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

- |      |   |
|------|---|
| [87] | ITU-T Recommendation I.112 (1993): "Vocabulary of terms for ISDNs".   |
| [88] | CCITT Recommendation I.130 (1988): "Method for characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".                |
| [89] | ITU-Recommendation I.140 (1993): "Attribute technique for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN". |
| [90] | ITU-T Recommendation I.210 (1993): "Principles of telecommunication services supported by an ISDN and the means used to describe them".                                 |

- [91] ITU-T Recommendation I.411 (1993): "ISDN user network interfaces - reference configurations".
- [92] CCITT Recommendation Q.9 (1988): "Vocabulary of switching and signalling terms".
- [93] ETS 300 007 (1991): "Integrated Services Digital Network (ISDN); Support of packet-mode terminal equipment by an ISDN".
- [94] ETS 300 011 (1990): "Integrated Services Digital Network (ISDN); Primary rate user-network interface layer 1 specification and test principles".
- [95] ETS 300 012 (1990): "Integrated Services Digital Network (ISDN); Basic user-network interface layer 1 specification and test principles".
- [96] ETS 300 058-1: "Integrated Services Digital Network (ISDN); Call Waiting (CW) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [97] ETS 300 075: "Terminal Equipment (TE); Processable data; File transfer".
- [98] ETS 300 092-1: "Integrated Services Digital Network (ISDN); Calling Line Identification Presentation (CLIP) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [99] ETS 300 093-1: "Integrated Services Digital Network (ISDN); Calling Line Identification Restriction (CLIR) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [100] ETS 300 122-1: "Integrated Services Digital Network (ISDN); Generic keypad protocol for the support of supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [101] ETS 300 196-1: "Integrated Services Digital Network (ISDN); Generic functional protocol for the support of supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [102] ETS 300 207-1: "Integrated Services Digital Network (ISDN); Diversion supplementary services; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [103] ETS 300 286-1: "Integrated Services Digital Network (ISDN); User-to-User Signalling (UUS) supplementary service; Digital Subscriber Signalling System No. one (DSS1) protocol; Part 1: Protocol specification".
- [104] ETS 300 402-1 (1995): "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Data link layer; Part 1: General aspects [ITU-T Recommendation Q.920 (1993), modified]".
- [105] ETS 300 402-2 (1995): "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Data link layer; Part 2: General protocol specification [ITU-T Recommendation Q.921 (1993), modified]".
- [106] ETS 300 403-2 (1995): "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 2: Specification and Description Language (SDL) diagrams".
- [107] ETS 300 485 (1995): "Integrated Services Digital Network (ISDN); Definition and usage of cause and location in Digital Subscriber Signalling System No. one (DSS1) and Signalling System No. 7 ISDN User Part (ISUP)".

NOTE: The references listed in this ETS are a continuation of publications referenced in ITU-T Recommendation Q.931.

## Definitions

For the purposes of this ETS, the following definitions apply, together with those given in the referenced publications:

**access channel; channel:** See CCITT Recommendation Q.9 [92], definition 0008.

**B-channel:** A 64 kbit/s channel accompanied by timing intended to carry a wide variety of user information streams. A B-channel does not carry signalling information for circuit switching by the ISDN.

**basic access:** See CCITT Recommendation Q.9 [92], definition 1551.

**basic service; basic telecommunication service:** See CCITT Recommendation Q.9 [92], definition 7018.

**call:** See CCITT Recommendation Q.9 [92], definition 2201.

**call control message:** A message as defined in subclause 3.1 of this ETS, which on sending or receipt causes a change of the call state at either the network or the user; and also PROGRESS and INFORMATION messages.

**call establishment; connection establishment:** See CCITT Recommendation Q.9 [92], definition 2207.

**call reference:** An identifier of a signalling transaction. The signalling transaction may either be bearer related, in which case the signalling transaction can be used to control that bearer, or bearer independent, in which case there is no bearer associated with that signalling transaction. All signalling transactions in this ETS are bearer related except those associated with the global call reference. Where there is only one bearer required for a call, then the call reference of the associated bearer related signalling transaction may be used to identify the call. In this ETS there is only one bearer for each call.

**call state:** A state as defined in subclause 2.1 of this ETS, for either the user side or network side as appropriate. A call state may exist for each call reference value (and at the network side for each additional responding CEI in the incoming call states).

**circuit switched; circuit switching:** See CCITT Recommendation Q.9 [92], definition 1125.

**comprehension required:** The requirement that the coding structure and meaning of an information element shall be understood by its receiver for the message to be processed. A specific range of values for information element identifiers is provided for those information elements for which comprehension is required.

**connection:** See CCITT Recommendation Q.9 [92], definition 0011. In this ETS, the term is taken to include a bearer and its associated control signalling.

**D-channel:** A channel primarily intended to carry signalling information for circuit switching by the ISDN.

**data link connection endpoint identifier:** Identifier used by a layer 3 protocol entity to address its peer entity.

**dummy call reference:** A call reference value of one octet length encoded as "0000 0000".

**en bloc receiving:** A procedure, used in call establishment of an incoming call, to enable the network to send called party number digits to the user in a single message.

**en bloc sending:** A procedure, used in call establishment of an outgoing call, to enable the user to send called party number digits to the network in a single message.

**global call reference:** A Call reference information element with a call reference value of zero. The length of the call reference value is encoded in the first octet of the information element. The Global call reference identifies all call references currently associated with the appropriate data link connection endpoint identifier.

**Incoming (call):** A call incoming to the user side of the interface.

**Integrated Services Digital Network (ISDN):** See ITU-T Recommendation I.112 [87], definition 308.

**interface:** See CCITT Recommendation Q.9 [92], definition 4001.

**Network Service Access Point (NSAP) address; OSI NSAP address:** See CCITT Recommendation Q.9 [92], definition 2083.

**network:** The DSS1 protocol entity at the network side of the user-network interface.

**on demand:** See ITU-T Recommendation I.140 [89], annex A, clause A.2.

**Open System Interconnection (OSI):** The concept of interconnecting systems in accordance with the architecture described in the Open System Interconnection Reference model (CCITT Recommendation X.200 [78]).

**outgoing (call):** A call outgoing from the user side of the interface.

**overlap receiving:** A procedure, used in call establishment of an incoming call, to enable the network to send called party number digits to the user in successive messages, as and when they are made available from the remote network.

**overlap sending:** A procedure, used in call establishment of an outgoing call, to enable the user to send called party number digits to the network in successive messages, as and when they are made available by the user.

**point-to-multipoint configuration; multipoint terminal configuration; multipoint configuration:** A terminal configuration in which there is more than one signalling entity.

**point-to-multipoint data link; broadcast data link:** A data link connection with the capability to support more than two connection endpoints.

**point-to-point configuration; single-point terminal configuration; single-point configuration:** A terminal configuration in which there is one signalling entity.

**point-to-point data link:** A data link on which a frame is directed to a single endpoint.

**primary rate access:** See CCITT Recommendation Q.9 [92], definition 1552.

**service; telecommunication service:** See ITU-T Recommendation I.112 [87], definition 201.

**supplementary service:** See ITU-T Recommendation I.210 [90], subclause 2.4.

**user:** The DSS1 protocol entity at the user side of the user-network interface.

iTeh STANDARD PREVIEW  
(standards.iteh.ai)

<https://standards.iteh.ai/catalog/standards/sist/68dc65ce-bf78-4910-b556-ecf483b617cc/sist-ets-300-403-1-1999>



**Throughout the text of ITU-T Recommendation Q.931**

Replace references throughout the text as shown below.

Reference in ITU-T Recommendation Q.931	Modified reference
ITU-T Recommendation I.430 [46]	ETS 300 012 [95]
ITU-T Recommendation I.431 [27]	ETS 300 011 [94]
ITU-T Recommendation Q.850 [67]	ETS 300 485 [107]
ITU-T Recommendation Q.920 [45]	ITU-T Recommendation Q.920 as modified by ETS 300 402-1 [104]
ITU-T Recommendation Q.921 [3]	ITU-T Recommendation Q.921 as modified by ETS 300 402-2 [105]
ITU-T Recommendation Q.931	ITU-T Recommendation Q.931 as modified by this ETS
ITU-T Recommendation Q.951 [85], section 3	ETS 300 092-1 [98]
ITU-T Recommendation Q.951 [85], section 4	ETS 300 093-1 [99]
ITU-T Recommendation Q.952 [86]	ETS 300 207-1 [102]
ITU-T Recommendation Q.953 [84], section 1	ETS 300 058-1 [96]
ITU-T Recommendation Q.957 [54], section 1	ETS 300 286-1 [103]

**Pages 1 and 2, clause 2**

Replace the second paragraph by:

In the paragraphs which follow, states are defined for circuit switched calls in subclause 2.1 (call states) and for the interface in subclause 2.4 (global call reference states).

Replace the three last paragraphs by:

A detailed description of the procedures for call control are given in clause 5 in terms of:

- a) the messages defined in clause 3 which are transferred across the user-network interface;
- b) the information processing and actions that take place at the user side and the network side. Detailed SDL diagrams for call control of circuit switched calls are contained in ETS 300 403-2 [106].

**Page 2, subclause 2.1, last paragraph**

Delete the last paragraph referring to annex D.

**Pages 4 to 6, subclause 2.2**

Delete subclause 2.2 and all of its subclauses. The basic packet-mode access connection control states for access to the ISDN virtual bearer service are defined in ETS 300 007 [93] and are outside the scope of this ETS.

**Pages 6 to 8, subclause 2.3**

Delete subclause 2.3 and all of its subclauses. It is outside the scope of this ETS.

**Page 8, subclause 2.4, last paragraph**

Replace the last paragraph by:

The global call reference shall be handled independently for incoming and outgoing sides, i.e. two independent state machines in an entity shall be referenced by the global call reference.

Page 8

ETS 300 403-1: November 1995

## Page 8, subclause 2.4.1.1, subclause heading

Replace the subclause heading by the following:

## 2.4.1.1 Restart Null (Rest 0)

## Page 9, subclause 2.4.2.1, subclause heading

Replace the subclause heading by the following:

## 2.4.2.1 Restart Null (Rest 0)

## Page 9, clause 3, note 1

Delete the last sentence "Annex D ... interfaces".

## Page 10, table 3-1/Q.931

Include SEGMENT as a message in the *Miscellaneous messages*: part of table 3-1/Q.931 with a reference to subclause 3.5.1.

## Page 11, table 3-2/Q.931

Modify table 3-2/Q.931 as follows:

Message type:	ALERTING			
Significance:	global			
Direction:	both			
		<b>iTeh STANDARD PREVIEW</b>		
		(standardsiteh.ai)		
		SIST ETS 300 403-1:1999		
		<a href="https://standardsiteh.ai/catalog/standards/sist/68dc63ce-bf79-456-483b617cc-b011-3-1-1999">https://standardsiteh.ai/catalog/standards/sist/68dc63ce-bf79-456-483b617cc-b011-3-1-1999</a>		
Information element	Reference	Direction	Type	Length
Protocol discriminator	4.2	both	M	1
Call reference	4.3	both	M	2 - 3
Message type	4.4	both	M	1
Bearer capability	4.5	both	O (note 1)	4 - 12
Channel identification	4.5	both (note 2) u → n	O (note 3)	2 - 34
Progress indicator	4.5	both	O (note 4)	2 - 4
Display	4.5	n → u	O (note 5)	2 - 82 (note 6)
Signal	4.5	n → u	O (note 7)	2 - 3
High layer compatibility	4.5	both	O (note 8)	2 - 5
NOTE 1:	The Bearer capability information element is included when the procedures of subclause 5.11 for bearer capability selection apply. When present, progress description #5 "interworking has occurred and has resulted in a telecommunication service change" shall also be present.			
NOTE 2:	<del>Included in the network-to-user direction for support of the procedures in annex D.</del>			
NOTE 3:	Mandatory if this message is the first message in response to SETUP, unless the user accepts the B-channel indicated in the SETUP message.			
NOTE 4:	Included in the event of interworking. Included in the network-to-user direction in connection with the provision of in-band information/patterns. Included in the user-to-network direction in connection with the provision of in-band information/patterns if annex K is implemented or in accordance with the procedures of subclause 5.11.3 and subclause 5.12.3.			
NOTE 5:	Included if the network provides information that can be presented to the user.			
NOTE 6:	The minimum length is 2 octets; the maximum length is <del>network dependent and is either 34 or 82 octets.</del>			
NOTE 7:	<del>Included if the network optionally provides information describing tones or alerting signals.</del>			
NOTE 8:	The High layer compatibility information element is included when the procedures of subclause 5.12 for high layer compatibility selection apply. When present, progress description #5, "interworking has occurred and has resulted in a telecommunication service change", shall also be present.			

## Page 12, table 3-3/Q.931

Modify table 3-3/Q.931 as follows:

Message type: CALL PROCEEDING				
Significance: local				
Direction: both				
Information element	Reference	Direction	Type	Length
Protocol discriminator	4.2	both	M	1
Call reference	4.3	both	M	2 - 3
Message type	4.4	both	M	1
Bearer capability	4.5	both	O (note 5)	4 - 12
Channel identification	4.5	both	O (note 1)	2 - 34
Progress indicator	4.5	both	O (note 2)	2 - 4
Display	4.5	n → u	O (note 3)	2 - 82 (note 4)
High layer compatibility	4.5	both	O (note 6)	2 - 5
NOTE 1:	Mandatory in the network-to-user direction if this message is the first message in response to SETUP. Mandatory in the user-to-network direction if this message is the first message in response to SETUP, unless the user accepts the B-channel indicated in the SETUP message.			
NOTE 2:	Included in the event of interworking. Included in the network-to-user direction in connection with the provision of in-band information/patterns. Included in the user-to-network direction in connection with the provision of in-band information/patterns if annex K is implemented or in accordance with the procedures of subclause 5.11.3 and subclause 5.12.3.			
NOTE 3:	Included if the network provides information that can be presented to the user.			
NOTE 4:	The minimum length is 2 octets; the maximum length is network dependent and is either 34 or 82 octets.			
NOTE 5:	The Bearer capability information element is included when the procedures of subclause 5.11 for bearer capability selection apply. When present, progress description #5 "interworking has occurred and has resulted in a telecommunication service change", shall also be present.			
NOTE 6:	The High layer compatibility information element is included when the procedures of subclause 5.12 for high layer compatibility selection apply. When present, progress description #5, "interworking has occurred and has resulted in a telecommunication service change", shall also be present.			

## Page 13, table 3-4/Q.931

Modify table 3-4/Q.931 as follows:

Message type:	CONNECT			
Significance:	global			
Direction:	both			
Information element	Reference	Direction	Type	Length
Protocol discriminator	4.2	both	M	1
Call reference	4.3	both	M	2 - 3
Message type	4.4	both	M	1
Bearer capability	4.5	both	O (note 1)	4 - 12
Channel identification	4.5	<del>both (note 2)</del> u → n	O (note 3)	2 - <del>34</del>
Progress indicator	4.5	both	O (note 4)	2 - 4
Display	4.5	n → u	O (note 5)	<del>2 - 82</del> (note 6)
Date/time	4.6	n → u	O (note 7)	2 - 7
<del>Signal</del>	<del>4.5</del>	<del>n → u</del>	<del>O (note 8)</del>	<del>2 - 3</del>
Low layer compatibility	4.5	both	O (note 9)	2 - <del>18 16</del>
High layer compatibility	4.5	both	O (note 10)	2 - 5
NOTE 1:	The Bearer capability information element is included when the procedures of subclause 5.11 for bearer capability selection apply.			
NOTE 2:	<del>Included in the network-to-user direction for support of the procedures in annex D.</del>			
NOTE 3:	Mandatory if this message is the first message in response to SETUP, unless the user accepts the B-channel indicated in the SETUP message.			
NOTE 4:	Included in the event of interworking or in connection with the provision of in-band information/patterns.			
NOTE 5:	Included if the network provides information that can be presented to the user.			
NOTE 6:	The minimum length is 2 octets; the maximum length is <del>network dependent and is either 34 or 82 octets.</del>			
NOTE 7:	As a network option, may be included to provide date and time information to the calling user for all calls or for calls involving specific telecommunication services.			
NOTE 8:	<del>Included if the network optionally provides information describing tones.</del>			
NOTE 9:	Included in the user-to-network direction when the answering user wants to return low layer compatibility information to the calling user. Included in the network-to-user direction if the user awarded the call included a Low layer compatibility information element in the CONNECT message. Optionally included for low layer compatibility negotiation, but some networks may not transport this information element to the calling user (see annex J).			
NOTE 10:	The High layer compatibility information element is included when the procedures of subclause 5.12 for high layer compatibility selection apply.			

## Page 14, table 3-5/Q.931

Modify table 3-5/Q.931 as follows:

Message type: CONNECT ACKNOWLEDGE				
Significance: global				
Direction: both				
Information element	Reference	Direction	Type	Length
Protocol discriminator	4.2	both	M	1
Call reference	4.3	both	M	2 - 3
Message type	4.4	both	M	1
Display	4.5	n → u	O (note 1)	2 - 82 (note 2)
Signal	4.5	<del>n → u</del>	<del>O (note 3)</del>	<del>2 - 3</del>
NOTE 1: Included if the network provides information that can be presented to the user.				
NOTE 2: The minimum length is 2 octets; the maximum length is <del>network dependent and is either 34 or 82 octets.</del>				
NOTE 3: <del>Included if the network optionally provides additional information describing tones.</del>				

## Page 15, table 3-6/Q.931

Modify table 3-6/Q.931 as follows:

Message type: DISCONNECT				
Significance: global				
Direction: both				
Information element	Reference	Direction	Type	Length
Protocol discriminator	4.2	both	M	1
Call reference	4.3	both	M	2 - 3
Message type	4.4	both	M	1
Cause	4.5	both	M	4 - 32
Progress indicator	4.5	(note 1) n → u	O (note 2)	2 - 4
Display	4.5	n → u	O (note 3)	2 - 82 (note 4)
Signal	4.5	<del>n → u</del>	<del>O (note 5)</del>	<del>2 - 3</del>
NOTE 1: Included in the network-to-user direction if the network provides in-band tones. <del>See annex D for usage in the user to network direction.</del>				
NOTE 2: Included by the network if in-band tones are provided. <del>However, the user may include the Progress Indicator and provide in-band tones (see annex D). In such cases the network will ignore this information element and will not convey the in-band tones.</del>				
NOTE 3: Included if the network provides information that can be presented to the user.				
NOTE 4: The minimum length is 2 octets; the maximum length is <del>network dependent and is either 34 or 82 octets.</del>				
NOTE 5: <del>Included if the network optionally provides additional information describing tones.</del>				

## Page 16, table 3-7/Q.931

Modify table 3-7/Q.931 as follows:

Message type:	INFORMATION			
Significance:	local (note 1)			
Direction:	both			
Information element	Reference	Direction	Type	Length
Protocol discriminator	4.2	both	M	1
Call reference	4.3	both	M	2 - 3 (note 2)
Message type	4.4	both	M	1
Sending complete	4.5	both	O (note 3)	1
Cause	4.5	n → u	O (note 9)	2 - 32
Display	4.5	n → u	O (note 4)	2 - 82 (note 5)
Keypad facility	4.5	u → n (note 10)	O (note 6)	2 - 34
Signal	4.5	n → u	O (note 7)	2 - 3
Called party number	4.5	u → n both	O (note 8)	2 - 23
NOTE 1:	This message has local significance, but may carry information of global significance.			
NOTE 2:	<del>This message may be set with the dummy call reference defined in § 4.3 when feature key management procedures are used (see Recommendation Q.932); otherwise the minimum length is 2 octets.</del>			
NOTE 3:	Included if the user optionally indicates completion of overlap sending to the network, or if the network optionally indicates completion of overlap receiving to the user.			
NOTE 4:	Included if the network provides information that can be presented to the user.			
NOTE 5:	The minimum length is 2 octets; the maximum length is network dependent and is either 34 or 82 octets.			
NOTE 6:	<del>Either The Called party number or the Keypad facility information element is included by the user to convey called party number information to the network during overlap sending. The Keypad facility information element may also be included if the user wants to convey other call establishment information to the network or to convey supplementary service information (see clause 7).</del>			
NOTE 7:	Included if the network optionally provides additional information describing tones.			
NOTE 8:	<del>Either The Called party number or the Keypad facility information element is included by the user to convey called party number information to the network during overlap sending. The Called party number information element is included by the network to transfer called party number information to the user during overlap receiving.</del>			
NOTE 9:	As a network option, may be used for stimulus operation of supplementary services.			
NOTE 10:	The use of the Keypad facility information element in the network-to-user direction to convey supplementary service information as part of the keypad protocol is a network option.			

## Page 17, table 3-8/Q.931

Modify table 3-8/Q.931 as follows:

Message type: NOTIFY				
Significance: access				
Direction: both				
Information element	Reference	Direction	Type	Length
Protocol discriminator	4.2	both	M	1
Call reference	4.3	both	M	2 - 3
Message type	4.4	both	M	1
Bearer capability	4.5	n → u	O (note 1)	2 - 12
Notification indicator	4.5	both	M	3
Display	4.5	n → u	O (note 2)	2 - 82 (note 3)
NOTE 1: Included by the network to indicate a change in bearer capability (see annex L).				
NOTE 2: Included if the network provides information that can be presented to the user.				
NOTE 3: The minimum length is 2 octets; the maximum length is network dependent and is either 34 or 82 octets.				

## Page 18, table 3-9/Q.931

Modify table 3-9/Q.931 as follows:

Message type: PROGRESS				
Significance: global				
Direction: both				
Information element	Reference	Direction	Type	Length
Protocol discriminator	4.2	both	M	1
Call reference	4.3	both	M	2 - 3
Message type	4.4	both	M	1
Bearer capability	4.5	both	O (note 1)	2 - 12
Cause	4.5	both	O (note 2)	2 - 32
Progress indicator	4.5	both	M	4
Display	4.5	n → u	O (note 3)	2 - 82 (note 4)
High layer compatibility	4.5	both	O (note 5)	2 - 5
NOTE 1: The Bearer capability information element is included when the procedures of subclause 5.11 for bearer capability selection apply. The Bearer capability information element indicates the bearer service now being used for the call.				
NOTE 2: Included by the user or the network to provide additional information concerning the provision of in-band information/patterns.				
NOTE 3: Included if the network provides information that can be presented to the user.				
NOTE 4: The minimum length is 2 octets; the maximum length is network dependent and is either 34 or 82 octets.				
NOTE 5: The High layer compatibility information element is included when the optional procedures of subclause 5.12 for high layer compatibility selection apply. The High layer compatibility information element indicates the high layer compatibility now being used for the call.				