
Sistemi oskrbe s plinom - Podzemna plinska skladišča - 4. del: Funkcionalna priporočila za skladiščenje v skalnih kavernah

Gas supply systems - Underground gas storage - Part 4: Functional recommendations for storage in rock caverns

Gasversorgungssysteme - Untertagespeicherung von Gas - Teil 4: Funktionale Empfehlungen für die Speicherung in Felskavernen

Systeme d'alimentation en gaz - Stockage souterrain de gaz - Partie 4: Recommandations fonctionnelles pour le stockage en cavités minées

<https://standards.iteh.ai/catalog/standards/sist/e4bda2cb-c762-4af3-ae1b-50094a0213c3/sist-en-1918-4-1999>

Ta slovenski standard je istoveten z: EN 1918-4:1998

ICS:

75.200	Oprema za skladiščenje nafte, naftnih proizvodov in zemeljskega plina	Petroleum products and natural gas handling equipment
--------	---	---

SIST EN 1918-4:1999**en**

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 1918-4:1999](#)

<https://standards.iteh.ai/catalog/standards/sist/e4bda2cb-c762-4af3-ae1b-50094a0213c3/sist-en-1918-4-1999>

EUROPEAN STANDARD

EN 1918-4

NORME EUROPÉENNE

EUROPÄISCHE NORM

February 1998

ICS 75.200

Descriptors: storage, natural gas, definitions, specifications, environmental protection, design, safety, geology, tests, operating requirements, maintenance, inspection

English version

Gas supply systems - Underground gas storage - Part 4: Functional recommendations for storage in rock caverns

Système d'alimentation en gaz - Stockage souterrain de gaz - Partie 4: Recommandations fonctionnelles pour le stockage en cavités minées

Gasversorgungssysteme - Untertagespeicherung von Gas - Teil 4: Funktionale Empfehlungen für die Speicherung in Felskavernen

This European Standard was approved by CEN on 22 January 1998.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

<https://standards.iteh.ai/catalog/standards/sist/e4bda2cb-c762-4a13-ac1b-50094a0213c3/sist-en-1918-4-1999>



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Central Secretariat: rue de Stassart, 36 B-1050 Brussels

Contents

	Page
Foreword	3
Introduction	3
1 Scope	6
2 Definitions	6
3 General	7
3.1 Long term containment of stored products	7
3.2 Environmental conservation	7
3.3 Safety	8
3.4 Monitoring	8
4 Design	8
4.1 Design principles	8
4.2 Geological exploration	9
4.3 Hydraulic containment	10
4.4 Determination of the maximum operating pressure	10
4.5 Caverns stability	11
4.6 Construction parameters	11
4.7 Lines connecting caverns to surface	11
4.8 Monitoring systems	12
4.9 Neighbouring subsurface activities	13
5 Construction	13
6 Testing and commissioning	14
6.1 Air pressure test	14
6.2 First filling	14
7 Operation, monitoring and maintenance	15
7.1 Operation principles	15
7.2 Monitoring	15
7.3 Maintenance	16

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 1918-4:1999

<https://standards.iteh.ai/catalog/standards/sist-en-1918-4-1999/50094a0213c3/sist-en-1918-4-1999>

Foreword

This European Standard has been prepared by Technical Committee CEN/TC 234 "Gas supply", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by August 1998, and conflicting national standards shall be withdrawn at the latest by August 1998.

It is Part 4 of a standard on underground gas storage which includes the five following Parts:

- Part 1 - Functional recommendations for storage in aquifers
- Part 2 - Functional recommendations for storage in oil and gas fields
- Part 3 - Functional recommendations for storage in solution mined salt cavities
- Part 4 - Functional recommendations for storage in rock caverns
- Part 5 - Functional recommendations for surface facilities

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

[SIST EN 1918-4:1999](https://standards.iteh.ai/catalog/standards/sist/e4bda2cb-c762-4af3-ae1b-50094a0213c3/sist-en-1918-4-1999)

Introduction
<https://standards.iteh.ai/catalog/standards/sist/e4bda2cb-c762-4af3-ae1b-50094a0213c3/sist-en-1918-4-1999>

Use of mined cavern storage.

Unlined mined caverns technology is widely used in the field of underground storage for:

- liquids (crude oil, distillates, etc.);
- liquefied petroleum gas (LPG).

R & D projects are currently under way to extend the field of application of this technology to underground storage for natural gas. The following areas are being investigated:

- compressed natural gas (CNG) in lined or unlined rock caverns;
- liquefied natural gas (LNG) in lined or unlined rock caverns.

Underground storage in mined caverns is an attractive alternative to underground storage in salt leached caverns especially where the local geological setting does not contain salt or where the salt does not display suitable characteristics for solution mining.

The technology, provided it is correctly implemented, is applicable to the following geological conditions:

- hard igneous or metamorphic rocks such as granite, gneiss, andesites or shales;
- sedimentary rocks such as limestones, cemented sandstones, quartzites, chalk or shales;
- marls.

The main prerequisites for unlined cavern storage are the presence of a sufficient natural water head above the caverns to ensure the hydrodynamic containment of the product, and a rockmass quality sufficient to ensure the long term stability of the excavation with, if needed, a structural reinforcement.

Underground storage in mined caverns is a safe way to create important reserves of LPG in the immediate vicinity of producing, importing or consuming centres such as:

- refineries, import or export terminals;
- petrochemical complexes for which LPG constitutes a feedstock;
- local storage for seasonal peak shaving connected with bottling plants and aimed at a local domestic market;
- regional feedstock for resale (distribution by truck, railway or boat).

This Part of EN 1918 focuses on underground storage in unlined mined caverns for LPG. It does not cover refrigerated gas storage.

Technical description

The three key parameters governing the satisfactory operation of an underground storage facility in a mined cavern include:

- long term stability;
- leaktightness and absence of environmental impact;
- absence of impact on product quality during storage time. The product stored is delivered after the storage period in a state compatible with the users' requirements (with or without implementation of surface treatment).

Very generally, a mined cavern storage facility comprises one or several galleries, excavated from an access shaft or ramp and sited deep enough to ensure the hydraulic containment of the product to be stored.

The access works are first used for the excavation of the caverns and may consist of:

- an inclined tunnel;
- one or several shafts with extraction equipment;
- a combination of one or several shafts and an inclined tunnel.

Before the storage facility is put into operation, the caverns are isolated from the access shaft and/or ramp by concrete plugs located near the cavern entrance. The shaft and/or ramp is then flooded with water.

The storage cavern(s) are made up of main galleries of variable section, according to rock type and depth. The gallery length depends upon the arrangement of galleries, often in parallel, and the required storage capacity.

Connection galleries, generally of smaller section, may link the main galleries together. They allow circulation of personnel, materials and equipment, and ventilation during the construction phase. They allow circulation of water and stored product, at the various levels of excavation, during the operation phase. Connection galleries contribute to the storage capacity.

The most commonly used excavation method in hard rock is drilling and blasting. Alternative methods include roadheaders or tunnelling machines. The choice of method is determined mainly by the rockmass properties and the size of the excavations but also by the cost and availability of equipment.

The underground storage space is connected to the surface by a series of lines accommodated in one or more operating shafts or in operating wells, drilled, cased and cemented. They include:

- inlet line(s);
- outlet line(s) fitted with submersible pump(s) for product delivery;
- seepage water line(s) and pump(s);
- instrumentation line(s);
- vent line(s).

When installed in a shaft, the operating pipes are anchored in a concrete sealing plug located immediately above the cavern crown. After pipe installation, the shaft is flooded with water for the operation phase.

In some cases, horizontal and/or vertical water curtains, may be provided to enhance the permanent groundwater flow towards the storage caverns.

A horizontal water curtain may consist of a gallery of small section, generally located above the storage caverns, from which boreholes are drilled.

A vertical water curtain consists of vertical or subvertical boreholes drilled from the surface, or from a purpose-designed gallery. The vertical water curtain is mainly used to avoid hydrogeological interference between two or more storage caverns, and allow independent operation of each one.

Figure 1 illustrates a mined rock cavern cross-section.

Working principle

SIST EN 1918-4:1999

<https://standards.iteh.ai/catalog/standards/sist/e4bda2cb-c762-4af3-ae1b-50094a0213c3/sist-en-1918-4-1999>

The hydraulic containment principle for LPG storage in unlined underground caverns is that the product is contained by the groundwater pressure prevailing in the adjacent rockmass. The cavern is located at such a depth that the water naturally present in the surrounding rock flows everywhere towards the cavern preventing the stored product from migrating. The favourable effects of the threshold displacement pressure are considered as an additional safety term.

The product, lighter than and hardly miscible with water, is in this way hydraulically contained within the storage space.

The water which collects in the cavern during operation is removed by pumping, treated and disposed of or recycled.

Furthermore, depending on the required commercial product specifications, coalescers and/or dryers are implemented at the surface if necessary for the product during withdrawal. Stripping units are implemented before disposal or recycling if necessary for the seepage water.

1 Scope

This standard specifies procedures and practices which are safe and environmentally acceptable.

It covers the functional recommendations for design, construction, testing, commissioning, operation and maintenance of underground gas storage facilities in rock caverns up to and including the top flanges of the casings. It does not cover refrigerated gas storage.

The necessary surface facilities for an underground gas storage are described in EN 1918-5.

In this context "gas" is any gaseous fuel which is in a gaseous state at a temperature of 15 °C under a pressure of 1 bar.

This European Standard specifies common basic principles for gas supply systems. Users of this European Standard should be aware that more detailed national standards and/or codes of practice may exist in the CEN member countries.

This European Standard is intended to be applied in association with these national standards and/or codes of practice and does not replace them.

This standard is not intended to be applied retrospectively to existing facilities.

iTeh STANDARD PREVIEW
(standards.iteh.ai)

2 Definitions

For the purpose of this standard, the following definitions apply:

2.1 casing (for a rock cavern)

Pipe or set of pipes that can be screwed or welded together to form a string surrounding the tubing connecting the cavern to the surface.

2.2 cementing

Operation whereby a cement slurry is pumped and circulated down a well through the casing and then upwards into the annular space between the casing and the open or cased hole.

2.3 containment

Capability of a cavern to prevent migration of stored hydrocarbons.

2.4 drilling

All technical activities connected with the construction of a well.

2.5 exploration

All technical activities connected with the investigation of a geological site.

2.6 logging

Measurement of any physical parameter versus depth in a well.

2.7 maximum operating pressure (MOP) (for a rock cavern)

Maximum value of the pressure of any fluid contained in a cavern which can be accepted in normal operation and maintenance.

NOTE 1: It is defined at a reference point which is in general the roof of the cavern.

NOTE 2: Its value is defined to ensure the containment of the product.

2.8 modelling

Generating the image of a structure from the information gathered.

2.9 numerical simulation

Computer simulation of a system.

EXAMPLES: stability analysis, hydraulic flow pattern around an excavation.

2.10 permeability

Capacity of a rock to allow fluids to flow through its pores.

NOTE: It is measured experimentally and is usually expressed in darcy.

2.11 porosity

Volume of the pore space (voids) within a formation expressed as a percentage of the total volume of the material containing the pores.

2.12 saturation

Percentage of pore space occupied by fluid in the material .

2.13 subsurface safety valve

Valve installed in tubing or casing beneath the wellhead for the purpose of stopping the flow of gas in emergency.

2.14 tubing

Pipe or set of pipes that can be screwed, welded or flanged together to form a string, through which fluids are injected or withdrawn.

<https://standards.iteh.ai/catalog/standards/sist/e4bda2cb-c762-4af3-ae1b-50094a0213c3/sist-en-1918-4-1999>

3 General

This clause gives general requirements for underground gas storage. More specific requirements for underground gas storage in solution-mined salt cavities are given in clauses 4, 5, 6, and 7.

3.1 Long-term containment of stored products

The storage facility shall be designed to ensure the continuing long-term containment of the stored products.

This presupposes:

- adequate prior knowledge of the geological formation in which the storage is to be developed and of its geological environment;
- acquisition of all relevant information needed for specifying parameter limits for construction and operation;
- demonstration that the storage is capable of ensuring long-term containment of the stored products through its hydraulic and mechanical integrity.

The construction facility shall be constructed and operated so as to maintain the integrity of the containment.

No other installation or activity shall affect the integrity of containment.