



Designation: F3082/F3082M – 22

# Standard Specification for Weights and Centers of Gravity of Aircraft<sup>1</sup>

This standard is issued under the fixed designation F3082/F3082M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

## 1. Scope

1.1 This specification establishes the airworthiness design standards associated with aeroplane weight and center of gravity.

1.2 The term “aeroplane” is utilized in this specification as it was originally conceived for normal category fixed wing aircraft with a maximum certificated weight of 19 000 lb or less and a passenger seating configuration up to 19 as defined in the Rules. However, these standards may be more broadly applicable and their usage should not be unnecessarily limited.

1.3 The applicant for a design approval shall seek the individual guidance of their respective civil aviation authority (CAA) body concerning the use of this specification as part of a certification plan. For information on which CAA regulatory bodies have accepted this specification (in whole or in part) as a means of compliance to their small aircraft airworthiness regulations (hereinafter referred to as “the Rules”), refer to ASTM Committee F44 webpage ([www.astm.org/COMMITTEE/F44.htm](http://www.astm.org/COMMITTEE/F44.htm)), which includes CAA website links.

1.4 *Units*—The values stated in either SI units or inch-pound units are to be regarded separately as standard. The values stated in each system may not be exact equivalents; therefore, each system shall be used independently of the other. Combining values from the two systems may result in non-conformance with the standard.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.6 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the*

*Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

## 2. Referenced Documents

2.1 *ASTM Standards:*<sup>2</sup>

F3060 [Terminology for Aircraft](#)

F3063/F3063M [Specification for Aircraft Fuel Storage and Delivery](#)

## 3. Terminology

3.1 See Terminology F3060 for definitions and abbreviations.

## 4. Weight and CG Limits

4.1 *Load Distribution Limits*—The applicant must determine limits for weights and centers of gravity that provide for the safe operation of the airplane.

4.1.1 Ranges of weights and centers of gravity within which the aeroplane may be safely operated shall be established. If a weight and center of gravity combination is allowable only within certain lateral load distribution limits that could be inadvertently exceeded, these limits shall be established for the corresponding weight and center of gravity combinations.

4.1.2 The load distribution limits shall not exceed any of the following:

(1) The selected limits,

(2) The limits at which the structure is proven, or

(3) The limits at which compliance with each applicable flight requirement is shown.

4.2 *Removable Ballast*—Removable ballast may be used in showing compliance with the flight requirements if:

4.2.1 The place for carrying ballast is properly designed and easily accessible to enable, during pre-flight inspection, that the ballast is properly installed.

<sup>1</sup> This specification is under the jurisdiction of ASTM Committee F44 on General Aviation Aircraft and is the direct responsibility of Subcommittee F44.20 on Flight.

Current edition approved Aug. 1, 2022. Published August 2022. Originally approved in 2016. Last previous edition approved in 2017 as F3082/F3082M – 17. DOI: 10.1520/F3082\_F3082M-22.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

4.2.2 Instructions are included in the aeroplane flight manual, approved manual material, or markings and placards for the proper placement of the removable ballast under each loading condition for which removable ballast is necessary.

#### 4.3 *Weight Limits:*

4.3.1 *Maximum Weight*—The maximum weight is the highest weight at which compliance with each applicable requirement (other than those complied with at the design landing weight) is shown. The maximum weight shall be established so that it is:

4.3.1.1 Not more than the least of:

- (1) The highest weight selected by the applicant;
- (2) The design maximum weight, which is the highest weight at which compliance with each applicable structural loading condition (other than those complied with at the design landing weight) is shown;
- (3) The highest weight at which compliance with each applicable flight requirement is shown, and

4.3.1.2 Not less than the weight with:

(1) Each seat occupied, assuming a weight of 77 kg [170 lb] for each occupant or 86 kg [190 lb] for Level 1 aeroplanes with a stall speed of 45 kts or lower and for aeroplanes approved for aerobatics except that seats other than pilot seats may be placarded for a lesser weight, and

(a) Oil at full capacity,

(b) At least enough fuel for maximum continuous power operation for:

- (1) 30 min for day-VFR-approved aeroplanes, and
- (2) 45 min for night-VFR- and IFR-approved aeroplanes,

or

(3) Level 1 aeroplanes with a stall speed of 45 kts or less enough fuel for 1 h of operation, or

(2) The required minimum crew, and fuel and oil to full capacity.

4.3.2 *Minimum Weight*—The minimum weight (the lowest weight at which compliance with each applicable requirement is shown) shall be established so that it is not more than the sum of:

4.3.2.1 The empty weight determined under Section 6,

4.3.2.2 The weight of the required minimum crew (assuming a weight of 77 kg [170 lb] for each crewmember), or for Level 1 aeroplanes with a stall speed of 45 kts or less a weight of 55 kg [120 lb], and

4.3.2.3 For turbojet powered aeroplanes, 5 % of the total fuel capacity of that particular fuel tank arrangement under investigation.

**TABLE 1 General Tolerances**

| Item                              | Tolerance         |
|-----------------------------------|-------------------|
| Weight                            | +5 %, –10 %       |
| Critical items affected by weight | +5 %, –1 %        |
| C.G.                              | ±7 % total travel |

4.3.2.4 For other aeroplanes, the weight of the fuel necessary for 30 min of operation at maximum continuous power.

## 5. Requirements Compliance

5.1 Each of the Flight Standards shall be met at critical combinations of weight and center of gravity within the range of loading conditions for which certification is requested. This shall be shown by:

5.1.1 Tests upon an aeroplane of the type for which certification is requested or by calculations based on, and equal in accuracy to, the results of testing, and

5.1.2 Systematic investigation of each probable combination of weight and center of gravity, if compliance cannot be reasonably inferred from combinations investigated.

5.2 The general tolerances in Table 1 are allowed during flight testing. However, greater tolerances may be allowed in particular tests, if properly justified.

## 6. Empty Weight and CG Condition

6.1 The condition of the aeroplane at the time of determining empty weight shall be one that is well defined and can be easily repeated.

6.2 *Empty Weight and Corresponding Center of Gravity:*

6.2.1 The empty weight and corresponding center of gravity shall be determined by weighing the aeroplane with:

6.2.1.1 Fixed ballast,

6.2.1.2 Unusable fuel determined under Specification F3063/F3063M, and

6.2.1.3 Full operating fluids including:

(1) Oil,

(2) Hydraulic fluid, and

(3) Other fluids required for normal operation of aeroplane systems, except potable water, lavatory precharge water, and water intended for injection in the engines.

## 7. Keywords

7.1 aircraft; airworthiness; design; flight; general aviation; operational limitations; performance

**ANNEX**
**(Mandatory Information)**
**A1. CORRELATION OF STANDARD – CONTENT AND THE RULES**
**TABLE A1.1 Correlation Sorted by Standard**


| Spec.        | Rev | Section | Subpart | 14 CFR 23  | Subpart | CS-23      |
|--------------|-----|---------|---------|------------|---------|------------|
| F3082/F3082M | 22  | 4       | B       | 23.2100(a) | B       | 23.2100(a) |
| F3082/F3082M | 22  | 5       | B       | 23.2100(b) | B       | 23.2100(b) |
| F3082/F3082M | 22  | 6       | B       | 23.2100(C) | B       | 23.2100(c) |

**TABLE A1.2 Correlation Sorted by FAA 14 CFR 23**

| 14 CFR 23  | Spec.        | Rev | Section |
|------------|--------------|-----|---------|
| 23.2100(a) | F3082/F3082M | 22  | 4       |
| 23.2100(b) | F3082/F3082M | 22  | 5       |
| 23.2100(C) | F3082/F3082M | 22  | 6       |

**TABLE A1.3 Correlation Sorted by EASA CS-23**

| CS-23      | Spec.        | Rev | Section |
|------------|--------------|-----|---------|
| 23.2100(a) | F3082/F3082M | 22  | 4       |
| 23.2100(b) | F3082/F3082M | 22  | 5       |
| 23.2100(C) | F3082/F3082M | 22  | 6       |

  
[\(https://standards.iteh.ai/\)](https://standards.iteh.ai/)  
 Document Preview  
 (Nonmandatory Information)

**XI. REVISIONS**

<https://standards.iteh.ai/catalog/standards/sist/10764fab-5cad-4b55-ae1e-686463038f46/astm-f3082-f3082m-22>

| Section | Change   | Reason for Change   |
|---------|--|---|
| General | This change is to harmonize the specification sections with the Performance Based Rules. There are no changes to the technical content. Sections have been moved to more closely align with the Rules. | Reduce confusion about what sections are applicable to the rule paragraphs.   |
| 4.1     | Subsection 4.1 was Subsection 4.2.   | To include Load Distribution Limits requirements in Section 4 to align with rule paragraph (a).                               |
| 4.2     | Subsection 4.2 was Subsection 4.5.   | Moved Subsection 4.5 to Subsection 4.2 to make it part of the compliance showing requirements of rule paragraph (a).          |
| 4.3.2.1 | Revised reference to Section 6; was referenced to Subsection 4.4.  | To change the reference to agree with section re-numbering.   |
| 5       | Added new Section 5.   | Added new Section 5 to align with rule paragraph (b) requirements.  |
| 5.1.2   | Subsection 5.1.2 was Subsection 4.1.2.   | Moved Subsection 4.1.2 to Subsection 5.1.2 to make it part of the compliance showing requirements of rule paragraph (b).      |
| 5.2     | Moved Table 1 from 4.2.1 to 5.2.   | Moved table to make it a part of Subsection 5.2 on tolerances.  |
| 6       | Added new Section 6 using title from Subsection 4.4.   | Added new Section 6 to align with rule paragraph (c).   |
| 6.1     | Subsection 6.1 was Subsection 4.4.2.   | Moved Subsection 4.4.2 to Subsection 6.1 to make it part of Determination of Empty Wt and CG requirements.                    |
| 6.2     | Subsection 6.2 was Subsection 4.4.1 content.   | Moved Subsection 4.4.1 content to Subsection 6.2 to make it part of section 6, Determination of Empty Wt and CG requirements. |
| 7       | Section 7 was Section 5.   | Renumbered Section 5 to Section 7 to accommodate addition of new Sections 5 and 6 in previous sections.                       |