# INTERNATIONAL STANDARD

# IEC 60966-2-6

Second edition 2003-03

Radio frequency and coaxial cable assemblies -

# Part 2-6:

Detail specification for cable assemblies for radio and TV receivers - Frequency range 0 to 3 000 MHz, IEC 61169-24 connectors

Ensemble de cordons coaxiaux et de cordons pour fréquences radioélectriques –

Partie 2-6:

Spécification particulière pour cordons de connexion de récepteurs TV ou radio – Bande de fréquences 60966-2-6-2003 de 0 à 3 000 MHz, connecteurs CEI 61169-24



## **Publication numbering**

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

#### Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

## Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

- IEC Web Site (<u>www.iec.ch</u>)
- Catalogue of IEC publications

The on-line catalogue on the EC web site (http://www.iec.ch/searchpub/cur fut.htm) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

IEC Just Rublished

This summary of recently issued publications (<a href="http://www.iec.ch/online\_news/ustp.b/jpcentry.htm">http://www.iec.ch/online\_news/ustp.b/jpcentry.htm</a>) is also available by email. Please contact the Customer Service Centre (see below) for further information.

Customer Service Centre

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

Email: <u>custserv@iec.ch</u> Tel: +41 22 919 02 11 Fax: +41 22 919 03 00

# INTERNATIONAL STANDARD

# IEC 60966-2-6

Second edition 2003-03

Radio frequency and coaxial cable assemblies -

# Part 2-6:

Detail specification for cable assemblies for radio and TV receivers - Frequency range 0 to 3 000 MHz, IEC 61169-24 connectors

Ensemble de cordons coaxiaux et de cordons pour fréquences radioélectriques —

Partie 2-6:

Spécification particulière pour cordons de connexion de récepteurs TV ou radio – Bande de fréquences 60966-2-6-2003 de 0 à 3 000 MHz, connecteurs CEI 60169-24

© IEC 2003 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



PRICE CODE

F

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

### RADIO FREQUENCY AND COAXIAL CABLE ASSEMBLIES -

# Part 2- 6: Detail specification for cable assemblies for radio and TV receivers - Frequency range 0 to 3 000 MHz, IEC 61169-24 connectors

#### **FOREWORD**

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports of guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. The IEO shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60966-2-6 has been prepared by subcommittee 46A: Coaxial cables, of IEC technical committee 46: Cables, wires, waveguides, r.f. connectors, r.f. and microwave passive components and accessories.

This second edition cancels and replaces the first edition published in 1998, of which it constitutes a technical revision.

The text of this standard is based on the following documents:

FDIS	Report on voting
46A/510/FDIS	46A/543/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until 2006. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this standard may be issued at a later date.

### INTRODUCTION

This detail specification applies to flexible coaxial cables described in IEC 60096-2. It relates to cable assemblies for radio and TV receivers, and in particular to the cable subfamily F.

This detail specification should be used together with the following IEC publications:

IEC 60966-1:1999, Radio frequency and coaxial cable assemblies – Part 1: Generic specification – General requirements and test methods

IEC 60966-2-1:1991, Radio frequency and coaxial cable assemblies – Part 2-1: Sectional specification for flexible coaxial cable assemblies

IEC 60966-2-2:1992, Radio frequency and coaxial cable assemblies — Part 2-2: Blank detail specification for flexible coaxial cable assemblies

IEC 61169-24:2001, Radio frequency connectors – Part 24: Sectional specification – Radio frequency coaxial connectors with screw coupling, typically for use in 75 ohm cable distribution systems (type F)

IEC 60410:1973, Sampling plans and procedures for inspection by attributes

IEC 61022:1989, Interconnection of radio and TV receivers to feeder system outlets

IEC 61196-1:1995, Radio-frequency cables — Part 1: Generic specification — General, definitions, requirements and test methods

(https://standards.iteh.ai)

Decument Preview

https://standards.iteh.ai

by stand ds/200451cfb-6596-4350-be84-686f711fe5eb/iec-60966-2-6-2003

	Prepared by	[2] Document No. 60966-2-6	
	IEC SC 46A	Issue: Second issue	
		Date: 21/03/03	
[3]	Available from:	[4] Generic specification: IEC 60966-1	
	IEC 3 rue de Varembé	Sectional specification: IEC 60966-2-1	
Ge	Genève Suisse	Blank detail specification: IEC 60966-2-2	
[5]	Additional references:	:	
	Detail specifi	ication for coaxial cable assemblies for radio and TV received	rs
		L	
	'		
161		IEC 727/03	
[6]	Characteristic impedan		
[6] [7]	Characteristic impedance		
[7]	(h	nce: 75 Ω [8] Frequency range: 0 to 3 000 MHz	
	Characteristic impedant Weight: 40 g/m + 50 g (	nce: 75 Ω [8] Frequency range: 0 to 3 000 MHz	
[7]	(h	rce: 75 Ω [8] Frequency range: 0 to 3 000 MHz  (typically) [10] Minimum inside radius:	
[7]	(h	(typically)  [10] Minimum inside radius:  for static bending 25 mm  for dynamic bending 75 mm	
[7] [9] [11] [13]	Weight: 40 g/m + 50 g (	(typically)  [10] Minimum inside radius:  for static bending 25 mm  for dynamic bending 75 mm	-60966-2-6
[9] [11] [13] Conn	Weight: 40 g/m + 50 g (  Climatic category: 40/7)  ector type:	(typically)  [10] Minimum inside radius: for static bending 25 mm for dynamic bending 75 mm  [12] Applicable test group: Ba, Eb, Eh, Ee, Mn  a IEC 61169-24 (F) Straight plug	.60966-2 <b>-</b> 6
[9] [11] [13] Conn	Weight: 40 g/m + 50 g ( Climatic category: 40/7	(typically)  [10] Minimum inside radius:  for static bending 25 mm  for dynamic bending 75 mm  [12] Applicable test group: Ba, Eb, Eh, Ee, Mn  a  IEC 61169-24 (F)  Straight plug  IEC 61196-6 (under development)	60966-2-6
[9] [11] [13] Conn	Weight: 40 g/m + 50 g (  Climatic category: 40/7)  ector type:	(typically)  [10] Minimum inside radius: for static bending 25 mm for dynamic bending 75 mm  [12] Applicable test group: Ba, Eb, Eh, Ee, Mn  a IEC 61169-24 (F) Straight plug	-60966-2-6
[7] [9] [11] [13] Conn	Weight: 40 g/m + 50 g (  Climatic category: 40/7/  ector type:	(typically)  [10] Minimum inside radius: for static bending 25 mm for dynamic bending 75 mm  [12] Applicable test group: Ba, Eb, Eh, Ee, Mn  a IEC 61169-24 (F) Straight plug  IEC 61196-6 (under development) 75 yy	.60966-2-6
[7] [9] [11] [13] Conn Cable	Weight: 40 g/m + 50 g (  Climatic category: 40/7)  ector type:	(typically)  [10] Minimum inside radius: for static bending 25 mm for dynamic bending 75 mm  [12] Applicable test group: Ba, Eb, Eh, Ee, Mn  a  IEC 61169-24 (F) Straight plug  IEC 61196-6 (under development) 75 yy or equivalent	.60966-2-6
[7] [9] [11] [13] Conn Cable	Weight: 40 g/m + 50 g (  Climatic category: 40/7)  ector type:	(typically)  [10] Minimum inside radius: for static bending 25 mm for dynamic bending 75 mm  [12] Applicable test group: Ba, Eb, Eh, Ee, Mn  a IEC 61169-24 (F) Straight plug  IEC 61196-6 (under development) 75 yy or equivalent  Optional	·60966-2-6