



Designation: **E394 – 15 E394 – 22**

Standard Test Method for Iron in Trace Quantities Using the 1,10-Phenanthroline Method¹

This standard is issued under the fixed designation E394; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reappraisal. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reappraisal.

1. Scope*

1.1 This test method covers the determination of trace concentrations of iron in the range from 1 to 100 $\mu\text{g}/\mu\text{g/g}$ in a wide variety of products.

~~1.2 This test method is intended to be general for the final steps in the determination of iron and does not include procedures for sample preparation.~~

1.2 This test method is applicable to samples whose solutions have a pH less than 2. It is assumed that the pH is adjusted to In determining the conformance of the test results using this method to applicable specifications; results shall be rounded off in accordance with the rounding-off method of Practice E29 within this range in the sample preparation.

1.4 Review the current Safety Data Sheets (SDS) for detailed information concerning toxicity, first-aid procedures, handling, and safety precautions.

1.3 The values given stated in SI units are the standard. Values in parentheses are for information only to be regarded as standard. No other units of measurement are included in this standard.

~~1.6 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.~~

1.4 Consult current OSHA regulations, suppliers' Safety Data Sheets, and local regulations for all materials used in this specification.

1.5 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*²

¹ This test method is under the jurisdiction of ASTM Committee D16 on Aromatic, Industrial, Specialty and Related Chemicals and is the direct responsibility of Subcommittee D16.04 on Instrumental Analysis.

Current edition approved Nov. 1, 2015; Sept. 1, 2022. Published January 2016; September 2022. Originally approved in 1970. Last previous edition approved in 2009; 2015 as E394 – 09; E394 – 15. DOI: 10.1520/E0394-15.10.1520/E0394-22.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

*A Summary of Changes section appears at the end of this standard

[D1193 Specification for Reagent Water](#)

[D6809 Guide for Quality Control and Quality Assurance Procedures for Aromatic Hydrocarbons and Related Materials](#)

[E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications](#)

[E60 Practice for Analysis of Metals, Ores, and Related Materials by Spectrophotometry](#)

[E180 Practice for Determining the Precision of ASTM Methods for Analysis and Testing of Industrial and Specialty Chemicals](#)
(Withdrawn 2009)³

~~[E200 Practice for Preparation, Standardization, and Storage of Standard and Reagent Solutions for Chemical Analysis](#)~~

[E275 Practice for Describing and Measuring Performance of Ultraviolet and Visible Spectrophotometers](#)

[E300 Practice for Sampling Industrial Chemicals](#)

3. Summary of Test Method

3.1 This test method is based upon a photometric determination of the 1,10-phenanthroline complex with the iron(II) ion. The sample is dissolved in a suitable solvent and the iron is reduced to the divalent state by the addition of hydroxylamine hydrochloride. The color is then developed, by the addition of 1,10-phenanthroline. After a short reaction period, the absorbance of the solution is measured at approximately ~~510 nm~~ 510 nm using a suitable photometer. The absorbance of the solution, once the color is developed, is stable for at least several months.

4. Significance and Use

4.1 This test method is suitable for determining trace concentrations of iron in a wide variety of products, provided that appropriate sample preparation has rendered the iron and sample matrix soluble in water or other suitable solvent (see [10.1](#) and [Note 54](#)).

4.2 This test method assumes that the amount of color developed is proportional to the amount of iron in the test solution. The calibration curve is linear over the specified range. Possible interferences are described in [Section 5](#).

5. Interferences

5.1 Fortune and Mellon⁴ have made a comprehensive study of the interferences of various inorganic ions in this determination. [Table 1](#) and [Table 2](#), taken from their report, show the effects of various cations and anions on the determination of 2.0 µg/g (ppm) iron. If the maximum level of 500 µg/g (ppm) does not interfere, it is very likely that the ion will not interfere in any quantity. The data were obtained under slightly different conditions than those specified in the present test method, but the interferences should be similar. For a more detailed description of interferences, the original literature should be consulted.

5.2 Aldehydes, ketones, and oxidizing agents interfere by consuming the hydroxylamine hydrochloride added as a reducing agent.

6. Apparatus

6.1 *Photometer*, capable of measuring light absorption at 510 nm and holding a 5-cm or 1-cm cell. Check the performance of the photometer at regular intervals according to the guidelines given in [Practice E275](#) and the manufacturer's manual.

NOTE 1—If a filter photometer is used, a narrow band filter having its maximum transmission at 480 to 520 nm should be used. A discussion of photometers and photometric practice is given in [Practice E60](#).

6.2 *Absorption Cells*, 5-cm or 1-cm light path.

7. Reagents and Materials

7.1 *Purity of Reagents*—Unless otherwise indicated, it is intended that all reagents shall conform to the specifications of the Committee on Analytical Reagents of the American Chemical Society, where such specifications are available.⁵ Other grades may be used, provided it is first ascertained that the reagent is of sufficiently high purity to permit its use without lessening the accuracy of the determination.

³ The last approved version of this historical standard is referenced on www.astm.org.

⁴ Fortune, W. B., and Mellon, M. G., *Industrial and Engineering Chemistry, Analytical Edition*, IENAA Vol 10, 1938, pp. 60–64.

⁵ *Reagent Chemicals, American Chemical Society Specifications*; *ACS Reagent Chemicals, Specifications and Procedures for Reagents and Standard-Grade Reference Materials*, American Chemical Society, Washington, DC. For suggestions on the testing of reagents not listed by the American Chemical Society, see *Analar Standards for Laboratory Chemicals*, BDH Ltd., Poole, Dorset, U.K., and the *United States Pharmacopeia and National Formulary*, U.S. Pharmacopeial Convention, Inc. (USP); (USPC), Rockville, MD.

TABLE 1 Effect of Cations on the Determination of 2 µg/g (ppm) Iron

Ion	Added As	Maximum Added Without Interference, µg/g (ppm)	Applicable pH Range
Aluminum	AlCl ₃	500	2.0–3.0
Ammonium	NH ₄ Cl	500	2.0–9.0
Antimony	SbCl ₃	30	3.0–9.0
Arsenic	As ₂ O ₅	500	3.0–9.0
Arsenic	As ₂ O ₃	500	3.0–9.0
Barium	BaCl ₂	500	3.0–9.0
Beryllium	Be(NO ₃) ₂	500	3.0–5.5
Bismuth	Bi(NO ₃) ₃	... ^A	... ^A
Cadmium	Cd(NO ₃) ₂	50	3.0–9.0
Calcium	Ca(NO ₃) ₂	500	2.0–9.0
Chromium	Cr ₂ (SO ₄) ₃	20	2.0–9.0
Cobalt	Co(NO ₃) ₂	10	3.0–5.0
Copper	Cu(NO ₃) ₂	10	2.5–4.0
Lead	Pb(C ₂ H ₃ O ₂) ₂	500	2.0–9.0
Lithium	LiCl	500	2.0–9.0
Magnesium	Mg(NO ₃) ₂	500	2.0–9.0
Manganese	MnSO ₄	500	2.0–9.0
Mercury	HgCl ₂	1	2.0–9.0
Mercury	Hg ₂ (NO ₃) ₂	10	3.2–9.0
Molybdenum	(NH ₄) ₆ Mo ₇ O ₂₄	100	5.5–9.0
Nickel	Ni(NO ₃) ₂	2	2.5–9.0
Potassium	KCl	1000	2.0–9.0
Silver	AgNO ₃	... ^A	... ^A
Sodium	NaCl	1000	2.0–9.0
Strontium	Sr(NO ₃) ₂	500	2.0–9.0
Thorium	Th(NO ₃) ₄	250	2.0–9.0
Tin	H ₂ SnCl ₆	20	3.0–6.0
Tin	H ₂ SnCl ₄	10	2.0–6.0
Tungsten	Na ₂ WO ₄	10	2.5–9.0
Uranium	UO ₂ (C ₂ H ₃ O ₂) ₂	100	2.0–6.0
Zinc	Zn(NO ₃) ₂	10	2.0–9.0
Zirconium	Zr(NO ₃) ₄	50	2.0–9.0

^A Must be completely absent because of precipitation.

TABLE 2 Effect of Anions on the Determination of 2 µg/g (ppm) Iron

Ion	Added As	Maximum Added Without Interference, µg/g (ppm)	Applicable pH Range
Acetate	NaC ₂ H ₃ O ₂	500	2.0–9.0
Tetaborate	Na ₂ B ₄ O ₇	500	3.0–9.0
Bromide	NaBr	500	2.0–9.0
Carbonate	Na ₂ CO ₃	500	3.0–9.0
Chlorate	KClO ₃	500	2.5–9.0
Chloride	NaCl	1000	2.0–9.0
Citrate	H ₃ C ₆ H ₅ O ₇	500	2.0–9.0
Cyanide	KCN	10	2.0–9.0
Dichromate	K ₂ Cr ₂ O ₇	20	2.5–9.0
Fluoride	NaF	500	4.0–9.0
Iodide	KI	500	2.0–9.0
Nitrate	KNO ₃	500	2.0–9.0
Nitrite	KNO ₂	500	2.5–9.0
Oxalate	(NH ₄) ₂ C ₂ O ₄	500	6.0–9.0
Perchlorate	KClO ₄	100	2.0–9.0
Phosphate	(NH ₄) ₂ HPO ₄	20	2.0–9.0
Pyrophosphate	Na ₄ P ₂ O ₇	50	6.0–9.0
Silicate	Na ₂ SiO ₃	100	2.0–4.5
Sulfate	(NH ₄) ₂ SO ₄	500	2.0–9.0
Sulfite	Na ₂ SO ₃	500	2.0–9.0
Tartrate	(NH ₄) ₂ C ₄ H ₅ O ₆	500	3.0–9.0
Thiocyanate	KCNS	500	2.0–9.0
Thiosulfate	Na ₂ S ₂ O ₃	500	3.0–9.0

7.2 Purity of Water—Unless otherwise indicated, references to water shall be understood to mean Type I or II reagent water as defined in Specification **D1193**.

7.3 Hydroxylamine Hydrochloride Solution (100 g/L)—Dissolve 10 g of hydroxylamine hydrochloride (HONH₂·HCl) in approximately 60 mL of water, filter, and dilute to 100 mL.

7.4 *Iron, Standard Solution* (1 mL = 0.01 mg Fe)⁶—(Note 2)—Dissolve 0.1000 g of iron wire in 10 mL of hydrochloric acid (HCl, 1 + 1) and 1 mL of bromine water. Boil until the excess bromine is removed. Add 200 mL of HCl, cool, and dilute to 1 L in a volumetric flask. Dilute 100 mL of this solution to 1 L. may be prepared from one of the following options:

Note 2—As an alternative, the standard iron solution may be prepared by weighing exactly 0.7022 g of iron (II) ammonium sulfate hexahydrate (FeSO₄·(NH₄)₂SO₄·6H₂O, minimum purity, 99.5 %) in 500 mL of water containing 20 mL of sulfuric acid (H₂SO₄, sp gr 1.84) and diluting to 1 L with water. Dilute 100 mL of this solution to 1 L.

7.4.1 *Option 1*—Dissolve 0.1000 g of iron wire in 10 mL of hydrochloric acid (HCl, 1 + 1) and 1 mL of bromine water (which is bromine saturated water at 20 °C). Boil until the excess bromine is removed. Add 200 mL of HCl, cool, and dilute to 1 L in a volumetric flask. Dilute 100 mL of this solution to 1 L.

7.4.2 *Option 2*—Weigh 0.70 ± 0.01 g of iron (II) ammonium sulfate hexahydrate (FeSO₄·(NH₄)₂SO₄·6H₂O, minimum purity, 99.5 %) in 500 mL of water containing 20 mL of sulfuric acid (H₂SO₄, sp gr 1.84) and diluting to 1 L with water. Dilute 100 mL of this solution to 1 L.

7.4.3 *Option 3*—Purchased certified iron standard aqueous solution may also be utilized if its pH is less than 2.

7.5 *1,10-Phenanthroline Solution* (3 g/L)—Dissolve 0.9 g of 1,10-phenanthroline monohydrate in 30 mL of methanol and dilute to 300 mL with water.⁷

7.6 *Ammonium Acetate—Acetic Acid Solution*—Dissolve 100 g of ammonium acetate (CH₃COONH₄) in about 600 mL of water, filter, add 200 mL of glacial acetic acid to the filtrate, and dilute to 1 L with water.

7.7 *Sulfuric Acid, ACS trace metals grade.*

8. Sampling

8.1 Collect the sample in accordance with Practice E300.

8.2 Because this is a general test method for the final steps in determining iron, specific procedures for sample preparation are not included (see procedure is intended for trace levels of iron, care must be taken to ensure that the sample container and sampling point do not contribute rust 4.3;(iron) 4.1 and to the 4.2)-sample.

9. Calibration

9.1 By means of suitable pipets or a buret, transfer 0 (reagent blank), 2, 4, 6, 8, and 10 mL, respectively, of the standard iron solution to each of six 100-mL, glass-stoppered volumetric flasks. These flasks contain 0, 20, 40, 60, 80, and 100 µg of iron, respectively. Dilute the contents of each flask to 80 mL with water. Develop the color and measure the absorbance of each calibration standard as described in 10.3 and 10.4.

9.2 Plot the results in an X-Y graph, with the micrograms of iron on the x-axis and the respective absorbances on the y-axis. Visually evaluate the calibration graph obtained for linearity and for the absence of obvious outlying values. If so, proceed to the next step. If not, investigate for an assignable cause.

9.2.1 Establish a linear regression function from the calibration data using the statistical method of least squares, for example, with the aid of a spreadsheet. The formula for a linear calibration function is:

$$y = a + bx \quad (1)$$

⁶ This solution is also described in Practice used for calibration only. E200.

⁷ This solution is used for calibration only.

⁷ Frederick, G., and Richter, F. P., *Phenanthrolines and Substituted Phenanthroline Indicators*, GFS Publication No. 205, 1944 (no charge).

where:

b = slope of calibration line, and

a = intercept.

9.2.2 Evaluate the linearity of the calibration function by calculating the correlation coefficient r . A typical proper value is $r \geq \pm 0.9900$.

NOTE 2—If the photometer readings are percent transmittance, they may be converted to absorbance as follows:

$$A = \log\left(\frac{100}{T}\right) \quad (2)$$

where:

A = absorbance, and

T = percent transmittance.

10. Procedure

10.1 Weigh to three significant figures a sample (pH less than 2) containing 1 to 100 μg of iron into a 100-mL, glass-stoppered volumetric flask (Note 43). pH of sample should be less than 2; otherwise adjust with sulfuric acid, ACS trace metals grade. If the sample is water soluble, dissolve it in water and dilute to 80 mL with water. If the sample is not water soluble, methanol or another suitable solvent may be used (Note 54).

NOTE 3—The sample size should not exceed 80 mL. When using large samples, the miscibility of the samples and the reagents should be checked before the determination is made. In any case, preliminary tests must be made to determine if the sample or any impurities in the sample interfere in any way with the analysis. If a 1-cm cell is used, the sample must contain at least 5 μg of iron.

NOTE 4—Solvents that have been found suitable for use without recalibration include water, methanol, acetic acid, acetonitrile, and di- and triethylene glycol. Acetone is not suitable. No solvents other than those listed have been tested.

10.2 To prepare a reagent blank, add a quantity of water, approximately equal to the sample size in volume, to a second volumetric flask. Dilute this to 80 mL with the same solvent used to dissolve the sample.

NOTE 5—When running a number of samples, only one reagent blank is needed. The reagent blank should have the same composition after dilution as the sample. For example, if 10 mL of methanol is taken as a sample, 10 mL of spectro pure methanol should be included in the reagent blank. If 25 mL of methanol is taken as a sample, 25 mL of spectro pure methanol should be included in the reagent blank.

10.3 Add to each flask 2 mL of the hydroxylamine hydrochloride solution. Stopper and homogenize the solution by swirling the flask. Add to each flask 5 mL of the 1,10-phenanthroline solution and adjust the pH of the solution to between 3.0 and 4.0 by the dropwise addition of the ammonium acetate-acetic acid solution (see Note 76). It may be necessary to adjust the pH of the blank

TABLE 3 Iron Precision

Level	Repeatability			Within-laboratory, Between-Days			Reproducibility		
	Coefficient of Variation, %	Degrees of Freedom	95 % Limit, %	Coefficient of Variation, %	Degrees of Freedom	95 % Limit, %	Coefficient of Variation, %	Degrees of Freedom	95 % Limit, %
Less than 0.5 $\mu\text{g/g}$ (ppm)	7.540	24	21.11	5.7541	12	16.11	19.2700	4	53.96
Greater than 0.5 $\mu\text{g/g}$ (ppm)	2.7977	14	7.83	3.2222	7	9.02	16.9241	6	47.39

TABLE 3 Iron Precision

Level	Repeatability			Within-laboratory, Between-Days			Reproducibility		
	Std. Dev	Degrees of Freedom	r	Std. Dev	Degrees of Freedom		Std. Dev	Degrees of Freedom	R
0.156 $\mu\text{g/g}$	0.011	18	0.031	0.010	9	0.027	0.013	8	0.035
0.502 $\mu\text{g/g}$	0.011	20	0.032	0.012	10	0.035	0.030	9	0.84
2.126 $\mu\text{g/g}$	0.055	22	0.154	0.058	11	0.164	0.101	10	0.284