



Edition 2.0 2025-02 REDLINE VERSION

# INTERNATIONAL STANDARD

Plugs and socket-outlets for household and similar purposes –
Part 2-6: Particular requirements for switched socket-outlets with interlock for fixed electrical installations

## Document Preview

IEC 60884-2-6:2025

https://standards.iteh.ai/catalog/standards/iec/f2d3eac8-ce3f-4127-adae-8bf7006f528a/iec-60884-2-6-2025





### THIS PUBLICATION IS COPYRIGHT PROTECTED Copyright © 2025 IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

**IEC Secretariat** 3, rue de Varembé CH-1211 Geneva 20 Switzerland

Tel.: +41 22 919 02 11 info@iec.ch

www.iec.ch

#### About the IEC

The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

#### IEC publications search - webstore.iec.ch/advsearchform

The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee, ...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

#### IEC Customer Service Centre - webstore.iec.ch/csc

If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

#### IEC Products & Services Portal - products.iec.ch

Discover our powerful search engine and read freely all the publications previews, graphical symbols and the glossary. With a subscription you will always have access to up to date content tailored to your needs.

#### Electropedia - www.electropedia.org

The world's leading online dictionary on electrotechnology, containing more than 22 500 terminological entries in English and French, with equivalent terms in 25 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.





Edition 2.0 2025-02 REDLINE VERSION

# INTERNATIONAL STANDARD

Plugs and socket-outlets for household and similar purposes –
Part 2-6: Particular requirements for switched socket-outlets with interlock for fixed electrical installations

## Document Preview

IEC 60884-2-6:2025

https://standards.iteh.ai/catalog/standards/iec/f2d3eac8-ce3f-4127-adae-8bf7006f528a/iec-60884-2-6-2025

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.120.30 ISBN 978-2-8327-0265-9

Warning! Make sure that you obtained this publication from an authorized distributor.

## **CONTENTS**

FOF	REWORD	3
1	Scope	5
2	Normative references	5
3	Terms and definitions	6
4	General requirements	6
5	General notes remarks tests	7
6	Ratings	7
7	Classification	7
8	Marking	8
9	Checking of dimensions	9
10	Protection against electric shock	9
11	Provision for earthing	9
12	Terminals and terminations	10
13	Construction of fixed socket-outlets	10
14	Construction of plugs and portable socket-outlets	11
15	Interlocked socket-outlets	11
16	Resistance to ageing, to harmful ingress of water protection provided by enclosures, and resistance to humidity	13
17	Insulation resistance and electric strength	14
18	Operation of earthing contacts	14
19	Temperature rise	14
20	Breaking capacity	14
21	Normal operation	14
22	Force necessary to withdraw the plug	84-2 <sub>15</sub> -2
23	Flexible cables and their connection	15
24	Mechanical strength	15
25	Resistance to heat	15
26	Screws, current-carrying parts and connections	15
27	Creepage distances, clearances and distances through sealing compound	16
28	Resistance of insulating material to abnormal heat, to fire and to tracking	16
29	Resistance to rusting	16
30	Additional tests on pins provided with insulating sleeves	16
31	EMC requirements	16
32	Electromagnetic fields (EMF) requirements	16
٩nn	exes	17
Annex A (normative) Safety-related routine tests for factory-wired portable accessories (protection against electric shock and correct polarity)		17
٩nn	ex B (informative) Alternative gripping tests	17
	ex C (normative) Switches incorporated in portable socket-outlets	
Ann	ex I (normative) Additional requirements and tests for plugs and socket-outlets for I-load (HL) application	

#### INTERNATIONAL ELECTROTECHNICAL COMMISSION

# PLUGS AND SOCKET-OUTLETS FOR HOUSEHOLD AND SIMILAR PURPOSES –

# Part 2-6: Particular requirements for switched socket-outlets with interlock for fixed electrical installations

#### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition IEC 60884-2-6:1997. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

– 4 –

IEC 60884-2-6 has been prepared by subcommittee 23B: Plugs, socket-outlets and switches, of IEC technical committee 23: Electrical accessories. It is an International Standard.

This second edition cancels and replaces the first edition published in 1997. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

a) alignment to IEC 60884-1, fourth edition.

The text of this International Standard is based on the following documents:

Draft	Report on voting
23B/1547/FDIS	23B/1561/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at <a href="https://www.iec.ch/members\_experts/refdocs">www.iec.ch/members\_experts/refdocs</a>. The main document types developed by IEC are described in greater detail at <a href="https://www.iec.ch/publications">www.iec.ch/publications</a>.

This document is to be used in conjunction with IEC 60884-1:2022.

This document supplements or modifies the corresponding clauses in IEC 60884-1:2022, so as to convert that publication into the IEC standard: Particular requirements for switched socket-outlets without interlock for fixed installations. 4-2-6:2025

When a particular subclause of IEC 60884-1:2022 is mentioned in this document, that subclause applies as far as reasonable. Where this document states "addition", "modification" or "replacement", the relevant text of IEC 60884-1:2022 is to be adapted accordingly.

In this document the following print types are used:

- requirements proper: in roman type;
- test specifications: in italic type;
- Explanatory matter: in smaller roman type.

Subclauses, notes, figures and tables or figures which are additional to those in IEC 60884-1:2022 are numbered starting from 101.

A list of all the parts in the IEC 60884 series, under the general title *Plugs and socket-outlets* for household and similar purposes, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- · reconfirmed,
- · withdrawn, or
- revised.

# PLUGS AND SOCKET-OUTLETS FOR HOUSEHOLD AND SIMILAR PURPOSES –

# Part 2-6: Particular requirements for switched socket-outlets with interlock for fixed electrical installations

### 1 Scope

Replace IEC 60884-1:2022, Clause 1 with the following:

This part of IEC 60884 applies to switched socket-outlets with interlock for AC only, for fixed electrical installations, with or without earthing contact, with rated voltage above 50 V but not exceeding 440 V and a rated current not exceeding 32 A, intended for household and similar purposes, either indoors or outdoors.

Switched socket-outlets with interlock according to this document consist of a combination of socket-outlets according to IEC 60884-1, interlocked with a switch according to IEC 60669-1 and/or IEC 60669-2-1 supplied as a complete—unit accessory.

The rated current is limited to 16 A maximum for fixed accessories provided with screwless terminals.

This document does not cover requirements for flush mounting boxes.

However, it covers those requirements for surface-type mounting boxes which are necessary for the tests on socket-outlets.

NOTE 1 General requirements for mounting boxes are covered by IEC 60670.

NOTE 2 Interlocked socket-outlets incorporating devices according to IEC 60898, IEC 61008 and IEC 61009 are not covered by this document. This document may can be used as a guide for the requirements and tests of these accessories where relevant.

This document does not apply to

- interlocked socket-outlets for industrial purposes;
- interlocked socket-outlets for EV;
- interlocked socket-outlets for SELV.

Accessories complying with this standard are suitable for use at an ambient temperature not normally exceeding 25 °C, but occasionally reaching 35 °C.

Plugs and socket-outlets complying with this document are suitable for use at ambient temperatures not normally exceeding +40 °C, but their average temperature over a period of 24 h does not exceed +35 °C, with a lower limit of the ambient air temperature of -5 °C.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60884-1:2022, Clause 2 is applicable, except as follows:

Add to the list of normative references:

IEC 60669-1:<del>1993</del>2017, Switches for household and similar fixed-electrical installations – Part 1: General requirements

IEC 60669-2-1:<del>1996</del>2021, Switches for household and similar fixed electrical installations – Part 2-1: Particular requirements – Electronic switches control devices

IEC 60884-1:<del>1994</del>2022, Plugs and socket-outlets for household and similar purposes – Part 1: General requirements

#### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- IEC Electropedia: available at https://www.electropedia.org/
- ISO Online browsing platform: available at https://www.iso.org/obp

IEC 60884-1:2022, Clause 3 is applicable, except as follows:

Addition:

#### 3.101

#### interlock

device, either electrical or electronic or mechanical or a combination of these, which prevents the pins/contacts of a plug from becoming live before the plug is in proper engagement with a socket-outlet and which either prevents the plug from being withdrawn while its pin/contacts are live or makes the contacts of the socket-outlet dead before the plug is withdrawn

#### 3.102

### switched socket-outlet with interlock

factory assembled unit accessory consisting of a socket-outlet with an integral switching device controlling the socket-outlet, which is provided with an interlock

#### 3.103

#### retaining device

mechanical arrangement which holds a plug in position when it is in proper engagement, and prevents its unintentional withdrawal

#### 4 General requirements

IEC 60884-1:2022, Clause 4 is applicable.

#### General notes remarks on tests

IEC 60884-1:2022, Clause 5 is applicable, except as follows:

#### 5.4 Additional samples

Add after the fourth second paragraph:

For the test of Clause 15, it is possible that three additional specimens may be are necessary.

#### **Ratings**

IEC 60884-1:2022, Clause 6 is applicable.

#### Classification 7

IEC 60884-1:2022, Clause 7 is applicable, except as follows:

- 7.2 Add the following subclauses:
- **7.2.101** Switched socket-outlets with interlock are classified:
- 7.2.101.1 According to the method of actuating the switch:
- rotary;
- tumbler;
- rocker;
- push-button;
- touch;
- proximity;
- optical;
- acoustic;
- other external influences.
- **7.2.101.2** According to the number of poles of the switch:
- single-pole;
- double-pole;
- three-pole;
- three-pole with neutral.
- **7.2.101.3** According to the type of interlock:
- mechanical;
- electrical;
- electronic;
- a combination of any of these.
- 7.2.101.4 According to the retaining device:
- without device:
- with device.

#### 8 Marking

IEC 60884-1:2022, Clause 8 is applicable, except as follows:

#### 8.1 General

Add the following dashed list items before Note 2:

- symbol of mini-gap construction, if applicable;
- symbol of micro-gap construction, if applicable;
- symbol for semiconductor switching device, if applicable.

#### 8.2 Symbols

Add the following dashed list items before the notes:

_	Mini-gap construction	n
_	Micro-gap construction	μ
_	Semiconductor switching device(under consideration)	3
_	"OFF" position	C
_	"ON" position	I

#### Addition:

### 8.101 Identification of line terminals

Terminals of switched socket-outlets with interlock intended for the connection of the phase conductors shall be identified, unless the method of connection is of no importance or is self-evident or is indicated in a wiring diagram. Such identification may take the form of a letter L or in the case of more than one terminal, the letters  $L_1$ ,  $L_2$ ,  $L_3$ , etc., which may be accompanied by an arrow pointing to the relevant terminal(s).

– 8 –

Alternatively, the surface of such terminals shall be bare brass or copper, other terminals being covered with a metallic layer of another colour.

These indications shall not be placed on screws or any other easily removable parts.

### 8.102 Indication of the actual switch position

Switched socket-outlets with interlock shall be so marked that the direction of movement of the actuating member to its different positions or the actual switch position, is clearly indicated.

These indications shall be clearly visible on switched socket-outlets with interlock fitted with their cover or cover plate as for normal use. If these indications are placed on the cover or cover plate, it shall not be possible to fix the cover or cover plate in a position such that the indications are incorrect.

For indicating the direction of movement of the operating means, the symbols "O" and " I " may be used.

The short, straight line indicating the "ON" position shall be radial for rotary switches, perpendicular to the axis of rotation of the dolly for tumbler switches and rocker switches, and vertical for push-button switches when mounted vertically in its intended position.

#### 9 Checking of dimensions

IEC 60884-1:2022, Clause 9 is applicable.

### 10 Protection against electric shock

IEC 60884-1:2022, Clause 10 is applicable, except as follows:

Addition:

#### 10.101 Requirements for operating parts

Knobs, operating levers, push-buttons, rockers and the like, for operating switches in switched socket-outlets with interlock shall be of insulating material, unless their accessible metal parts are separated from the metal parts of the mechanism by double insulation or reinforced insulation, or in the case of switched socket-outlets with interlock with earthing terminals, they are reliably connected to earth.

Compliance is checked by inspection and by the tests of Clause 17 and Clause 21.

NOTE - For definition of the terms "double insulation" and "reinforced insulation", see IEC 60536.

#### 10.102 Requirements for accessible metal parts (protrusion from enclosure)

Metal parts of the switch mechanism, such as the spindle or the pivot of the dolly or rocker, that are not insulated from live parts, shall not protrude from the enclosure.

Compliance is checked by inspection. If necessary, the actuating member may be removed or broken.

If the actuating member has to be broken, compliance is checked after the test of Clause 28.

#### 10.103 Requirements for accessible metal parts (accessibility)

Metal parts of the switch mechanism, such as the spindle or the pivot of the dolly or rocker, shall not be accessible when the switched socket-outlet with interlock is mounted as for normal use.

In addition, these metal parts shall be insulated from accessible metal parts, including metal frames supporting the base of flush-type switched socket-outlets with interlock, liable to be mounted in a metal box, and also from screws used for fixing the base to its support.

This additional requirement does not apply if the metal parts of the mechanism are separated from live parts in such a way that the creepage distances and clearances have at least twice the values specified in 27.1, or as an alternative for switched socket-outlets with interlock provided with earthing terminals, if they are reliably connected to earth.

Compliance is checked by inspection. If necessary, measurement and the tests of Clause 17 and Clause 20 may be used.

### 11 Provision for earthing

IEC 60884-1:2022, Clause 11 is applicable.

#### 12 Terminals and terminations

IEC 60884-1:2022, Clause 12 is applicable.

#### 13 Construction of fixed socket-outlets

IEC 60884-1:2022, Clause 13 is applicable, except as follows:

Addition:

#### 13.101 Switch poles

Switches shall be constructed to match the number of poles of the socket-outlet, except that the neutral pole is not switched in unswitched neutral socket-outlets.

The earthing contact is not considered as a pole and the earth circuit shall not be switched.

The position of the switch operating member shall be such that it does not prevent, nor shall its correct operation be prevented by, the proper insertion of the corresponding plug or plugs.

NOTE – This may be checked by reference to the appropriate standard sheets for the system of plugs and socketoutlets used in the country in question.

Compliance is checked by inspection and by a manual test.

### 13.102 Attachment of knobs / Standards.itell.21

Knobs of rotary switches shall be securely coupled to the shaft or to the part operating the mechanism.

Compliance is checked by the following test. 84.2.6

//standards.iteh.ai/catalog/standards/iec/f2d3eac8-ce3f-4127-adae-8bf7006f528a/iec-60884-2-6-2025

The knob is subjected for 1 min to an axial pull of 100 N.

After this, knobs of switches having only one direction of operation are turned, if possible, without undue force, 100 times in the reverse direction.

During the test the knob shall not become detached.

#### 13.103 Indication of the position

The actuating member of a switch, when released, shall automatically take up the position corresponding to that of the moving contacts, except that, for those with a single push-button, the actuating member may take up a single rest position.

#### 13.104 Rest and intermediate position

Switches shall be so constructed that the moving contacts can come to rest only in the "ON" or "OFF" position, an intermediate position being, however, permissible if it corresponds to the intermediate position of the actuating member and if the insulation between the fixed and moving contacts is then adequate.

When in the intermediate position, the insulation between the fixed and moving contacts is checked by applying a voltage of substantially sine-wave form, having a frequency of 50 Hz or 60 Hz, for 1 min across the switch gap, the test voltage being 1 250 V for switched socket-outlets with interlock having a rated voltage up to and including 130 V, or 2 000 V for switched socket-outlets with interlock having a rated voltage exceeding 130 V.