



Designation: D2850 – 23

Standard Test Method for Unconsolidated-Undrained Triaxial Compression Test on Cohesive Soils¹

This standard is issued under the fixed designation D2850; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This test method covers determination of the strength and stress-strain relationships of a cylindrical specimen of either intact, compacted, or remolded cohesive soil. Specimens are subjected to a confining fluid pressure in a triaxial chamber. No drainage of the specimen is permitted during the application of the confining fluid pressure or during the compression phase of the test. The specimen is axially loaded at a constant rate of axial deformation (strain controlled).

1.2 This test method provides data for determining undrained strength properties and stress-strain relations for soils. This test method provides for the measurement of the total stresses applied to the specimen, that is, the stresses are not corrected for pore-water pressure.

NOTE 1—The determination of the unconfined compressive strength of cohesive soils is covered by Test Method [D2166/D2166M](#).

NOTE 2—The determination of the consolidated, undrained strength of cohesive soils with pore pressure measurement is covered by Test Method [D4767](#).

1.3 All observed and calculated values shall conform to the guidelines for significant digits and rounding established in Practice [D6026](#).

1.3.1 The procedures used to specify how data are collected/recorded or calculated in this standard are regarded as the industry standard. In addition, they are representative of the significant digits that generally should be retained. The procedures used do not consider material variation, purpose for obtaining the data, special purpose studies, or any considerations for the user's objectives; and it is common practice to increase or reduce significant digits of reported data to be commensurate with these considerations. It is beyond the scope of this standard to consider significant digits used in analysis methods for engineering design.

1.4 *Units*—The values stated in SI units are to be regarded as the standard. The values given in parentheses are mathemati-

cal conversions to inch-pound units, which are provided for information only and are not considered standard. Reporting of test results in units other than SI shall not be regarded as nonconformance with this test method.

1.4.1 The converted inch-pound units use the gravitational system of units. In this system, the pound (lbf) represents a unit of force (weight), while the unit for mass is slugs. The slug unit is not given, unless dynamic ($F = ma$) calculations are involved.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.6 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*²

[D422 Test Method for Particle-Size Analysis of Soils](#) (Withdrawn 2016)³

[D653 Terminology Relating to Soil, Rock, and Contained Fluids](#)

[D854 Test Methods for Specific Gravity of Soil Solids by Water Pycnometer](#)

[D1587/D1587M Practice for Thin-Walled Tube Sampling of Fine-Grained Soils for Geotechnical Purposes](#)

[D2166/D2166M Test Method for Unconfined Compressive Strength of Cohesive Soil](#)

[D2216 Test Methods for Laboratory Determination of Water \(Moisture\) Content of Soil and Rock by Mass](#)

¹ This test method is under the jurisdiction of ASTM Committee [D18](#) on Soil and Rock and is the direct responsibility of Subcommittee [D18.05](#) on Strength and Compressibility of Soils.

Current edition approved Feb. 1, 2023. Published February 2023. Originally approved in 1970. Last previous edition approved in 2015 as D2850 – 15. DOI: 10.1520/D2850-23.

² For referenced ASTM Standards, visit the ASTM website, www.astm.org, or contact Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ The last approved version of this historical standard is referenced on www.astm.org.

*A Summary of Changes section appears at the end of this standard

- [D2487 Practice for Classification of Soils for Engineering Purposes \(Unified Soil Classification System\)](#)
- [D2488 Practice for Description and Identification of Soils \(Visual-Manual Procedures\)](#)
- [D3740 Practice for Minimum Requirements for Agencies Engaged in Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction](#)
- [D4220/D4220M Practices for Preserving and Transporting Soil Samples \(Withdrawn 2023\)³](#)
- [D4318 Test Methods for Liquid Limit, Plastic Limit, and Plasticity Index of Soils](#)
- [D4753 Guide for Evaluating, Selecting, and Specifying Balances and Standard Masses for Use in Soil, Rock, and Construction Materials Testing](#)
- [D4767 Test Method for Consolidated Undrained Triaxial Compression Test for Cohesive Soils](#)
- [D6026 Practice for Using Significant Digits and Data Records in Geotechnical Data](#)
- [D6913/D6913M Test Methods for Particle-Size Distribution \(Gradation\) of Soils Using Sieve Analysis](#)

3. Terminology

3.1 *Definitions*—For definitions of common technical terms in this standard, refer to Terminology [D653](#).

3.2 *Definitions of Terms Specific to This Standard:*

3.2.1 *failure*—a stress condition selected to represent the maximum stress supported by a test specimen.

3.2.1.1 *Discussion*—Failure is often taken to correspond to the maximum principal stress difference (deviator stress) attained or the principal stress difference (deviator stress) at 15 % axial strain, whichever is obtained first during the performance of a test.

3.2.2 *unconsolidated-undrained compressive strength*—the value of the principal stress difference (deviator stress) at failure.

3.2.3 *unconsolidated-undrained shear strength*—the value of the principal stress difference (deviator stress) at failure divided by two.

4. Summary of Test Method

4.1 A cylindrical soil specimen with known dimensions and mass is sealed between loading platens inside the chamber using a flexible membrane. A confining pressure is applied to the specimen in the chamber and the specimen is given time to equalize without consolidation, as drainage of the specimen pore water is not allowed at any time during the test. The specimen is then loaded axially using a strain rate between 0.3 and 1 %/min such that the time to failure does not exceed approximately 15 min. During the shearing phase of the test, measurements of elapsed time, axial deformation, axial load, and chamber pressure are taken. Based on these data, the soil specimen unconsolidated-undrained compressive strength and unconsolidated-undrained shear strength are determined.

5. Significance and Use

5.1 In this test method, the compressive strength of a soil is determined in terms of the total stress, therefore, the resulting

strength depends on the pressure developed in the pore fluid during loading. In this test method, fluid flow is not permitted from or into the soil specimen as the load is applied, therefore the resulting pore pressure, and hence strength, differs from that developed in the case where drainage can occur.

5.2 If the test specimens is 100 % saturated, consolidation cannot occur when the confining pressure is applied nor during the shear portion of the test since drainage is not permitted. Therefore, if several specimens of the same material are tested, and if they are all at approximately the same water content and void ratio when they are tested, they will have approximately the same unconsolidated-undrained shear strength.

5.3 If the test specimens are partially saturated, or compacted/reconstituted specimens, where the degree of saturation is less than 100 %, consolidation may occur when the confining pressure is applied and during application of axial load, even though drainage is not permitted. Therefore, if several partially saturated specimens of the same material are tested at different confining stresses, they will not have the same unconsolidated-undrained shear strength.

5.4 Mohr failure envelopes may be plotted from a series of unconsolidated undrained triaxial tests. The Mohr's circles at failure based on total stresses are constructed by plotting a half circle with a radius of half the principal stress difference (deviator stress) beginning at the axial stress (major principal stress) and ending at the confining stress (minor principal stress) on a graph with principal stresses as the abscissa and shear stress as the ordinate and equal scale in both directions. The failure envelopes will usually be a horizontal line for saturated specimens and a curved line for partially saturated specimens.

5.5 The unconsolidated-undrained shear strength is applicable to situations where the loads are assumed to take place so rapidly that there is insufficient time for the induced pore-water pressure to dissipate and for consolidation to occur during the loading period (that is, drainage does not occur).

5.6 Compressive strengths determined using this procedure may not apply in cases where the loading conditions in the field differ significantly from those used in this test method.

NOTE 3—The quality of the results produced by this standard is dependent on the competence of the personnel performing it, and the suitability of the equipment and facilities used. Agencies that meet the criteria of Practice [D3740](#) are generally considered capable of competent testing. Users of this test method are cautioned that compliance with Practice [D3740](#) does not ensure reliable results. Reliable results depend on several factors; Practice [D3740](#) provides a means of evaluating some of those factors.

6. Apparatus

6.1 *Axial Loading Device*—The axial loading device shall be screw jack driven by an electric motor through a geared transmission, a hydraulic loading device, or any other compression device with sufficient capacity and control to provide the rate of loading prescribed in [8.5](#). The rate of advance of the loading device shall not deviate by more than ± 5 % from the selected value. Vibrations due to the operation of the loading device shall be sufficiently small to not cause dimensional changes in the specimen.

NOTE 4—A loading device may be said to provide sufficiently small vibrations if there are no visible ripples in a glass of water placed on the loading platen when the device is operating at the speed at which the test is performed.

6.2 Axial Load-Measuring Device—The axial load-measuring device shall be capable of measuring the axial load to at least three significant digits (readability); have a full scale accuracy not to exceed 0.25 %; and a capacity that is not greater than four times the axial load at failure. Commonly, an electronic load cell is used and may be integrated with the axial loading device.

6.3 Triaxial Compression Chamber—The triaxial chamber shall consist of a top plate and a baseplate separated by a cylinder. The cylinder shall be constructed of any material capable of withstanding the applied pressure. It is desirable to use a transparent material or have a cylinder provided with viewing ports so the behavior of the specimen may be observed. The top plate shall have a vent valve such that air can be forced out of the chamber as it is filled. The base plate shall have an inlet to fill the chamber.

6.4 Axial Load Piston—The piston passing through the top of the chamber and its seal must be designed so the variation in axial load due to friction does not exceed 0.1 % of the axial load at failure as measured in 9.6 and so there is negligible lateral bending of the piston during loading.

NOTE 5—The use of two linear ball bushings to guide the piston is recommended to reduce the friction and maintain alignment.

NOTE 6—A minimum piston diameter of one sixth the specimen diameter has been used successfully in many laboratories to minimize lateral bending.

6.5 Pressure-maintaining and Measurement Devices—The pressure-maintaining and measurement devices shall be capable of applying, controlling, and measuring the chamber pressure to within ± 2 kPa (0.3 psi) for pressures less than 200 kPa (29 psi) and to within ± 1 % for pressures greater than 200 kPa (29 psi).

6.5.1 A pressure transducer measuring the applied chamber pressure shall have an accuracy not to exceed ± 0.25 % of full range, a capacity in excess of the applied chamber pressure, and a readability equivalent to at least three significant digits at the maximum applied chamber pressure. This device commonly consists of a reservoir connected to the triaxial chamber and partially filled with the chamber fluid (usually water), with the upper part of the reservoir connected to a compressed gas supply; the gas pressure being controlled by a pressure regulator and measured by an electronic pressure transducer.

6.6 Specimen Cap and Base—An impermeable rigid cap and base shall be used to prevent drainage of the specimen. The specimen cap and base shall be constructed of a noncorrosive impermeable material, and each shall have a circular plane surface of contact with the specimen and a circular cross section. The mass of the specimen cap shall produce an axial stress on the specimen of less than 1 kPa (0.1 psi). The diameter of the cap and base shall be equal to the initial diameter of the specimen. The specimen base shall be connected to the triaxial compression chamber to prevent lateral motion or tilting, and the specimen cap shall be designed such that eccentricity of the piston-to-cap contact relative to the

vertical axis of the specimen does not exceed 1.3 mm (0.05 in.). The end of the piston and specimen cap contact area shall be designed so that tilting of the specimen cap during the test is minimal. The cylindrical surface of the specimen base and cap that contacts the membrane to form a seal shall be smooth and free of scratches.

NOTE 7—To determine the axial stress from the top cap, measure the mass of the top cap in grams and area of the top cap in cm^2 . The stress from the top cap, in kN/m^2 (= kPa), is equal to the mass in grams times the acceleration due to gravity (9.8087 m/sec^2) divided by the area in cm^2 times $10,000 \text{ cm}^2/\text{m}^2$ divided by 1000 N/kN and 1000 g/kg.

6.7 Deformation Indicator—The vertical deformation of the specimen is usually determined from the travel of the piston acting on the top of the specimen. The piston travel shall be measured using a deformation indicator with a range of at least 20 % of the initial height of the specimen and an accuracy not to exceed 0.25 % of the initial specimen height. The deformation indicator is commonly a linear variable differential transformer (LVDT) or other measuring device meeting the requirements for accuracy and range.

6.8 Rubber Membrane—The rubber membrane used to encase the specimen shall provide reliable protection against leakage. Membranes shall be carefully inspected prior to use, and if any flaws or pinholes are evident, the membrane shall be discarded. To offer minimum restraint to the specimen, the unstretched membrane diameter shall be between 90 and 95 % of that of the specimen. The membrane thickness shall not exceed 1 % of the diameter of the specimen. The membrane shall be sealed to the specimen base and cap with rubber O-rings for which the unstressed inside diameter is between 75 and 85 % of the diameter of the cap and base, or by any method that will produce a positive seal. An equation for correcting the principal stress difference (deviator stress) for the effect of the strength of the membrane is given in 9.8.

6.9 Sample Extruder—The sample extruder shall be capable of extruding the soil core from the sampling tube in the same direction of travel in which the sample entered the tube and with minimum disturbance of the sample. If the soil core is not extruded vertically, care should be taken to avoid bending stresses on the core due to gravity. Conditions at the time of sample removal may dictate the direction of removal, but the principal concern is to keep the degree of disturbance minimal.

6.10 Specimen-Size Measurement Devices—Devices used to measure the height and diameter of the specimen to three or more significant digits (readability) with an accuracy not to exceed 0.25 % of its full range. The devices shall be constructed such that during use the specimen is not disturbed or deformed.

NOTE 8—Circumferential measuring tapes are recommended over calipers for measuring the diameter.

6.11 Timer—A timing device indicating the elapsed testing time to the nearest 1 s shall be used for establishing the rate of strain application prescribed in 8.5 and recording the time during specimen compression as required in 8.6.

6.12 Balances—A balance or scale conforming to the requirements of Specification **D4753** readable (with no estimation) to 0.1 % of the test mass, or better.

6.13 *Miscellaneous Apparatus*—Specimen trimming and carving tools including a wire saw, steel straightedge, miter box and vertical trimming lathe, apparatus for preparing remolded specimens, membrane and O-ring expander, water content containers, and data sheets shall be provided as required.

7. Test Specimens

7.1 *Specimen Size*—Specimens shall be cylindrical and have a minimum diameter of 33 mm (1.3 in.). The average height-to-average diameter ratio shall be between 2 and 2.5. The largest particle size shall be smaller than one sixth the specimen diameter. If, after completion of a test, it is found based on visual observation that oversize particles are present, indicate this information in the report of test data (see 10.2.14).

NOTE 9—If oversize particles are found in the specimen after testing, a particle-size analysis may be performed in accordance with Test Method D422 or D6913/D6913M to confirm the visual observation and the results provided with the test report (see 10.2.4).

7.2 *Intact Specimens*—Prepare intact specimens from large intact samples or from samples secured in accordance with Practice D1587/D1587M or other acceptable intact tube sampling procedures. Samples shall be preserved and transported in accordance with the practices for Group C samples in Practices D4220/D4220M. Specimens obtained by tube sampling may be tested without trimming except for cutting the end surfaces plane and perpendicular to the longitudinal axis of the specimen, provided soil characteristics are such that no significant disturbance results from sampling. Handle specimens carefully to minimize disturbance, changes in cross section, or change in water content. If compression or any type of noticeable disturbance would be caused by the extrusion device, split the sample tube lengthwise or cut the tube in suitable sections to facilitate removal of the specimen with minimum disturbance. Prepare trimmed specimens, in an environment such as a controlled high-humidity room where soil water content change is minimized. Where removal of pebbles or crumbling resulting from trimming causes voids on the surface of the specimen, carefully fill the voids with remolded soil obtained from the trimmings. When the sample condition permits, a vertical trimming lathe may be used to reduce the specimen to the required diameter. After obtaining the required diameter, place the specimen in a miter box and cut the specimen to the final height with a wire saw or other suitable device. Trim the surfaces with the steel straightedge. Perform one or more water content determinations on material trimmed from the specimen in accordance with Test Method D2216. Determine the mass and dimensions of the specimen consistent with 6.12 and 6.10. A minimum of three height measurements (120° apart) and at least three diameter measurements at the quarter points of the height shall be made to determine the average height and diameter of the specimen.

7.3 *Compacted/Reconstituted Specimens*—Soil required for compacted/reconstituted specimens shall be thoroughly mixed with sufficient water to produce the desired water content. If water is added to the soil, store the material in a covered container for at least 16 h prior to compaction. Compacted/reconstituted specimens may be prepared by compacting ma-

terial in at least six layers using a split mold of circular cross section having dimensions meeting the requirements enumerated in 7.1. Specimens may be compacted/reconstituted to the desired density by either: (1) kneading or tamping each layer until the accumulative mass of the soil placed in the mold is compacted/reconstituted to a known volume; or (2) by adjusting the number of layers, the number of tamps per layer, and the force per tamp. The top of each layer shall be scarified prior to the addition of material for the next layer. The tamper used to compact the material shall have a diameter equal to or less than one half the diameter of the mold. After a specimen is formed, with the ends perpendicular to the longitudinal axis, remove the mold and determine the mass and dimensions of the specimen using the devices described in 6.12 and 6.10. Perform one or more water content determinations on excess material used to prepare the specimen in accordance with Test Method D2216.

7.4 *Remolded Specimens*—Specimens may be prepared either from a failed intact specimen or from a disturbed sample, providing it is representative of the failed intact specimen. In the case of failed intact specimens, wrap the material in a thin rubber membrane and work the material thoroughly with the finger to ensure complete remolding. Avoid entrapping air in the specimen. Exercise care to obtain a uniform density, to remold to the same void ratio as the intact specimen, and to preserve the water content of the soil. Form the disturbed material into a mold of circular cross section having dimensions meeting the requirements of 7.1. After removal from the mold, determine the mass and dimensions of the test specimen consistent with 6.12 and 6.10. A minimum of three height measurements (120° apart) and at least three diameter measurements at the quarter points of the height shall be made to determine the average height and diameter of the specimen.

NOTE 10—It is common for the unit weight of the specimen after removal from the mold to be less than the value based on the volume of the mold. This occurs as a result of the specimen swelling after removal of the lateral confinement due to the mold.

8. Procedure

8.1 Place the membrane on the membrane expander or, if it is to be rolled onto the specimen, roll the membrane onto the impermeable rigid cap or base. Place the specimen on the base. Place the rubber membrane around the specimen and seal it at the cap and base with O-rings or other positive seals at each end. A thin coating of silicon grease on the vertical surfaces of the cap or base will aid in sealing the membrane.

8.2 With the specimen encased in the rubber membrane, which is sealed to the specimen cap and base and positioned in the chamber, assemble the triaxial chamber. Bring the axial load piston into contact with the specimen cap several times to permit proper seating and alignment of the piston with the cap. When the piston is brought into contact the final time, record the reading on the deformation indicator to three significant digits. During this procedure, take care not to apply an axial stress to the specimen exceeding approximately 0.5 % of the estimated compressive strength. Lock the piston in place above the specimen cap after checking the seating and alignment and keep locked until application of the chamber pressure.