



# Standard Practice for Human Engineering Design for Marine Systems, Equipment, and Facilities<sup>1,2</sup>

This standard is issued under the fixed designation F1166; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

*This standard has been approved for use by agencies of the U.S. Department of Defense.*

## 1. Scope

1.1 This practice provides ergonomic design criteria from a human-machine perspective for the design and construction of maritime vessels and structures and for equipment, systems, and subsystems contained therein, including vendor-purchased hardware and software.

1.1.1 The focus of these design criteria is on the design and evaluation of human-machine interfaces, including the interfaces between humans on the one side and controls and displays, physical environments, structures, consoles, panels and workstations, layout and arrangement of ship spaces, maintenance workplaces, labels and signage, alarms, computer screens, material handling, valves, and other specific equipment on the other.

1.2 The criteria contained within this practice shall be applied to the design and construction of all hardware and software within a ship or maritime structure that the human crew members come in contact in any manner for operation, habitability, and maintenance purposes.

1.3 Unless otherwise stated in specific provisions of a ship or maritime structure design contract or specification, this practice is to be used to design maritime vessels, structures, equipment, systems, and subsystems to fit the full potential user population range of 5th % females to 95th % males.

1.4 This practice is divided into the following sections and subsections:

### TABLE OF CONTENTS

Section and Subsections	Title
1	Scope
2	Referenced Documents
3	Terminology
4	Significance and Use
5	Controls
5.1	Principles of Control Design
5.2	General Design Guidelines

<sup>1</sup> This practice is under the jurisdiction of ASTM Committee F25 on Ships and Marine Technology and is the direct responsibility of Subcommittee F25.07 on General Requirements.

Current edition approved June 15, 2021; Sept. 1, 2022. Published November 2021; May 2023. Originally approved in 1988. Last previous edition approved in 2013 as F1166 – 07 (2013); F1166 – 21. DOI: 10.1520/F1166-21; 10.1520/F1166-22.

<sup>2</sup> A user-friendly format of this standard is available for download from ASTM’s website. While the content is the same, ASTM Practice F1166 in standard published format should be considered the official version (for any legal or liability purposes).

**TABLE OF CONTENTS**

Section and Subsections	Title
5.3	Control Movement
5.4	Control Spacing
5.5	Coding of Controls
5.6	Control Use and Design
6	Displays
6.1	Visual Displays
6.2	Location, Orientation, Lighting, and Arrangement of Displays
6.3	Display Illumination
6.4	Display Types
6.5	Audible Displays
7	Alarms
7.1	General Alarm Requirements
7.2	Visual Alarms
7.3	Audible Alarms
7.4	Voice Messages
7.5	Alarm Initiation Stations
7.6	Alarm Requirements by IMO
8	Integration of Controls, Displays, and Alarms
8.1	Principles of Design
8.2	Grouping Relationships—Principles of Arrangement
8.3	Separating Groupings
8.4	Position Relationships of Displays and Alarms
8.5	Position Relationships of Controls to Associated Displays and Alarms
8.6	Control and Display Movement Relationships
8.7	Spatial Relationship Between Controls, Displays, and Equipment
8.8	Alternative Approach to Grouping Design
8.9	Special Requirements for Control and Display Integration on Bridges
9	Anthropometry
9.1	General Design Requirements
9.2	Static Anthropometric Data
10	Workplace Arrangements
10.1	Basic Principles of Workplace Design
10.2	Seated Workstation
10.3	Standing Workstation
10.4	Kneeling Workstation
10.5	Squatting Workstation
10.6	Shelving
10.7	Status Boards and File Cabinets
10.8	Work Benches
10.9	Vertical Strainers and Filters
10.10	Reach Limitations at Workstations
10.11	Safety Eyewash Fountains and Showers
10.12	Pedestal-Mounted Controls and Displays
10.13	Hand Cranks and Pumps
10.14	Bulkhead-Mounted Equipment
10.15	Equipment Racks, Cabinets, and Individual Equipment Spacing
10.16	Consoles and Control Panels
10.17	Bridge Design
11	Access Aids: Stairs, Handrails, Railings, Vertical Ladders, Ramps, Doors, Lightening Holes, Hatches, Kick-Out Panels, Passageways and Walkways, and Work Platforms)
11.1	Stairs, Ladders, and Ramps
11.2	Stairs
11.3	Ramps
11.4	Vertical Ladders
11.5	Vertical Ladders with Safety Cages
11.6	Vertical Ladders with Positive Fall Protection Devices
11.7	Special Ladder Requirements
11.8	Handle/Hand Grab
11.9	Individual Rung Ladders
11.10	D-Ring Ladders
11.11	Handrails
11.12	Walkways, Passageways, and Alternate Means of Personnel Movement
11.13	Elevated Work Platforms
11.14	Hatches, Manways, Lightening Holes, Inspection Ports, and Kick-Out Panels
11.15	Doors and Arches
11.16	Permanent Means of Access (PMA)
12	Valve Placement, Orientation, and Location
12.1	General Design Requirements
12.2	Valve Criticality and Location
12.3	Valve-Mounting Heights and Orientations: Handwheel Operated
12.4	Valve-Mounting Heights and Orientations: Lever-Operated Valves
12.5	Alternative Valve Orientations
12.6	Valve Manifolds
13	Human-Computer Interface

**TABLE OF CONTENTS**

Section and Subsections	Title
13.1	General Design Requirements
13.2	System Operations
13.3	Computer Displays
13.4	Display Content
13.5	Display Coding
13.6	Dynamic Displays
13.7	Display Format
13.8	Textual Data Displays
13.9	Graphic Displays
13.10	Audio Displays
13.11	Data Entry
13.12	Interactive Control
13.13	Graphic Controls
13.14	Windows
13.15	Menus
13.16	Forms
13.17	Alarms
13.18	Language
13.19	Feedback
13.20	Prompts
13.21	Defaults
13.22	Error Management/Data Protection
13.23	Data Security
13.24	Help
13.25	Software
13.26	Data Transmission/Messaging
13.27	Input Devices
13.28	Cursors
13.29	Printing
14	Habitability
14.1	Noise
14.2	Indoor Climate
14.3	Lighting
14.4	Whole-body Vibration and Shock
15	Labeling
15.1	Design Criteria of Labels
15.2	Abbreviations
15.3	Symbols
15.4	Component Labels on Consoles and Panels
15.5	Equipment Identification Labels
15.6	Electrical System Labels
15.7	Room, Deck Space, and Void Identification Labels
15.8	Pipe Marker Labels
15.9	Safe Working Load Identification Labels
15.10	Load Weight Identification Labels
15.11	Hazard Identification Signs
15.12	Information Signs
15.13	Instruction Labels
15.14	Graphical Schematics or Diagrams
15.15	Orientation Plans
15.16	Emergency Instructions
16	Material Handling
16.1	Design to Support Manual Material Lifting and Carrying
16.2	Weight Lifting
16.3	Weight Carrying
16.4	Design of Handles and Grasp Areas
16.5	Design of Auxiliary Hoisting and Carrying Devices
16.6	Hand Trucks and Wheeled Dollies
16.7	Crane Design
17	Design for Maintenance
17.1	General Design Requirements
17.2	Maintenance Accessibility
17.3	Maintenance Environments
17.4	Lubrication
17.5	Cases
17.6	Covers
17.7	Fasteners
17.8	Hatches, Manways, Lightening Holes for Maintenance Access
17.9	Diagnostics and Troubleshooting
17.10	Equipment Modularization
17.11	Equipment Mounting and Installation
17.12	Standardization
17.13	Electrical Wires and Cables
17.14	Conductors

iTeh Standards  
<https://standards.iteh.ai>  
 Document Preview

ASTM F1166-22

<https://standards.iteh.ai/catalog/standards/sist/c28ce371-5eac-471a-bd8b-999a7c15874d/astm-f1166-22>

**TABLE OF CONTENTS**

Section and Subsections	Title
17.15	Connectors
17.16	Test Equipment
17.17	Fuses and Circuit Breakers
17.18	Hydraulic Systems
17.19	Stored Energy Devices
17.20	Pipe Flanges, Spools, and Blinds
17.21	Test and Sample Points
18	Hazards and Safety
18.1	Hierarchy of Controls
18.2	Safety Labels, Signs, and Excluded Area Markings
18.3	General Workplace Hazards
18.4	General Equipment-Related Hazards
18.5	Electrical Hazards
18.6	Mechanical Hazards
18.7	Fluid Hazards
18.8	Safety Barriers
18.9	Fall Protection
18.10	Emergency Egress
19	Communications
19.1	Communication System Requirements
19.2	Microphones
19.3	Headsets
19.4	Loudspeakers
19.5	Telephone Systems
20	Keywords
21	Acknowledgement
Appendix X1	Small Boat and High Speed Craft (HSC) Appendix
Appendix X2	Human Factors Engineering (HFE) Design Checklist
Appendix X3	<u>Guidance for the Selection and Testing of Slip Resistant Walking Surfaces</u>

**LIST OF FIGURES**

Figure	Title
1	Control Movement Expectations
2	Foot-Operated Switches Design Requirements
3	Pedal Location and Design Requirements
4	Lateral Spacing for Pedals
5	Design Criteria for Discrete Rotary Controls
6	Separation Requirements for Discrete Rotary Controls
7	Dimension, Resistance, and Separation of Continuous Rotary Controls
8	Proper Mounting of Rapidly Operated Cranks
9	Dimensions, Resistance, and Separations Required for Cranks
10	Design Criteria for Pushbuttons
11	Two Types of Legend Switches (Backlit Pushbuttons)
12	Size, Displacement, and Resistance for Legend Switches
13	Design Requirements for Various Types of Toggle Switches
14	Design Requirements for Rocker Switches
15	Dimensions, Resistance, and Separation for Discrete Slide Switch Controls
16	Dimensions, Resistance, and Separation for Continuous Slide Controls
17	Dimensions, Resistance, and Separation for Levers
18	Dimensions, Resistance, and Separation for Slide Levers
19	Dimensions, Displacement, and Separation of Push-Pull Controls
20	Visual Lines of Sight
21	Primary and Secondary Fields-of-view
22	Design Criteria for Major, Intermediate, and Minor Scale Markings
23	Scale Graduation, Pointer Position, and Scale Numbering Alternatives
24	Scale Number Placement
25	Color and Shape Coding of Ranges on an Analog Display
26	Zero Position and Pointer Movement for Circular Dial Displays
27	Aligned Pointers for Rapid Check Readings
28	Digital Display Design Requirements
29	Grouping Controls and Displays by Common Function
30	Grouping Controls and Displays by Individual Equipment
31	Mirror-Imaged Arrangement of Individual Equipment Control and Display Groupings (Not Recommended)
32	Grouping Controls and Displays by Common Equipment
33	Grouping Controls and Displays by Sequence of Use
34	Grouping with Physical Separation
35	Grouping with Boundary Lines and Borders
36	Grouping with Colored and Shaded Pads
37	Grouping with Sub-panels
38	Position of Individual Controls and Associated Displays for Right-handed Operator
39	Arrangement of Multiple Rows of Controls and Displays
40	Arrangement of Multiple Rows of Displays and a Single Row of Controls

**LIST OF FIGURES**

Figure	Title
41	Positional Relationship between Alarm, Display, and Control
42	Positional Relationship between Control Pointer and Status Indicator
43	Control and Display Movement Relationship
44	Spatial Relationship Between Controls, Displays, and Equipment
45	Spatial Relationships Between Equipment and Control Panels
46	Spatial Relationships for Redundant Controls and Displays
47	Panel Layout That Replicates Location of Equipment in Remote Space
48	Mimic of Physical Equipment Functional Layout
49	Mimic of Functional Groups Irrespective of Equipment Layout
50	Standing Body Dimensions
51	Seated Body Dimensions
52	Depth and Breadth Dimensions
53	Hand and Foot Dimensions
54	Gloved Hand Dimensions
55	Head Dimensions
56	Changes in Levels up to a Maximum of 6 mm (¼ in.)
57	Seated Workspace Dimensions
58	Dimensions for a Computer Workstation
59	Dimensions for Single or Multiple Personnel at a Table or Other Duty Station Not Requiring a Desk
60	Seating at CRT-Type Workstations
61	Clearance Behind a Seated Workstation
62	Control Mounting Height for Seated Personnel
63	Display Mounting Height for Seated Personnel
64	Control Mounting Height for Standing Personnel
65	Display Mounting Height for Standing Personnel
66	Control Mounting Height for a Kneeling Person
67	Display Mounting Height for Kneeling Personnel
68	Required Dimensions for a Kneeling Worker
69	Control Mounting Height for Squatting Personnel
70	Display Mounting Heights for Squatting Personnel
71	Required Dimensions for a Squatting Worker
72	Workplace Dimensions for Shelves with Full Access
73	Workplace Dimensions for Shelves Located Above a Cabinet
74	Workplace Dimensions for Shelves Requiring Vision Over the Top
75	Front Clearance Requirement for Lower Shelves
76	Mounting Height of Status Boards
77	Clearance in Front of Filing Cabinets
78	Workbench Dimensions
79	Safe Reach Distances Over an Obstacle or Barrier
80	Mounting Heights for Bulkhead-mounted Equipment in Passageways
81	Mounting Heights for Common Electrical Fixtures
82	Direct Spatial Relationships Between Controls and Equipment
83	Spatial Relationship of Fore and Aft Equipment to Controls and Displays on a Console Located Athwartship
84	Seated Single-operator Console Dimensions
85	Wraparound Seated Console
86	Special Width Console
87	Multi-tiered Standing Console
88	Multi-tiered Seated Console
89	Dimensions for Desktop Standing Console
90	Cargo and Ballast Transfer Consoles
91	Stair Dimensions
92	Straight Run Ramp Dimensions
93	Ramp with Turning Platform
94	Ramp with Switchback Turning Platform
95	Vertical Ladder Dimensions
96	Dimensions for a Vertical Ladder Arrangement
97	Platform/Landing Dimensions for Vertical Ladder Penetration
98	Caged Ladder Dimensions
99	Cage Shape and Size
100	Ladder and Climber Safety Device Dimensions
101	Extended Railing for Ladder Fall Protection (Front View)
102	Extended Railing for Ladder Fall Protection (Side View)
103	Extended Railing and Cage for Ladder Fall Protection (Front View)
104	Extended Railing and Cage for Ladder Fall Protection (Side View)
105	Handles or Hand Grabs for Use as Ladder Extensions
106	Handle for Transition from a Ladder to an Intermediate Platform
107	Recommended Design Criteria for Individual Rung Ladders
108	Dimensions for D-Ring Ladders
109	Fixed Handrail Design
110	Removable Handrail Dimensions
111	Special Handrail Design Dimensions
112	Transition Handrail Dimensions
113	Additional Personnel Movement-related Design Features
114	Dimensions for Rectangular Access Openings Installed in a Vertical Orientation Requiring a Step to Reach the Opening
115	Dimensions for Rectangular, Square, and Round Hatches, Manways, and Lightening Holes
116	Dimensions for Lightening Holes

**LIST OF FIGURES**

Figure	Title
117	Access to Vertical Escape Hatches
118	Access to Overhead Hatch
119	Access into a Cargo Hold Through a Raised Hatch
120	Door Placement
121	Desirable Upper Limits for Handwheel Torque
122	Mounting Heights for Handwheel Valves With Vertical Stems
123	Mounting Heights for Handwheel Valves With Horizontal Stems
124	Mounting Heights for Handwheel Valves With Angled Stems
125	Mounting Heights for Lever-Operated Valves With Vertical Stems
126	Mounting Heights for Lever-Operated Valves With Horizontal Stems
127	Direction of Travel for Valve Levers Accessible From One Side Only
128	Physical Reach from a Stooping or Squatting Position
129	Mounting Position for Valve Levers and Handwheels Below Standing Surface
130	Orientation and Reach from Ladder Parallel to Valves
131	Orientation and Reach from Ladder Perpendicular to Valves
132	Operating Valves from a Ladder
133	Valve Manifold for Tanks Located Athwartship
134	Valve Manifold for Tanks Located Fore and Aft
135	Valve Manifold for Fill, High-suction, and Low-suction Valves
136	Default Push Button
137	Push Button States
138	Radio Buttons
139	Check Boxes
140	Slider Control
141	Message Window Design
142	Finger-Operated Displacement Joystick Specifications
143	Trackball Dimensions, Resistance, and Clearance
144	Permissible Noise Exposure Limits
145	Large Enclosure Ventilation Requirements
146	Surface Reflectance Values
147	Health Guidance Zones for Limited Exposures
148	Independent Symbols
149	Guidelines for Labels on Consoles and Panels
150	Control and Control Setting Labels
151	Control and Display Group Labels
152	Control Setting Labels for Multiple Controls
153	Equipment Label Format
154	Sensor Label
155	Pipe Marker Labels
156	Pipe Marker Labels with Two Colors
157	Hazard Signal Word Headers
158	Examples of Text and Symbol on Signs
159	Example of Information Sign
160	Handle Dimensions
161	Use of Hand Trucks
162	Use of Dollies
163	Case Orientation
164	Access Opening Covers
165	Example of Alignment Pins
166	Cable Arrangements
167	Suggested Cable Arrangement in a Junction Box
168	Fluid Line Connection Recommendations
169	Areas To Place Items on Bulkhead
170	Safety Barriers
X1.1	Primary and Secondary Fields of View

**LIST OF TABLES**

Table	Title
1	Recommended Manual Controls
2	Control Movement Expectations
3	Minimum Spacing Between Two Controls
4	Comparison of Displacement and Isometric Controls
5	Typical Status Display and Alarm Color Codes for North American Industry
6	Character Sizes for Digital Displays
7	Functional Evaluation of Types of Audio Signals
8	Guidelines for Color Coding of Visual Alarms
9	General Recommendations for Sound Loudness and Frequency
10	Guidelines for Selecting Audible Alarm Sounds
11	Clothing and Postural Effects
12	International Geographical Regions for Which Anthropometric Data Are Available
13	Standing Height Dimensions—International Population
14	Seated Eye Height Dimensions—International Population
15	Forward Functional Reach Dimensions—International Population
16	Male Anthropometric Data from Four Regions of the World

**LIST OF TABLES**

Table	Title
17	Female Anthropometric Data from Four Regions of the World
18	Weights for American Adult Females and Males
19	Seated Workspace Dimensions
20	Dimensions for a Seated Computer Workstation
21	Maximum Overhead Extended and Gripping Reach
22	Selection of Access Type
23	Stair Dimensions
24	Stair Widths
25	Handrail Arrangements
26	Recommended Ramp Angle Inclinations
27	Walkway and Passageway Dimensions
28	Dimensions for Additional Personnel Movement-related Features
29	Access Opening and Mounting Depth Dimensions for Levers and Handwheels Mounted Below the Standing Surface
30	System Response Time Limits
31	Advantages and Disadvantages of Nonkeyboard Input Devices
32	Keyboard Push-button Characteristics
33	Pointer Shapes and Associated Functions
34	Pointing Device Button Actions
35	Limiting Dimensions for Mouse
36	Maximum Permissible Noise Levels
37	Noise Attenuation from Hearing Protectors
38	Lighting Levels for Ships and Maritime Structures
39	Maximum Brightness Ratios
40	Operational Environment Types
41	Examples of Equipment Labels
42	Pipe Label Format
43	Example Color-Coding Scheme for Vessel/structure Piping
44	Chromaticity Coordinates for Color Coding
45	Message Text Character Heights
46	Design Weight Limits for Lifting
47	Design Weight Limits for Carrying
48	Limiting Factors
49	Seated, Forward Reach (Both Arms)
50	Cross-Legged Seated, Forward Reach (Both Arms)
51	Standing, Forward Reach (Both Arms)
52	Standing, Forward Reach (Preferred Arm)
53	Standing, Lateral Reach (Preferred Arm)
54	Opening Dimensions for Single-hand Access with Tools
55	Opening Dimensions for Single-hand Access without Tools
56	Opening Dimensions for Arm Access without Tools
57	Opening Dimensions for Two-hand Access
58	Thermal Temperature Limits
59	Shock Current Intensities and Their Probable Consequences
60	Minimum Speech Intelligibility Scores
X1.1	Visibility Standards for HSC and Small Boat Application
X1.2	Forward Functional Reach Measurements for North American Population
X2.1	Human Factors Checklist for Design

1.5 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.

1.6 This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.

## 2. Referenced Documents

### 2.1 ASTM Standards:<sup>3</sup>

[F1646 Terminology Relating to Walkway Safety and Footwear](#)

[F2508 Practice for Validation, Calibration, and Certification of Walkway Tribometers Using Reference Surfaces](#)

[F2965 Guide for Selection of Walkway Surfaces and Treatments When Considering Aggressive Contaminant Conditions in Commercial and Industrial \(Not Including Construction\) Environments \(Withdrawn 2022\)<sup>4</sup>](#)

[F3132 Practice for Selection of Walkway Surfaces When Considering Pedestrian Safety](#)

[F3539 Practice for Creation of Walkway Tribometer Interlaboratory Study Reports and Test Procedures](#)

<sup>3</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

<sup>4</sup> The last approved version of this historical standard is referenced on [www.astm.org](http://www.astm.org).



## 2.2 Overall References:

ABS Guidance Notes for the Application of Ergonomics to Marine Systems, August 2013 (Updated August 2018)  
MIL-STD-1472 Department of Defense Design Criteria Standard: Human Engineering

## 2.3 Alarms:

DOT/FAA/HF-STD-001B Ahlstrom, V. (2016). Human Factors Design Standard (HFDS) Atlantic City International Airport, NJ: Federal Aviation Administration William J. Hughes Technical Center  
Engineering Equipment and Materials User's Association (EEMUA) Publication # 191 Alarm Systems, a Guide to Design, Management and Procurement  
International Maritime Organization (IMO) Resolution A.830(19) Code on Alarms and Indicators

## 2.4 Integration of Controls, Displays, and Alarms:

ABS (October 2003) Guidance Notes on Ergonomic Design of Navigation Bridges

## 2.5 Anthropometry:

ADULTDATA: The Handbook of Adult Anthropometrics and Strength Measurements—Data for Design Safety Institute for Occupational Ergonomics, University of Nottingham, UK, 1998  
International Labor Office (ILO) International Data on Anthropometry, 1990  
McDowell, M. A., Fryar, C. D., Hirsch, R., and Ogden, C. L. Anthropometric Reference Data for Children and Adults: U.S. Population, 2003-2006, Advance Data from Vital and Health Statistics No. 361, U.S. Department of Health and Human Services, Centers for Disease Control and Prevention, July 2005  
Anthropometric Survey of U.S. Army Personnel: Methods and Summary Statistics, Technical Report NATICK/TR-15./007 U.S. Army NATICK Soldier RD&E Center, 2014  
Woodson, W. Human Factors Design Handbook, 1981

## 2.6 Access Aids:

ABS Guide for Means of Access to Tanks and Holds for Inspection, April 2016 (Updated March 2018)  
International Maritime Organization (IMO) Guidelines for Safe Access to Tanker Bows, IMO Resolution MSC.62 (67) 1996  
International Maritime Organization (IMO) International Convention on Loadlines, 1966

## 2.7 Human-Computer Interface:

Defense Information Systems Agency (DISA) Common Operating Environment (COE) User Interface Specifications (UIS) 2003  
DOT/FAA/HF-STD-001B Ahlstrom, V. (2016) Human Factors Design Standard (HFDS). Atlantic City International Airport, NJ: Federal Aviation Administration William J. Hughes Technical Center  
ANSI/HFES Standard No. 100–2007 American National Standard for Human Factors Engineering of Computer Workstations, Human Factors and Ergonomics Society, Inc., Santa Monica, CA, 2007

## 2.8 Habitability:

ABS (February 2016) Guide for Crew Habitability on Ships  
Directive 2002/44/EC of the European Parliament and of the Council (25 June 2002) on the minimum health and safety requirements regarding the exposure of workers to the risks arising from physical agents (vibration)  
DNVGL-OS-A301, April 2016 DNV-GL Offshore Standard for Human Comfort  
International Maritime Organization (IMO) Resolution MSC.337(91) Code on Noise Levels on Board Ships  
IEC 1260:1995 Electroacoustics — Octave-band and fractional-octave-band filters  
ISO 2041:1990 Vibration and shock — Vocabulary  
ISO 2531:2009 Ductile iron pipes, fittings, accessories and their joints for water applications  
ISO 2631-1:1997 Mechanical vibration and shock — Evaluation of human exposure to whole-body vibration  
ISO 5805:1997 Mechanical vibration and shock — Human exposure — Vocabulary  
ISO 8041:1990 Human response to vibration — Measuring instrumentation

## 2.9 Labeling:

ANSI Z535.2 Environmental and Facility Safety Sign Standard  
ANSI Z535.3 Criteria for Safety Symbols  
Globally Harmonized System of Classification and Labelling of Chemicals (GHS)  
Peterson, R., Price, B., LaBrecque, J., Bass, D., and Ziemba, A., Development of Impact Injury Design Rule for High Speed Craft, Naval Surface Warfare Center, Panama City, FL, August 26, 2004

## 2.10 Material Handling:

Lifting: TLV Physical Agents, 7th edition, American Conference of Governmental Industrial Hygienists, 2005  
DOT/FAA/HF-STD-001B Ahlstrom, V. (2016). Human Factors Design Standard (HFDS). Atlantic City International Airport, NJ: Federal Aviation Administration William J. Hughes Technical Center  
Katrin Kroemer Elbert, Henrike Kroemer, Anne D. Kroemer Hoffman Ergonomics: How to Design for Ease and Efficiency, 3rd edition, 2018



2.11 *Maintenance:*

[MIL-HDBK-454](#) General Guidelines for Electronic Equipment

[MIL-STD-130](#) Department of Defense Standard Practice for Identification Marking of U.S. Military Property

2.12 *Communications:*

[DOT/FAA/HF-STD-001B](#) Ahlstrom, V. (2016). Human Factors Design Standard (HFDS). Atlantic City International Airport, NJ: Federal Aviation Administration William J. Hughes Technical Center

2.13 *Hazards and Safety:*

[ANSI/ASSP Z590.3-2011](#) Prevention Through Design Guidelines for Addressing Occupational Hazards and Risks in Design and Redesign Processes

[MIL-STD-882E](#) Department of Defense Standard Practice, System Safety

2.14 *Small Boat and High Speed Craft Appendix:*

[American Boat and Yacht Council \(2014\)](#) Reboarding Means, Ladders, Handholds, Rails and Lifelines (ABYC H-41)

[American Boat and Yacht Council \(2019\)](#) Field of Vision from the Helm Position (ABYC H-1)

[Dobbins, T., Rowley, I., and Campbell, L. \(2008\)](#) High Speed Craft Human Factors Design Guide (Report Number ABCD-TR-08-01 v1.0). UK MOD Defence Equipment and Support Agency (DE&S); Directorate of Sea Systems supported by the ABCD Working Group

[International Maritime Organization \(2000\)](#) Adoption of the International Code of Safety for High-Speed Craft: 2000 HSC Code (MSC.97(73))

[International Maritime Organization \(2000\)](#) Maritime Safety Committee Circular 982: Guidelines on Ergonomic Criteria for Bridge Equipment and Layout (MSC.1-Circ. 982)

[The International Organization for Standardization \(2007\)](#) Ship's bridge layout and associated equipment — Requirements and guidelines: Annex A (normative): Bridge layout for high speed craft (ISO 8468, 3rd edition)

[The International Organization for Standardization \(2016\)](#) Small craft – Principle data (ISO 8666, 2nd edition)

[The International Organization for Standardization \(2019\)](#) Small craft – Field of vision from the steering position (ISO 11591, 3rd edition)

[United States Coast Guard \(2001\)](#) Navigation and Vessel Inspection Circular Number 5-01

[Guidance for Enhancing the Operational Safety of Domestic High Speed Vessels \(COMDTPUB P16700.4\)](#)

2.15 *Slip-resistant Walking Surfaces:*

[ANSI A326.3](#) Test Method for Measuring Dynamic Coefficient of Friction of Hard Surface Materials

[EN 16165](#) Determination of slip resistance of pedestrian surfaces – Methods of evaluation

[Vessel Sanitation Program 2018 Construction Guidelines](#) U.S. Department of Health and Human Services, U.S. Public Health Service, CDC

[SA HB 198:2014 Handbook: Guide to the specification and testing of slip resistance of pedestrian surfaces, Standards Australia](#)

### 3. Terminology

#### 3.1 *Definitions of Terms Specific to This Standard:*

3.1.1 *accessible, adj*—an item is considered accessible when it can be operated, manipulated, inspected, serviced, removed, or replaced by the suitably clothed and equipped user with applicable body dimensions conforming to the anthropometric range and database specified by the procuring activity or, if not specified by the procuring activity, with applicable 5th to 95th percentile body dimensions as defined in Section 9.

##### 3.1.1.1 *Discussion*—

Applicable body dimensions are those dimensions that are design critical to the operation, manipulation, inspection, service, removal, or replacement task.

3.1.2 *advisory signal, n*—signal that indicates a safe or normal configuration, condition of performance, or operation of equipment or attracts attention and imparts information for routine action purposes.

3.1.3 *alarm, n*—visual or audible signal or both of a condition, or a predetermined out-of-tolerance condition, for machinery, equipment, components, or systems that require attention and response by a crewmember.

3.1.4 *alarm filtering, n*—technique by which unnecessary alarms are eliminated.

3.1.5 *alarm priority, n*—predicted assessment of the potential consequence of a condition or situation and the resulting urgency of mitigating responses required of personnel, that is, the more severe the potential consequence, the higher the alarm priority.

3.1.6 *alarm suppression, n*—(1) technique in which when a single-alarm event leads to subsequent alarm events (for example,

cascading alarms), the initiating alarm is presented but the subsequent events are not (that is, are suppressed); and (2) technique by which alarm messages are not displayed but are available to the user upon request.

3.1.7 *analog display, n*—type of display that shows the complete range of a measured parameter on a continuous scale and by means of a pointer, or equivalent, indicating an instantaneous value of the parameter on the scale.

3.1.8 *angle of inclination, n*—angle that the stair rises measured from the deck or surface on which the stair is sitting to the underside of the stair stringers.

3.1.9 *annunciator, n*—(1) type of transilluminated display that provides written text, pictorial data, or both to a user to show status or condition of a system or equipment; and (2) (also called a legend light) type of transilluminated display consisting of a light source located behind a cover that contains a printed label (that is, legend).

3.1.9.1 *Discussion*—

The color of the light (usually red, green, white, or blue), whether it is ON or OFF, and the printed label all provide information to the operator about the status of a piece of equipment or system.

3.1.10 *anthropometrics, n*—(1) study of the physical size, strength, and range of motion of the human body and the application of that data to the design of systems, equipment, workspaces, and tools to maximize human performance and safety in a work setting; and (2) measurement of human variability of body dimensions and strength as a function of gender, race, and regional origin.

3.1.11 *anti-two-block alarm, n*—alarm used to warn a crane operator of the impending collision of the traveling block and crane tip sheave.

3.1.12 *articulation index (AI), n*—technique used to measure how intelligible (that is, understandable) spoken words are that are received over communication equipment and is expressed as a percentage of speech units that are understood by a listener when heard out of context.

3.1.13 *assembly, n*—number of parts or subassemblies or any combination thereof joined together to perform a specific function and capable of disassembly.

3.1.13.1 *Discussion*—

The distinction between an assembly and a subassembly is determined by the individual application. An assembly in one instance may be a subassembly in another in which it forms a portion of an assembly.

3.1.14 *assisted lifting devices, n*—items such as cranes, hoists, mobile A-frame and hydraulic jacking units, monorails, trolleys, or padeyes used by individuals to lift or move materials and equipment or both that is too heavy for direct manual lifting or carrying.

3.1.15 *audible alarm, n*—alarm comprised of tones, verbal messages, or verbal messages combined with tones and not all audible alarms are associated with visual alarms.

3.1.16 *auditory display, n*—device that provides readings, status, or condition of machinery, equipment, or system-operating parameters through the use of sound signals or spoken messages.

3.1.17 *band pass, n*—electronic filter designed to respond only to selected audio frequencies while blocking all other frequencies.

3.1.17.1 *Discussion*—

Commonly used in telephones.

3.1.18 *binaural, n*—sound coming to a headset from dual channels or signal paths with a different channel or signal path presented to each headset.

3.1.19 *case, n*—part of an item of equipment that encloses and protects the equipment from its surroundings and protects the surroundings—including personnel—from the equipment.

3.1.20 *caution signal, n*—signal that indicates the existence of a condition requiring attention but not immediate action.

3.1.21 *coaming, n*—vertical steel plate extending up 50 to 76 mm (2 to 3 in.) from the deck and placed around equipment or other areas in which liquids (for example, oil, water, grey or black water, and oily water) could be spilled to contain the liquids within a confined area.

3.1.22 *color pad, n*—area on a console or panel face that is shaded a different color than the panel itself to highlight a set of controls, displays, or alarms, or combination thereof, that are related in some manner.

3.1.23 *command, n*—instructions that cause a device to perform some action.

3.1.24 *command language, n*—limited programming language used strictly for executing a series of commands (for example, Linux or any DOS shells).

3.1.25 *console, n*—group of controls and displays associated with one or more individual pieces of equipment or systems mounted together on a structure dedicated to the control and monitoring of the individual equipment or systems.

3.1.25.1 *Discussion*—

Consoles may be freestanding units and include angled and vertical surfaces.

3.1.26 *continuous control, n*—continuous control is an actuator that operates at any point or value along a continuous scale (for example, engine throttle).

3.1.27 *contrast ratio, n*—ratio of the differences in luminance between the item on a video display and the background.

3.1.28 *control, n*—(1) any switch, pushbutton, knob, lever, keyboard, mouse, or other device manually manipulated by the operator/maintainer to alter or maintain the status of a particular piece of equipment or system; and (2) a device an operator or maintainer uses to input a signal, change the operating status of equipment or systems, or to manipulate displayed data. Examples include switches, knobs, cranks, thumbwheels, levers, keyboards, and foot pedals.

3.1.29 *cursor, n*—marker on the display screen that indicates the position where the computer expects the next input or will display the next output.

3.1.29.1 *Discussion*—

The cursor may be positioned by the computer or by the user.

3.1.30 *danger signal, n*—signal that indicates the existence of a hazardous condition requiring immediate action to prevent loss of life, major equipment damage or environmental contamination, or serious loss of mission capability.

3.1.31 *dead-man switch, n*—control that automatically stops machinery or systems from operating once the control is released by the operator.

3.1.32 *dependent symbol, n*—symbols that alone do not impart any specific information to the user but require the existence of supporting data to provide useful information.

3.1.33 *detent control, n*—(1) type of discrete control, characterized by the control locking into each position setting until the operator exerts extra force to move the control out of the setting.

3.1.33.1 *Discussion*—

These types of controls are preferable for machinery equipment or system operation requiring control in discrete steps or different modes.

(2) type of discrete control in which each control position setting is identified by a audible click and the control “locks” into that position setting until the operator exerts extra force to move the control out of that setting and into the next one.

3.1.34 *digital display, n*—type of display that uses numeric characters to provide an instantaneous value of a parameter.

3.1.35 *directly accessible, adj*—to be directly accessible, an object, space, component, or piece of equipment shall be in an area reachable without having to use tools or disassemble an access opening; be clear of, or protected from, obstructions, moving

equipment, hot surfaces, or other obstructions that would prevent safe contact by the user; allow the user to get as close as necessary (for example, arm's reach) to perform the required tasks; be reachable by means of a permanent access; and allow all of the above by a person wearing the required protective clothing and carrying tools, spare parts, and test equipment as required.

3.1.36 *directly visible, adj*—a directly visible object (for example, control, display, hazard warning, and so forth) shall not be located behind a door or other closure cover and shall be readable from the normal user position within the provided ambient lighting and from a position that does not require the reader to stand on pipes, cable trays, structural members, or other surfaces not intended to be a regular working surface or assume awkward body postures.

3.1.37 *discrete control, n*—actuator that allows for the selection between two or more mutually exclusive operating functions or points along a scale (for example, switching a machine ON or OFF or selecting one of three pumps to run).

3.1.38 *displacement joystick, n*—joystick that moves out of the detent in the direction it is pushed.

3.1.38.1 *Discussion*—

Displacement joysticks are usually spring-loaded so that they return to a neutral center (detent) position.

3.1.39 *display, n*—any gauge, light counter, printer, annunciator, sight glass, horn, siren, digital counter, cathode ray tube (CRT) screen, or any other device that provides visual or auditory information to the human operator/maintainer about the status of a piece of equipment or system.

3.1.40 *dynamic display, n*—display screen that is, or has portions within that are, updated on a regular basis, primarily alphanumeric values.

3.1.41 *emergency shutdown stations (ESDs), n*—manual controls that are located throughout a ship or maritime structure that shut down equipment, systems, or complete structures and initiate an alarm at the same time.

3.1.42 *fixed ladder, n*—ladder permanently attached to a structure, building, or equipment.

3.1.43 *foot candle (fc, lm/ft<sup>2</sup> or ft-c), n*—a non-SI measure of light intensity or illuminance, the amount of light striking a surface, in lumens per square foot. One foot candle is equal to approximately 10.76 lux (the corresponding SI unit).

3.1.44 *foot lambert (fl or ft-L), n*—a non-SI measure of luminance, the amount of light reflected from a surface. A foot-lambert equals  $1/\pi$  candela per square foot, or 3.426 candela per square metre (the corresponding SI unit).

3.1.45 *flicker, n*—perception of rapid fluctuations in luminance levels characterized by an impression of jerky movements.

3.1.46 *function keys, n*—labeled keys that serve as keyboard shortcuts (for example, F1, F2, F3, or with the function name such as Delete or Insert) by combining in one key the actions of a sequence of individual keys.

3.1.47 *general emergency alarms, n*—alarm given in the case of an emergency involving all persons on a vessel or other maritime facility and these alarms sound throughout a vessel or maritime installation and are intended to be heard by all personnel.

3.1.47.1 *Discussion*—

General emergency alarms relate to conditions of a serious nature such as announcing a fire or flooding, demanding evacuation of an area, or demanding abandonment of a vessel or installation.

3.1.48 *glare, n*—luminance or amount of light-per-unit area emitted or reflected from a surface, within a specific area of personnel's field of view, that is greater than the luminance to which the eye is adjusted compared to the remainder of the field of view.

3.1.49 *graphic label, n*—type of label used to present information through line schematics, diagrams, charts, tables, and pictures.

3.1.50 *handle or handgrab, n*—U-shaped bar attached directly to bulkheads or other structures used by a person to hold onto where handholds are required such as when passing through hatches or lightening holes or climbing vertically through deck openings.

3.1.51 *handrail*, *n*—vertical barrier consisting of two or more horizontal rails connected to vertical stanchions that are erected along exposed edges of floor openings, wall openings, ramps, steps, platforms, and walkways to prevent a person from falling from one elevation to another.

3.1.52 *hazard identification sign*, *n*—type of sign used to identify and provide information about situations that may be hazardous to personnel, equipment, or the environment; there are two types of hazards: “DANGER” and “CAUTION.”

3.1.53 *hazard label*, *n*—type of label used to identify and provide information about situations that may be hazardous to personnel, equipment, or the environment and only two types of hazards should be allowed, that is, “DANGER” and “CAUTION,” based on the following criteria.

3.1.53.1 *DANGER*—used where the hazard could result in serious injury or death to a person, serious damage to vital equipment, or a major environmental problem.

3.1.53.2 *CAUTION*—used where the hazard could result in a minor injury to a person, minor damage to the equipment, or a minor environmental problem.

3.1.54 *hierarchical menus*, *n*—large series of options or menus that are organized as a multilevel, branching structure in which an option in a higher-level menu is the name of another menu at the next lower level and the options in the lowest-level menus are not the names of other menus.

3.1.55 *human engineering (ergonomics)*, *n*—scientific discipline concerned with the understanding of interactions among humans and other elements of a system and the profession that applies theory, principles, data, and methods to design to optimize human well-being and overall system performance.

3.1.56 *human machine interface (HMI)*, *n*—means by which humans and machines/computers communicate/work with each other to control and operate systems.

3.1.57 *human systems integration (HSI)*, *n*—systems engineering discipline that is focused on human performance, human skills and training, manpower, personnel survivability, health and safety, and quality of life at sea.

3.1.58 *hyperlinks*, *n*—text that provides the capability to, when selected using a pointing device or ENTER key, direct the user to another location within the window or another window.

3.1.58.1 *Discussion*—  
Hyperlinks are generally indicated by textual formats such as alternate text color or underlining or both.

3.1.59 *icon*, *n*—picture or drawing that represents an actual piece of equipment or system on the ship or maritime structure.

3.1.60 *identification label*, *n*—type of label used to: (1) identify, and be placed on, all individual equipment or components, for example, valves, gauges, junction boxes, filters, pumps, sensor, consoles, transmitters, pressure vessels, control panels, local motor controllers, fans, heaters, cabinets, lockers, and all other items used by the crew for operation, maintenance, or habitability use; (2) identify spaces (for example, rooms, compartments, open deck areas, buildings, tanks, voids, or any area in which the crew may enter); and (3) identify individual controls, displays, alarms, or groups thereof as shown in Section 8 that appear on consoles, control panels, or are individually mounted.

3.1.61 *independent symbol*, *n*—pictorial representation that alone provides information to personnel without requiring elaboration by supporting text.

3.1.62 *individual rung ladder*, *n*—fixed ladder, each rung of which is individually attached to a structure, building, or equipment rather than to ladder stringers.

3.1.63 *information label or placard*, *n*—type of label or placard used to present nonprocedural information of a general nature related to health, first aid, sanitation, rules, housekeeping, and general conduct.

3.1.64 *instruction label, n*—instruction label provides step-by-step instructions for accomplishing a specific task (operation or maintenance related) along with hazard and safety information related to performing the task.

3.1.65 *isometric joystick, n*—joystick that has no perceptible movement but output is a function of applied force.

3.1.66 *jitter, n*—interference in electron-gun displays (for example, CRT displays) as a result of magnetic fields from other devices such as motors and generator sets.

3.1.67 *keyboard lockout, n*—state determined by an application in which the application does not accept input from the keyboard.

3.1.68 *kickout panel, n*—part of a joiner bulkhead or wall that is marked and designed especially to be “kicked out” and used as an emergency escape exit.

3.1.69 *label, n*—term, when used alone, shall mean any type of plate, sign, placard, inscription, legend, marking, or combination of these, that is used for purposes of identification or to impart visual information or instructions to the reader.

3.1.69.1 *Discussion*—

This term is used generically herein to describe all the specific types of labels described in Section 15.

3.1.70 *ladder, n*—appliance consisting of two side rails (that is, stringers) joined at regular intervals by crosspieces called rungs, or steps, on which a person steps during ascent or descent of the ladder from one elevation to another.

3.1.71 *legible, adj*—defines the state in which alphanumeric characters or other written information is presented in a form such that each character or number is recognized as being different from the other.

3.1.72 *lighted pushbutton, n*—type of annunciator in which the pushbutton lights up when it is pushed and goes off when the button is pushed again.

3.1.72.1 *Discussion*—

The pushbutton serves as a control and display since the light indicates the status (that is, ON or OFF, OPEN or CLOSED, and so forth) of the controlled item.

<https://standards.iteh.ai/catalog/standards/sist/c28ce371-5eac-471a-bd8b-999a7c15874d/astm-f1166-22>

3.1.73 *lightening hole, n*—hole (often oval in shape) cut in the steel structure of an inner-bottom plate at specific locations so as to reduce the weight of the ship without degrading its structural integrity; allow liquids that might be in a tank or hold to move freely; and provide personnel access from one tank or space to another for maintenance, repair, and construction purposes.

3.1.74 *local operating alarms, n*—alarms located within specific operating spaces close to the equipment or systems they monitor.

3.1.75 *luminance, n*—total light emitted from a video display calculated on the basis of the brightest portion or average level over the entire area of video display.

3.1.76 *maintainability, design for, n*—design decisions made directed toward achieving those combined characteristics of equipment and facilities that will enable the accomplishment of necessary maintenance quickly, safely, accurately, and effectively with minimum requirements for personnel, skills, special tools, and cost.

3.1.77 *maintenance, n*—all actions necessary for retaining material in (or restoring it to) a condition capable of a specified level of performance.

3.1.77.1 *Discussion*—

Maintenance includes inspecting, servicing, removal, replacement, repair, modification, modernization, overhaul, condition determination, corrosion control, and initial provisioning of support items.

3.1.78 *manual material handling, v*—act of a person physically lifting, carrying, pushing, pulling, or holding any item or load as a part of performing any duty.



3.1.79 *may, v*—term is used in this practice to mean that the related criteria can or cannot be used at the discretion of the designer without the procuring authority or organization being notified.

3.1.80 *menu, n*—list of options from which a user makes a selection or selections.

3.1.81 *modified rhyme test (MRT), n*—another technique used to measure how intelligible spoken words are that are received over communication equipment.

3.1.82 *monaural, n*—sound coming to a headset from a single channel or signal path.

3.1.83 *multi-rotation control, n*—a control device such as a knob, crank, or handwheel which allows for adjustment over more than 360 degrees of rotation where precise settings are required over a wide range of adjustment.

3.1.84 *noise-canceling microphone, n*—design feature that reduces the masking effect of ambient noise upon speech impressed on a microphone to make the speaker's voice more intelligible.

3.1.85 *normal line of sight, n*—line drawn from the human eye to a visual object, such as a gauge or panel, which is 15° below horizontal as a result of the downward tilt of the human head under normal conditions.

3.1.86 *nose or nosing, n*—that portion of a tread projecting beyond the face of the tread immediately below.

3.1.87 *open riser, n*—air space between treads of a stairway without upright members (risers) between the treads.

3.1.88 *palettes (graphic menus), n*—set of unlabeled symbols, typically presented within small rectangles in which the symbols may be icons, patterns, characters, or drawings that represent an operation.

3.1.88.1 *Discussion*—

Palettes are used widely in drawing and painting packages but are commonly found in word-processing applications as well.

3.1.89 *panel, n*—(1) any surface in which controls, displays, or alarms, or combination thereof, relating to equipment or system conditions are placed.

3.1.89.1 *Discussion*—

Panels typically are flat vertical surfaces. Panels are sometimes referred to as control boards.

(2) concentration of individual controls and displays used to operate one or more pieces of equipment, usually mounted on a flat plate attached to, or located near, the equipment itself.

3.1.90 *panel and console labels, n*—labels that appear on operator consoles and panels to identify individual controls or displays or groups of controls and displays.

3.1.91 *peak clipping, v*—simple form of signal processing that limits the amplitude of signals that exceed a predetermined level to prevent the audio output from being too loud and causing listener discomfort.

3.1.92 *percentile, n*—given the range of variability of (human) bodily dimensions, anthropometric data are typically expressed as percentile statistics, such as 5th or 95th percentile and a percentile statistic defines the anthropometric point at which a percentage of a population falls above or below that value.

3.1.92.1 *Discussion*—

For example, the seated eye height of a 95th percentile North American male is 853 mm (33.5 in.), so, by definition, 5 % of North American males will have a seated eye height of greater than this figure, and 95 % will have a lesser seated eye height.

3.1.93 *permanent access, n*—means of access (for example, walkway, passageway, stair, ladder, platform, clear deck area, and so forth) shall be a permanent structure (that is, not portable) firmly secured in place or kept clear of any obstruction or both and always immediately available for use without requiring the operator to reconfigure structures.