



Designation: **F3173/F3173M – 21a F3173/F3173M – 23**

Standard Specification for Aircraft Handling Characteristics¹

This standard is issued under the fixed designation F3173/F3173M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reappraisal. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reappraisal.

1. Scope

1.1 This specification addresses the airworthiness requirements for aeroplane handling characteristics in flight and on ground and water.

1.2 The material was developed through open consensus of international experts in general aviation. This information was created by focusing on Normal Category aeroplanes; however, the content may be more broadly applicable, and should not be unduly limited. The topics covered within this specification are: Flight Characteristics, ~~Trim Requirements, Stability Requirements, Controllability, Trim, Stability,~~ Ground and Water Handling Characteristics, ~~Vibration and~~ Vibration, Buffet, and High-Speed High-speed Characteristics.

1.3 An applicant intending to propose this information as Means of Compliance for a design approval must seek guidance from their respective oversight authority (for example, published guidance from applicable CAAs) concerning the acceptable use and application thereof. For information on which oversight authorities have accepted this specification (in whole or in part) as an acceptable Means of Compliance to their regulatory requirements (hereinafter “the Rules”), refer to the ASTM Committee F44 web page (www.astm.org/COMMITTEE/F44.htm). **Annex A1** maps the Means of Compliance of the ASTM standards to EASA CS-23, amendment 5, or later, and FAA 14 CFR Part 23, amendment 64, or later, rules.

1.4 *Units*—This specification may present information in either SI units, English Engineering units, or both; the values stated in each system are not necessarily exact equivalents; therefore, to ensure conformance with the standard, each system shall be used independently of the other, and values from the two systems shall not be combined.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.6 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 ASTM Standards:²

[F3060 Terminology for Aircraft](#)

[F3061/F3061M Specification for Systems and Equipment in Aircraft](#)

¹ This specification is under the jurisdiction of ASTM Committee F44 on General Aviation Aircraft and is the direct responsibility of Subcommittee F44.20 on Flight. Current edition approved Sept. 1, 2024/May 1, 2023. Published September 2024/June 2023. Originally approved in 2021. Last previous edition approved in 2021 as F3173/F3173M/F3173/F3173M – 21a, –21. DOI: 10.1520/F3173_F3173M-21A.10.1520/F3173_F3173M-23.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard’s Document Summary page on the ASTM website.

[F3116/F3116M Specification for Design Loads and Conditions](#)
[F3174/F3174M Specification for Establishing Operating Limitations and Information for Aeroplanes](#)
[F3179/F3179M Specification for Performance of Aircraft](#)
[F3232/F3232M Specification for Flight Controls in Small Aircraft](#)
[F3233/F3233M Specification for Flight and Navigation Instrumentation in Aircraft](#)

2.2 *EASA Standard*:³

[EASA CS-23 Normal, Utility, Aerobatic and Commuter Aeroplanes](#)

2.3 *FAA Standard*:⁴

[14 CFR Part 23 Airworthiness Standards: Normal Category Airplanes](#)

3. Terminology

3.1 Refer to Terminology [F3060](#) referenced in Section 2.

4. Flight Characteristics ~~Characteristics~~—General

4.1 *General*—Unless otherwise specified in a specific requirement, the aeroplane shall meet the requirements of ~~4.2–4.9~~, Sections ~~5–8~~, ~~9.1~~, and ~~9.29.1–9.4~~ at all practical loading conditions and operating altitudes for which certification has been requested, not exceeding that established in ~~Maximum Operating Altitude~~ Specification [F3174/F3174M](#) *Maximum Operating Altitude* and without requiring exceptional piloting skill, alertness, or strength.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ASTM F3173/F3173M-23](#)

<https://standards.iteh.ai/catalog/standards/sist/718a761b-e3df-49ff-a2f0-69b7de872ee7/astm-f3173-f3173m-23>

³ Available from European Union Aviation Safety Agency (EASA), Konrad-Adenauer-Ufer 3, D-50668 Cologne, Germany, <https://www.easa.europa.eu>.

⁴ Available from Federal Aviation Administration (FAA), 800 Independence Ave., SW, Washington, DC 20591, <http://www.faa.gov>.

~~4.2 Control Forces:~~

~~4.2.1 The aeroplane shall be safely controllable and maneuverable during all flight phases including:~~

~~4.2.1.1 Takeoff;~~

~~4.2.1.2 Climb;~~

~~4.2.1.3 Level flight;~~

~~4.2.1.4 Descent;~~

~~4.2.1.5 Go-around; and~~

~~4.2.1.6 Landing (power on and idle power) with the wing flaps extended and retracted.~~

~~4.2.2 It shall be possible to make a smooth transition from one flight condition to another (including turns and slips) without danger of exceeding the limit load factor under any probable operating condition (including, for multiengine aeroplanes, those conditions normally encountered in the sudden critical loss of thrust):~~

~~4.2.3 If marginal conditions exist with regard to required pilot strength, the control forces necessary shall be determined by quantitative tests. In no case may the control forces under the conditions specified in 4.2.1 and 4.2.2 exceed those prescribed in Table 1.~~

iTeh Standards

TABLE 1 Control Forces

Level 1 Aeroplanes With $V_{S0} \leq 45$ KCAS			
Control	Longitudinal	Lateral	Directional
(a) For temporary application:	—	—	—
Stick	200 N [45 lbf]	100 N [22 lbf]	—
Wheel	250 N [56 lbf]	200 N [45 lbf]	—
Rudder pedal	—	—	400 N [90 lbf]
(b) For prolonged application:	20 N [4 lbf]	15 N [3 lbf]	100 N [22 lbf]
Level 1 Aeroplanes With $V_{S0} > 45$ KCAS and Level 2, 3 and 4 Aeroplanes			
Control	Longitudinal	Lateral	Directional
(a) For temporary application:	—	—	—
Stick	267 N [60 lbf]	133 N [30 lbf]	—
Wheel (two hands on rim)	334 N [75 lbf]	222 N [50 lbf]	—
Wheel (one hand on rim)	222 N [50 lbf]	111 N [25 lbf]	—
Rudder pedal	—	—	667 N [150 lbf]
(b) For prolonged application:	44 N [10 lbf]	22 N [5 lbf]	89 N [20 lbf]

~~4.3 Longitudinal Control:~~

~~4.3.1 With the aeroplane as nearly as possible in trim at $1.3 V_{S1}$, it shall be possible, at speeds below the trim speed, to pitch the nose downward so that the rate of increase in airspeed allows prompt acceleration to the trim speed with:~~

~~4.3.1.1 Maximum continuous power on each engine;~~

~~4.3.1.2 Idle power; and~~

~~4.3.1.3 Wing flap and landing gear:~~

~~(1) Retracted and~~

~~(2) Extended.~~

~~4.3.2 Unless otherwise required, it shall be possible to carry out the following maneuvers without requiring the application of single-handed control forces exceeding those specified in Table 1. The trimming controls shall not be adjusted during the maneuvers:~~

4.3.2.1 With the landing gear extended, the flaps retracted, and the aeroplane as nearly as possible in trim at $1.4 V_{S1}$, extend the flaps as rapidly as possible and allow the airspeed to transition from $1.4 V_{S1}$ to $1.4 V_{S0}$:

- (1) With power idle and
- (2) With the power necessary to maintain level flight in the initial condition.

4.3.2.2 With landing gear and flaps extended, idle power, and the aeroplane as nearly as possible in trim at $1.3 V_{S0}$, quickly apply takeoff power and retract the flaps as rapidly as possible to the recommended go-around setting and allow the airspeed to transition from $1.3 V_{S0}$ to $1.3 V_{S1}$. Retract the gear when a positive rate of climb is established.

4.3.2.3 With landing gear and flaps extended, power necessary to maintain level flight at $1.1 V_{S0}$ and the aeroplane as nearly as possible in trim, it shall be possible to maintain approximately level flight while retracting the flaps as rapidly as possible with simultaneous application of maximum continuous power. Power must not be reduced during the level acceleration unless a flap speed exceedance (V_{FE} of the initial position) is imminent. The maneuver is completed when the flaps have reached the selected position and the airspeed is not less than $1.3 V_{S1}$. If gated flap positions are provided, the flap retraction may be demonstrated in stages with power and trim reset for level flight at $1.1 V_{S1}$, in the initial configuration for each stage:

- (1) From the fully extended position to the most extended gated position;
- (2) Between intermediate gated positions, if applicable; and
- (3) From the least extended gated position to the fully retracted position.

4.3.2.4 With idle power, flaps and landing gear retracted and the aeroplane as nearly as possible in trim at $1.4 V_{S1}$, apply takeoff power rapidly while maintaining the same airspeed.

4.3.2.5 With idle power, landing gear and flaps extended, and the aeroplane as nearly as possible in trim at V_{REF} , obtain and maintain airspeeds between $1.1 V_{S0}$ and either $1.7 V_{S0}$ or V_{FE} , whichever is lower without requiring the application of two-handed control forces exceeding those specified in [Table 1](#).

4.3.2.6 With maximum takeoff power, landing gear retracted, flaps in the takeoff position, and the aeroplane as nearly as possible in trim at V_{FE} appropriate to the takeoff flap position, retract the flaps as rapidly as possible while maintaining constant speed.

4.3.3 At speeds above $V_{MO}/M_{MO}/V_{NE}$, and up to the maximum speed shown under [8.1](#):

4.3.3.1 For Level 1 aeroplanes with $V_{S0} \leq 45$ KCAS, it must be possible to raise the nose at all permitted e.g. positions and engine powers:

4.3.3.2 For Level 1 aeroplanes with $V_{S0} > 45$ KCAS and Level 2, 3, and 4 aeroplanes, a maneuvering capability of 1.5 g shall be demonstrated to provide a margin to recover from upset or inadvertent speed increase.

4.3.4 For Level 1 aeroplanes with $V_{S0} > 45$ KCAS and Level 2, 3, and 4 aeroplanes, it shall be possible, with a pilot control force of not more than 45 N [10 lbf], to maintain a speed of not more than V_{REF} during an idle power glide with landing gear and wing flaps extended, for any weight of the aeroplane, up to and including the maximum weight.

4.3.5 For Level 1 aeroplanes with $V_{S0} > 45$ KCAS and Level 2, 3, and 4 aeroplanes, by using normal flight and power controls, except as otherwise noted in [4.3.5.1](#) and [4.3.5.2](#), it shall be possible to arrest the rate of descent to zero at an attitude suitable for a controlled landing without exceeding the operational and structural limitations of the aeroplane, as follows:

4.3.5.1 For single-engine aeroplanes and multiengine aeroplanes, without the use of the primary longitudinal control system; and

4.3.5.2 For multiengine aeroplanes:

- (1) Without the use of the primary directional control and
- (2) If a single failure of any one connecting or transmitting link would affect both the longitudinal and directional primary control system, without the primary longitudinal and directional control system.

4.3.6 For Level 1 aeroplanes with $V_{S0} \leq 45$ KCAS, for any trim setting required under [5.3.1](#), it must be possible to takeoff, climb, descend, and land the aeroplane in required configurations with no adverse effect and with acceptable forces.

4.4 Directional and Lateral Control:

~~4.4.1 For each multiengine aeroplane, it shall be possible, while holding the wings level within 5°, to make sudden changes in heading safely in both directions. This ability shall be shown at 1.4 V_{SI} with heading changes up to 15°, except that the heading change at which the rudder force corresponds to the limits specified in Table 1 need not be exceeded, with the:~~

~~4.4.1.1 Critical loss of thrust and its propeller in the minimum drag position;~~

~~4.4.1.2 Remaining engines at maximum continuous power;~~

~~4.4.1.3 Landing gear:~~

~~(1) Retracted, and~~

~~(2) Extended.~~

~~4.4.1.4 Flaps retracted.~~

~~4.4.2 For each multiengine aeroplane, it shall be possible to regain full control of the aeroplane without exceeding a bank angle of 45°, reaching a dangerous attitude, or encountering dangerous characteristics in the event of a sudden and complete loss of critical thrust, making allowance for a delay of 2 s in the initiation of recovery action appropriate to the situation, with the aeroplane initially in trim, in the following condition:~~

~~4.4.2.1 Maximum continuous power on each engine;~~

~~4.4.2.2 The wing flaps retracted;~~

~~4.4.2.3 The landing gear retracted;~~

~~4.4.2.4 A speed equal to that at which compliance with Specification **F3179/F3179M En Route Climb/Descent: All Engines Operating** has been shown, and~~

~~4.4.2.5 All propeller controls in the position at which compliance with Specification **F3179/F3179M En Route Climb/Descent: All Engines Operating** has been shown.~~

~~4.4.3 For Level 1 aeroplanes with $V_{SO} > 45$ KCAS and Level 2, 3, and 4 aeroplanes, it shall be shown that the aeroplane is safely controllable without the use of the primary lateral control system in any all-engine configuration(s) and at any speed or altitude within the approved operating envelope. It shall also be shown that the aeroplane's flight characteristics are not impaired below a level needed to permit continued safe flight and the ability to maintain attitudes suitable for a controlled landing without exceeding the operational and structural limitations of the aeroplane. If a single failure of any one connecting or transmitting link in the lateral control system would also cause the loss of additional control system(s), compliance with the above requirement shall be shown with those additional systems also assumed to be inoperative.~~

~~4.5 Minimum Control Speed:~~

~~4.5.1 V_{MC} is the calibrated airspeed at which, following a sudden critical loss of thrust, it is possible to maintain control of the aeroplane with the failed components of the propulsion system remaining inoperative. Thereafter, it shall be possible to maintain straight flight at the same speed with an angle of bank of not more than 5°. The method used to simulate critical loss of thrust shall represent the most critical mode of powerplant failure expected in service with respect to controllability.~~

~~4.5.2 V_{MC} for takeoff shall not exceed 1.2 V_{SI} , where V_{SI} is determined at the maximum takeoff weight.~~

~~4.5.3 V_{MC} shall be determined with the most unfavorable weight and center-of-gravity position and the aeroplane airborne and the ground effect negligible, for the takeoff configuration(s) with:~~

~~4.5.3.1 Maximum available takeoff power initially on each engine;~~

~~4.5.3.2 The aeroplane trimmed for takeoff;~~

~~4.5.3.3 Flaps in the takeoff position(s);~~

~~4.5.3.4 Landing gear retracted; and~~

~~4.5.3.5 All propeller controls in the recommended takeoff position throughout.~~

~~4.5.4 For all aeroplanes except low-speed Level 1 and 2 aeroplanes, the conditions of 4.5.1 shall also be met for the landing configuration with:~~

~~4.5.4.1 Maximum available takeoff power initially on each engine;~~

~~4.5.4.2 The aeroplane trimmed for an approach, with all engines operating, at V_{REF} , at an approach gradient equal to the steepest used in the landing distance demonstration of Specification **F3179/F3179M** *Landing Distance*;~~

~~4.5.4.3 Flaps in the landing position;~~

~~4.5.4.4 Landing gear extended; and~~

~~4.5.4.5 All propeller controls in the position recommended for approach with all engines operating.~~

~~4.5.5 A minimum speed to render the critical engine inoperative intentionally shall be established and designated as the safe, intentional, one-engine-inoperative speed (V_{SSE}).~~

~~4.5.6 At V_{MC} , the rudder pedal force required to maintain control shall not exceed the temporary rudder pedal force limit specified in **Table 1** and it shall not be necessary to reduce power of the operative engine(s). During the maneuver, the aeroplane shall not assume any dangerous attitude and it shall be possible to prevent a heading change of more than 20°.~~

~~4.5.7 At the option of the applicant, to comply with the requirements of Specification **F3179/F3179M** *Takeoff Speed*, V_{MCG} may be determined. V_{MCG} is the minimum control speed on the ground and is the calibrated airspeed during the takeoff run at which, following a sudden critical loss of thrust, it is possible to maintain control of the aeroplane using the rudder control alone (without the use of nose wheel steering) as limited by the temporary rudder pedal force limit specified in **Table 1** and using the lateral control to the extent of keeping the wings level to enable the takeoff to be safely continued. In the determination of V_{MCG} , assuming that the path of the aeroplane accelerating with all engines operating is along the centerline of the runway, its path from the point at which the critical engine is made inoperative to the point at which recovery to a direction parallel to the centerline is completed may not deviate more than 9.1 m [30 ft] laterally from the centerline at any point. V_{MCG} shall be established with:~~

~~4.5.7.1 The aeroplane in each takeoff configuration or, at the option of the applicant, in the most critical takeoff configuration;~~

~~4.5.7.2 Maximum available takeoff power on the operating engines;~~

~~4.5.7.3 The most unfavorable center of gravity position;~~

~~4.5.7.4 The aeroplane trimmed for takeoff; and~~

~~4.5.7.5 The most unfavorable weight in the range of takeoff weights.~~

~~4.6 *Aerobic Maneuvers*—Each aerobic aeroplane shall be able to perform safely the aerobic maneuvers for which certification is requested. Safe entry speeds for successful completion of these maneuvers shall be determined.~~

~~4.7 *Control during Landings*—It shall be possible, while in the landing configuration, to complete a landing without causing substantial damage or serious injury. The one-hand control force limits specified in **Table 1** shall not be exceeded following an approach to land.~~

~~4.7.1 At a speed of V_{REF} minus 5 knots;~~

~~4.7.2 With the aeroplane in trim, or as nearly as possible in trim and without the trimming control being moved throughout the maneuver;~~

~~4.7.3 At an approach gradient equal to:~~



4.7.3.1 For Level 1 aeroplanes with $V_{S0} \leq 45$ KCAS, that resulting from an approach at idle power, or

4.7.3.2 For Level 1 aeroplanes with $V_{S0} > 45$ KCAS and Level 2, 3, and 4 aeroplanes, the steepest used in the landing distance demonstration of Specification ~~F3179/F3179M~~ *Landing Distance*.

4.7.4 With only those power changes, if any, that would be made when landing normally from an approach at V_{REF} .

4.8 ~~Elevator Control Force in Maneuvers:~~

4.8.1 The elevator control force needed to achieve the positive limit maneuvering load factor shall not be less than:

4.8.1.1 For wheel controls, $W/10$ N (where W is the maximum mass in kg) [$W/100$ lbf (where W = maximum weight in lbf)] or 89 N [20 lbf], whichever is greater, except that it need not be greater than 222 N [50 lbf], or

4.8.1.2 For stick controls, $W/14$ N (where W is the maximum mass in kg) [$W/140$ lbf (where W = maximum weight in lbf)] or 67 N [15 lbf], whichever is greater, except that it need not be greater than 156 N [35 lbf].

4.8.2 The requirement of 4.8.1 shall be met at 75 percent of maximum continuous power for reciprocating engines, or the maximum continuous power for turbine engines and with the wing flaps and landing gear retracted:

4.8.2.1 In a turn, with the trim setting used for wings level flight at V_0 , and

4.8.2.2 In a turn, with the trim setting used for the maximum wings level flight speed, except that the speed may not exceed V_{NE} or V_{MO}/M_{MO} , whichever is appropriate.

4.8.3 There shall be no excessive decrease in the gradient of the curve of stick force versus maneuvering load factor with increasing load factor.

4.9 ~~Rate of Roll:~~

4.9.1 ~~Takeoff~~—It shall be possible, using a favorable combination of controls, to roll the aeroplane from a steady 30° banked turn through an angle of 60°, so as to reverse the direction of the turn within:

4.9.1.1 For an aeroplane of 2722 kg [6000 lb] or less maximum weight, 5 s from initiation of roll and

4.9.1.2 For an aeroplane of over 2722 kg [6000 lb], $(W + 200) / 590$ s where W is the weight in kg [$(W + 500) / 1300$ s where W = weight in lbs] but not more than 10 s.

4.9.2 The requirement of 4.9.1 shall be met when rolling the aeroplane in each direction with:

4.9.2.1 Flaps in the takeoff position;

4.9.2.2 Landing gear retracted;

4.9.2.3 For a single-engine aeroplane, at maximum takeoff power, and a multiengine aeroplane with the critical loss of thrust with the affected propeller(s) in the minimum drag position and the other engines at maximum takeoff power; and

4.9.2.4 The aeroplane trimmed, or trimmed as nearly as possible, in straight flight at a speed equal to the greater of $1.2 V_{S1}$ or $1.1 V_{MC}$.

4.9.3 ~~Approach~~—It shall be possible, using a favorable combination of controls, to roll the aeroplane from a steady 30° banked turn through an angle of 60°, so as to reverse the direction of the turn within:

4.9.3.1 For an aeroplane of 2722 kg [6000 lb] or less maximum weight, 4 s from initiation of roll and

4.9.3.2 For an aeroplane of over 2722 kg [6000 lb] maximum weight, $(W + 1300) / 1000$ s where W is weight in kg [$(W + 2800) / 2200$ s where W = weight in pounds] but not more than 7 s.



4.9.4 The requirement of 4.9.3 shall be met when rolling the aeroplane in each direction in the following conditions:

4.9.4.1 Flaps in the landing position(s);

4.9.4.2 Landing gear extended;

4.9.4.3 All engines operating at the power for a 3° approach, and

4.9.4.4 The aeroplane trimmed at V_{REF} .

5. Controllability

5.1 *General:*

5.1.1 The aeroplane shall be safely controllable and maneuverable during all flight phases including:

5.1.1.1 Takeoff,

5.1.1.2 Climb,

5.1.1.3 Level flight,

5.1.1.4 Descent,

5.1.1.5 Go-around, and

5.1.1.6 Landing (power on and idle power) with the wing flaps extended and retracted.

5.1.2 It shall be possible to make a smooth transition from one flight condition to another (including turns and slips) without danger of exceeding the limit load factor under any probable operating condition (including, for multiengine aeroplanes, those conditions normally encountered in the sudden critical loss of thrust).

5.1.3 If marginal conditions exist with regard to required pilot strength, the control forces necessary shall be determined by quantitative tests. In no case may the control forces under the conditions specified in 5.1.1 and 5.1.2 exceed those prescribed in Table 1.

5.2 *Longitudinal Control:*

5.2.1 With the aeroplane as nearly as possible in trim at 1.3 V_{S1} , it shall be possible, at speeds below the trim speed, to pitch the nose downward so that the rate of increase in airspeed allows prompt acceleration to the trim speed with:

5.2.1.1 Maximum continuous power on each engine;

5.2.1.2 Idle power; and

5.2.1.3 Wing flap and landing gear:

(1) Retracted and

(2) Extended.

5.2.2 Unless otherwise required, it shall be possible to carry out the following maneuvers without requiring the application of single-handed control forces exceeding those specified in Table 1. The trimming controls shall not be adjusted during the maneuvers.

5.2.2.1 With the landing gear extended, the flaps retracted, and the aeroplane as nearly as possible in trim at 1.4 V_{S1} , extend the flaps as rapidly as possible and allow the airspeed to transition from 1.4 V_{S1} to 1.4 V_{S0} :

(1) With power idle and

(2) With the power necessary to maintain level flight in the initial condition.

5.2.2.2 With landing gear and flaps extended, idle power, and the aeroplane as nearly as possible in trim at $1.3 V_{S0}$, quickly apply takeoff power and retract the flaps as rapidly as possible to the recommended go around setting and allow the airspeed to transition from $1.3 V_{S0}$ to $1.3 V_{S1}$. Retract the gear when a positive rate of climb is established.

5.2.2.3 With landing gear and flaps extended, power necessary to maintain level flight at $1.1 V_{S0}$ and the aeroplane as nearly as possible in trim, it shall be possible to maintain approximately level flight while retracting the flaps as rapidly as possible with simultaneous application of maximum continuous power. Power must not be reduced during the level acceleration unless a flap speed exceedance (V_{FE} of the initial position) is imminent. The maneuver is completed when the flaps have reached the selected position and the airspeed is not less than $1.3 V_{S1}$. If gated flap positions are provided, the flap retraction may be demonstrated in stages with power and trim reset for level flight at $1.1 V_{S1}$, in the initial configuration for each stage:

- (1) From the fully extended position to the most extended gated position;
- (2) Between intermediate gated positions, if applicable; and
- (3) From the least extended gated position to the fully retracted position.

5.2.2.4 With idle power, flaps and landing gear retracted and the aeroplane as nearly as possible in trim at $1.4 V_{S1}$, apply takeoff power rapidly while maintaining the same airspeed.

5.2.2.5 With idle power, landing gear and flaps extended, and the aeroplane as nearly as possible in trim at V_{REF} , obtain and maintain airspeeds between $1.1 V_{S0}$ and either $1.7 V_{S0}$ or V_{FE} , whichever is lower without requiring the application of two-handed control forces exceeding those specified in [Table 1](#).

5.2.2.6 With maximum takeoff power, landing gear retracted, flaps in the takeoff position, and the aeroplane as nearly as possible in trim at V_{FE} appropriate to the takeoff flap position, retract the flaps as rapidly as possible while maintaining constant speed.

5.2.3 At speeds above $V_{MO}/M_{MO}/V_{NE}$, and up to the maximum speed shown under [9.1](#):

5.2.3.1 For Level 1 aeroplanes with $V_{S0} \leq 45$ KCAS, it must be possible to raise the nose at all permitted c.g. positions and engine powers.

5.2.3.2 For Level 1 aeroplanes with $V_{S0} > 45$ KCAS and Level 2, 3, and 4 aeroplanes, a maneuvering capability of 1.5 g shall be demonstrated to provide a margin to recover from upset or inadvertent speed increase.

5.2.4 For Level 1 aeroplanes with $V_{S0} > 45$ KCAS and Level 2, 3, and 4 aeroplanes, it shall be possible, with a pilot control force of not more than 45 N [10 lbf], to maintain a speed of not more than V_{REF} during an idle power glide with landing gear and wing flaps extended, for any weight of the aeroplane, up to and including the maximum weight.

5.2.5 For Level 1 aeroplanes with $V_{S0} > 45$ KCAS and Level 2, 3, and 4 aeroplanes, by using normal flight and power controls, except as otherwise noted in [5.2.5.1](#) and [5.2.5.2](#), it shall be possible to arrest the rate of descent to zero at an attitude suitable for a controlled landing without exceeding the operational and structural limitations of the aeroplane, as follows:

5.2.5.1 For single-engine aeroplanes and multiengine aeroplanes, without the use of the primary longitudinal control system; and

5.2.5.2 For multiengine aeroplanes:

- (1) Without the use of the primary directional control and
- (2) If a single failure of any one connecting or transmitting link would affect both the longitudinal and directional primary control system, without the primary longitudinal and directional control system.

5.2.6 For Level 1 aeroplanes with $V_{S0} \leq 45$ KCAS, for any trim setting required under [6.3.1](#), it must be possible to takeoff, climb, descend, and land the aeroplane in required configurations with no adverse effect and with acceptable forces.

5.3 Directional and Lateral Control:

5.3.1 For each multiengine aeroplane, it shall be possible, while holding the wings level within 5° , to make sudden changes in heading safely in both directions. This ability shall be shown at $1.4 V_{S1}$ with heading changes up to 15° , except that the heading change at which the rudder force corresponds to the limits specified in [Table 1](#) need not be exceeded, with the:

5.3.1.1 Critical loss of thrust and its propeller in the minimum drag position;

5.3.1.2 Remaining engines at maximum continuous power;

5.3.1.3 Landing gear:

- (1) Retracted, and
- (2) Extended.

5.3.1.4 Flaps retracted.

5.3.2 For each multiengine aeroplane, it shall be possible to regain full control of the aeroplane without exceeding a bank angle of 45°, reaching a dangerous attitude, or encountering dangerous characteristics in the event of a sudden and complete loss of critical thrust, making allowance for a delay of 2 s in the initiation of recovery action appropriate to the situation, with the aeroplane initially in trim, in the following condition:

5.3.2.1 Maximum continuous power on each engine,

5.3.2.2 The wing flaps retracted,

5.3.2.3 The landing gear retracted,

5.3.2.4 A speed equal to that at which compliance with Specification **F3179/F3179M** *Climb Information* for the all engines operating condition has been shown, and

5.3.2.5 All propeller controls in the position at which compliance with Specification **F3179/F3179M** *Climb Information* for the all engines operating condition has been shown.

5.3.3 For Level 1 aeroplanes with $V_{SO} > 45$ KCAS and Level 2, 3, and 4 aeroplanes, it shall be shown that the aeroplane is safely controllable without the use of the primary lateral control system in any all-engine configuration(s) and at any speed or altitude within the approved operating envelope. It shall also be shown that the aeroplane's flight characteristics are not impaired below a level needed to permit continued safe flight and the ability to maintain attitudes suitable for a controlled landing without exceeding the operational and structural limitations of the aeroplane. If a single failure of any one connecting or transmitting link in the lateral control system would also cause the loss of additional control system(s), compliance with the above requirement shall be shown with those additional systems also assumed to be inoperative.

<https://standards.iteh.ai/catalog/standards/sist/718a761b-e3df-49ff-a2f0-69b7de872ee7/astm-f3173-f3173m-23>

5.4 Elevator Control Force in Maneuvers:

5.4.1 The elevator control force needed to achieve the positive limit maneuvering load factor shall not be less than:

5.4.1.1 For wheel controls, $W/10$ N (where W is the maximum mass in kg) [$W/100$ lbf (where W = maximum weight in lbf)] or 89 N [20 lbf], whichever is greater, except that it need not be greater than 222 N [50 lbf], or

5.4.1.2 For stick controls, $W/14$ N (where W is the maximum mass in kg) [$W/140$ lbf (where W = maximum weight in lbf)] or 67 N [15 lbf], whichever is greater, except that it need not be greater than 156 N [35 lbf].

5.4.2 The requirement of 5.4.1 shall be met at 75 percent of maximum continuous power for reciprocating engines, or the maximum continuous power for turbine engines and with the wing flaps and landing gear retracted:

5.4.2.1 In a turn, with the trim setting used for wings level flight at V_{O_1} and

5.4.2.2 In a turn, with the trim setting used for the maximum wings level flight speed, except that the speed may not exceed V_{NE} or V_{MO}/M_{MO} , whichever is appropriate.

5.4.3 There shall be no excessive decrease in the gradient of the curve of stick force versus maneuvering load factor with increasing load factor.

5.5 Rate of Roll:

5.5.1 Takeoff—It shall be possible, using a favorable combination of controls, to roll the aeroplane from a steady 30° banked turn through an angle of 60°, so as to reverse the direction of the turn within:

5.5.1.1 For an aeroplane of 2722 kg [6000 lb] or less maximum weight, 5 s from initiation of roll and

5.5.1.2 For an aeroplane of over 2722 kg [6000 lb], $(W + 200) / 590$ s where W is the weight in kg [$(W + 500) / 1300$ s where $W =$ weight in lbs] but not more than 10 s.

5.5.2 The requirement of **5.5.1** shall be met when rolling the aeroplane in each direction with:

5.5.2.1 Flaps in the takeoff position;

5.5.2.2 Landing gear retracted;

5.5.2.3 For a single-engine aeroplane, at maximum takeoff power, and a multiengine aeroplane with the critical loss of thrust with the affected propeller(s) in the minimum drag position and the other engines at maximum takeoff power; and

5.5.2.4 The aeroplane trimmed, or trimmed as nearly as possible, in straight flight at a speed equal to the greater of $1.2 V_{S1}$ or $1.1 V_{MC}$.

5.5.3 Approach—It shall be possible, using a favorable combination of controls, to roll the aeroplane from a steady 30° banked turn through an angle of 60°, so as to reverse the direction of the turn within:

5.5.3.1 For an aeroplane of 2722 kg [6000 lb] or less maximum weight, 4 s from initiation of roll and

5.5.3.2 For an aeroplane of over 2722 kg [6000 lb] maximum weight, $(W + 1300) / 1000$ s where W is weight in kg [$(W + 2800) / 2200$ s where $W =$ weight in pounds] but not more than 7 s.

5.5.4 The requirement of **5.5.3** shall be met when rolling the aeroplane in each direction in the following conditions:

5.5.4.1 Flaps in the landing position(s),

5.5.4.2 Landing gear extended,

5.5.4.3 All engines operating at the power for a 3° approach, and

5.5.4.4 The aeroplane trimmed at V_{REF} .

5.6 Control during Landings—It shall be possible, while in the landing configuration, to complete a landing without causing substantial damage or serious injury. The one-hand control force limits specified in **Table 1** shall not be exceeded following an approach to land.

5.6.1 At a speed of V_{REF} minus 5 knots;

5.6.2 With the aeroplane in trim, or as nearly as possible in trim and without the trimming control being moved throughout the maneuver;

5.6.3 At an approach gradient equal to:

5.6.3.1 For Level 1 aeroplanes with $V_{S0} \leq 45$ KCAS, that resulting from an approach at idle power, or

5.6.3.2 For Level 1 aeroplanes with $V_{S0} > 45$ KCAS and Level 2, 3, and 4 aeroplanes, the steepest used in the landing distance demonstration of Specification **F3179/F3179M Landing**.

5.6.4 With only those power changes, if any, that would be made when landing normally from an approach at V_{REF} .

5.7 Minimum Control Speed: