



Designation: **D6681—17** **D6681 – 23**

Standard Test Method for Evaluation of Engine Oils in a High Speed, Single-Cylinder Diesel Engine—Caterpillar 1P Test Procedure¹

This standard is issued under the fixed designation D6681; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reappraisal. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reappraisal.

INTRODUCTION

Any properly equipped laboratory without outside assistance can use the test method described in this standard. However, the ASTM Test Monitoring Center (TMC)² provides calibration oils and an assessment of the test results obtained on those oils by the laboratory. By this means the laboratory will know whether their use of the test method gives results statistically similar to those obtained by other laboratories. Furthermore, various agencies require that a laboratory utilize the TMC services in seeking qualification of oils against specifications. For example, the U.S. Army has such a requirement in some of its engine oil specifications. Accordingly, this test method is written for those laboratories that use the TMC services. Laboratories that choose not to use these services should ignore those portions of the test method that refer to the TMC. Information Letters issued periodically by the TMC may modify this method.³ In addition, the TMC may issue supplementary memoranda related to the test method.

(<https://standards.iteh.ai>)
Document Preview

1. Scope*

1.1 This test method covers and is required to evaluate the performance of engine oils intended to satisfy certain American Petroleum Institute (API) C service categories (included in Specification **D4485**). It is performed in a laboratory using a standardized high-speed, single-cylinder diesel engine.⁴ Piston and ring groove deposit-forming tendency and oil consumption is measured. The piston, the rings, and the liner are also examined for distress and the rings for mobility.

1.2 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.2.1 *Exceptions*—Where there is no direct SI equivalent such as screw threads, National Pipe Threads/diameters, tubing size, or where there is a sole source supply equipment specification.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.* Being an engine test method, this standard does have definite hazards that require safe practices (see **Appendix X2** on Safety).

¹ This test method is under the jurisdiction of ASTM Committee **D02** on Petroleum Products, Liquid Fuels, and Lubricants and is the direct responsibility of Subcommittee **D02.B0.02** on Heavy Duty Engine Oils.

Current edition approved ~~May 1, 2017~~ July 1, 2023. Published ~~May 2017~~ July 2023. Originally approved in 2001. Last previous edition approved in ~~2016~~ 2017 as **D6681—16** **D6681 – 17**. DOI: ~~10.1520/D6681-17~~ 10.1520/D6681-23.

² ASTM Test Monitoring Center (TMC), 6555 Penn Ave., Pittsburgh, PA 15206-4489-203 Armstrong Drive, Freeport, PA 16229.

³ This edition incorporates revisions contained in all information letters through ~~16-1-23-1~~. Users of this test method shall contact the ASTM Test Monitoring Center to obtain the most recent information letters.

⁴ Available from Caterpillar Inc., Engine System Technology Development, P.O. Box 610, Mossville, IL 61552-0610.

*A Summary of Changes section appears at the end of this standard

1.4 The following is the Table of Contents:

	Section
Scope	1
Referenced Documents	2
Terminology	3
Summary of Test Method	4
Significance and Use	5
Apparatus and Installation	6
Intake Air System	6.2.1
Exhaust System	6.2.2
Fuel System	6.2.3
Oil Consumption System	6.2.4
Engine Oil System	6.2.5
Oil Heating System	6.2.5.1
Oil Sample Valve	6.2.5.2
Engine Coolant System	6.2.6
Engine Instrumentation	6.2.7
Reagents and Materials	7
Oil Samples	8
Preparation of Apparatus	9
General Engine Assembly Practices	9.1
Complete Engine Inspection	9.2
Copper Components	9.3
Engine Lubricant System Flush	9.4
Engine Piston Cooling Jets	9.5
Engine Measurements and Inspections	9.6
Cylinder Head	9.7
Valve Guide Bushings	9.8
Fuel Injector	9.9
Piston and Rings	9.10
Cylinder Liner	9.11
Compression Ratio	9.12
Engine Timing	9.13
Engine Coolant System Cleaning Procedure	9.14
Calibration and Standardization	10
Test Cell Instrumentation	10.1
Instrumentation Standards	10.2
Coolant Flow	10.3
Re-calibration Requirements	10.4
Fuel Injectors	10.5
Air Flow	10.6
Intake Air Barrel	10.7
Fuel Filter	10.8
Oil Scale Flow Rates	10.9
Calibration of Test Stands	10.10
Extending Test Stand Calibration Period	10.11
Test Run Numbering	10.13
Humidity Calibration Requirements	10.14
Calibration of Piston Deposit Raters	10.15
Procedure	11
Engine Break-in Procedure	11.1
Cool-down Procedure	11.2
Warm-up Procedure	11.3
Shutdowns and Lost Time	11.4
Periodic Measurements	11.5
Engine Control Systems	11.6
Engine Coolant	11.6.1
Engine Fuel System	11.6.2
Engine Oil Temperature	11.6.3
Exhaust Pressure	11.6.4
Intake Air	11.6.5
Post-Test Procedures	11.7
Piston Ring Side Clearances	11.7.1
Piston Ratings	11.7.2
Referee Ratings	11.7.3
Ring End Gap Increase	11.7.4
Cylinder Liner Wear	11.7.5
Cylinder Liner Bore Polish	11.7.6
Photographs	11.7.7
Calculation and Interpretation of Results	12
Test Validity	12.1
Calculations	12.2
Quality Index	12.2.1
Oil Consumption	12.2.2

	Section
Report	13
Forms and Data Dictionary	13.1
Test Validity	13.2
Report Specifics	13.3
Precision and Bias	14
Precision	14.1
Bias	14.1.4
Keywords	15
Annexes	
Engine and Parts Warranty	Annex A1
Instrument Locations, Measurements, and Calculations	Annex A2
Cooling System Arrangement	Annex A3
Intake Air Mass Flow Sensor Installation	Annex A4
Fuel System Design and Required Components	Annex A5
Oil System	Annex A6
Exhaust and Intake Barrel Piping	Annex A7
Humidity Probe Installation (Location)	Annex A8
Return Goods Authorization (Claim Form)	Annex A9
Engine Assembly Information	Annex A10
Flushing Instructions and Apparatus	Annex A11
Warm-up, Cool-down and Testing Conditions	Annex A12
Piston and Liner Rating Modifications	Annex A13
Additional Report Forms	Annex A14
Test Report Forms	Annex A15
Appendixes	
Various Examples for Reference Purposes	Appendix X1
Safety	Appendix X2

1.5 This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.

2. Referenced Documents

2.1 ASTM Standards:⁵

- D86 Test Method for Distillation of Petroleum Products and Liquid Fuels at Atmospheric Pressure
- D93 Test Methods for Flash Point by Pensky-Martens Closed Cup Tester
- D97 Test Method for Pour Point of Petroleum Products
- D130 Test Method for Corrosiveness to Copper from Petroleum Products by Copper Strip Test
- D235 Specification for Mineral Spirits (Petroleum Spirits) (Hydrocarbon Dry Cleaning Solvent)
- D445 Test Method for Kinematic Viscosity of Transparent and Opaque Liquids (and Calculation of Dynamic Viscosity)
- D482 Test Method for Ash from Petroleum Products
- D524 Test Method for Ramsbottom Carbon Residue of Petroleum Products
- D613 Test Method for Cetane Number of Diesel Fuel Oil
- D664 Test Method for Acid Number of Petroleum Products by Potentiometric Titration
- D1319 Test Method for Hydrocarbon Types in Liquid Petroleum Products by Fluorescent Indicator Adsorption
- D2274 Test Method for Oxidation Stability of Distillate Fuel Oil (Accelerated Method)
- D2425 Test Method for Hydrocarbon Types in Middle Distillates by Mass Spectrometry
- D2500 Test Method for Cloud Point of Petroleum Products and Liquid Fuels
- D2622 Test Method for Sulfur in Petroleum Products by Wavelength Dispersive X-ray Fluorescence Spectrometry
- D2709 Test Method for Water and Sediment in Middle Distillate Fuels by Centrifuge
- D3227 Test Method for (Thiol Mercaptan) Sulfur in Gasoline, Kerosine, Aviation Turbine, and Distillate Fuels (Potentiometric Method)
- D3524 Test Method for Diesel Fuel Diluent in Used Diesel Engine Oils by Gas Chromatography
- D4175 Terminology Relating to Petroleum Products, Liquid Fuels, and Lubricants
- D4052 Test Method for Density, Relative Density, and API Gravity of Liquids by Digital Density Meter
- D4485 Specification for Performance of Active API Service Category Engine Oils
- D4739 Test Method for Base Number Determination by Potentiometric Hydrochloric Acid Titration
- D5185 Test Method for Multielement Determination of Used and Unused Lubricating Oils and Base Oils by Inductively Coupled Plasma Atomic Emission Spectrometry (ICP-AES)

⁵ For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

D5862 Test Method for Evaluation of Engine Oils in Two-Stroke Cycle Turbo-Supercharged 6V92TA Diesel Engine (Withdrawn 2009)⁶

D6202 Test Method for Automotive Engine Oils on the Fuel Economy of Passenger Cars and Light-Duty Trucks in the Sequence VIA Spark Ignition Engine (Withdrawn 2009)⁶

D6593 Test Method for Evaluation of Automotive Engine Oils for Inhibition of Deposit Formation in a Spark-Ignition Internal Combustion Engine Fueled with Gasoline and Operated Under Low-Temperature, Light-Duty Conditions

D7422 Test Method for Evaluation of Diesel Engine Oils in T-12 Exhaust Gas Recirculation Diesel Engine

E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications

G40 Terminology Relating to Wear and Erosion

2.2 *SAE Standard:*

SAE J183 Engine Oil Performance and Engine Service Classification⁷

2.3 *API Standard:*

API 1509 Engine Service Classification and Guide to Crankcase Oil Selection⁸

2.4 *Other ASTM Document:*

ASTM Deposit Rating Manual 20 (formerly CRC Manual 20)⁹

3. Terminology

3.1 *Definitions:*

3.1.1 *additive, n*—a material added to another, usually in a small amount, to impart or enhance desirable properties or to suppress undesirable properties. **D4175**

3.1.2 *automotive, adj*—descriptive of equipment associated with self-propelled machinery, usually vehicles driven by internal combustion engines. **D4485**

3.1.3 *blind reference oil, n*—a reference oil, the identity of which is unknown by the test facility. **D4175**

3.1.3.1 *Discussion—*

This is a coded reference oil which is submitted by a source independent from the test facility.

3.1.4 *blowby, n—in internal combustion engines*, that portion of the the combustion products and unburned air/fuel mixture that leaks past piston rings into the engine crankcase during operation. **D4175**

3.1.5 *calibrate, v*—to determine the indication or output of a device (e.g., thermometer, manometer, engine) with respect to that of a standard. **D4175**

3.1.6 *calibrated test stand, n*—a test stand on which the testing of reference material(s), conducted as specified in the standard, provided acceptable test results. **Sub. B Glossary**²

3.1.6.1 *Discussion—*

In several automotive lubricant standard test methods, the ASTM Test Monitoring Center provides testing guidance and determines acceptability.

3.1.7 *candidate oil, n*—an oil which is intended to have the performance characteristics necessary to satisfy a specification and is to be tested against that specification. **D4175**

3.1.7.1 *Discussion—*

These oils are mainly submitted for testing as *candidates* to satisfy a specified performance; hence the designation of the term.

3.1.8 *debris, n—in internal combustion engines*, solid contaminant materials unintentionally introduced into the engine or resulting from wear. **D5862**

3.1.9 *dispersant, n—in engine oil*, an additive that reduces deposits on oil-wetted engine surfaces primarily through suspension of particles. **D4175**

⁶ The last approved version of this historical standard is referenced on www.astm.org.

⁷ Available from SAE International (SAE), 400 Commonwealth Dr., Warrendale, PA 15096, <http://www.sae.org>.

⁸ Available from American Petroleum Institute (API), 1220 L. St., NW, Washington, DC 20005-4070, <http://www.api.org>.

⁹ For Stock #TMCML20, visit the ASTM website, www.astm.org, or contact ASTM International Customer Service at service@astm.org.

3.1.10 *engine oil*, *n*—a liquid that reduces friction or wear, or both, between the moving parts within an engine; removes heat, particularly from the underside of pistons; and serves as a combustion gas sealant for the piston rings. **D5862**

3.1.10.1 *Discussion*—

It may contain additives to enhance certain properties. Inhibition of engine rusting, deposit formation, valve train wear, oil oxidation and, foaming are examples.

3.1.11 *heavy-duty*, *adj*—*in internal combustion engine operation*, characterized by average speeds, power output, and internal temperatures that are generally close to the potential maximums. **D4485**

3.1.12 *lubricant*, *n*—any material interposed between two surfaces that reduces the friction or wear, or both, between them. **D5862**

3.1.13 *lubricating oil*, *n*—a liquid lubricant, usually comprising several ingredients, including a major portion of base oil and minor portions of various additives. **D4175²**

3.1.14 *oxidation*, *n*—*of engine oil*, the reaction of the oil with an electron acceptor, generally oxygen, that can produce deleterious acidic or resinous materials often manifested as sludge formation, varnish formation, viscosity increase, or corrosion, or a combination thereof. **D4175**

3.1.15 *non-reference oil*, *n*—any oil other than a reference oil; such as a research formulation, commercial oil, or candidate oil. **D4175**

3.1.16 *purchaser*, *n*—*of an ASTM test*, person or organization that pays for the conduct of an ASTM test method on a specified product. **D6202**

3.1.17 *reference oil*, *n*—an oil of known performance characteristics, used as a basis for comparison.

3.1.17.1 *Discussion*—

Reference oils are used to calibrate testing facilities, to compare the performance of other oils, or to evaluate other material (such as seals) that interact with oils. **D4175**

3.1.18 *scoring*, *n*—*in tribology*, a severe form of wear characterized by the formation of extensive grooves and scratches in the direction of sliding. **G40**

<https://standards.iteh.ai/catalog/standards/sist/b3eb230-6b33-49ce-9333-44f4365d8780/astm-d6681-23>

3.1.19 *scuffing*, *n*—*in lubrication*, damage caused by instantaneous localized welding between surfaces in relative motion which does not result in immobilization of the parts. **D6593**

3.1.20 *sponsor*, *n*—*of an ASTM test method*, an organization that is responsible for ensuring supply of the apparatus used in the test procedure portion of the test method. **D4175**

3.1.20.1 *Discussion*—

In some instances, such as a test method for chemical analysis, an ASTM working group can be the sponsor of the test method. In other instances, a company with a self-interest may or may not be the developer of the test procedure used within the method, but is the sponsor of the test method.

3.1.21 *used oil*, *n*—any oil that has been in a piece of equipment (for example, an engine, gearbox, transformer, or turbine), whether operated or not. **D4175**

3.1.22 *varnish*, *n*—*in internal combustion engines*, a hard, dry, generally lustrous deposit that can be removed by solvents but not by wiping with a cloth. **D4175**

3.1.23 *wear*, *n*—the loss of material from a surface, generally occurring between two surfaces in relative motion, and resulting from mechanical or chemical action or a combination of both. **D7422**

4. Summary of Test Method

4.1 Prior to each test, the power section of the engine is disassembled, solvent-cleaned, measured, and rebuilt in strict accordance

with the specifications. A new piston, ring assembly, and cylinder liner are measured and installed for each test. The engine crankcase is solvent-cleaned and worn or defective parts are replaced. The test stand is equipped with feedback control systems for fuel rate, engine speed, and other engine operating conditions. A suitable system for filtering, compressing, humidifying, and heating the inlet air is required along with a system for controlling the engine exhaust pressure. Test operations involve the control of the single-cylinder diesel test engine for a total of 360 h at specified speeds and fuel rate input using the test oil as a lubricant. A defined break-in precedes each test and is also used when restarting an engine. At the end of the test, the piston deposits are rated, the piston, rings and liners are photographed, inspected and measured, oil consumption is calculated and the oil is analyzed to determine the test results. Critical engine conditions are statistically analyzed to determine if the test was precisely operated. Test acceptability parameters for each calibration test are also statistically analyzed to determine if the engine/test stand produce the specified results.

5. Significance and Use

5.1 This is an accelerated engine oil test, performed in a standardized, calibrated, stationary single-cylinder diesel engine that gives a measure of (1) piston and ring groove deposit forming tendency, (2) piston, ring and liner scuffing and (3) oil consumption. The test is used in the establishment of diesel engine oil specification requirements as cited in Specification **D4485** for appropriate API Performance Category C oils (API 1509). The test method can also be used in diesel engine oil development.

6. Apparatus and Installation

6.1 The test engine is an electronically controlled, direct injection, in-head camshaft, single-cylinder diesel engine with a four-valve arrangement. The engine has a 137.2 mm bore and a 165.1 mm stroke resulting in a displacement of 2.4 L.

6.1.1 The electronic control module (ECM) defines the desired engine fuel timing, monitors and limits maximum engine speed, maximum engine power, minimum oil pressure, and, optionally, maximum engine crankcase pressure. The ECM also controls the fuel injection duration that defines the engine fuel rate based on set conditions from the test cell feedback control systems. The oil pressure is also set by the ECM with signals to the 1Y3867 engine air pressure controller (Mamac) to modulate the facility air supply to the 1Y3898 Johnson Controls relief valve.

6.1.2 The 1Y3700 engine arrangement also consists of inlet air piping and hoses from the cylinder head to the air barrel and exhaust piping and bellows from the cylinder head to the exhaust barrel that are specifically designed for oil testing. See the Caterpillar Service Manual.⁴

6.2 Equip the engine test stand with the following accessories or equipment:

6.2.1 *Intake Air System*—The intake air system components from the cylinder head to the air barrel are a part of the basic 1Y3700 engine arrangement. These components consisting of an adapter, elbow, hose, clamps, and flanged tube can be found in the 1Y3700 Parts Book.⁴

6.2.1.1 Purchase the 1Y3978 intake air barrel (which is almost identical to the exhaust barrel except for the top cover) that has been specifically designed from one of the three approved manufacturers.^{10,11} Install the intake air barrel at the location shown in **Annex A7**. Do not add insulation to the barrel.

6.2.1.2 Paint the inside of the intake air piping with Caterpillar yellow primer or red Glyptal prior to installation.^{12,11}

6.2.1.3 Install the air heater elements in the intake air barrel as specified in **Annex A7** (even if they will not be supplied with electricity).^{13,11}

6.2.1.4 Use an air filter capable of filtering particles 10 μ (or smaller).

¹⁰ The sole sources of supply of the intake air barrel known to the committee at this time are Cimino Machinery Corp., 5958 South Central Ave., Chicago, IL 60638; Gaspar Inc., 4106 Mahoning Rd. N.E., Canton, OH 44705; and M.L. Wyrick Welding, 2301 Zanderson Highway 16 N, Jourdanton, TX 78026.

¹¹ If you are aware of alternative suppliers, please provide this information to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee¹, which you may attend.

¹² The sole source of supply of the crankcase paint primer known to the committee at this time is BASF Coating and Colorant Div., P.O. Box 1297, Morganton, NC 28655. (Primer No.A123590 and BASF Part No.U27YD005, Yellow CAT Primer Part No.IE2083A.)

¹³ The sole source of supply of the air heater elements known to the committee at this time is Watlow Air Heaters, Chicago, IL 708-490-3900.

6.2.1.5 Use a Sierra Model 780 airflow meter with Feature 1 = F6, Feature 2 = CG and calibration temperature = 60 °C to measure intake airflow for each calibration test.^{14,11} [Annex A4](#) shows the piping requirements for the installation of the Sierra Model 780 airflow meter.

6.2.1.6 Measure the inlet air temperature at the location shown in [Annex A2](#). Measure the inlet air pressure at the air barrel as shown in [Annex A7](#). The location of the 1Y3977 humidity probe is shown in [Annex A8](#). The sample line might require insulation to prevent dropping below dew point temperature and shall not be hygroscopic. Drain taps may be installed at the low points of the combustion air system.

6.2.1.7 Use feedback-equipped controls to maintain filtered, compressed, and humidified inlet air at the conditions specified in [Annex A12](#).

6.2.2 *Exhaust System*—The exhaust system components from the cylinder head to the exhaust barrel are part of the basic 1Y3700 engine arrangement. These components consisting of an adapter, elbow, bellows, flange, and clamps can be found in the 1Y3700 Parts Book.

6.2.2.1 Purchase the 1Y3976 exhaust barrel (which is almost identical to the intake barrel except for the top cover) that has been specifically designed from one of the three approved manufacturers. Install the exhaust barrel at the location shown in [Annex A7](#). Do not add insulation to the barrel.

6.2.2.2 Install a restriction valve downstream from the exhaust barrel. The distance between the valve and barrel is not specified. The location of the exhaust thermocouple is shown in [Annex A2](#). Measure the exhaust pressure at the exhaust barrel shown in [Annex A7](#).

6.2.2.3 Use feedback-equipped controls to maintain the exhaust gases at the pressure specified in [Annex A12](#).

6.2.3 *Fuel System*—The fuel system schematic is shown in [Annex A5](#). Desired fuel injection timing is controlled by the engine computer at 13° BTC. Measure the fuel rate using micro motion device with a maximum range of 90 kg/h scaled to the 1P operation range specified in [Annex A12](#).^{15,11} Use the day tank specified in [Annex A5](#). Measure fuel temperature at the fuel filter base as shown in [Annex A2](#) and control it using the cell facility feedback system. Use the required fuel heat exchanger(s) and arrange them as specified in [Annex A5](#). Use the Fisher regulator specified in [Annex A5](#).

6.2.4 *Oil Consumption System*—Use an oil scale system to accurately measure oil consumption (see [Fig. A6.2](#) and [Fig. A6.3](#)). The oil scale system shall have a resolution as listed in [Annex A2](#). Use flexible hoses similar to Aeroquip flexible hose, FC352-08, to-and-from the oil scale reservoir to eliminate measurement errors.^{16,11} Use No.5 TFE-fluorocarbon, steel-braided hoses to and from the oil scale pumps. The hose length to-and-from the oil scale cart shall not exceed 2.7 m. Use the special oil pan adapter described in [Fig. A6.4](#).

6.2.5 *Engine Oil System*—A schematic of the oil system is shown in [Fig. A6.1](#). Measure oil pressure at the engine oil manifold (see [Annex A2](#)). An engine oil pressure sensor transmits a signal to the ECM that maintains oil pressure at 415 kPa. The ECM transmits a signal to an engine-mounted Mamac air pressure controller. The Mamac modulates the facility air pressure of 280 kPa to levels that vary between 0 kPa to 140 kPa and directs it to the normally closed Johnson Controls relief valve. Because the engine oil pressure sensor calibration might vary from the cell data acquisition transducer, vary the oil pressure adjust signal to the ECM to maintain the oil pressure at the test specifications. See the Electronic Installation and Operation manual for additional information. The ECM maintains the oil pressure regardless of engine speed. Measure the oil temperatures at locations shown in [Annex A2](#).

6.2.5.1 *Oil Heating System*—Use an external oil heating system provided by the test facility to maintain the engine oil manifold temperature specified in [Annex A12](#). An example system is shown in [Appendix X1](#). A special 1Y3908 oil cooler bonnet has been designed to allow separate fluids to the engine coolant tower arrangement (see [Fig. A6.9](#)). Plug the 1Y3660 oil cooler adapter and 1Y3908 heat exchanger bonnet as shown in [Annex A6](#). Use Paratherm NF for the heating fluid.^{17,11} The temperature of the Paratherm NF is measured by the thermocouple shown in [Annex A2](#).

¹⁴ The sole source of supply of the airflow meter known to the committee at this time is Sierra Instruments, Inc., 5 Harris Ct., Monterey, CA 93940.

¹⁵ The sole source of supply of the apparatus known to the committee at this time is Micro Motion, Inc. 7070 Winchester Circle, Boulder, CO 80301.

¹⁶ The sole source of supply of the flexible hose known to the committee at this time is Aeroquip Industrial Div, 1225 W. Main Street, Van Wert, OH 45891.

¹⁷ The sole source of supply of the fluid known to the committee at this time is Paratherm NF Oil, Conshohocken, PA 19428.

6.2.5.2 *Oil Sample Valve*—Refer to **Annex A2** for the installation location and component makeup of the oil sample valve. Use of alternate equivalent components for the sample valve is permitted.

6.2.6 *Engine Coolant System*—The coolant system schematic is shown in **Annex A3**. Control the coolant temperature out of the engine using a cell facility feedback system. Use a 1Y3898 Johnson Controls valve or equivalent fail-open valve to regulate the coolant temperature out of the engine as shown by the schematic in **Annex A3**. If the 1Y3898 Johnson valve is used, supply facility air pressure at 280 kPa to the controller that regulates air pressure to the valve at 0 kPa to 140 kPa. Install a feedback-equipped control system to pneumatically adjust the valve. Remove the 1Y3832 hose originally supplied with the engine and install a sight glass using the components shown in **Annex A3**.

6.2.7 *Engine Instrumentation*—Use feedback-equipped systems to control the engine operating temperatures, pressures, and flow rates. Measure the engine operating conditions at the locations shown in **Annex A2**. For temperature measurements, use thermocouples 1Y468 (intake air), 1Y467 (engine exhaust) and 1Y466 (fluids-water, oil, and fuel) or equivalent thermocouples as specified in **Annex A2**. Instrument measurement and reporting resolutions are shown in **Annex A2**.

6.2.8 A dynamometer with feedback control to maintain engine torque and speed. Use a starting system capable of at least breakaway torque of 136 N·m and sustained torque of 102 N·m at 200 r/min.

6.2.9 Compressed air at 35 kPa to the top of the coolant tower as specified in **Annex A3** to ensure water does not boil out of the antifreeze mixture and result in less heat rejection from the engine.

6.2.10 Measure engine blowby downstream of the engine breather housing by measuring the delta pressure across an orifice or an equivalent device.

6.2.11 The crankcase pressure is above atmospheric pressure with this engine arrangement. Measure it at the location shown in **Annex A2**.

6.3 Obtain information concerning the test engine, engine electronics system, new engine parts, replacement parts, and permissible substitution or replacement parts from Caterpillar, Inc.

6.4 Engine and parts warranty information can be found in **Annex A1**. Use the form listed in **Annex A9** for returning defective parts.

7. Reagents and Materials

7.1 *Purity of Reagents*—Reagent grade chemicals shall be used in all tests. Unless otherwise indicated, it is intended that all reagents conform to the specifications of the Committee on Analytical Reagents of the American Chemical Society where such specifications are available.¹⁸ Other grades may be used, provided it is first ascertained that the reagent is of sufficiently high purity to permit its use without lessening the accuracy of the determination.

7.2 *Diesel Piston Rating Booth*, as described by ASTM Deposit Rating Manual 20.

7.3 *Diesel Piston Rating Lamp*, as described by ASTM Deposit Rating Manual 20

7.4 *Dispersant Engine Cleaner*.^{19,11}

7.5 *Engine Coolant*—Use a 50/50 mixture of mineral-free water and Caterpillar brand coolant (P/N 8C684 for 3.8 L or 8C3686 for 208 L drum) for engine coolant. Mineral-free water is defined as water having a mineral content no higher than 34.2 mg/kg total dissolved solids. The coolant mixture may be reused for up to 1600 h. Keep the mixture at a 50:50 ratio as determined by

¹⁸ *Reagent Chemicals, American Chemical Society Specifications, ACS Reagent Chemicals, Specifications and Procedures for Reagents and Standard-Grade Reference Materials*, American Chemical Society, Washington, DC. For ~~Suggestions~~ suggestions on the testing of reagents not listed by the American Chemical Society, see *Annual Analytical Standards for Laboratory Chemicals*, BDH Ltd., Poole, Dorset, U.K., and the *United States Pharmacopeia and National Formulary*, U.S. Pharmacopeial Convention, Inc. (USPC), Rockville, MD.

¹⁹ The sole source of supply of the engine cleaner known to the committee at this time is The Lubrizol Corp., 29400 Lakeland Blvd., Cleveland, OH 44092

using either Caterpillar testers 5P3514 or 5PO957 or an equivalent tester. Keep the coolant mixture contamination free. Total solids shall remain below 5000 mg/kg. Keep the additive level correct using Caterpillar test kit P/N 8T5296.

7.6 *Lead Shot*, commercial grade, approximately 5 mm in diameter.

7.7 *Light Grease*.

7.8 *Mobil EF-411*, available from ExxonMobil for engine assembly and calibration of the oil scale pump flow rates.^{20,11}

7.9 *Paratherm NF*, as supplied by Paratherm and used as the fluid to heat the engine oil.^{17,11}

7.10 *Pentane (Solvent)*, purity > 99 %, high-performance, liquid chromatography grade.

7.11 *Reference Oil*, as supplied by the TMC for calibration of the test stand.

7.12 *REO 217*, as supplied by the CRC and used when any copper components are changed.

7.13 *Sodium Bisulfate (NaHSO₄)*, commercial grade.

7.14 *Solvent*—Use only mineral spirits meeting the requirements of Specification **D235**, Type II, Class C for Aromatic Content (0 % to 2 %) by vol, Flash Point (61 °C, min) and Color (not darker than + 25 on Saybolt Scale or 25 on Pt-Co Scale). (**Warning**—Combustible. Health hazard.) Obtain a Certificate of Analysis for each batch of solvent from the supplier.

7.15 *Fuel*—Obtain the required test fuel from Chevron Phillips^{21,11} as PC-9-HS Reference Diesel Fuel (see **Annex A14**).

7.16 *Test Oil*—The total amount of oil needed for each lubricant test is approximately 42 L.

7.17 *Trisodium Phosphate (Na₃PO₄)*, commercial grade.

7.18 *5.4000 in. Ring Bore Standard Class Z Master*.^{22,11}

8. Oil Samples

8.1 Take purge samples of 250 mL at 48 h, 72 h, 120 h, 144 h, 168 h, 192 h, 216 h, 264 h, 312 h, and 336 h. Following removal of each purge sample, remove a 30 mL sample, then add 317 g ± 10 g of new oil. It is not necessary to perform analysis on these samples of 30 mL. Use the purge sample to return to the full mark.

8.1.1 Take purge samples of 250 mL at 0 h (new) and 24 h, 96 h, 240 h, 288 h, and 360 h. Following removal of each purge sample, remove a 90 mL sample and add 370 g ± 10 g of new oil.

8.1.2 Analyze all 90 mL samples for viscosity by Test Method **D445** at 100 °C and 40 °C, TBN by Test Method **D4739**, TAN by Test Method **D664**, and the wear metals Al, Cr, Cu, Fe, Pb, Si by Test Method **D5185**. Analyze the samples for fuel dilution taken at 24 h, 240 h, and 360 h by Test Method **D3524**. See **Fig. A6.7** and **Fig. A6.8** for two graphical examples and a sample worksheet.

9. Preparation of Apparatus

9.1 *General Engine Assembly Practices*—As a part of good laboratory practice, inspect all components and assemblies that are exposed when the engine is disassembled and record the information for future reference. Inspect valve train components, bearings, journals, housings, seals and gaskets, and so forth and replace as needed. Assemble the engine with components and bolt torques

²⁰ The sole source of supply of the oil known to the committee at this time is Mobil EF-411, from Golden West Oil Co., 3010 Aniol St., San Antonio, TX 78219.

²¹ The sole source for 1P fuel known to the committee at this time is Chevron Phillips Chemical Co., Chevron Tower, 1301 McKinney Street, Houston, TX 77010-3030.

²² The sole source of supply of the apparatus known to the committee at this time is Morse-Hemco, 457 Douglas Ave., Holland, MI 49423.

as specified in the 1Y3700 engine Service Manual (see **Annex A10** for a partial list). It is the intent of this procedure for all engine assemblies and adjustments to be targeted to the mean of the specified values. Clean and lubricate the components in keeping with good assembly practices. Keep airborne dirt and debris to a minimum in the assembly area. Maintain standard engine assembly techniques and practices (such as staggering piston ring gap positions, and so forth).

9.2 *Complete Engine Inspection*—Perform a complete engine inspection at intervals of 13 000 h. Ensure that wearing surfaces such as main bearings and journals, rod bearings and journals, camshaft bearings, valve train components, fuel system components, and so forth all are within manufacturer’s specifications. Refer to the 1Y3700 Service Manual for disassembly, assembly, inspections, and specifications. Paint crankcases as necessary with either Caterpillar yellow primer or red Glyptal.^{12,11}

9.3 *Copper Components*—Anytime a copper part is replaced, run an engine test using REO 217 until two consecutive periods of 12 h show a stable copper level. To eliminate the need to perform this pacification process when replacing the engine oil cooler, use of a nickel-plated oil cooler is permitted.

9.4 *Engine Lubricant System Flush*—Flush the engine of used oil before every test. **Annex A11** shows the engine flush procedure and apparatus. A flushing instruction sheet shown in **Annex A11** gives the step-by-step process required for flushing. The 1Y3700 engine arrangement includes five flushing nozzles in the crankcase and front cover (see **Annex A11**). These nozzles are piped in parallel with the 1Y3935 filter flushing adapter (or equivalent) from a laboratory-provided manifold that pressurizes fluids supplied by a flush cart (see **Appendix X1**). Seal the gear train housing during flush with a 1Y3917 round plug with a 117-8801 o-ring as shown in **Annex A11**. Seal the crankcase using a 1Y3979 block flush cover with an internal bleed passage for the cam oil supply. Bolt a 1Y3980 plastic jet aiming fixture to the flush cover that is also used for flushing (see **Annex A11**). If the test oil is not available at engine assembly, Mobil EF411 oil may be substituted.

9.5 *Engine Piston Cooling Jets*—The piston cooling jets are flow-checked at the supplier and serialized to ensure proper performance, but the minimal rod clearances might result in jet movement during assembly. Verify proper jet flow positioning using EF-411 before each test with the 1Y3980 plastic jet aiming fixture and oil pressure to the manifold of 415 kPa. Record the cooling jet serial number.

9.6 *Engine Measurements and Inspections*—Measure and inspect the engine components prior to each test (see **Table A10.2** for partial specification list). Refer to the 1Y3700 Service Manual for information concerning component reusability and assembly not found in this procedure. The part numbers of components that need replacing are found in the 1Y3700 Parts Manual. Record the crankshaft angles at the specified maximum injector lift, exhaust, and intake maximum lift before each test using the reference listed in **Fig. A10.7**. Record component part numbers and serial numbers and other required measurements as shown in the test report. Inspect and reuse the rocker arm roller followers and camshaft lobe surfaces based on Caterpillar Service Publication SEBF8256.⁴

9.7 *Cylinder Head*—A reconditioned head is required for each test. Measurements after reconditioning shall be within specifications as shown in the 1Y3700 Service Manual. Do not swap the cylinder head/jug assembly from test stand-to-test stand. Use the head/jug assembly used to calibrate the stand for all non-reference oil testing in that stand. **Fig. A10.1** shows the cylinder head nut torque sequence.

9.8 *Valve Guide Bushings*—Clean the valve guide bushings with a solvent and bristle brush prior to assembly. Lubricate the bushings and valve stems with Mobil EF-411 prior to assembly. See the 1Y3700 Service Manual for guide reusability specifications. Install new valve guide seals for each test.

9.9 *Fuel Injector*—Remove the fuel injector from the cylinder head before reconditioning commences. Refer to the 1Y3700 Service Manual for removal and assembly. Return defective fuel injectors to Caterpillar for warranty and failure-mode testing using the form listed in **Annex A9**.

9.10 *Piston and Rings*—Use a new piston (1Y3400 iron crown, 1Y3659 aluminum skirt) and new rings (1Y3802, 1Y3803, 1Y3804) for each test.

9.10.1 Clean all three rings with pentane and a lint-free 100 % cotton towel.

9.10.2 Measure the ring side clearances and ring end gaps for all three rings (see **Fig. A10.2** and **Table A10.1**). Keystone ring side

clearance measurements require the ring to be confined in a dedicated slotted liner (see [Appendix X1](#)) or a ring gage^{15,11} 137.16 mm in diameter. Measure the side clearances using four feeler gages of equal width and thickness of 0.01 mm at intervals of 90° around the piston. Measure the rectangular ring side clearance this way as well. Measure the minimum side clearance as specified in ASTM Deposit Rating Manual 20.

9.10.3 Record the measurements for these parts before and after each test. Compare the measurements before the test and after the test to determine the amount of wear.

9.10.4 Assemble the piston with the part number toward the camshaft.

9.11 *Cylinder Liner*—Use a new 1Y3805 or 1Y3997 cylinder liner for each test.

9.11.1 After removing the protective oil/grease with mineral spirits (see [7.14](#)), clean the liner bore with a hot tap water and heavy-duty clothes washing detergent solution, then rinse with hot tap water.

9.11.2 Measure and record the liner surface finish. The surface finish specification shown in [Fig. A10.3](#) does not apply to the 1Y3997 cylinder liner.

9.11.3 Oil the liner bore with only Mobil EF-411. Assemble the cylinder liner, block and head with the torque specification shown in the 1Y3700 Service Manual or [Fig. A10.1](#).

9.11.4 Measure the liner with a dial bore gage to ensure that the out-of-round and taper conditions are within specified tolerances measured at seven intervals as shown in [Fig. A10.3](#). Measure the cylinder liner projection using the modified indicator shown in [Fig. A10.4](#).

9.11.5 Torque the cylinder liner support ring using the procedure shown in [Fig. A10.5](#).

9.12 *Compression Ratio*—Before starting each test, measure the piston-to-head clearance to ensure the proper compression ratio is used. Determine this dimension by using lead balls, each with a diameter of approximately 3.5 mm. Locate four lead balls on the top of the piston at 90° intervals on the major and minor piston diameters. Hold them in place with light grease. With the piston near the top of the stroke, install the head and block assembly and torque to specifications. Turn the engine over top center by hand to compress the lead balls then remove the head and block assembly and measure the thickness of the lead balls to obtain the average piston-to-head clearance. The piston-to-head clearance specification is 1.62 mm ± 0.07 mm. Use multiple 1Y3817 block gaskets to adjust the clearance. If the piston-to-head measurement exceeds the tolerance specification, check the crankshaft main and rod journals, connecting rod and main bearings, and piston pin and rod bushing for excessive wear. The specified compression ratio for the 1Y3700 engine is 16.2 to 1.

9.13 *Engine Timing*—The engine ECM sets desired fuel injection timing to 13° BTC. Record this timing using the engine technician service tool. Mechanically time the actual engine components as shown in [Annex A10](#). Install the electronic sensors as shown in the Electronic Installation and Operation manual. Correctly assemble both the mechanical and electrical systems to produce the desired fuel timing.

9.14 *Engine Coolant System Cleaning Procedure*—Clean the coolant system when visual inspections show the presence of any oil, grease, mineral deposits, or rust following the procedure listed in [Annex A3](#).

9.15 After the engine components have been prepared and assembled, perform the following:

9.15.1 Fill the crankcase with 5800 g ± 50 g of test oil.

9.15.2 Install a new 1R0713 oil filter.

9.15.3 Fill the coolant system with coolant specified in [Section 7](#).

9.15.4 Ensure the facility coolant to the engine heat exchanger is operational.

9.15.5 Pressurize the fuel system to remove air, then return the system to a non-pressurized state before starting engine.

9.15.6 Ensure all other systems and facilities are operational before starting the engine break-in.

10. Calibration and Standardization

10.1 *Test Cell Instrumentation*—Calibrate all facility read-out instrumentation used for the test immediately prior to subsequent stand calibration. Instrumentation calibration prior to subsequent stand calibration tests (that is, those that follow a failed or invalid first attempt) are at the discretion of the test laboratory. Refer to [Annex A2](#) for calibration tolerances and allowable *system* time constants.

10.2 *Instrumentation Standards*—Calibrate all temperature, pressure, flow, and speed measurement *standards* on a yearly basis. The calibration of all standards shall be traceable to a national bureau of standards. Maintain all calibration records for a minimum of two years.

10.3 *Coolant Flow*—Calibrate the coolant flow rate as follows: (1) calibrate the differential pressure transducer as outlined in [10.1](#) and [10.2](#) and, (2) replace the Barco venturi every two years.^{23,11} Use the following relationships as conversion factors from the differential pressure across the Barco venturi to liters per minute: 3.0 in. H₂O = 24.3 L/min, 7.1 in. H₂O = 37.8 L/min and 28 in. H₂O = 75.7 L/min or use [Eq 1](#) where ΔP is measured in in. H₂O.

$$L/min = \sqrt{\Delta P} \ 14.44 - 0.69 \quad (1)$$

10.4 *Re-calibration Requirements*—Re-calibration due to parts replacement is not required unless the engine crankcase or crankshaft, or both, require replacing or regrinding, or the crankshaft is removed for any other purpose besides bearing replacement, or the head/jug suffer a failure for any reason during the calibration period.

10.5 *Fuel Injectors*—The fuel injectors are calibrated during the manufacturing process. These fuel injectors can not be re-calibrated in the usual manner and require special test equipment to ensure proper flow, timing response, and spray patterns. Therefore, replace the fuel injector at the start of every calibration test (unless that test is the second of two required tests for a new stand or is a rerun of a previous calibration attempt). If the fuel injector is replaced on a calibrated stand, re-calibration is not required.

10.6 *Air Flow*—Install the Sierra Model 780 airflow meter to measure intake airflow. This meter should be calibrated yearly at a temperature of 60 °C. Measure the intake airflow during the break-in of every calibration test. Record the last value recorded during step five of the break-in as shown in [Annex A12](#).

10.7 *Intake Air Barrel*—Prior to each stand calibration test, inspect the intake air barrel for rust or debris. This may be done through either of the pipe flanges using a borescope or some other optical means.

10.8 *Fuel Filter*—Change the fuel filter before every calibration test.

10.9 *Oil Scale Flow Rates*—Verify the oil scale flow rates before the start of every calibration test using the procedure listed in [Annex A6](#).

10.10 *Calibration of Test Stands*—Use a blind calibration oil from the TMC to calibrate the engine stand. A stand calibration test is required every nine months. The calibration period begins on the start date of the acceptable calibration test. A test stand is considered calibrated when the test results are within the acceptability limits as published by TMC and the test is operationally valid. The TMC may request stand checks on calibration tests that fail to meet acceptability limits. If the calibration test is operationally valid, send the piston to another calibrated laboratory for a referee rating. The TMC issues a control chart analysis for each calibration test to the testing laboratory (see [Fig. A14.2](#)). The test stand is not considered calibrated if the calibration test was invalid or uninterpretable. Start any non-reference test prior to the expiration of the calibration period.

10.11 *Guidelines for Adjustments to Calibration Periods*—Reference oil test frequency may be adjusted for the following reasons:

²³ The sole source of supply of the apparatus known to the committee at this time is Hyspan Precision Products, Inc., 1685 Brandywine Avenue, Chula Vista, CA 91911.

10.11.1 *Procedural Deviations*—On occasions when a laboratory becomes aware of a significant deviation from the test method, such as might arise during an in-house review or a TMC inspection, the laboratory and the TMC shall agree on an appropriate course of action to remedy the deviation. This action might include the shortening of existing reference oil calibration periods.

10.11.2 *Parts and Fuel Shortages*—Under special circumstances, such as industry-wide parts or fuel shortages, the surveillance panel might direct the TMC to extend the time intervals between reference oil tests. These extensions shall not exceed one regular calibration period.

10.11.3 *Reference Oil Test Data Flow*—To ensure continuous severity and precision monitoring, calibration tests are conducted periodically throughout the year. There might be occasions when laboratories conduct a large portion of calibration tests in a short period of time. This could result in an unacceptably large time frame when very few calibration tests are conducted. The TMC can shorten or extend calibration periods as needed to provide a consistent flow of reference oil test data. Adjustments to calibration periods are made such that laboratories incur no net loss (or gain) in calibration status.

10.11.4 *Special Use of the Reference Oil Calibration System*—The surveillance panel has the option to use the reference oil system to evaluate changes that have potential impact on test severity and precision. This option is only taken when a program of donated tests is not feasible. The surveillance panel and the TMC shall develop a detailed plan for the test program. This plan requires all reference oil tests in the program to be completed as close to the same time as possible, so that no laboratory/stand calibration is left in an excessively long pending status. In order to maintain the integrity of the reference oil monitoring system, each reference oil test is conducted so as to be interpretable for stand calibration. To facilitate the required test scheduling, the surveillance panel might direct the TMC to lengthen and shorten reference oil calibration periods within laboratories such that the laboratories incur no net loss (or gain) in calibration status.

10.12 *Donated Reference Oil Test Programs*—The Surveillance Panel is charged with maintaining effective reference oil test severity and precision monitoring. During times of new parts introductions, new or re-blended reference oil additions, and procedural revisions, it might be necessary to evaluate the possible effects on severity and precision levels. The surveillance panel might choose to conduct a program of donated reference oil tests in those laboratories participating in the monitoring system, in order to quantify the effect of a particular change on severity and precision. Typically, the surveillance panel requests its panel members to volunteer enough reference oil test results to create a robust data set. Broad laboratory participation is needed to provide a representative sampling of the industry. To ensure the quality of the data obtained, donated tests are conducted on calibrated test stands. The surveillance panel shall arrange an appropriate number of donated tests and ensure completion of the test program in a timely manner.

[ASTM D6681-23](https://standards.iteh.ai/catalog/standards/sist/f33eb230-6f33-49ce-9333-44f4365d8780/astm-d6681-23)

<https://standards.iteh.ai/catalog/standards/sist/f33eb230-6f33-49ce-9333-44f4365d8780/astm-d6681-23>

10.13 *Test Run Numbering*—Number each test to identify the test stand number and the test run number. Number all runs sequentially. Append repeat calibration runs with a letter that is also sequential (that is, number the first rerun of test 45 as 46A, the second as 47B, and so forth). Maintain the letter suffix sequencing for each calibration test until the calibration has been accepted. Increment the run number for any test start.

10.14 *Humidity Calibration Requirements*—The accuracy of the laboratory's primary humidity measurement system shall be within ± 0.6 g of the humidity measuring chilled mirror dew point hygrometer or equivalent.

10.14.1 Calibrate the primary laboratory humidity measurement system within 48 h before the start of each stand calibration test or during the calibration test at each stand using a chilled mirror dew point hygrometer or equivalent with an accuracy of at least ± 0.55 °C at a dew point of 24 °C.

10.14.2 The calibration consists of a series of paired comparison measurements between the primary system and the chilled mirror dew point hygrometer or equivalent. The comparison period lasts from 20 min to 2 h with measurements taken at 1 min to 6 min intervals, for a total of 20 paired measurements. The measurement interval should be appropriate for the time constant of the humidity measuring instruments.

10.14.3 Ensure that the flow rate is within the equipment manufacturer's specification.

10.14.4 Take all measurements made with the dew point hygrometer or equivalent at atmospheric pressure and correct them to standard pressure conditions (101.12 kPa). Compute the difference between each pair of measurements and calculate the mean and standard deviation of the differences. The absolute value of the mean difference shall not exceed 0.6 g and the standard deviation shall be less than or equal to 0.3 g.

10.14.5 The primary humidity measurement system is deemed calibrated only if both of these requirements are met. If either of these requirements is not met, investigate the cause, make repairs, and recalibrate. Maintain the calibration data for a minimum of two years.

10.15 *Calibration of Piston Deposit Raters*—Each calendar year, each facility shall send at least one Heavy Duty Diesel Piston Rater to the ASTM ~~Heavy Duty Piston Rating Workshop held every Fall.~~ Standardized Testing Deposit Rating Workshop. Each rater shall rate a minimum of six diesel pistons. If this schedule is not suitable to a particular rater or test laboratory, then make alternative arrangements as soon as possible to have the rater calibrated.

11. Procedure

11.1 *Engine Break-in Procedure*—Open any drain taps at the low points of the combustion air system (if they are installed) during the start of the break-in and warm-ups, and following any shutdowns.

11.1.1 The engine break-in and operational conditions are specified in [Annex A12](#). The total break-in time is 85 min. During the break-in, fix all leaks and make adjustments to ensure proper engine operation. Record the ECM personality module part number and release date.

11.1.2 After the break-in period and while the engine is hot, drain the oil from the crankcase, oil cooler, engine oil filter, and weigh scale for 30 min. Then weigh 5800 g \pm 50 g of new test oil into the engine.

11.1.3 Start the engine, warm it up, and operate it for 360 h at the test conditions specified in step five of [Annex A12](#) with no oil changes.

11.1.4 Turn on the oil scale pumps once the engine has reached the beginning of Step 5 of the warm-up sequence. Record the oil mass in the oil scale as the full mark at the end of the fourth test hour. Throughout the test, record the oil scale reading at least once every 6 min.

11.1.5 Count test time from the moment the warm-up time is completed. The oil sample frequency is described in [Section 8](#).

11.1.6 Do not remove the cylinder head, piston, or power assembly from the engine during a test.

11.1.7 Reinitialize engine timing calibration after the cam shaft/gear or cylinder head has been removed. See the electronic installation and operation manual. Complete this during the first step of the break-in.

11.2 *Cool-down Procedure*—Except for emergency (uncontrolled) stops, shut the engine down by operating it at conditions shown in Steps 4, 3, 2, and then 1 in [Annex A12](#).

11.3 *Warm-up Procedure*—Use the same procedure used for engine break-in to warm-up the engine for all subsequent starts throughout the test.

11.4 *Shutdowns and Lost Time*—Record the test hours, date, and length of off-test conditions for all occurrences. Record when the engine has early inspections or early test termination with the reasons for the occurrences. If the cool down procedure is not used, identify the shutdown as an *Emergency Shutdown*. A maximum allowed time of off-test conditions is 125 h. If the engine shuts down, immediately stop the oil scale pumps. In the event of an emergency shutdown, leave the engine shut down for 2 h (or more) to allow complete engine cool down before restarting. In order to limit foreign matter entering the combustion chamber and to protect piston deposits, rotate the engine to top dead center of the compression stroke during downtime.

11.5 *Periodic Measurements*—Record all engine conditions listed in Step 5 of [Annex A12](#) as a snapshot at least once every 6 min. Record humidity readings using the laboratory's primary humidity measurement system. Correct the recorded humidity values to standard pressure conditions of 101.12 kPa. Record the fuel position as indicated by the electronic technician at test hours 24, 240, and 360.

11.6 *Engine Control Systems:*

11.6.1 *Engine Coolant*—Pressurize the coolant system to 35.0 kPa \pm 7 kPa as shown in [Annex A3](#) to ensure the water does not boil out of the antifreeze. Manually adjust the coolant flow rate by turning the valve on top of the coolant tower to maintain the conditions specified in [Annex A12](#).

11.6.2 *Engine Fuel System*—Control the fuel rate by modifying the fuel limit adjusting the ECM using a facility controller that compares the actual fuel rate to the specified fuel rate listed in [Annex A12](#). See the Electronic Installation and Operation manual for more details. Manually adjust the Fisher regulator to control fuel pressure. Maintain the fuel pressure and temperature as specified in [Annex A12](#).

11.6.3 *Engine Oil Temperature*—Maintain the oil manifold temperature to test specifications as shown in [Annex A12](#). The temperature of the Paratherm NF shall not exceed 165 °C at any time during break-in, warm-up, or testing. Shut off the external oil heater (but not its circulating pump) the moment the engine goes to cool-down.

11.6.4 *Exhaust Pressure*—Set the pressure as specified in [Annex A12](#) using a facility feedback-controlled restrictor valve.

11.6.5 *Intake Air*—Filter, compress, and humidify the inlet air to the conditions specified in [Annex A12](#). Heat (or cool, if necessary) the inlet air to the conditions in [Annex A12](#).

11.7 *Post-Test Procedures*—Remove the piston and ring assembly from the engine. Mark the location of the ring gaps on top of the piston.

11.7.1 *Piston Ring Side Clearances*—Measure the piston ring side clearances prior to removal of the rings to determine the level of deposit formation (see [Annex A10](#)). Align ring gaps to the EOT ring gap marks on the top of the piston. Do not force the feeler gages between the ring and groove to disturb or remove the deposits.

11.7.2 *Piston Ratings*—Immerse the piston assembly in mineral spirits (see [7.14](#)) and air-dry it prior to any rating.

11.7.2.1 Process and measure the piston deposits according to the Modified CRC Diesel Piston Rating Method described in ASTM Deposit Rating Manual 20 modified by the directions listed in [Annex A13](#). Rate only two levels of carbon (heavy and light) on the second groove and all lands, and only one level of carbon (light) for the under-crown and cooling groove. Use a combined varnish rating method for the third groove, third land, fourth land, under-crown, and cooling groove (see [Annex A13](#)). An example rating worksheet is shown in [Appendix X1](#).

11.7.2.2 Another heavy-duty engine deposit rater shall verify all piston deposit ratings done by the testing laboratory. In special cases where another rater is not available, the rating may be verified by other qualified laboratory personnel. Record the initials of both the rater and the verifying rater.

11.7.3 *Referee Ratings*—The referee laboratory rates the entire piston. Wrap all pistons to be referee-rated in paper with ASTM desiccant chips. Then place them in plastic and seal before shipping to the referee laboratory. Report referee ratings to the TMC within ten days of EOT for calibration tests. Referee-rate piston deposits for all non-reference tests reviewed by Caterpillar.

11.7.4 *Ring End Gap Increase*—Remove all carbon from the rings. If scraping of the rings is necessary, use only a wooden instrument or equivalent. Measure and record the ring end gaps.

11.7.5 *Cylinder Liner Wear*—Use a surface profile measurement to determine the liner wear step in both transverse and longitudinal directions relative to the crankshaft. Remove deposits on the liner above the piston ring travel. Take transverse and longitudinal measurements at the wear step location approximately 13 mm from the top of the liner at four locations. Record the measurements as the liner wear step.

11.7.6 *Cylinder Liner Bore Polish*—Section the cylinder liner through the front and rear axis and measure the cylinder liner to determine the amount of bore polishing. Use the liner rating method listed in [Annex A13](#).

11.7.7 *Photographs*—Photograph the piston and rings showing the thrust, anti-thrust, front, rear, and undercrown positions (see [Appendix X1](#)). Place the rings on top of the piston to show ring gaps (thrust view) and 180° from gaps (anti-thrust view). Show the piston from the crown down to at least the bottom of the pin bore. Photograph the piston crown and skirt as one assembly. Photograph the bore ID of the sectioned liner (see [Appendix X1](#)).