

SLOVENSKI STANDARD SIST ETS 300 679 E1:2003

01-december-2003

Terminalska oprema (TE) – Telefonija za slušno prizadete – Telefonski aparati, električno spojeni s slušnimi pripomočki

Terminal Equipment (TE); Telephony for the hearing impaired; Electrical coupling of telephone sets to hearing aids

iTeh STANDARD PREVIEW (standards.iteh.ai)

Ta slovenski standard je istoveten 25 300 679 Edition 1 14-

26e15cdebc12/sist-ets-300-679-e1-2003

ICS:

11.180.15 Pripomočki za gluhe osebe in Aids for deaf and hearing

osebe z okvaro sluha impaired people

33.050.10 Telefonska oprema Telephone equipment

SIST ETS 300 679 E1:2003 en

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ETS 300 679 E1:2003



EUROPEAN TELECOMMUNICATION

ETS 300 679

September 1996

Source: ETSI TC-TE Reference: DE/TE-04093

ICS: 33.020

Key words: Telephony, electrical coupling, hearing aids, PWSN

iTeh STANDARD PREVIEW Terminal Equipment (TE);

Telephony for the hearing impaired;

Electrical coupling of telephone sets to hearing aids

se15cdebc12/sist-ets-300-679-e1-2003

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - Internet: secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

Page 2

ETS 300 679: September 1996

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ETS 300 679 E1:2003

Contents

Forev	vord			5		
Introc	luction			5		
1	Scope					
2	Normative references					
3	Abbreviations					
4	Electrical characteristics					
	4.1 Point of connection in the telephone set					
	4.2		I characteristics at interconnection point			
		4.2.1	Setting the acoustic receive and signal generator reference drive levels			
		4.2.2	Impedance			
		4.2.3	Sensitivity			
		4.2.4	Frequency characteristic			
		4.2.5	Maximum output			
		4.2.6	Noise			
		4.2.7	Linearity check			
	4.3		Lineality check			
	4.5	Salety	eh STANDARD PREVIEW	3		
5	latoroonu		EII STANDARD PREVIEW	_		
5	mercom	iection wi	th the telephone set	8		
6	Toot pro		(Standards.iten.ar)	0		
O	6.1	Sotting t	ne reference drive level	9		
		Setting ti	ing the glassification of the first state of the state of	8		
	6.2	Determir	ning the electrical impedance at the interconnection point ment of the sensitivity with the interconnection point interconnection po	11		
	6.3	Measure	ment of the sensitivity	11		
	6.4	Determin	ling the frequency characteristic	11		
	6.5		ning the maximum output level			
	6.6		ning the electrical noise level			
	6.7	Checking	g the input/output linearity	11		
Anne	x A (norm	ative):	Packaging, labelling and user instructions	12		
A.1	Packagir	ng and lab	elling	12		
A.2	User inst	ructions		12		
A.3	Product \$	Suppliers	Information	12		
	x B (inforn		Rationale for electrical output sensitivity chosen			
	,	,				
	x C (inforn	,	Coupling to the hearing aid			
C.1	Connector position					
C.2	Interconr	necting lea	ad	14		
Anne	x D (inforn	mative):	Bibliography	15		
Histo	rv			16		

Page 4

ETS 300 679: September 1996

Blank page

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ETS 300 679 E1:2003

Page 5

ETS 300 679: September 1996

Foreword

This European Telecommunication Standard (ETS) has been produced by the Terminal Equipment (TE) Technical Committee of the European Telecommunications Standards Institute (ETSI).

Transposition dates				
Date of adoption of this ETS:	23 August 1996			
Date of latest announcement of this ETS (doa):	31 December 1996			
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	30 June 1997			
Date of withdrawal of any conflicting National Standard (dow):	30 June 1997			

Introduction

This ETS is the third in a series developed especially to meet the needs of people with hearing impairments who want to use the telephone. The first, ETS 300 381, covers inductive coupling and the second, ETS 300 488, covers additional amplification. This ETS covers the possibility of electrical coupling from a telephone set to a hearing aid, and all three ETSs are in general accordance with ITU-T Recommendation P.37. This ETS is intended to be compatible with the IEC Publication 118, Part 6, which covers the characteristics of electrical input ports for hearing aids. It is anticipated that electrical coupling would benefit a limited number of users and should be regarded as an additional method and not a replacement for inductive coupling.

It is envisaged that direct electrical connection between a hearing aid and a telephone set could be used in other applications that require electrical connection to the Public Switched Telephone Network (PSTN), for example to couple into other non-telephony amplification systems such as public address, or recording systems. Another alternative would be the direct electrical connection to a hearing aid transducer or headset, given that the device had sufficient sensitivity 679-e1-2003

Some of the applications envisaged would need to address safety and/or protection issues and, although these and the applications themselves do not come within the scope of ETSI standards, attention is drawn to them here for information.

I-ETS 300 245-4 (covering the Additional Equipment Interface standard) could find application for coupling to the receive path of a telephone into a hearing aid.

NOTE:

It is possible that the system described could enable hearing aid users to use low-powered GSM (Group Special Mobile) telephones or DECT (Digital Enhanced Cordless Telephone). In this case some attention would need to be paid to ensure that disturbing signals are controlled sufficiently to prevent modulated carrier signals from interferencing with the hearing aid. It is not possible to be more specific at this stage.

Page 6

ETS 300 679: September 1996

Blank page

iTeh STANDARD PREVIEW (standards.iteh.ai)

SIST ETS 300 679 E1:2003

Page 7

ETS 300 679: September 1996

1 Scope

This European Telecommunication Standard (ETS) specifies the electrical characteristics for the electrical coupling of the telephony function implemented in Terminal Equipment (TE) to hearing aids. It specifies the level and frequency response relative to the acoustic output at the earphone, and also the noise and maximum level.

This ETS applies to all apparatus that is capable of supporting telephony and can be connected to the Public Switched Telephone Network (PSTN) or Integrated Services Digital Network (ISDN), which are intended for direct application to the ear, using for example traditional handsets or operator's headsets, and which provide an electrical output port for the prime purpose of coupling electrically to a hearing aid. This ETS may also be invoked for mobile apparatus and apparatus having cordless handsets that provide the facility for electrical coupling to hearing aids.

Although handsfree and loudspeaking devices are outside the scope of this ETS, if such apparatus also supports handset telephony as a separate function, this ETS may be invoked as part of that function.

2 Normative references

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

[1]	ITU-T Recommendation P.57 (1994): "Artificial ears".
[2]	iT dEC Publication 268-11 (1987): "Sound System Equipment Part 11: Application of Connectors for the Interconnection of Sound System Components". (standards.iteh.ai)
[3]	CCITT Handbook on Telephonometry, ITU (1992).
[4]	ITU-T Recommendation P 64 (1994): "Determination of sensitivity/frequency https://standards.ite.hav.gata.org/standards/standar
[5]	CCITT Recommendation P.53 (1988): "Psophometers (apparatus for the objective measurement of circuit noise)".

3 Abbreviations

For the purposes of this ETS, the following abbreviations apply:

dBVp Decibels relative to 1 Volt, psophometrically weighted

ERP Ear Reference Point

ISDN Integrated Services Digital Network
PSTN Public Switched Telephone Network

TE Terminal Equipment