



Designation: D2379 – 09 (Reapproved 2023)

Standard Test Method for Acidity of Formaldehyde Solutions¹

This standard is issued under the fixed designation D2379; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method covers the determination of the acidity of commercially available formaldehyde solutions.

1.2 For purposes of determining conformance of an observed or a calculated value using this test method to relevant specifications, test result(s) shall be rounded off “to the nearest unit” in the last right-hand digit used in expressing the specification limit, in accordance with the rounding-off method of Practice E29.

1.3 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.4 For hazard information and guidance, see the supplier’s Safety Data Sheet.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.* Specific hazard statements are given in Section 7.

1.6 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*²

D1193 Specification for Reagent Water

D2380 Test Method for Methanol Content of Formaldehyde Solutions

¹ This test method is under the jurisdiction of ASTM Committee D01 on Paint and Related Coatings, Materials, and Applications and is the direct responsibility of Subcommittee D01.35 on Solvents, Plasticizers, and Chemical Intermediates.

Current edition approved July 1, 2023. Published August 2023. Originally approved in 1965. Last previous edition approved in 2017 as D2379 – 09 (2017). DOI: 10.1520/D2379-09R23.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard’s Document Summary page on the ASTM website.

E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications

E200 Practice for Preparation, Standardization, and Storage of Standard and Reagent Solutions for Chemical Analysis

3. Summary of Test Method

3.1 A specimen is titrated with standard alkali to the bromthymol blue end point.

4. Significance and Use

4.1 This test method provides a measurement of acidity (as formic acid) in formaldehyde solutions. The results of these measurements can be used for specification acceptance.

5. Apparatus

5.1 *Buret*, 25 mL, calibrated in 0.1 mL divisions. A TFE-fluorocarbon resin stopcock is suitable for this purpose.

6. Reagents and Materials

6.1 *Purity of Reagents*—Reagent grade chemicals shall be used in all tests. Unless otherwise indicated, it is intended that all reagents shall conform to the specifications of the Committee on Analytical Reagents of the American Chemical Society, where such specifications are available.³ Other grades may be used, provided it is first ascertained that the reagent is of sufficiently high purity to permit its use without lessening the accuracy of the determination.

6.2 *Purity of Water*—Reference to water shall be understood to mean reagent water conforming to Type IV or better of Specification D1193.

6.3 *Bromthymol Blue Indicator Solution (1.0 g/L)*—Dissolve 0.1 g of the water-soluble form of bromthymol blue indicator powder in 100 mL of water.

6.4 *Sodium Hydroxide, Standard Solution (0.1 N)*—Prepare and standardize 0.1 N sodium hydroxide (NaOH) solution as described in Practice E200.

³ *ACS Reagent Chemicals, Specifications and Procedures for Reagents and Standard-Grade Reference Materials*, American Chemical Society, Washington, DC. For suggestions on the testing of reagents not listed by the American Chemical Society, see *Analar Standards for Laboratory Chemicals*, BDH Ltd., Poole, Dorset, U.K., and the *United States Pharmacopeia and National Formulary*, U.S. Pharmacopeial Convention, Inc. (USPC), Rockville, MD.

7. Hazards

7.1 Formaldehyde and formaldehyde solutions are hazardous and exposure to them should be minimized to avoid acute effects and possible sensitization. Consult your supplier's Safety Data Sheet for specific hazard information.

7.2 Sodium hydroxide solutions are corrosive and hazardous. Exercise steps to prevent contact with the skin or eyes. Consult supplier's Material Safety Data Sheet for specific hazard.

8. Procedure

8.1 Measure 50 mL of the sample into a 250 mL Erlenmeyer flask, add 3 or 4 drops of bromthymol blue indicator solution, and titrate with 0.1 *N* NaOH solution to a blue end point.

8.2 If good laboratory practice dictates that the concentration of NaOH be adjusted as a result of higher or lower acid levels, then adjust as necessary using Practice E200, and titrate to a blue end point.

9. Calculation

9.1 Calculate the percent of formic acid as follows:

$$\text{Formic acid, weight \%} = [(V \times N \times 0.046)/(S \times D)] \times 100 \quad (1)$$

where:

- V* = millilitres of NaOH solution, required for titration of the specimen,
- N* = normality of the NaOH solution,
- 0.046 = the milliequivalent weight of formic acid,
- S* = millilitres of sample used, and
- D* = specific gravity of sample.

The value of *D* from Test Method D2380, may be used, although specific gravity estimated to the second decimal is adequate.

10. Report

10.1 Report the percent formic acid to the nearest 0.001 %. Duplicate determinations which agree within 0.002 % absolute are acceptable for averaging (95 % confidence level).

11. Precision and Bias

11.1 In an interlaboratory study of this test method, the within-laboratory standard deviation was found to be 0.0007 % absolute at 60 degrees of freedom, and the between-laboratories standard deviation 0.0031 % absolute at 9 degrees of freedom. Based on these standard deviations, the following criteria should be used for judging the acceptability of results at the 95 % confidence level:

11.1.1 *Repeatability*—Two results, each the mean of duplicates, obtained by the same analyst on different days should be considered suspect if they differ by more than 0.002 % absolute.

11.1.2 *Reproducibility*—Two results, each the mean of duplicates, obtained by analysis in different laboratories, should be considered suspect if they differ by more than 0.010 % absolute.

NOTE 1—The above precision estimates are based on an interlaboratory study involving ten laboratories using three samples with two analysts performing duplicate runs on each of two days. The mean level of the acidity value of the samples studied was 0.02 %.

11.2 *Bias*—Bias of this test method has not been determined because primary standards do not exist.

12. Keywords

12.1 formaldehyde; formic acid

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; http://www.copyright.com/