



Designation: **F3061/F3061M–23 F3061/F3061M – 23a**

Standard Specification for Systems and Equipment in Aircraft¹

This standard is issued under the fixed designation F3061/F3061M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reappraisal. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reappraisal.

1. Scope

1.1 This specification covers the systems and equipment aspects of airworthiness and design for aircraft. The material was developed through open consensus of international experts in general aviation. This information was created by focusing on Level 1, 2, 3, and 4 Normal Category aeroplanes. The content may be more broadly applicable; it is the responsibility of the Applicant to substantiate broader applicability as a specific means of compliance. The topics covered within this specification are: Basic Information, Electrical Systems, Environmental Requirements, Manual Flight Controls, Automatic Flight Controls, Flight Data and Voice Recording, Hazard Mitigation, Hydraulic Systems, Instrumentation, Mechanical Systems and Equipment, Exterior Lighting, Oxygen Systems, Pneumatic Systems, Lightning Protection, and High-Intensity Radiated Field (HIRF) Protection.

1.2 An applicant intending to propose this information as Means of Compliance for a design approval must seek guidance from their respective oversight authority (for example, published guidance from applicable civil aviation authorities (CAAs) concerning the acceptable use and application thereof. For information on which oversight authorities have accepted this standard (in whole or in part) as an acceptable Means of Compliance to their regulatory requirements (hereinafter “the Rules”), refer to the ASTM Committee F44 web page (www.astm.org/COMMITTEE/F44.htm).

1.3 This document may present information in either SI units, English Engineering units, or both; the values stated in each system may not be exact equivalents. Each system shall be used independently of the other; combining values from the two systems may result in nonconformance with the standard.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.5 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 Following is a list of external standards referenced throughout this specification; the earliest revision acceptable for use is indicated. In all cases later document revisions are acceptable if shown to be equivalent to the listed revision, or if otherwise formally accepted by the governing civil aviation authority; earlier revisions are not acceptable.

¹ This specification is under the jurisdiction of ASTM Committee F44 on General Aviation Aircraft and is the direct responsibility of Subcommittee F44.50 on Systems and Equipment.

Current edition approved Feb. 1, 2023/Sept. 1, 2023. Published February 2023/September 2023. Originally approved in 2015. Last previous edition approved in 2022/2023 as F3061/F3061M–22b. DOI: 10.1520/F3061–F3061M–23–23. DOI: 10.1520/F3061–F3061M–23A.

2.2 ASTM Standards:²

- F3060 Terminology for Aircraft
- F3083/F3083M Specification for Emergency Conditions, Occupant Safety and Accommodations
- F3116/F3116M Specification for Design Loads and Conditions
- F3117/F3117M Specification for Crew Interface in Aircraft
- F3153 Specification for Verification of Aircraft Systems and Equipment
- F3173/F3173M Specification for Aircraft Handling Characteristics
- F3179/F3179M Specification for Performance of Aircraft
- F3227/F3227M Specification for Environmental Systems in Aircraft
- F3228 Specification for Flight Data and Voice Recording in Small Aircraft
- F3230 Practice for Safety Assessment of Systems and Equipment in Small Aircraft
- F3231/F3231M Specification for Electrical Systems for Aircraft with Combustion Engine Electrical Power Generation
- F3232/F3232M Specification for Flight Controls in Small Aircraft
- F3233/F3233M Specification for Flight and Navigation Instrumentation in Aircraft
- F3234/F3234M Specification for Exterior Lighting in Small Aircraft
- F3236 Specification for High Intensity Radiated Field (HIRF) Protection in Small Aircraft
- F3309/F3309M Practice for Simplified Safety Assessment of Systems and Equipment in Small Aircraft
- F3316/F3316M Specification for Electrical Systems for Aircraft with Electric or Hybrid-Electric Propulsion
- F3367 Practice for Simplified Methods for Addressing High-Intensity Radiated Fields (HIRF) and Indirect Effects of Lightning on Aircraft
- F3532 Practice for Protection of Aircraft Systems from Intentional Unauthorized Electronic Interactions

2.3 SAE Standard:³

- SAE ARP4754, Rev A Guidelines for Development of Civil Aircraft Systems

2.4 Other Standards:

- AC/AMC 20-136 Protection of Aircraft Electrical/Electronic Systems against the Indirect Effects of Lightning⁴
- FAA-S-8081-14B, Change 5 Private Pilot Practical Test Standards for Airplane⁴
- RTCA DO-178, Rev B Software Considerations in Airborne Systems and Equipment Certification⁵
- RTCA DO-254 Design Assurance Guidance for Airborne Electronic Hardware⁵

3. Terminology

3.1 Terminology specific to this standard is provided below. For general terminology, refer to Terminology **F3060**.

3.2 *Definitions of Terms Specific to This Standard:* [9a18b5-233e-4264-bffe-f2ea5c7a1a01/astm-f3061-f3061m-23a](https://www.astm.org/standards/F3061/F3061M-23a)

3.2.1 *continued safe flight and landing, n*—continued safe flight and landing is defined as the capability for continued controlled flight and landing, possibly using emergency procedures, but without requiring pilot skill beyond that needed to pass the Private Pilot Practical Test Standard for Airplane (refer to FAA-S-8081-14B), or requiring pilot forces beyond those defined in Specification **F3173/F3173M**. Landing may occur either at an airport or at an emergency landing location consistent with established emergency procedures. Some aircraft damage may be realized, either during flight or upon landing.

3.2.2 *development assurance level, n*—a development assurance level is an indication of the level of those planned and systematic actions used to substantiate, to an adequate level of confidence, that errors in requirements, design, and implementation have been identified and corrected such that the system satisfies the applicable certification basis.

3.2.3 *pneumatic system elements, n*—components associated with systems that use bleed air or other sources of compressed gas for their function (ice protection, vapor cycle cooling, rudder bias, door seal inflation, brake heating, emergency gear extension, emergency braking, etc.) Within the context of pressurization systems, pneumatic system elements include the valve(s) that regulates cabin inflow as well as all upstream equipment items that utilize bleed air; refer to **3.2.4**.

3.2.4 *pressurization system elements, n*—components downstream of the valve(s) that regulates cabin inflow; refer to **3.2.3**.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ Available from SAE International (SAE), 400 Commonwealth Dr., Warrendale, PA 15096, <http://www.sae.org>.

⁴ Available from Federal Aviation Administration (FAA), 800 Independence Ave., SW, Washington, DC 20591, <http://www.faa.gov>.

⁵ Available from RTCA, 1150 18th NW, Suite 910, Washington, DC 20036, <https://www.rtca.org>.

3.2.5 *primary function, n*—a primary function is a function that is installed to comply with applicable requirements for a required function and that provides the most pertinent controls or information instantly and directly to the pilot.

3.2.6 *primary system, n*—a primary system is a system that provides a primary function.

3.2.7 *secondary system, n*—a secondary system is a redundancy system that provides the same function as the primary system.

3.2.8 *unsafe system operating condition, n*—an unsafe system operating condition is any system operating condition which, if not detected and properly accommodated by crew action, would cause one or more serious injuries.

4. Basic Information

NOTE 1—The requirements of this chapter are applicable to all systems and equipment installed in the aircraft. These requirements are in addition to and do not supersede any additional system specific requirements identified elsewhere in these design standards or contained in the rules of the governing civil aviation authority.

4.1 *Function and Installation:*

4.1.1 Each item of installed equipment must be of a kind and design appropriate to its intended function.

4.1.2 Each item of installed equipment must be marked in a way that makes it clear to an installer the equipment’s identification, function, or operating limitations, or any applicable combination of these factors. It is acceptable to reference equipment installation manuals for function or limitation information.

4.1.3 Each item of installed equipment must be installed according to limitations specified for that equipment.

4.1.4 Each item of installed equipment must function properly when installed.

4.1.5 The aircraft systems and equipment required for type certification or by operating rules must be designed and installed so that they perform as intended under the aircraft operating and environmental conditions.

ASTM F3061/F3061M-23a

NOTE 2—The intent of this requirement is to provide assurance that the required systems and equipment will function as intended in the expected operating and environmental conditions. It is recognized that random failures will occur throughout the aircraft life and that the failed device may no longer “perform as intended.” The acceptability of such failures or combination of failures and their associated risks are addressed under the requirements of 4.2.

4.1.6

Level 1 and Low-Stall and Day-VFR	All Others
Reserved	All aircraft systems and equipment must be designed and installed so that they do not adversely affect the safety of the aircraft or its occupants.

4.1.7 All aircraft systems and equipment must be designed and installed so that they do not adversely affect the proper functioning of those systems or equipment, or both, covered by 4.1.5.

4.1.8 Those systems and equipment not required for type certification or by operating rules are not required to perform their intended function under all aircraft operating and environmental conditions, provided that the resultant failure conditions are classified as “Negligible Failure Condition” in the assessment conducted per 4.2.1; refer to Practice F3230.

4.1.8.1 Non-required systems and equipment with failure conditions classified more severe than “Negligible Failure Condition” are not required to perform their intended function under all aircraft operating and environmental conditions, provided the failure is appropriately annunciated to the crew.

4.1.8.2 When addressing the requirements of 4.2, if any credit is taken for the installation, or any aspect, of these non-required systems, the portion of the system for which credit is taken must comply with 4.1.4.

4.2 System Safety Requirements:

4.2.1 An assessment of the aircraft and system functions must be performed to identify and classify the various Failure Conditions associated with each function.

4.2.1.1 Practice **F3230** provides one method of satisfying 4.2 for all normal category aircraft.

4.2.1.2 Practice **F3309/F3309M** provides one method of satisfying 4.2 for a limited set of aircraft as defined in that practice.

4.2.2 The equipment, systems, and installations must be designed to minimize hazards to the aircraft in the event of a probable malfunction or failure.

4.2.2.1

Level 1 and Low-Stall and Day-VFR	All Others
Reserved	The aircraft systems and associated components, considered separately and in relation to other systems, must be designed and installed so that each Catastrophic Failure Condition is "extremely improbable."

4.2.2.2

Level 1 and Low-Stall and Day-VFR	All Others
Reserved	The aircraft systems and associated components, considered separately and in relation to other systems, must be designed and installed so that each Hazardous Failure Condition is "extremely remote."

4.2.2.3

Level 1 and Low-Stall and Day-VFR	All Others
Reserved	The aircraft systems and associated components, considered separately and in relation to other systems, must be designed and installed so that each Major Failure Condition is "remote."

iTeh Standards

(https://standards.itih.ai)

ASTM F3061/F3061M-23a

https://standards.itih.ai/catalog/standards/sist/9e9a18b5-233e-4264-bffe-f2ea5c7a1a01/astm-f3061-f3061m-23a

4.2.2.4

Level 1 and Low-Stall and Day-VFR	All Others
Reserved	For definitions of the failure condition severities and the qualitative probability terms used in 4.2.2, refer to Practice F3230.

4.2.3 As used in 4.2, the term “systems” refers to all pneumatic systems, fluid systems, electrical systems, mechanical systems, and powerplant systems included in the aircraft design except as provided in 4.2.3.1 through 4.2.3.3.

4.2.3.1 Powerplant systems provided as part of the type-certified engine are not subject to the provisions of 4.2.

4.2.3.2 The flight structure (such as wing, fuselage, empennage, engine-mounting, control surfaces and their associated simple systems, and landing gear and their primary attachments) are not subject to the provisions of 4.2.

4.2.3.3 Single failures within brake systems, including associated systems and components, are not subject to the provisions of 4.2 provided it is shown that the aircraft can be brought to rest, with a braked-roll stopping distance of not more than two times that obtained in determining the landing distance per Specification F3179/F3179M, following:

- (1) Failure of any electrical, pneumatic, hydraulic, or mechanical connecting or transmitting element; or
- (2) Loss of any single source of hydraulic or other brake-operating energy.

NOTE 3—The allowances of 4.2.3.3 have traditionally been applied only to jet aircraft with high takeoff and landing speeds.

4.2.4

Level 1 and Low-Stall and Day-VFR	All Others
Reserved	Based on the results of the assessment per 4.2.1, the depth of analysis required to show compliance may be determined in accordance with Practice F3230 or Practice F3309/F3309M.

4.2.5

Level 1 and Low-Stall and Day-VFR	All Others
Reserved	Software and Airborne Electronic Hardware must be designed with the appropriate development assurance level as specified in Table 1 or in accordance with the Development Assurance Level (DAL) assignment methodology outlined in SAE ARP4754; refer to 3.2.2.

Reserved

4.2.5.1

TABLE 1 Development Assurance Level Requirements

Assessment Level ^A	Classification of Failure Conditions ^A				
	Negligible	Minor	Major	Hazardous	Catastrophic
	Software (SW) and Airborne Electronic Hardware (AEH) Development Assurance Levels (DALs) ^B				
I	No SW and/or HW DAL Requirement	P=D	P=C, S=D (See ^C)	P=C, S=D (See ^C)	P=C, S=C (See ^C)
II		P=D	P=C, S=D (See ^C)	P=C, S=C (See ^C)	P=C, S=C (See ^C)
III		P=D	P=C, S=D (See ^C)	P=C, S=C (See ^C)	P=B, S=C (See ^C)
IV		P=D	P=C, S=D (See ^C)	P=B, S=C (See ^C)	P=A, S=B (See ^C)

^A Refer to Practice F3230.

^B The letters of the alphabet used above denote the typical SW and AEH DALs. “P” indicates the primary system; “S” indicates the secondary system; “A,” “B,” “C,” and “D” indicate the DAL in accordance with RTCA DO-178B/DO-178 or RTCA DO-254 as applicable. For example, an indication of “P=A” would translate to a SW or AEH DAL of “A” on the primary system.

^C A secondary system is not necessarily required; however, if a secondary system is needed to meet the probability goals of Practice F3230, then that secondary system must meet the stated DAL goal.

Level 1 and Low-Stall and Day-VFR	All Others
Reserved	In showing compliance with the provisions of 4.2.5, once a DAL is assigned, acceptable means of compliance may be found in RTCA DO-178 or RTCA DO-254, or both; refer to Section 2.

4.2.6

Level 1 and Low-Stall and Day-VFR	All Others
Reserved	Information concerning an unsafe system operating condition must be provided in a timely manner to the crew to enable them to take appropriate corrective action; refer to 3.2.8.

4.2.6.1

Level 1 and Low-Stall and Day-VFR	All Others
Reserved	In showing compliance with the provisions of 4.2.6, if immediate pilot awareness and immediate or subsequent corrective action is required, the information required by 4.2.6 must be presented in accordance with Specification F3117/F3117M.

4.2.6.2

Level 1 and Low-Stall and Day-VFR	All Others
Reserved	In showing compliance with the provisions of 4.2.6, one method of assessing an unsafe system operating condition is presented in Appendix X2.

iTeh Standards
(<https://standards.itih.ai>)
Document Preview

[ASTM F3061/F3061M-23a](https://standards.itih.ai/catalog/standards/sist/9e9a18b5-233e-4264-bffe-f2ea5c7a1a01/astm-f3061-f3061m-23a)

<https://standards.itih.ai/catalog/standards/sist/9e9a18b5-233e-4264-bffe-f2ea5c7a1a01/astm-f3061-f3061m-23a>

4.3 Systems and Equipment, Network Information Security Protection:

4.3.1

Level 1 and Low-Stall and Day-VFR	All Others
Reserved	Connectivity of aircraft systems to external networks or devices can lead to an increased risk of intentional unauthorized electronic interactions (IUEI). Aircraft systems and equipment must have mitigations to protect against failure conditions that could result from IUEI.

4.3.2 When aircraft systems are connected to external networks or devices, a security assessment must be performed that:

4.3.2.1

Level 1 and Low-Stall and Day-VFR	All Others
Reserved	Identifies any security risks that could lead to abnormal system operation that would be considered a failure condition;

4.3.2.2

Level 1 and Low-Stall and Day-VFR	All Others
Reserved	Demonstrates that adequate mitigations have been provided to prevent the failure condition from occurring. The mitigations must be shown to be appropriate for the severity of failure condition that they protect against.

4.3.3 Practice **F3532** is an acceptable method of meeting 4.3.1 and 4.3.2.

4.4 Software and Airborne Electronic Hardware:

Level 1 and Low-Stall and Day-VFR	All other Level 1 and level 2	All Others
Reserved	Software and airborne electronic hardware can be addressed via development assurance in accordance with 4.4.1 Or Via System level verification in accordance with 4.4.2.	Software and airborne electronic hardware must be addressed via development assurance in accordance with 4.4.1.

4.4.1 Development Assurance—Software and Airborne Electronic Hardware must be designed with the appropriate Development Assurance Level (DAL) as specified in **Table 1** or in accordance with the Development Assurance Level assignment methodology outlined in SAE ARP4754; refer to **3.2.2**.

4.4.1.1 Once a DAL has been assigned, RTCA DO-178 provides an acceptable means to satisfy the requirements of 4.4.1 for software and DO-254 provides an acceptable means to satisfy 4.4.1 for AEH; refer to **Section 2**.

4.4.2 System Level Verification—Software and airborne electronic hardware within systems and equipment installed in certification level 1 and 2 normal category aircraft may be approved using system level verification.

4.4.2.1 Specification **F3153** provides an acceptable method to meet the requirements of 4.4.2; Refer to **Section 2**.

NOTE 4—The acceptability of this method varies between regulatory agencies. It is generally not considered an acceptable approach for complex, novel systems such as fly-by-wire or propulsion systems. The applicant must seek individual guidance from their respective CAA concerning the use of system level verification.

5. Electrical Systems

5.1 Electrical System Requirements—In addition to the applicable requirements of this specification, electrical systems shall comply with the provisions of **5.1.1** and **5.1.2**.

5.1.1 Electrical systems for aircraft equipped with combustion-engine propulsion shall comply with the provisions of Specification **F3231/F3231M**.

5.1.2 Electrical systems for aircraft equipped with electric propulsion shall comply with the provisions of Specification [F3316/F3316M](#).

6. Environmental Requirements

6.1 *Ventilation Requirements*—In addition to the applicable requirements of this specification, ventilation systems shall comply with the corresponding provisions of Specification [F3227/F3227M](#).

6.2 *Pressurization Requirements*—In addition to the applicable requirements of this specification, pressurization systems shall comply with the corresponding provisions of Specification [F3227/F3227M](#).

7. Manual Flight Controls

7.1 *Manual Flight Control Requirements*—In addition to the applicable requirements of this specification, manual flight controls shall comply with the corresponding provisions of Specification [F3232/F3232M](#).

8. Automatic Flight Controls

8.1 *Automatic Flight Control Requirements*—In addition to the applicable requirements of this specification, automatic flight controls shall comply with the corresponding provisions of Specification [F3232/F3232M](#).

9. Flight Data and Voice Recording

9.1 *Flight Recorder Requirements*—In addition to the applicable requirements of this specification, flight data and voice recording installations shall comply with the provisions of Specification [F3228](#).

10. Hazard Mitigation

10.1 *Takeoff Warning System:*

Level 1	All Others
Reserved	Unless it can be shown that a lift or longitudinal trim device that affects the takeoff performance of the aircraft would not give an unsafe takeoff configuration when selected out of an approved takeoff position, a takeoff warning system must be installed and meet the requirements of 10.1.1 through 10.1.4 .

10.1.1

Level 1	All Others
Reserved	In showing compliance with 10.1 , the system must provide to the pilots an aural warning that is automatically activated during the initial portion of the takeoff roll if the aircraft is in a configuration that would not allow a safe takeoff.

10.1.2

Level 1	All Others
Reserved	The warning provided in accordance with 10.1.1 must continue until the configuration is changed to allow safe takeoff, or action is taken by the pilot to abandon the takeoff roll.

10.1.3

Level 1	All Others
Reserved	In showing compliance with 10.1 , the means used to activate the system must function properly for all authorized takeoff power settings and procedures and throughout the ranges of takeoff weights, altitudes, and temperatures for which certification is requested.

10.1.4

Level 1	All Others
Reserved	For the purpose of showing compliance with 10.1 , an unsafe takeoff configuration is the inability to rotate or the inability to prevent an immediate stall after rotation. This section is not intended to apply to control locks; refer to Specification F3232/F3232M .

10.2 *Pilot Compartment*—For each pilot compartment, the pilot and the aerodynamic controls listed in Specification **F3117/F3117M**, excluding cables and control rods, must be suitably protected from items of mass departing a propeller.

10.2.1 The provisions of **10.2** may be met by ensuring that no part of the pilot or the controls lies in the region between the plane of rotation of any inboard propeller and the surface generated by a line passing through the center of the propeller hub making an angle of 5° forward or aft of the plane of rotation of the propeller.

10.3 *Flammable Fluid Fire Protection:*

10.3.1 Lines, tanks, or equipment containing fuel, oil, or other flammable fluids may not be installed in compartments to be used by the crew or passengers unless adequately shielded, isolated, or otherwise protected so that any breakage or failure of such an item would not create a hazard.

10.3.2 In each area where flammable fluids or vapors might escape by leakage of a fluid system, there must be means to minimize the probability of ignition of the fluids and vapors, and the resultant hazard if ignition does occur; compliance must be shown by analysis or test.

10.3.3

Level 1	All Others
Reserved	Possible sources and paths of fluid leakage, and means of detecting leakage, must be considered when showing compliance with 10.3.2 .

10.3.4

Level 1	All Others
Reserved	Flammability characteristics of fluids, including effects of any combustible or absorbing materials, must be considered when showing compliance with 10.3.2 .

10.3.5

	Level 1	All Others
Reserved		Possible ignition sources, including electrical faults, overheating of equipment, and malfunctioning of protective devices, must be considered when showing compliance with 10.3.2.

10.3.6

	Level 1	All Others
Reserved		Means available for controlling or extinguishing a fire, such as stopping flow of fluids, shutting down equipment, fireproof containment, or use of extinguishing agents, must be considered when showing compliance with 10.3.2.

10.3.7

	Level 1	All Others
Reserved		Ability of aircraft components that are critical to safety of flight to withstand fire and heat must be considered when showing compliance with 10.3.2.

10.3.8

	Level 1	All Others
Reserved		If action by the flight crew is required to prevent or counteract a fluid fire (for example, equipment shutdown or actuation of a fire extinguisher), quick acting means must be provided to alert the crew.

10.3.9

	Level 1	All Others
Reserved		Each area where flammable fluids or vapors might escape by leakage of a fluid system must be identified and defined.

10.4 *Fire Protection of Cargo and Baggage Compartments:*
<https://standards.iteh.ai/catalog/standards/sist/9e9a18b5-233e-4264-bffe-f2ea5c7a1a01/astm-f3061-f3061m-23a>

10.4.1 Sources of heat within each cargo and baggage compartment that are capable of igniting the compartment contents must be shielded and insulated to prevent such ignition.

10.4.2

Level 1	All Others
<p>If the requirements of either 10.4.3 or 10.4.4 are not met, each cargo and baggage compartment must be located where the presence of a fire would be easily discovered by the pilots when seated at their duty station, or it must be equipped with a smoke or fire detector system to give a warning at the pilots' station, and provide sufficient access to enable a pilot to effectively reach any part of the compartment with the contents of a hand held fire extinguisher.</p>	<p>Reserved</p>

10.4.3

Level 1	All Others
<p>If the requirements of either 10.4.2 or 10.4.4 are not met, each cargo and baggage compartment must be equipped with a smoke or fire detector system to give a warning at the pilots' station. In addition, each compartment must meet the requirements of Specification F3083/F3083M.</p>	<p>Reserved</p>

10.4.4

Level 1	All Others
<p>If the requirements of either 10.4.2 or 10.4.3 are not met, each cargo and baggage compartment must be constructed and sealed to contain any fire within the compartment.</p>	<p>Reserved</p>

10.5 *Fire Protection of Flight Controls*—Flight controls located in designated fire zones, or in adjacent areas that would be subjected to the effects of fire in the designated fire zones, must be constructed of fireproof material or be shielded so that they are capable of withstanding the effects of a fire.


<https://standards.iteh.ai>
 Document Preview

[ASTM F3061/F3061M-23a](#)

<https://standards.iteh.ai/catalog/standards/sist/9e9a18b5-233e-4264-bffe-f2ea5c7a1a01/astm-f3061-f3061m-23a>

10.6 *Lines, Fittings, and Components:*

10.6.1 Except as provided in 10.6.3 and 10.6.4, components, lines, and fittings must be shielded or located so as to safeguard against the ignition of leaking flammable fluid.

10.6.2 Except as provided in 10.6.3 and 10.6.4, flexible hose assemblies (hose and end fittings) must be shown to be suitable for the particular application.

10.6.3 Subsections 10.6.1 and 10.6.2 do not apply to lines, fittings, and components, which are already approved as part of the type certificated engine.

10.6.4 Subsections 10.6.1 and 10.6.2 do not apply to vent and drain lines, and their fittings, whose failure will not result in, or add to, a fire hazard.

10.7 *Shutoff Means:*

10.7.1

	Single Engine	All Others
Reserved		Each engine installation must have means to shut off or otherwise prevent hazardous quantities of flammable liquids from flowing into, within, or through any engine compartment, except in lines, fittings, and components forming an integral part of an engine.

10.7.2

	Single Engine	All Others
Reserved		The closing of the fuel shutoff valve for any engine may not make any fuel unavailable to the remaining engines that would be available to those engines with that valve open.

10.7.3

	Single Engine	All Others
Reserved		Operation of any shutoff means may not interfere with the later emergency operation of other equipment such as propeller feathering devices.

10.7.4

	Single Engine	All Others
Reserved		Each shutoff must be outside of the engine compartment unless an equal degree of safety is provided with the shutoff inside the compartment.

10.7.5

	Single Engine	All Others
Reserved		Not more than 0.95 L [0.25 US gal] of flammable fluid may escape into the engine compartment after engine shutoff. For those installations where the flammable fluid that escapes after shutdown cannot be limited to 0.95 L [0.25 US gal], it must be demonstrated that this greater amount can be safely contained or drained overboard.

10.7.6

	Single Engine	All Others
Reserved		There must be means to guard against inadvertent operations of each shutoff means, and to make it possible for the crew to reopen the shutoff means in flight after it has been closed.

10.7.7

	Single Engine	All Others
Reserved		Engine installations need not have an engine oil system shutoff if the conditions of 10.7.7.1 and 10.7.7.2 are met.

10.7.7.1

	Single Engine	All Others
Reserved		To comply with 10.7.7, the oil tank must be integral with, or mounted on, the engine.

IteH Standards
(<https://standards.iteh.ai>)
Document Preview

ASTM F3061/F3061M-23a

<https://standards.iteh.ai/catalog/standards/sist/9e9a18b5-233e-4264-bffe-f2ea5c7a1a01/astm-f3061-f3061m-23a>