



SLOVENSKI STANDARD
SIST EN 300 175-1 V1.6.1:2003
01-december-2003

8 [[]HJbY]nVc`ýUbYVfYnj fj] bYHfY_ca i b]_UMfYfB97HLÈG_i db]j a Ygb]_`f7 ÷È
%fXY. `DfY[`YX

Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1:
Overview

iteh STANDARD PREVIEW
(standards.iteh.ai)

Ta slovenski standard je istoveten z: ^{SIST EN 300 175-1 V1.6.1:2003} **EN 300 175-1 Version 1.6.1**
<https://standards.iteh.ai/catalog/standards/sist/b50eb43c-9bce-4595-a3ab-422de3c0f2f6/sist-en-300-175-1-v1-6-1-2003>

ICS:

33.070.30 Öä åæ ^ Å à [|zæ ^ Digital Enhanced Cordless
à!^: ç|çã } ^ Å | ^ \ [{ ~ } å æ åæ Telecommunications (DECT)
ÇÖÓÓVD

SIST EN 300 175-1 V1.6.1:2003 en

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 175-1 V1.6.1:2003

<https://standards.iteh.ai/catalog/standards/sist/b50eb43c-9bcc-4595-a3ab-422de3c0f2f6/sist-en-300-175-1-v1-6-1-2003>

ETSI EN 300 175-1 V1.6.1 (2002-01)

European Standard (Telecommunications series)

Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview

iTeh STANDARD PREVIEW
(standards.iteh.ai)

[SIST EN 300 175-1 V1.6.1:2003](https://standards.iteh.ai/catalog/standards/sist/b50eb43c-9bcc-4595-a3ab-422de3c0f2f6/sist-en-300-175-1-v1-6-1-2003)

<https://standards.iteh.ai/catalog/standards/sist/b50eb43c-9bcc-4595-a3ab-422de3c0f2f6/sist-en-300-175-1-v1-6-1-2003>



Reference

REN/DECT-000194-1

Keywords

DECT, radio

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

iTeh STANDARD PREVIEW
(standards.iteh.ai)

SIST EN 300 175-1 V1.6.1:2003

<https://standards.iteh.ai/catalog/standards/sist/b50eb43c-9bcc-4595-a3ab-422de3c0f2f6/sist-en-300-175-1-v1-6-1-2003>

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2002.
All rights reserved.

Contents

Intellectual Property Rights	4
Foreword.....	4
1 Scope	5
2 References	5
3 Definitions and abbreviations.....	6
3.1 Definitions	6
3.2 Abbreviations	13
4 Structure	17
4.1 Part 1: Overview.....	17
4.2 Part 2: Physical Layer (PHL)	17
4.3 Part 3: Medium Access Control (MAC) layer.....	18
4.4 Part 4: Data Link Control (DLC) layer.....	18
4.5 Part 5: Network (NWK) layer	18
4.6 Part 6: Identities and addressing.....	18
4.7 Part 7: Security features	18
4.8 Part 8: Speech coding and transmission	18
5 The objectives of the CI standard.....	19
6 General description of the system.....	20
7 Description of the protocol architecture.....	21
7.1 General	21
7.2 The DECT layered structure.....	21
7.3 Physical Layer (PHL).....	21
7.4 MAC layer.....	22
7.5 DLC layer.....	22
7.6 Network (NWK) layer.....	22
7.7 Lower Layer Management Entity (LLME)	22
7.8 Interworking Units (IWU).....	23
8 Proprietary escapes within the CI.....	23
8.1 Primary escape routes.....	23
8.2 Secondary escape routes.....	24
9 Levels of conformance	24
Annex A (informative): Bibliography.....	25
History	26

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This European Standard (Telecommunications series) has been produced by ETSI Project Digital Enhanced Cordless Telecommunications (DECT).

The present document is part 1 of a multi-part deliverable covering the Common Interface (CI) for the Digital Enhanced Cordless Telecommunications (DECT), as identified below:

Part 1: "Overview";

Part 2: "Physical Layer (PHL)";

Part 3: "Medium Access Control (MAC) layer";

Part 4: "Data Link Control (DLC) layer";

Part 5: "Network (NWK) layer";

Part 6: "Identities and addressing";

Part 7: "Security features";

Part 8: "Speech coding and transmission".

The following aspects of the present document are subject to controlled distribution:

- a) DECT identities, as defined in EN 300 175-6 [4];
- b) DECT cryptographic algorithms.

The cryptographic algorithms specify the details of the DECT standard authentication algorithm and the DECT standard cipher.

These aspects are distributed on an individual basis. Further information and details of the current distribution procedures can be obtained from the ETSI Secretariat at the address on the second page of the present document.

Further details of the DECT system may be found in TR 101 178 [7], ETR 043 [9] and TR 102 185 [10].

National transposition dates	
Date of adoption of this EN:	11 January 2002
Date of latest announcement of this EN (doa):	30 April 2002
Date of latest publication of new National Standard or endorsement of this EN (dop/e):	31 October 2002
Date of withdrawal of any conflicting National Standard (dow):	31 October 2002

1 Scope

The present document gives an introduction and overview of the complete Digital Enhanced Cordless Telecommunications (DECT) Common Interface (CI).

This part of the DECT CI contains an abstract of the other parts of the DECT standard together with a general description of:

- the objectives of the present document;
- the DECT Common Interface;
- the protocol architecture of DECT.

The present document also provides an extensive vocabulary; in particular it contains the common definitions of all the technical terms used in different parts of the present document.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

- iTEh STANDARD PREVIEW
(standards.iteh.ai)
- ETSI EN 300 175-1 V1.6.1
https://standards.iteh.ai/catalog/standards/sist/b50eb43c-9bcc-4595-a3ab-72edc9312b33/etsi-en-300-175-1-v1-6-1-2003
- [1] ETSI EN 300 175-3: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer".
- [2] ETSI EN 300 175-4: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 4: Data Link Control (DLC) layer".
- [3] ETSI EN 300 175-5: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) layer".
- [4] ETSI EN 300 175-6: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 6: Identities and addressing".
- [5] ETSI EN 300 175-8: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Part 8: Speech coding and transmission".
- [6] ETSI EN 300 176: "Digital Enhanced Cordless Telecommunications (DECT); Approval test specification; (Part 1: Radio; Part 2: Speech)".
- [7] ETSI TR 101 178: "Digital Enhanced Cordless Telecommunications (DECT); A High Level Guide to the DECT Standardization".
- [8] ETSI ETR 310: "Digital Enhanced Cordless Telecommunications (DECT); Traffic capacity and spectrum requirements for multi-system and multi-service DECT applications co-existing in a common frequency band".
- [9] ETSI ETR 043: "Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Services and facilities requirements specification".
- [10] ETSI TR 102 185: "Digital Enhanced Cordless Telecommunications (DECT); Data Services Profile (DSP); Profile overview".
- [11] ETSI EN 300 403-1: "Integrated Services Digital Network (ISDN); Digital Subscriber Signalling System No. one (DSS1) protocol; Signalling network layer for circuit-mode basic call control; Part 1: Protocol specification [ITU-T Recommendation Q.931 (1993), modified]".

- [12] ITU-R Recommendation SM.1046-1 (1997): "Definition of spectrum use and efficiency of a radio system".
- [13] ITU-R Recommendation M.816-1 (1997): "Framework for services supported on International Mobile Telecommunications-2000 (IMT-2000)".
- [14] ITU-R Recommendation M.1457 (2000): "Detailed specifications of the radio interfaces of International Mobile Telecommunications-2000 (IMT-2000)".
- [15] ITU-T Recommendation X.25: "Interface between Data Terminal Equipment (DTE) and Data Circuit-terminating Equipment (DCE) for terminals operating in the packet mode and connected to public data networks by dedicated circuit".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

Access Rights Class (ARC): type of access to a DECT network, such as public, residential or private

Access Rights Details (ARD): unique number within one ARC

Access Rights Identity (ARI): globally unique identity that shows the access rights related to a service provider

PARI = Primary ARI;

SARI = Secondary ARI;

TARI = Tertiary ARI.

algorithm: mathematical process or function that transforms an input into an output

algorithm identifier: designator to show which algorithm is in use, so that the correct one may be chosen

antenna diversity: diversity implies that the Radio Fixed Part (RFP) for each bearer independently can select different antenna properties such as gain, polarization, coverage patterns, and other features that may effect the practical coverage. A typical example is space diversity, provided by two vertically polarized antennas separated by 10 - 20 cm.

asymmetric algorithm: See public key algorithm.

attach: process whereby a Portable Part (PP) within the coverage area of a Fixed Part (FP) to which it has access rights, notifies the FP that it is operative

authentication: corroboration that an entity is the one that is claimed

authentication of FT: process whereby the identity of an FT is verified to a DECT PT

authentication of PT: process whereby a DECT PT is positively verified to be a legitimate user of a particular FP

authentication (of a subscriber): process whereby a DECT subscriber is positively verified to be a legitimate user of a particular FP

authentication of user: process whereby a DECT user is positively verified to be a legitimate user of a particular FP

bearer: See Medium Access Control (MAC) bearer or bearer service.

bearer handover: internal handover process provided by the MAC layer, whereby one MAC connection can modify its underlying bearers while maintaining the service provided to the Data Link Control (DLC) layer

bearer service: type of telecommunication service that provides a defined capability for the transmission of signals between user-network interfaces

broadcast: simplex point-to-multipoint mode of transmission

C-plane: control plane of the DECT protocol stacks, which contains all of the internal DECT protocol control, but may also include some external user information

call: all of the Network (NWK) layer processes involved in one NWK layer peer-to-peer association

cell: domain served by a single antenna(e) system (including a leaky feeder) of one FP

Central Control Fixed Part (CCFP): physical grouping that contains the central elements of a FP

centrex: implementation of a private telecommunication network exchange that is not located on the premises of the private network operator

Cipher Key (CK): value that is used to determine the transformation of plaintext to ciphertext in a cryptographic algorithm

Cipher Key (CK) generation: process for generating cryptographic keys

ciphertext: output of a cryptographic algorithm

channel: See "physical channel".

cluster: logical grouping of one or more cells between which bearer handover is possible

confidentiality: rendering information secret as ciphertext unless the capability is possessed to recover the plaintext from ciphertext

connection: See "MAC connection".

connection handover: internal handover process provided by the DLC layer, whereby one set of DLC entities (C-plane and U-plane) can re-route data from one MAC connection to a second new MAC connection, while maintaining the service provided to the NWK layer

Connectionless mode (C/L): transmission mode that transfers one packet (one self contained unit) of data from one source point to one (or more) destination points in a single phase

Connection Oriented mode (C/O): transmission mode that transfers data from one source point to one or more destination points using a protocol based on three phases: "Set-up", "Data transfer" and "Release"

Cordless Radio Fixed Part (CRFP): Wireless Relay Station (WRS) that provides independent bearer control to a PT and FT for relayed connections

countermeasure: device, instrument or procedure used to counteract or defend against a threat

coverage area: area over which reliable communication can be established and maintained

cryptography: secret writing

Data Encryption Standard (DES): United States Federal data encryption standard

Data Link Control (DLC): layer 2b of the DECT protocol stack

decipherment: rendering of ciphertext into plaintext

DECT Network (DNW): network that uses the DECT air interface to interconnect a local network to one or more portable applications

DECT Standard Authentication Algorithm (DSAA): algorithm used for authentication in DECT

DECT Standard Cipher (DSC): algorithm used for data encryption in DECT

Distributed Communication: the ability of a DECT terminal to provide means for or assist direct communication between any two terminals, members of a "closed" local DECT network

DLC broadcast: simplex "connectionless" mode of transmission from the DLC broadcast entity of one FT to the DLC broadcast entities in one or more PT

DLC data link (DLC link): association between two DLC layer entities

- DLC frame:** format used to structure all messages that are exchanged between DLC layer peer entities
- double duplex bearer:** use of two duplex bearers (see duplex bearer) which refer to the same MAC connection, sharing their simplex bearers (see simplex bearer) for the information flow
- double-simplex bearer:** use of two simplex bearers operating in the same direction on two physical channels
- double slot:** one 12th of a TDMA frame which is used to support one high capacity physical channel
- down-link:** transmission in the direction FT to PT
- duplex bearer:** use of two simplex bearers operating in opposite directions on two physical channels
- encipherment:** rendering of plaintext into ciphertext
- End System (ES):** logical grouping that contains application processes and supports telecommunication services
- Extended MAC control messages:** MAC messages of the B-field connection control set
- external handover:** process of switching a call in progress from one FP to another FP
- FEAL algorithm:** Fast Encryption Algorithm; a particular encryption algorithm in the public domain
- field:** continuous region of data (i.e. adjacent bits) that jointly convey information
- fixed geometry Portable Part (PP):** PP in which the electro-acoustic transducers and their associated acoustic components are held in fixed relative positions and/or orientations during all on-line conditions and test conditions of the PP
- Fixed Part (DECT Fixed Part) (FP):** physical grouping that contains all of the elements in the DECT network between the local network and the DECT air interface
- Fixed radio Termination (FT):** logical group of functions that contains all of the DECT processes and procedures on the fixed side of the DECT air interface
- flow control:** mechanism that is used to regulate the flow of data between two peer entities
- fragment:** one of the Service Data Units (SDUs) that is produced by the process of fragmentation
- fragmentation:** process of dividing a Protocol Data Unit (PDU) into more than one SDU for delivery to a lower layer
- frame:** See "TDMA frame" or "DLC frame".
- full slot (slot):** one 24th of a TDMA frame which is used to support one physical channel
- generic:** generalized set or general purpose set, often in the sense of basic or ordinary
- Generic Access Profile (GAP):** standard in addition to the DECT CI that ensures interoperability between FPs and PPs from different manufacturers
- geographically unique:** two FPs with the same PARI, or respectively two RFPs with the same RFPI, cannot be reached or listened to at the same geographical position
- Global NetWork (GNW):** telecommunication network capable of offering a long distance telecommunication service
- globally unique identity:** identity is unique within DECT (without geographical or other restrictions)
- guard space:** nominal interval between the end of a radio transmission in a given slot, and the start of a radio transmission in the next successive slot
- half slot:** one 48th of a TDMA frame which is used to support one physical channel
- handover:** process of switching a call in progress from one physical channel to another physical channel
- handset echo:** echo, perceptible by the far-end user, resulting from the coupling between the receiving and sending directions of the handset, mostly due to acoustic coupling between transducers
- Hybrid Part (HyP):** DECT terminal that provides FT as well as PT capabilities

impersonation: where one identity claims the part of another identity

incoming call: call received at a PP

Integrated Services Digital Network (ISDN): digital telecommunications infrastructure to the Consultative Committee on International Telegraphy and Telephony (CCITT) standards

intercell handover: switching of a call in progress from one cell to another cell

internal call: call between 2 users that does not make use of the local network resources

internal handover: handover processes that are completely internal to one FT

International Portable User Identity (IPUI): identity that uniquely defines one user within the domain defined by his access rights related to this IPUI

interoperability: capability of FPs and PPs, that enable a PP to obtain access to teleservices in more than one location area and/or from more than one operator (more than one service provider)

interoperator roaming: roaming between FP coverage areas of different operators (different service providers)

Interworking Unit (IWU): unit that is used to interconnect subnetworks

intracell handover: switching of a call in progress from one physical channel of one cell to another physical channel of the same cell

intraoperator roaming: roaming between different FP coverage areas of the same operator (same service provider)

Isochronous: essential characteristic of a time-scale or a signal such that the time intervals between consecutive significant instants either have the same duration or durations that are integral multiples of the shortest duration

key management: way in which cryptographic keys are generated, distributed and used

Key Stream Generator (KSG): cryptographic algorithm which produces a stream of binary digits which can be used for encipherment and decipherment

link: See "DLC data link".

Local Area Network (LAN): electronic systems which are interconnected and in physical proximity to each other

Local Network (LNW): telecommunication network capable of offering local telecommunication services

locally unique identity: identity is unique within one FP or location area, depending on application

location area: domain in which a PP may receive (and/or make) calls as a result of a single location registration

location registration: process whereby the position of a DECT portable termination is determined to the level of one location area, and this position is updated in one or more databases

logical channel: generic term for any distinct data path

logical connection: association between two instances of the MAC MBC that can be used by higher layers to exchange U-plane or C-plane data

Lower Layer Management Entity (LLME): management entity that spans a number of lower layers, and is used to describe all control activities which do not follow the rules of layering

Lower Tester (LT): logical grouping that contains the test equipment, a functionally equivalent DECT PT, a functionally equivalent DECT FT and a test controller

MAC bearer (bearer): service element that is provided by each Cell Site Function (CSF)

MAC connection (connection): association between one source MAC Multi-Bearer Control (MBC) entity and one destination MAC MBC entity

masquerading: where one identity plays the part of, or acts as, another identity

Medium Access Control (MAC): layer 2a of the DECT protocol stack