



Designation: **D8074 – 22** **D8074 – 23**

## Standard Test Method for Evaluation of Diesel Engine Oils in DD13 Diesel Engine<sup>1</sup>

This standard is issued under the fixed designation D8074; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

### INTRODUCTION

Portions of this test method are written for use by laboratories that make use of ASTM Test Monitoring Center (TMC)<sup>2</sup> services (see [Annex A1](#)).

The TMC provides reference oils, and engineering and statistical services to laboratories that desire to produce test results that are statistically similar to those produced by laboratories previously calibrated by the TMC.

In general, the Test Purchaser decides if a calibrated test stand is to be used. Organizations such as the American Chemistry Council require that a laboratory utilize the TMC services as part of their test registration process. In addition, the American Petroleum Institute and the Gear Lubricant Review Committee of the Lubricant Review Institute (SAE International) require that a laboratory use the TMC services in seeking qualification of oils against their specifications.

The advantage of using the TMC services to calibrate test stands is that the test laboratory (and hence the Test Purchaser) has an assurance that the test stand was operating at the proper level of test severity. It should also be borne in mind that results obtained in a non-calibrated test stand may not be the same as those obtained in a test stand participating in the ASTM TMC services process.

Laboratories that choose not to use the TMC services may simply disregard these portions.

### 1. Scope\*

<https://standards.iteh.ai/catalog/standards/sist/0ad05c05-d413-4f78-bb1f-20b5e010e940/astm-d8074-23>

1.1 This test method covers an engine test procedure for evaluating diesel engine oils for performance characteristics, including adhesive wear between an uncoated piston ring and cylinder liner. This test method is commonly referred to as the DD13 Scuffing Test.

1.2 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.2.1 *Exception*—Where there is no direct SI equivalent, such as the units for screw threads, National Pipe Threads/diameters, tubing size, and single source supply equipment specifications.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use. See [Annex A2](#) for specific safety precautions.*

<sup>1</sup> This test method is under the jurisdiction of ASTM Committee D02 on Petroleum Products, Liquid Fuels, and Lubricants and is the direct responsibility of Subcommittee D02.B0 on Automotive Lubricants.

Current edition approved April 1, 2022. Oct. 1, 2023. Published April 2022. November 2023. Originally approved in 2016. Last previous edition approved in 2019 as ~~D8074 – 19~~ D8074 – 22. DOI: ~~10.1520/D8074-22~~ 10.1520/D8074-23.

<sup>2</sup> Until the next revision of this test method, the ASTM Test Monitoring Center will update changes in the test method by means of information letters. Information letters may be obtained from the ASTM Test Monitoring Center, 203 Armstrong Drive, Freeport, PA 16229, [www.astmtmc.org](http://www.astmtmc.org). Attention: Director. This edition incorporates revisions in all information Letters through No. ~~19-1~~ 23-1.

\*A Summary of Changes section appears at the end of this standard

1.4 This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.

## 2. Referenced Documents

### 2.1 ASTM Standards:<sup>3</sup>

- D86 Test Method for Distillation of Petroleum Products and Liquid Fuels at Atmospheric Pressure
- D93 Test Methods for Flash Point by Pensky-Martens Closed Cup Tester
- D97 Test Method for Pour Point of Petroleum Products
- D130 Test Method for Corrosiveness to Copper from Petroleum Products by Copper Strip Test
- D235 Specification for Mineral Spirits (Petroleum Spirits) (Hydrocarbon Dry Cleaning Solvent)
- D287 Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer/Method)
- D445 Test Method for Kinematic Viscosity of Transparent and Opaque Liquids (and Calculation of Dynamic Viscosity)
- D482 Test Method for Ash from Petroleum Products
- D524 Test Method for Ramsbottom Carbon Residue of Petroleum Products
- D613 Test Method for Cetane Number of Diesel Fuel Oil
- D664 Test Method for Acid Number of Petroleum Products by Potentiometric Titration
- D975 Specification for Diesel Fuel
- D976 Test Method for Calculated Cetane Index of Distillate Fuels
- D1319 Test Method for Hydrocarbon Types in Liquid Petroleum Products by Fluorescent Indicator Adsorption
- D2274 Test Method for Oxidation Stability of Distillate Fuel Oil (Accelerated Method)
- D2500 Test Method for Cloud Point of Petroleum Products and Liquid Fuels
- D2622 Test Method for Sulfur in Petroleum Products by Wavelength Dispersive X-ray Fluorescence Spectrometry
- D2709 Test Method for Water and Sediment in Middle Distillate Fuels by Centrifuge
- D3338 Test Method for Estimation of Net Heat of Combustion of Aviation Fuels
- D3524 Test Method for Diesel Fuel Diluent in Used Diesel Engine Oils by Gas Chromatography
- D4052 Test Method for Density, Relative Density, and API Gravity of Liquids by Digital Density Meter
- D4175 Terminology Relating to Petroleum Products, Liquid Fuels, and Lubricants
- D4294 Test Method for Sulfur in Petroleum and Petroleum Products by Energy Dispersive X-ray Fluorescence Spectrometry
- D4683 Test Method for Measuring Viscosity of New and Used Engine Oils at High Shear Rate and High Temperature by Tapered Bearing Simulator Viscometer at 150 °C
- D4739 Test Method for Base Number Determination by Potentiometric Hydrochloric Acid Titration
- D5185 Test Method for Multielement Determination of Used and Unused Lubricating Oils and Base Oils by Inductively Coupled Plasma Atomic Emission Spectrometry (ICP-AES) [5-d413-4f78-bb1f20b5e010e940/astm-d8074-23](https://www.astm.org/standards/D5185)
- D5186 Test Method for Determination of the Aromatic Content and Polynuclear Aromatic Content of Diesel Fuels By Supercritical Fluid Chromatography
- D5453 Test Method for Determination of Total Sulfur in Light Hydrocarbons, Spark Ignition Engine Fuel, Diesel Engine Fuel, and Engine Oil by Ultraviolet Fluorescence
- D5967 Test Method for Evaluation of Diesel Engine Oils in T-8 Diesel Engine
- D6078 Test Method for Evaluating Lubricity of Diesel Fuels by the Scuffing Load Ball-on-Cylinder Lubricity Evaluator (SLBOCLE) (Withdrawn 2021)<sup>4</sup>
- D6984 Test Method for Evaluation of Automotive Engine Oils in the Sequence IIIF, Spark-Ignition Engine
- D7320 Test Method for Evaluation of Automotive Engine Oils in the Sequence IIIG, Spark-Ignition Engine
- E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications
- E168 Practices for General Techniques of Infrared Quantitative Analysis

### 2.2 Other Standards:

Code of Federal Regulations Title 40 Part 86.310-79<sup>5,6</sup>

### 2.3 Other ASTM Document:

ASTM Deposit Rating Manual 20 Formerly CRC Manual 20<sup>7</sup>

## 3. Terminology

### 3.1 Definitions:

<sup>3</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

<sup>4</sup> The last approved version of this historical standard is referenced on [www.astm.org](http://www.astm.org).

<sup>5</sup> Available from U.S. Government Printing Office, Superintendent of Documents, 732 N. Capitol St., NW, Washington, DC 20401-0001, <http://www.access.gpo.gov>.

<sup>6</sup> <https://www.gpo.gov/fdsys/granule/CFR-2013-title40-vol19/CFR-2013-title40-vol19-sec86-310-79>.

<sup>7</sup> For stock #TMCMLN20, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org).

3.1.1 *adhesive wear (scuffing), n*—wear due to localized bonding between contacting solid surfaces leading to material transfer between the two surfaces or loss from either surface. **D4175**

3.1.2 *blind reference oil, n*—a reference oil, the identity of which is unknown by the test facility.

3.1.2.1 *Discussion*—

This is a coded reference oil that is submitted by a source independent from the test facility. **D4175**

3.1.3 *blowby, n—in internal combustion engines*, that portion of the combustion products and unburned air/fuel mixture that leaks past piston rings into the engine crankcase during operation. **D4175**

3.1.4 *break-in, v—in internal combustion engines*, the running of a new engine under prescribed conditions to help stabilize engine response and help remove initial friction characteristics associated with new engine parts. **D4175**

3.1.5 *calibrate, v*—to determine the indication or output of a measuring device with respect to that of a standard. **D4175**

3.1.6 *calibrated test stand, n*—a test stand on which the testing of reference material(s), conducted as specified in the standard, provided acceptable test results.

3.1.6.1 *Discussion*—

In several automotive lubricant standard test methods, the ASTM Test Monitoring Center provides testing guidance and determines acceptability. **D4175**

3.1.7 *calibration test, n*—an engine test conducted on a reference oil under carefully prescribed conditions, the results of which are used to determine the suitability of the engine stand/laboratory for such tests on non-reference oils.

3.1.7.1 *Discussion*—

A calibration test also includes tests conducted on parts to ensure their suitability for use in reference and non-reference tests. **D4175**

3.1.8 *candidate oil, n*—an oil that is intended to have the performance characteristics necessary to satisfy a specification and is intended to be tested against that specification. **D4175**

3.1.9 *engine oil, n*—a liquid that reduces friction or wear, or both, between the moving parts within an engine; removes heat particularly from the underside of pistons; and serves as combustion gas sealant for the piston rings.

3.1.9.1 *Discussion*—

It may contain additives to enhance certain properties. Inhibition of engine rusting, deposit formation, valve train wear, oil oxidation, and foaming are examples. **D4175**

3.1.10 *exhaust gas recirculation (EGR), n*—the mixing of exhaust gas with intake air to reduce the formation of nitrogen oxides (NO<sub>x</sub>). **D4175**

3.1.11 *heavy-duty, adj—in internal combustion engine operation*, characterized by average speeds, power output and internal temperatures that are close to the potential maximums. **D4175**

3.1.12 *heavy-duty engine, n—in internal combustion engine types*, one that is designed to allow operation continuously at or close to its peak output.

3.1.13 *lubricant test monitoring system (LTMS), n*—an analytical system in which ASTM calibration test data are used to manage lubricant test precision and severity (bias). **D4175**

3.1.13.1 *LTMS date, n*—the date the test was completed unless a different date is assigned by the TMC. **D6984/D7320**

3.1.13.2 *LTMS time, n*—the time the test was completed unless a different time is assigned by the TMC. **D6984/D7320**

3.1.14 *lubricant, n*—any material interposed between two surfaces that reduces the friction or wear, or both, between them. **D4175**

3.1.15 *mass fraction of B*,  $w_{B,n}$ —mass of a component B in a mixture divided by the total mass of all the constituents of the mixture.

3.1.15.1 *Discussion*—

Values are expressed as pure numbers or the ratio of two units of mass (for example, mass fraction of lead is  $w_B = 1.3 \times 10^{-6} = 1.3 \text{ mg/kg}$ ). **D4175**

3.1.16 *non-reference oil*,  $n$ —any oil other than a reference oil; such as a research formulation, commercial oil or candidate oil. **D4175**

3.1.17 *non-standard test*,  $n$ —a test that is not conducted in conformance with the requirements in the standard test method; such as running on an uncalibrated test stand, using different test equipment, applying different equipment assembly procedures, or using modified operating conditions. **D4175**

3.1.18 *oxidation*,  $n$ —of engine oil, the reaction of the oil with an electron acceptor, generally oxygen, that can produce deleterious acidic or resinous materials often manifested as sludge formation, varnish formation, viscosity increase, or corrosion, or combination thereof. **D4175**

3.1.19 *quality index (QI)*,  $n$ —a mathematical formula that uses data from controlled parameters to calculate a value indicative of control performance. **D4175**

3.1.20 *quantity*,  $n$ —in the SI, a measurable property of a body or substance where the property has a magnitude expressed as the product of a number and a unit; there are seven, well-defined base quantities (length, time, mass, temperature, amount of substance, electric current and luminous intensity) from which all other quantities are derived (for example, volume whose SI unit is the cubic metre).

3.1.20.1 *Discussion*—

Symbols for quantities must be carefully defined; are written in italic font, can be upper or lower case, and can be qualified by adding further information in subscripts, or superscripts, or in parentheses (for example,  $t_{fuel} = 40 \text{ }^\circ\text{C}$ , where  $t$  is used as the symbol for the quantity Celsius temperature and  $t_{fuel}$  is the symbol for the specific quantity fuel temperature). **D4175**

3.1.21 *reference oil*,  $n$ —an oil of known performance characteristics, used as a basis for comparison.

3.1.21.1 *Discussion*—

Reference oils are used to calibrate testing facilities, to compare the performance of other oils, or to evaluate other materials (such as seals) that interact with oils. **D4175**

3.1.22 *sludge*,  $n$ —in internal combustion engines, a deposit, principally composed of insoluble resins and oxidation products from fuel combustion and the lubricant, that does not drain from engine parts but can be removed by wiping with a cloth. **D4175**

3.1.23 *standard test*,  $n$ —a test on a calibrated test stand, using the prescribed equipment in accordance with the requirements in the test method, and conducted in accordance with the specified operating conditions.

3.1.24 *test oil*,  $n$ —any oil subjected to evaluation in an established procedure.

3.1.24.1 *Discussion*—

It can be any oil selected by the laboratory conducting the test. It could be an experimental product or a commercially available oil. Often it is an oil that is a candidate for approval against engine oil specifications (such as manufacturers' or military specifications, and so forth). **D4175**

3.1.25 *test parameter*,  $n$ —a specified component, property, or condition of a test procedure.

3.1.25.1 *Discussion*—

Examples of components are fuel, lubricant, reagent, cleaner, and sealer; of properties are density, temperature, humidity, pressure, and viscosity; and of conditions are flow rate, time, speed, volume, length, and power. **D4175**

3.1.26 *volume fraction of B*,  $\phi_{B,n}$ —volume of component B divided by the total volume of the all the constituents of the mixture prior to mixing.

### 3.1.26.1 Discussion—

Values are expressed as pure numbers or the ratio of two units of volume (for example,  $\phi_B = 0.012 = 1.2 \% = 1.2 \text{ cL/L}$ ). **D4175**

3.1.27 *varnish, n*—in internal combustion engines, a hard, dry, generally lustrous deposit that can be removed by solvents but not by wiping with a cloth. **D4175**

3.1.28 *wear, n*—the loss of material from a surface, generally occurring between two surfaces in relative motion, and resulting from mechanical or chemical action or a combination of both. **D4175**

### 3.2 Definitions of Terms Specific to This Standard:

3.2.1 *new laboratory, n*—one that has never previously calibrated a test stand under this test method.

3.2.2 *new stand, n*—a test cell and support hardware which has never previously been calibrated under this test method.

3.2.3 *scuff, n*—a distress that disturbs the surface finish of the cylinder liner in such a manner as to prohibit identification of other prior surface finishes, including but not limited to polish and honing marks.

### 3.3 Acronyms:

3.3.1 CAC—charge air cooler

3.3.2 CAN—controller area network

3.3.3 CARB—California air resources board

3.3.4 DACA II—data acquisition and control automation II

3.3.5 DD—Detroit diesel

3.3.6 DDCSN—Detroit diesel customer support network

3.3.7 EGR—exhaust gas recirculation

<https://standards.iteh.ai/catalog/standards/sist/0ad05c05-d413-4f78-bb1f-20b5e010e940/astm-d8074-23>

3.3.8 EOT—end of test

3.3.9 ID—internal diameter

3.3.10 MCM—motor control module

3.3.11 OMS—oil mist separator

3.3.12 SOT—start of test

## 4. Summary of Test Method

4.1 This test method uses a Detroit<sup>8</sup> DD13 12.8 L, six-cylinder diesel engine with EGR.

4.2 The engine is disassembled prior to each test, the parts solvent-cleaned and measured, and rebuilt using all new pistons, uncoated rings, cylinder liners, and connecting rod bearings, in strict accordance with furnished specifications. The engine crankcase is solvent cleaned and worn or defective parts replaced.

4.3 The test stand is equipped with appropriate accessories for controlling speed, torque, and various engine operating conditions.

---

<sup>8</sup> Detroit is a registered trademark of Detroit Diesel Corporation, 13400 Outer Drive, West Detroit, MI 48239-4001, USA.

4.4 Following an engine break-in, the test oil is installed, the engine warmed up to the test conditions, and a two-stage procedure lasting a maximum of 200 h is initiated. Oil samples are taken periodically for the measurement of viscosity, soot, oxidation, and wear metals concentrations.

4.5 Scuffing is determined from analysis of end-of-test parts and test oil samples.

## 5. Significance and Use

5.1 This test method was developed to evaluate the liner scuffing and ring distress performance of engine oils in turbocharged and intercooled four-cycle diesel engines equipped with EGR, uncoated top rings, and running on ultra-low sulfur diesel fuel. Results are obtained from used oil analysis, operational data, and component measurements before and after test.

5.2 The test method may be used for engine oil specification acceptance when all details of the procedure are followed.

## 6. Apparatus

6.1 *Laboratory*—The ambient laboratory atmosphere shall be relatively free of dirt and other contaminants as required by good laboratory standards. Air filtration and temperature and humidity control in the engine buildup area helps prevent accumulation of dirt, rust, and other contaminants on engine parts and aids in measuring and selecting parts for assembly.

### 6.2 Test Engine:

6.2.1 The test engine is a Detroit DD13 diesel engine,<sup>9,10,11</sup> common rail fuel system, with high-flow injectors. It is a 12.8 L, open-chamber, in-line, six-cylinder, four-stroke, turbocharged, charge air-cooled, compression-ignition engine. The bore and stroke are 132 mm and 156 mm, respectively.

6.2.1.1 *Detroit Diesel Parts and Part Numbers*—Information about parts and part numbers is provided in **Annex A3**. Use test parts on a first-in/first-out basis.

6.2.2 *Detroit Diesel Customer Support Network (DDCSN)*—For engine rebuild specifications, use Online Power Service Literature rebuild manual.<sup>12</sup> In the event of a conflict with Section 8, the latter takes precedence.

### 6.2.3 Engine Cooling System:

6.2.3.1 For each test, use fresh Detroit Power Cool<sup>11</sup> (see 7.3) to limit scaling in the cooling system. Pressurize the system at the expansion tank.

6.2.3.2 To prevent air entrainment and to control coolant related parameters within specified limits, use a closed-loop, pressurized, external, engine-cooling system composed of a heat exchanger, an expansion tank, a water-out temperature-control valve, a flow meter, and a flow-control device. A schematic is shown in **Fig. A4.1**. Install a sight glass between the engine and the cooling tower to check for air entrainment and uniform flow in order to observe and prevent localized boiling. Fit the coolant tank with a radiator cap with a recommended 140 kPa relief pressure. Include in the cooling system a flow-control device between the engine and expansion tank and a flow meter between the expansion tank and engine inlet.

(1) Use the coolant heat exchanger to adequately control the coolant temperature at the jacket outlet to the set point in **Table 1**.

(2) Use a flow control device to throttle coolant flow within range specified in **Table 1**.

(3) Supply pressurized air to the top of the expansion tank. Regulate the air pressure to adequately control the coolant pressure at jacket inlet to the set points in **Table 1**. Depending on the configuration of the cooling system, air pressure up to 140 kPa may need to be supplied to achieve the set point.

6.2.3.3 Block the thermostat<sup>11</sup> wide open at 13 mm as shown in **Fig. A4.2**.

<sup>9</sup> The sole source of the apparatus known to the committee at this time is Detroit Diesel Corporation, 13400 Outer Drive, West Detroit, MI 48239-4001, USA.

<sup>10</sup> If you are aware of alternative suppliers, please provide this information to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee<sup>1</sup> which you may attend.

<sup>11</sup> Purchase from a local Detroit Diesel Dealer. The Detroit Diesel part number can be accessed from information provided in **A3.1**.

<sup>12</sup> Available at [www.ddcsn.com](http://www.ddcsn.com).

TABLE 1 Schedule of Conditions for the Test Procedure

Time, h	Set Point for Stage 1	Set Point for Stage 2
	30	170 standard <sup>A</sup>
Controlled Quantities, <sup>B</sup> units		
Engine Speed, r/min	1800	1800
Fuel Flow Rate, kg/h	32	71
Air Temperature in Engine Intake, °C	35	35
Coolant Temperature at Jacket Outlet, °C	105	105
Oil Temperature in Gallery, °C	118	118
Fuel Temperature at Engine Inlet, °C	38	38
Air Temperature in Intake Manifold, °C	75	87
Coolant Pressure at Jacket Inlet, kPa (gauge)	250	250
Exhaust Pressure in Tailpipe, kPa (absolute)	105.5	125.5
Air Pressure in Intake Manifold, kPa (absolute)	202.5	327.5
Air Pressure in Engine Intake, kPa (absolute)	96.4	94.8
Ranged Quantities, <sup>C</sup> units		
Coolant Flow Rate, L/min	340 to 360	340 to 360
Uncontrolled Quantities, units		
Blowby Flow Rate, L/min	Record	Record
OMS Speed, r/min	Record	Record
Barometric Pressure, kPa (absolute)	Record	Record
Air Pressure at Turbocharger Outlet, kPa (gauge)	Record	Record
Air Pressure at CAC Outlet, kPa (gauge)	Record	Record
Delta Air Pressure across CAC, kPa	Record	Record
Crankcase Pressure, kPa (gauge)	Record	Record
Air Pressure in the Coolant Tank, kPa (gauge)	Record	Record
Coolant Pressure at Jacket Outlet, kPa (gauge)	Record	Record
Delta Coolant Pressure for Jacket kPa (gauge)	Record	Record
Exhaust Pressure Pre-Turbocharger Front, kPa (gauge)	Record	Record
Exhaust Pressure Pre-Turbocharger Rear, kPa (gauge)	Record	Record
EGR Pressure, kPa (gauge)	Record	Record
Oil Pressure in Gallery, kPa (gauge)	Record	Record
Air Temperature at Turbocharger Outlet, °C	Record	Record
Air Temperature of Ambient Conditions, °C	Record	Record
Delta Coolant Temperature across Engine, °C	Record	Record
Delta Coolant Temperature across Coolant Jacket, °C	Record	Record
Coolant Temperature at Engine Inlet, °C	Record	Record
Coolant Temperature at Engine Outlet, °C	Record	Record
Coolant Temperature at Jacket Inlet, °C	Record	Record
EGR Temperature, °C	Record	Record
Exhaust Temperature the Exhaust Tailpipe, °C	Record	Record
Temperature of the Return Fuel, °C	Record	Record
Air Temperature at the CAC Outlet, °C	Record	Record
Oil Temperature in Sump, °C	Record	Record
Dew Point Temperature of Inlet Air, °C	Record	Record
Coolant Temperature at Engine Inlet, °C	Record	Record
Coolant Temperature at EGR Cooler Inlet, °C	Record	Record
Coolant Temperature at EGR Cooler Outlet, °C	Record	Record
Delta Coolant Temperature for EGR Cooler, °C	Record	Record
Torque, N·m	Record	Record
Mass of External Oil Tank, kg	Record	Record
Relative Humidity of Inlet Air, %	Record	Record

<sup>A</sup> Although 170 h is a standard test time, tests run for longer than 170 h are still valid tests.

<sup>B</sup> Target all controlled quantities at mean.

<sup>C</sup> All ranged quantities shall fall within the specified limits.

6.2.3.4 Vent the EGR cooler to the top of the expansion tank, away from the pressure feed, as shown in Fig. A4.3.

6.2.4 Auxiliary Oil System:

6.2.4.1 To maintain a constant oil level in the engine sump, connect it to a separate, closed reservoir with a minimum capacity of 15 L. Circulate oil through the reservoir with an auxiliary pump. The system schematic is shown in Fig. A4.4. Use lines with 10 mm internal diameter (ID) for the return to engine sump and 13 mm ID for suction from engine sump. Connect the rear, gear cover to a vent line with a minimum ID of 10 mm, as shown in Figs. A4.4 and A4.5.

6.2.4.2 Locate the suction line of the auxiliary oil-system on the intake side of the engine sump, at the lower, modified bulk-head fitting. Modify the (lower) factory plug by drilling a hole through it and welding a 3/4 in. pipe coupling to the exterior end. Weld a tube 20 mm diameter by 0.1 m long to one end of a 90° 3/4 in. elbow. Bend the 0.1 m long tube at 90°. Clean the threading, as needed, to allow the elbow to mate with the 3/4 in. fitting in the modified plug. Trim the 0.1 m long tube so that when the tube is

installed into the modified plug in the oil pan, the top of the tube is 267 mm down from the pan rail, as shown in Fig. A4.4. Examples of these modified parts are shown in Fig. A4.6.

6.2.4.3 Locate the return line, shown in Fig. A4.5, at the upper bulk-head fitting, as shown in Fig. A4.7. Modify the bulk-head fitting to connect to the 10 mm ID return line by drilling a hole through the (upper) factory plug and welding a  $\frac{3}{4}$  in. pipe coupling to the exterior end. Connect one end of an elbow to the  $\frac{3}{4}$  in. pipe coupling and connect the other end to the 10 mm ID return line.

6.2.4.4 Connect the vent line of the auxiliary oil-system to the top of the auxiliary oil reservoir and the air compressor block-off plate, as shown in Fig. A4.5.

6.2.4.5 Use Viking Pump Model SG053514<sup>13,10</sup> as the auxiliary oil pumps. Nominal pump speed is specified as 1725 r/min.

6.2.4.6 Locate a  $\frac{1}{4}$  in. oil sampling port within the pressurized oil circuit using a No. 4 Aeroquip<sup>14,10</sup> or equivalent and a small petcock valve, as shown in Fig. A4.5. Use a maximum sample-line length of 2.5 m.

6.2.4.7 Locate a pressurized, oil-filling line between the oil cooler and the oil-filter housing on the return to the filter housing. Connect the line to the oil pressure in gallery line via a tee. Refer to Fig. A4.7.

### 6.2.5 Oil-Cooling System:

6.2.5.1 *Remote Oil Heat Exchanger and Bypass Plate*—This section describes how to modify the engine to rout oil through a remote oil heat exchanger and how to modulate water flow through this oil heat exchanger to adequately control the oil temperature in the gallery to the set points in Table 1.

(1) Remove the stock heat exchanger from the oil-cooler module (see Fig. A4.8) and set the o-rings aside. Fabricate a 6.35 mm thick aluminum block-off plate using the oil cooler as a pattern (see Fig. A4.9). Install the block-off plate with o-rings and new M8  $\times$  1.25  $\times$  25 bolts. Torque the bolts to 30 N·m.

(2) Remove the oil thermostat cover by using Kent-Moore tool W470 589 030 900<sup>15,10</sup> to remove the thermostat. Disassemble the thermostat and set aside the thermostat housing and retaining ring. Machine a piece of aluminum bar stock to a diameter of 37.719 mm and a length of 85.725 mm. Insert this aluminum plug into the thermostat housing and reinstall the retaining ring (see Fig. A4.10).

(3) Connect the oil module to the remote heat exchanger by using two 19 mm ID lines to allow oil to flow through a 127 mm  $\times$  356 mm double-pass, stainless-steel, remote oil heat exchanger shown in Fig. A4.11. Oil shall flow through the shell portion of the heat exchanger. The combined length of the oil lines to and from the remote oil heat exchanger and the modified oil module shall not be greater than 2.6 m total length.

(4) Modify the oil module to create a fitting for an oil supply line to the remote oil heat exchanger as follows:

(a) drill a  $\frac{59}{64}$  in. or  $\frac{15}{16}$  in. hole in the bottom of the oil module (see Fig. A4.12);

(b) machine a piece of aluminum bar stock to a diameter of 38 mm and a length of 45 mm;

(c) drill and tap this piece of aluminum for a  $\frac{3}{4}$  in. NPT and cut one end at a 30° angle;

(d) weld this aluminum cylinder onto the previously drilled hole in the bottom of the oil module so the cylinder is pointing away from the side of the engine and towards the front of the engine;

(e) install a straight male  $\frac{3}{4}$  in. NPT to  $\frac{3}{4}$  in. NPT flare fitting.

(5) Modify the oil module to create a fitting for an oil-return line from the remote oil heat exchanger as follows:

(a) locate and remove the plug from the side of the housing;

(b) machine out the middle of the plug;

(c) weld a  $\frac{3}{4}$  in. NPT union half coupling;

(d) reinstall the modified plug and install a 90°,  $\frac{3}{4}$  in. NPT male to  $\frac{3}{4}$  in. flare fitting, as shown in Fig. A4.13.

6.2.5.2 Use the Detroit Diesel oil filter housing.<sup>11</sup>

6.2.6 *Blowby Meter*—Use a meter capable of providing data at a minimum frequency of 1 Hz. To prevent blowby condensate from draining back into the engine, ensure the blowby line has a downward slope to a collection bucket. Ensure the collection bucket has a minimum volume of 19 L. Locate the blowby meter downstream of the collection bucket. The slope of the blowby line downstream of the collection bucket is unspecified. This engine is also equipped with an oil mist separator (OMS) mounted on the engine to evacuate blowby gases.

<sup>13</sup> The sole source of supply of the apparatus known to the committee at this time is Viking Pump, Inc., a unit of IDEX Corporation, 406 State Street, P.O. Box 8, Cedar Falls, IA 50613-0008.

<sup>14</sup> The sole source of supply of the apparatus known to the committee at this time is Aeroquip Performance Products. www.aeroquipperformance.com.

<sup>15</sup> The sole source of supply of the apparatus known to the committee at this time is Kent-Moore, which is available from local suppliers.



6.2.7 *Air Supply and Filtration*—Use an air-filter element appropriately sized for a 12.8 L diesel engine. Replace the filter cartridge when the air pressure in engine intake cannot be reached. Install an adjustable valve (flapper) in the inlet air system to control the air pressure in engine intake to set points in **Table 1**. The adjustable valve (flapper) shall be at least two-pipe diameters before any temperature, pressure, and humidity measurement devices.

6.2.8 *Fuel Supply*—Heating, cooling, or both of the fuel supply may be required to achieve adequate fuel-temperature control with the set points specified in **Table 1**. A typical system is shown in **Fig. A4.14**.

6.2.9 *Specifications for the Charge Air Cooler (CAC)*—Select a CAC such that the pressure drop across the CAC is  $\leq 10$  kPa at test conditions. Provide sufficient cooling capacity to adequately control the air temperature in intake manifold to the set points specified in **Table 1**. Equip the CAC with a drain to remove condensate formed when moisture in the air passes by the cooler process water. Use the Detroit Diesel intake manifold.<sup>11</sup>

6.2.10 *Exhaust Pressure Control*—Install an adjustable valve (flapper) in the tailpipe after any temperature, pressure, or CO<sub>2</sub> measurement devices to adequately control exhaust pressure in tailpipe to set points in **Table 1**.

6.2.11 *Dynamometer*—Use a dynamometer capable of controlling engine speed to the set points in **Table 1**. A Midwest 1519<sup>16,10</sup> dynamometer has been found suitable for this purpose.

6.2.12 *Turbocharger Wastegate*—Supply regulated pressurized air directly to the wastegate on the turbocharger by bypassing the ECM-controlled air modulator to the wastegate on the engine. Regulate the air pressure supplied to the wastegate to adequately control air pressure in the intake manifold to set points in **Table 1**. It is recommended to supply up to 275 kPa of air pressure to allow adequate control of the waste gate.

6.2.13 *Oil Pump*—Use the Detroit Diesel oil pump.<sup>11</sup>

6.2.14 *OMS Speed Sensor*—Use the Detroit Diesel speed sensor<sup>11</sup> with Detroit Diesel bracket<sup>11</sup> and connector.<sup>11</sup> Use OMS gas vent Mack Trucks part number 21122541.<sup>17,10,18</sup>

6.2.15 *Engine-Control System*—The engine controls system is manufactured by Daimler Engineering and is available from Detroit Diesel.<sup>9,10</sup> It includes the CPC module, the Motor Control Module (MCM), the Daimler control station, and the wiring harness for the test stand.

6.2.16 *Block-off Plate for Dosing Injector*—Remove the dosing (7th) injector in the exhaust and install a block off plate as shown in **Fig. A4.15**. Fit a plug into the dosing block assembly to block the fuel line that would normally run to the dosing injector, as shown in **Fig. A4.16**.

## 7. Engine Fluids

7.1 *Test Oil*—Approximately 95 L of test oil are required for the test.

7.2 *Test Fuel*—Approximately 16 600 L of PC-10 ultra low sulfur diesel (ULSD) test fuel<sup>19,10</sup> are required per 200 h test. The fuel shall have the properties and tolerances shown in the “PC-10 Fuel Specification” section of the “TMC-Monitored Test Fuel Specifications” document maintained by the TMC.

7.3 *Coolant*—Use 50/50 Premixed Detroit Power Cool.<sup>11</sup>

7.4 *Build-up Oil*—Use Detroit 15W-40 Motor Oil.<sup>11</sup>

7.5 *Cleaning Materials:*

<sup>16</sup> The sole source of supply of the apparatus known to the committee at this time Dyne Systems, Inc., W209 N17391 Industrial Drive, Jackson, WI 53037, USA. Tel.: +1 800 657 0726.

<sup>17</sup> The sole source of supply of the apparatus known to the committee at this time is Mack Trucks Inc., 13302 Pennsylvania Avenue, Hagerstown, MD 21742, USA.

<sup>18</sup> Available from local Mack Trucks Inc. distributors.

<sup>19</sup> The sole source of the fuel known to the committee at this time is Chevron Phillips Chemical Company LP, 10001 Six Pines Drive, Suite 4036B, The Woodlands, TX 77387-4910, USA. Tel: +1 832 813 4859, email: fuels@cpchem.com.

7.5.1 For cleaning engine parts, use only mineral spirits (solvent) meeting the requirements in Specification **D235**, Type II, Class C for Aromatic Content (volume fraction 0 % to 2 %), Flash Point (142 °C, min) and Color (not darker than +25 on Saybolt Scale or 25 on Pt-Co Scale). (**Warning**—Combustible. Health hazard.) Obtain a Certificate of Analysis for each batch of solvent from the supplier.

7.5.2 Heptane. (**Warning**—Flammable. Health hazard.)

## 8. Preparation of Apparatus

### 8.1 *Cleaning of Parts:*

8.1.1 *Engine Block*—Thoroughly spray the engine with solvent to remove any oil remaining from the previous test and air-dry. Follow the optional use of an engine parts washer by a solvent wash and air-dry. Use a bristle brush to clean all oil galleries, OMS ports, and oil drainback holes. Use a Scotch-Brite<sup>20,10</sup> pad, or equivalent, to clean gasket surfaces, liner bores, and bearing saddles.

8.1.2 *Rocker Covers and Oil Pan*—Remove all sludge, varnish, and oil deposits. Rinse with solvent and air-dry. Follow the optional use of an engine parts washer by a solvent wash and air-dry.

8.1.3 *Auxiliary Oil System*—Flush all oil lines, heat exchanger, galleries, and external oil reservoirs with solvent to remove any previous test oil and then air-dry.

8.1.4 *Oil-Cooler Module*—Remove thermostat. Thoroughly clean with solvent to remove any previous test oil and then air-dry. Follow the optional use of an engine parts washer by a solvent wash and air-dry.

8.1.5 *Cylinder-Head*—Thoroughly clean the cylinder heads on the top side using solvent and a bristle brush. Use a Scotch-Brite, or equivalent, on the bottom side. Replace or rebuild cylinder head as necessary.

8.1.6 *Intake Manifold*—Remove and clean the intake manifold after a maximum of 200 h running under test conditions. Scrub the manifold using a bristle brush and solvent, wash using an engine parts washer and air dry.

8.1.7 *EGR Cooler*—Clean the EGR cooler before every test using either high-pressure air and hot water or an ultrasonic cleaner.

8.1.8 *EGR Venturi Unit*—Clean the venturi thoroughly before each test using a bristle brush. Do not use metal-cleaning equipment. Ensure the holes for the differential pressure sensor are cleaned.

8.1.9 *Fuel Module*—Clean as needed. Method used is not specified.

8.1.10 *Cylinder Liners*—Clean new cylinder liners prior to installing in the engine as follows:

- (1) wash with solvent;
- (2) scrub using a bristle brush and a detergent (Tide<sup>21,10</sup> has been found suitable for this purpose);
- (3) rinse with cold water;
- (4) wipe with heptane;
- (5) wipe thoroughly with Detroit 15W-40 Motor Oil<sup>11</sup> to protect from rust prior to installing in the engine;
- (6) after installing in engine, wipe clean with heptane.

### 8.2 *Preparation for Engine Build:*

8.2.1 *Fuel Module*—Inspect fuel cooler for debris and replace cooler if debris is found.

8.2.2 *Oil Pump*—Replace the oil pump after a maximum of 400 h running under test conditions.

8.2.3 *Components of the Gear Train*—Inspect and replace gears as necessary. Replace gear thrust washers prior to each engine build.

<sup>20</sup> The sole sources of supply of the material known to the committee at this time is 3M Corporate Headquarters, 3M Center, St. Paul, MN 55144-1000, USA.

<sup>21</sup> The sole source of supply of the apparatus known to the committee at this time is manufactured by Proctor and Gamble Company, 1 P&G Plaza, Cincinnati, OH 45202, USA. Tel. +1-513-983-1100. [www.pg.com](http://www.pg.com).

8.2.4 *Rocker Box*—Inspect saddles and replace as necessary.

8.2.5 *Crankshaft*—Inspect crankshaft prior to each build. At the laboratory’s discretion, polish or replace as necessary.

8.3 *Cylinder Liner, Piston, and Piston-Ring Assembly:*

8.3.1 *Fitting of Cylinder Liner*—For proper heat transfer, fit cylinder liners to the block using the procedure outlined using DDCSN.<sup>12</sup>

8.3.2 *Piston and Rings*—Cylinder liners, pistons, and rings are provided as a set and shall be used as a set. Examine piston rings for any handling damage. Record the pre-test measurements as detailed in 10.1.

8.4 *Injectors and Injection Pumps:*

8.4.1 *Injectors*—Use high-flow injector nozzles.<sup>11</sup> Injectors shall have a date code 2014 or later, indicated by the first two numbers of the date code (for example, “15...” denotes date code 2015). See Appendix X1 for location of date codes. Use only injectors with approved date codes.

8.5 *Assembly Instructions:*

8.5.1 *General:*

8.5.1.1 Use the test parts specified for this test without material or dimensional modification.

8.5.1.2 Use Detroit Genuine Parts<sup>22,10</sup> for all replacement test engine parts. Build kits containing screened and measured parts are provided by TEI.<sup>23,10</sup> Purchase these kits from TEI. For a list of parts supplied in the TEI kits see A3.2.

8.5.1.3 In the event of a temporary parts supply problem, the TMC may approve alternative parts. If such approved parts are used, record the approval in the test report.

8.5.1.4 Assemble all parts as illustrated in the DDCSN<sup>12</sup> online manual except where otherwise noted in this section.

8.5.1.5 Target all dimensions at the mean values of the specifications. Use Detroit 15W-40 Motor Oil<sup>11</sup> for lubricating parts during assembly.

8.5.2 *Thermostat*—Use the modified coolant thermostat as described in 6.2.3.3.

8.5.3 *Connecting-Rod Bearings*—Install new connecting-rod bearings for each test.

8.5.4 *Main Bearings*—Install new main bearings for each test.

8.5.5 *Cooling Nozzles for Piston Undercrown*—Take particular care in assembling the cooling nozzles for the piston-undercrown to insure proper piston cooling (follow installation instructions described in DDCSN<sup>12</sup>).

8.5.6 *Thrust Washers*—Install new thrust washers for each test.

8.5.7 *New Parts*—Use test parts on a first-in/first-out basis. Install new screened and measured parts (see A3.2) for each re-build.

8.6 *Measurements:*

8.6.1 *Calibrations*—Calibrate thermocouples, pressure gauges, and measuring equipment for speed, torque, and fuel-flow prior to each reference oil test or at any time readout data indicates a need.

<sup>22</sup> The sole source of supply of the apparatus known to the committee at this time is [www.demanddetroit.com/parts-service/parts/demandgenuine](http://www.demanddetroit.com/parts-service/parts/demandgenuine).

<sup>23</sup> The sole source of supply of the apparatus known to the committee at this time TEI, 12718 Cimarron Path, San Antonio, TX 78249-3423, USA. Tel. +1 210 690 1958, [tei-net.com](http://tei-net.com).

- 8.6.1.1 Conduct calibrations with at least two points that bracket the normal operating range.
- 8.6.1.2 Make these calibrations part of the laboratory record.
- 8.6.1.3 During calibration, connect leads, hoses and readout systems in the normally-used manner and calibrate with necessary standards.
- 8.6.1.4 For controlled temperatures, immerse thermocouples in calibration baths. Calibrate standards with instruments traceable to the National Institute of Standards and Technology<sup>24</sup> at a minimum of a yearly basis.
- 8.6.2 *Temperature Measurement and Delta Temperature Calculation:*
- 8.6.2.1 *General*—Measure temperature with thermocouples and conventional readout equipment. The thermocouple type is not specified. For temperatures in the 0 °C to 150 °C range, calibrate temperature measuring systems to  $\pm 0.5$  °C for at least two temperatures that bracket the normal operating range. Insert all thermocouples so that the tips are located midstream of the flow unless otherwise indicated.
- 8.6.2.2 *Air Temperature of Ambient Conditions*—Locate thermocouple in a convenient, well-ventilated position away from the engine and hot accessories.
- 8.6.2.3 *Coolant Temperature at Engine Outlet*—Locate the thermocouple within 305 mm of the engine block. An example location is shown in [Fig. A4.17](#).
- 8.6.2.4 *Coolant Temperature at Engine Inlet*—Locate the thermocouple within 305 mm of the engine block. An example location is shown in [Fig. A4.11](#).
- 8.6.2.5 *Coolant Temperature at Jacket Inlet*—Locate the coolant jacket inlet thermocouple in the coolant module, at an insertion depth of 76.2 mm from the face of the module, as shown in [Fig. A4.7](#).
- 8.6.2.6 *Coolant Temperature at Jacket Outlet*—Locate the coolant jacket outlet thermocouple in the coolant module, at an insertion depth of 50.8 mm from the face of the engine block, as shown in [Fig. A4.18](#).
- 8.6.2.7 *Oil Temperature in Gallery*—Locate the thermocouple at the intake side of the block in the rear, oil-gallery passage at an insertion depth of 60.3 mm from the face of the block. Fitting inserted in place of the factory plug. Refer to [Fig. A4.5](#) for location.
- 8.6.2.8 *Oil Temperature in Sump*—Using a front sump oil pan configuration, locate a thermocouple on the exhaust side of the oil pan, in the modified bulkhead connector. Thermocouple shall extend a minimum of 25.4 mm into oil pan. Refer to [Fig. A4.19](#).
- 8.6.2.9 *Air Temperature in Engine Intake*—Locate the thermocouple in the center of the air stream leading to the turbocharger inlet, as shown in [Fig. A4.20](#). Thermocouple shall be approximately 330 mm upstream of the turbo inlet connection.
- 8.6.2.10 *Fuel Temperature at Engine Inlet*—Locate the thermocouple at the fuel-supply line prior to the fuel-filter housing as shown in [Fig. A4.7](#).
- 8.6.2.11 *Fuel Temperature at Engine Return*—Locate the thermocouple at the fuel-return line after the fuel-filter housing as shown in [Fig. A4.7](#).
- 8.6.2.12 *Exhaust Temperature in Tailpipe*—Locate the thermocouple in the exhaust pipe approximately 270 mm downstream of the turbocharger outlet. Locate the thermocouple downstream of the exhaust pressure tap, and upstream of the CO<sub>2</sub> probe. Refer to [Fig. A4.15](#).
- 8.6.2.13 *Air Temperature in Intake Manifold*—Locate the thermocouple at an insertion depth of 50.8 mm from the exterior face of the manifold, as shown in [Fig. A4.21](#).

<sup>24</sup> National Institute of Standards and Technology, 100 Bureau Drive, Stop 2300, Gaithersburg, MD 20899-2300, USA. [www.nist.gov](http://www.nist.gov).

8.6.2.14 *EGR Temperature*—Locate the thermocouple on the straight portion of EGR pipe downstream of the pressure tap as shown in [Fig. A4.7](#).

8.6.2.15 *Air Temperature at the Turbocharger Outlet*—Locate the thermocouple downstream of the turbocharger outlet and prior to the CAC, as shown in [Fig. A4.20](#).

8.6.2.16 *Air Temperature at the CAC Outlet*—Locate the thermocouple downstream of the CAC outlet and prior to the EGR mixing, as shown in [Fig. A4.22](#).

8.6.2.17 *Dew Point Temperature of Inlet Air*—Locate the sensor to record the dew point temperature of the inlet air before the air filter.

8.6.2.18 *Delta Coolant Temperature for Engine*—Calculate as coolant temperature at engine outlet minus coolant temperature at engine inlet.

8.6.2.19 *Delta Coolant Temperature for Jacket*—Calculate as coolant temperature at jacket outlet minus coolant temperature at jacket inlet.

8.6.2.20 *Coolant Temperature at EGR Cooler Inlet*—Locate the thermocouple in the crossover pipe in the front of the engine, as shown in [Fig. A4.22](#).

8.6.2.21 *Coolant Temperature at EGR Cooler Outlet*—Locate the thermocouple into the upper plug of the coolant outlet elbow, as shown in [Fig. A4.17](#).

8.6.2.22 *Delta Coolant Temperature for EGR Cooler*—Calculate as coolant temperature at EGR cooler outlet minus coolant temperature at EGR cooler inlet.

8.6.2.23 *Additional Temperature Measurements*—Monitor any additional temperatures that the test laboratory regards as helpful in providing a consistent test procedure.

### 8.6.3 *Pressure Measurements and Delta Pressure Calculation:*

8.6.3.1 *Oil Pressure in Gallery*—Locate at oil charging manifold at the tee with the oil sampling line as shown in [Fig. A4.7](#).

8.6.3.2 *Air Pressure in Intake Manifold*—Take the measurement as illustrated in [Fig. A4.21](#).

8.6.3.3 *Air Pressure at Engine Intake (Air Restriction at Engine Intake)*—Measure with a static port (pressure tap hole) located upstream of inlet air temperature thermocouple (see [Fig. A4.20](#)).

8.6.3.4 *Exhaust Pressure in Tailpipe (Exhaust Back Pressure)*—Measure in a straight section of pipe upstream of the exhaust tailpipe thermocouple, with a pressure tap hole as shown in [Fig. A4.15](#). Do not locate the tap downstream of either the temperature thermocouple or the CO<sub>2</sub> probe.

8.6.3.5 *Crankcase Pressure*—Locate the pickup in the flywheel housing on the modified inspection plate. Refer to [Fig. A4.23](#).

8.6.3.6 *Air Pressure at Turbocharger Outlet*—Locate the pickup as shown in [Fig. A4.20](#). Locate the pressure tap upstream of the compressor outlet thermocouple.

8.6.3.7 *Air Pressure at CAC Outlet*—Locate the pickup after the CAC as shown in [Fig. A4.22](#). Locate the pressure tap upstream of the CAC outlet thermocouple.

8.6.3.8 *Delta Air Pressure Across CAC*—Calculate as turbocharger outlet pressure minus air pressure at the CAC Outlet.

8.6.3.9 *Air Pressure in the Coolant Tank*—Locate the pickup at the top of the coolant system expansion tank, as shown in [Fig. A4.23](#).

8.6.3.10 *Coolant Pressure at Jacket Inlet*—Locate the pickup as shown in [Fig. A4.7](#).

8.6.3.11 *Coolant Pressure at Jacket Outlet*—Locate the pickup as shown in [Fig. A4.18](#).

8.6.3.12 *Delta Coolant Pressure across Jacket*—Calculate as coolant pressure at jacket inlet minus pressure at jacket outlet.

8.6.3.13 *Barometric Pressure*—Record ambient cell pressure.

8.6.3.14 *EGR Pressure*—Locate the pickup on the straight portion of EGR pipe upstream of the thermocouple as shown in [Fig. A4.15](#).

8.6.3.15 *Exhaust Pressures prior to Turbocharger*—Locate pickups in each side of the exhaust manifold section, as shown in [Fig. A4.19](#).

#### 8.6.4 *Carbon Dioxide Measurements:*

8.6.4.1 *General*—Calibrate the sensors prior to each measurement taken during the course of the test. The CO<sub>2</sub> concentrations for the calibration span gases are specified as follows: the intake span gas shall be 3 % to 4 % CO<sub>2</sub>; the exhaust span gas shall be 1.5 % to 2 % CO<sub>2</sub>. The blend quality for all span gases shall be Primary Standard ± 1 %. The intake and exhaust CO<sub>2</sub> samples shall have a dew point no greater than 5 °C.

8.6.4.2 *Probe for Exhaust Carbon Dioxide*—Measure the volume fraction CO<sub>2</sub> in the exhaust gasses. Locate the probe downstream of the exhaust back-pressure tap and exhaust-tailpipe thermocouple. Use a 6.4 mm probe that meets the Code of Federal Regulations, Title 40 Part 86.310-79. The probe diameter shall not exceed the sample line diameter. Refer to [Fig. A4.15](#).

8.6.4.3 *Probe for Intake Manifold Carbon Dioxide*—Measure the volume fraction CO<sub>2</sub> in the intake air. Locate the probe in the intake manifold, as shown in [Fig. A4.21](#). Use a 6.4 mm probe that meets the Code of Federal Regulations, Title 40 Part 86.310-79. The probe diameter shall not exceed the sample line diameter.

#### 8.6.5 *Flow-Rate Measurements:*

8.6.5.1 *Blowby Flow Rate*—Connect the metering instrument to the OMS housing consistent with [6.2.6](#). An example is shown in [Fig. A4.24](#).

8.6.5.2 *Coolant Flow Rate*—Locate the meter between the expansion tank and engine inlet as shown in [Fig. A4.11](#).

8.6.5.3 *Fuel Flow Rate*—Locate the meter prior to day tank and the engine inlet so that only make-up or consumed fuel is measured (see [Fig. A4.14](#)). Use an appropriately sized day tank.

#### 8.6.6 *Miscellaneous Measurements:*

8.6.6.1 *Engine Speed*—Measure using an encoder or similar.

8.6.6.2 *OMS Speed*—Measure using equipment outlined in [6.2.14](#). An example is shown in [Fig. A4.19](#).

8.6.6.3 *Torque*—Use a load cell on the dynamometer. An example is shown in [Fig. A4.25](#).

8.6.6.4 *External Oil Tank Mass*—Use a load cell to suspend the external oil tank. An example is shown in [Fig. A4.5](#).

8.6.6.5 *Controller Area Network (CAN) Data*—Optionally, hand record the quantities in [Table 2](#) from diagnostic link.

8.6.7 *System Time Responses*—The maximum allowable system time responses are shown in [Table 3](#). Determine system time responses in accordance with the Data Acquisition and Control Automation II (DACA II) Task Force Report.<sup>25</sup>

## 9. Procedure

9.1 *General*—The test starts with a sequence involving a warmup, an engine break-in, and a cooldown. The test oil is then

<sup>25</sup> Available from the ASTM Test Monitoring Center, 203 Armstrong Drive, Freeport, PA 16229, Attention: Administrator.