



Designation: **D1793—17 D1793 – 23**

## Standard Test Method for Water Spotting of Emulsion Floor Polishes<sup>1</sup>

This standard is issued under the fixed designation D1793; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

### 1. Scope

1.1 This test method covers the determination of water spotting resistance of water emulsion floor polishes. The test method approximates the actual conditions of water spotting encountered in service.

1.2 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate ~~safety and health~~safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.3 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

### 2. Referenced Documents

2.1 *ASTM Standards:*<sup>2</sup>

[D1436 Test Methods for Application of Emulsion Floor Polishes to Substrates for Testing Purposes](#)

### 3. Terminology

3.1 *Definitions:*

3.1.1 *water spotting*—*spotting, n*—any change in appearance of surface resulting solely from the action of cool water.

### 4. Significance and Use

4.1 This test method measures the ability of a floor polish to resist spotting by water. This test method may be used to measure the extent of damage by a large amount of water or in a separate method to measure the amount of damage by a small amount of water that has evaporated to dryness. Reference polishes should be used for comparison.

NOTE 1—The test method may induce slight whitening, color change, noticeable change in appearance, including removal of the film, which is caused by contact with water.

<sup>1</sup> This test method is under the jurisdiction of ASTM Committee D21 on Polishes and is the direct responsibility of Subcommittee D21.04 on Performance Tests. Current edition approved March 1, 2017/Dec. 1, 2023. Published April 2017/December 2023. Originally approved in 1960. Last previous edition approved in 2015/2017 as D1793 – 92/D1793 – 17. (2015). DOI: 40.1520/D1793-17.10.1520/D1793-23.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.