
This document is not an ASTM standard and is intended only to provide the user of an ASTM standard an indication of what changes have been made to the previous version. Because it may not be technically possible to adequately depict all changes accurately, ASTM recommends that users consult prior editions as appropriate. In all cases only the current version of the standard as published by ASTM is to be considered the official document.



Standard Test Method for Determination of Erosion Control Product (ECP) Ability to Encourage Seed Germination and Plant Growth Under Bench-Scale Conditions¹

This standard is issued under the fixed designation D7322/D7322M; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope*

1.1 This test method covers guidelines, requirements, and procedures for evaluating the effect of Erosion Control Products (ECPs) on seed germination and vegetation enhancement.

1.2 This test method will evaluate the effects of both rolled erosion control products (RECPs) and hydraulically-applied erosion control products (HECPs) on seed germination in a controlled environment.

1.3 This test method utilizes bench-scale testing procedures and shall not be interpreted as indicative of field performance.

1.4 This test method is not intended to replace full-scale simulation or field testing in acquisition of performance values that are required in the design of erosion control measures utilizing RECPs and HECPs.

1.5 The values stated in either SI units or inch-pound units are to be regarded separately as standard. The values stated in each system may not be exact equivalents; therefore, each system shall be used independently of the other. Combining values from the two systems may result in non-conformance with the standard.

1.6 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.

1.7 This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.

2. Referenced Documents

2.1 ASTM Standards:²

D653 Terminology Relating to Soil, Rock, and Contained Fluids

D4354 Practice for Sampling of Geosynthetics and Rolled Erosion Control Products (RECPs) for Testing D5268 Specification for Topsoil Used for Landscaping and Construction Purposes

*A Summary of Changes section appears at the end of this standard

Copyright © ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959. United States

¹ This test method is under the jurisdiction of ASTM Committee D18 on Soil and Rock and is the direct responsibility of Subcommittee D18.25 on Erosion and Sediment Control Technology.

Current edition approved July 15, 2017 Dec. 15, 2023. Published August 2017 December 2023. Originally approved in 2007. Last previous edition approved in 20162017 as D7322 – 4617.^{e1}: DOI: 10.1520/D7322_D7322M-17.10.1520/D7322_D7322M-23.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For Annual Book of ASTM Standards volume information, refer to the standard's Document Summary page on the ASTM website.



D6475 Test Method for Measuring Mass per Unit Area of Erosion Control Blankets D6566 Test Method for Measuring Mass Per Unit Area of Turf Reinforcement Mats E145 Specification for Gravity-Convection and Forced-Ventilation Ovens

3. Terminology

3.1 For definitions of terms used in this test method, see Terminology D653.

4. Summary of Test Method

4.1 Containers containing soil are sown with seeds and then covered with an ECP. Additional containers of soil are sown with seed and left uncovered as *controls*. The light, temperature, and humidity are maintained and documented. The amount of germination and growth is measured periodically throughout the test, and the mass of vegetation is calculated at the conclusion of the test.

4.2 Each ECP under consideration as well as control containers of uncovered soil undergo testing in a controlled environment.

5. Significance and Use

5.1 This test method evaluates the effect of an ECP on seed germination and initial plant growth in a controlled environment.

5.2 The results of this test can be used to compare ECPs and other erosion control materials to determine which are the most effective at encouraging the growth of vegetation.

6. Apparatus

6.1 *Germination Containers*—Plastic pots nominally 20 ± 1 cm [8 ± 0.4 in.] inside diameter and having a height of 10 ± 1 cm [4 ± 0.4 in.]. The pots include a perforated bottom to allow drainage.

6.2 Controlled Environmental Chamber—Platform and surroundings capable of maintaining a constant temperature of $27 \pm 2^{\circ}$ C [81 ± 2°F], 45 ± 5 % relative humidity, and 9700 ± 1100 lux [900 ± 100 ft-candles], with a light source as outlined in A1.1.

6.3 *Photometer*—Instrument capable of measuring the illumination provided by a fluorescent light source, including both the visible and ultraviolet (UV) spectrum. <u>ASTM D7322/D7322M-23</u> https://standards.iteh.ai/catalog/standards/astm/1565f4ee-15e5-45e2-9a70-d24f2663c7c1/astm-d7322-d7322m-23 6.4 *Thermometer*—Capable of measuring temperature.

6.5 Hygrometer-Capable of measuring relative humidity.

6.6 *Balance*, weighing device, calibrated, capable of weighing to an accuracy of 0.1 g.

6.7 Drying Oven, thermostatically controlled, preferably of the forced-draft type, meeting the requirements of Specification E145 and capable of maintaining a uniform temperature of $100 \pm 5^{\circ}$ C throughout the drying chamber.

7. Test Seeds

7.1 The test should be conducted on one seed mix of tall fescue (Pure Live Seed, PLS = $80 \pm 5\%$). Seed shall be stored in a refrigerator.

NOTE 1—The test seed listed in this test method has been successful for product comparison purposes. However, this test may be used with alternative test seeds based on user needs. If test seeds different from those listed in this procedure are used, agreement should be established between the testing laboratory and the user of the test.

7.2 Unless otherwise requested, use ASTM topsoil. ASTM topsoil shall comply with Specification D5268.

8. Sampling

8.1 Perform ECP material sampling in accordance with Practice D4354.



8.2 *RECPs:*

8.2.1 The laboratory RECP sample should be 1 m^2 [10 ft²].

8.2.2 Cut three specimens from each RECP laboratory sample. The specimen should completely cover the soil in the germination pots.

8.3 *HECPs*:

8.3.1 The laboratory HECP sample should be sufficiently large to provide enough slurry to satisfy 8.3.2.

8.3.2 Mix an HECP slurry from each HECP laboratory sample. The amount of slurry should be sufficient to cover the soil in the germination pots at the prescribed coverage rate.

9. Procedure

9.1 Prepare Germination Containers:

9.1.1 Prepare three pots for each ECP to be tested and three control pots.

9.1.2 Place the soil growing medium in each pot. The growing medium shall be topsoil conforming to Specification D5268 with an in-place moisture content and unit weight determined as follows:

9.1.2.1 Condition and place the topsoil in each pot at a moist unit weight of 13.3 ± 0.8 kN/m³ [85 ± 5 pcf] and 35 to 40 % moisture content (approximately 60 % saturation).

9.1.2.2 Randomly select three 5 by 5 cm [2 by 2 in.] squares from each pot. Outline or mark, or both, the selected squares in each pot. Data will be periodically collected from within these squares. Alternatively, the entire pot can be used for data collection.

9.1.2.3 Sow each pot with 0.50 seeds per cm² [500 seeds per ft²]. This is approximately 176 seeds per pot and 13 seeds per selected square. Distribute the seeds as uniformly as possible throughout each pot.

9.1.2.4 Press the seeds firmly against the soil surface, and surface. For the control pots, apply a thin veneer of cover soil of no more than 3 mm [0.1 in.] thick over the seeds. Compress both the seed and the topsoil using a 23 kg [50 lb] circular mass having a nominal diameter equivalent to the pot inside diameter. No veneer is applied to the RECP or HECP protected pots.

9.1.2.5 Add sufficient water to bring the placed and compacted topsoil to approximately 100 % saturation. (Stop as soon as free water is apparent on the surface.)

9.1.2.6 If testing an RECP, each RECP specimen shall be weighed and measured to determine its mass per unit area in accordance with Test Method D6475 and Test Method D6566. Cover each of three pots with an RECP specimen. Three pots will be left uncovered to be controls. For RECP-covered pots, place the RECP over the pot, and hold firmly in place around the perimeter of the pot.

9.1.2.7 If testing an HECP, the amount of slurry to be placed on each pot shall be weighed and measured to determine its wet mass per unit area. Cover each of three pots with the HECP slurry. Three pots will be left uncovered to be controls. For HECP-covered pots, spread the HECP uniformly over the pot.

9.1.2.8 Place the pots in the controlled environmental chamber conditioned at $27 \pm 2^{\circ}$ C [$81 \pm 2^{\circ}$ F], $45 \pm 5\%$ relative humidity, and 9700 \pm 1100 lux [900 \pm 100 ft-candles]. Photoperiod should be 14 h of light per day. The test will proceed for 21 days.

9.2 Test Operation, Maintenance, and Data Collection:

9.2.1 Check and record temperature, relative humidity, and light every day along the length and width of the chamber at locations determined as follows: divide the entire illuminated area in half one way (left to right), then divide into thirds (top to bottom) and measure in the center of each section. Make any necessary adjustments. (See Fig. 1.)