



Designation: ~~D910–21~~ D910 – 24

Standard Specification for Leaded Aviation Gasolines¹

This standard is issued under the fixed designation D910; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

This standard has been approved for use by agencies of the U.S. Department of Defense.

1. Scope*

1.1 This specification covers formulating specifications for purchases of aviation gasoline under contract and is intended primarily for use by purchasing agencies.

1.2 This specification defines specific types of aviation gasolines for civil use. It does not include all gasolines satisfactory for reciprocating aviation engines. Certain equipment or conditions of use may permit a wider, or require a narrower, range of characteristics than is shown by this specification.

1.3 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.4 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

- 2.1 *ASTM Standards:*² <https://standards.iteh.ai/catalog/standards/astm/3e8034bf-0ae1-4f98-aea6-81ab5e39356c/astm-d910-24>
- [D86 Test Method for Distillation of Petroleum Products and Liquid Fuels at Atmospheric Pressure](#)
 - [D93 Test Methods for Flash Point by Pensky-Martens Closed Cup Tester](#)
 - [D130 Test Method for Corrosiveness to Copper from Petroleum Products by Copper Strip Test](#)
 - [D323 Test Method for Vapor Pressure of Petroleum Products \(Reid Method\)](#)
 - [D357 Method of Test for Knock Characteristics of Motor Fuels Below 100 Octane Number by the Motor Method; Replaced by D 2700 \(Withdrawn 1969\)³](#)
 - [D381 Test Method for Gum Content in Fuels by Jet Evaporation](#)
 - [D614 Method of Test for Knock Characteristics of Aviation Fuels by the Aviation Method; Replaced by D 2700 \(Withdrawn 1970\)³](#)
 - [D873 Test Method for Oxidation Stability of Aviation Fuels \(Potential Residue Method\)](#)
 - [D909 Test Method for Supercharge Rating of Spark-Ignition Aviation Gasoline](#)
 - [D1094 Test Method for Water Reaction of Aviation Fuels](#)
 - [D1266 Test Method for Sulfur in Petroleum Products \(Lamp Method\)](#)

¹ This specification is under the jurisdiction of ASTM Committee D02 on Petroleum Products, Liquid Fuels, and Lubricants and is the direct responsibility of Subcommittee D02.J0.02 on Aviation Piston Engine Fuels.

Current edition approved ~~May 1, 2021~~ March 1, 2024. Published ~~June 2021~~ March 2024. Originally approved in 1947 (replacing former D615). Last previous edition approved in ~~2020~~ 2021 as ~~D910~~ D910 – 21, ~~– 20a~~. DOI: ~~10.1520/D0910-21~~ DOI: 10.1520/D0910-24

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ The last approved version of this historical standard is referenced on www.astm.org.

*A Summary of Changes section appears at the end of this standard

- D1298 Test Method for Density, Relative Density, or API Gravity of Crude Petroleum and Liquid Petroleum Products by Hydrometer Method
- D1948 Method of Test for Knock Characteristics of Motor Fuels Above 100 Octane Number by the Motor Method; Replaced by D 2700 (Withdrawn 1968)³
- D2386 Test Method for Freezing Point of Aviation Fuels
- D2392 Test Method for Color of Dyed Aviation Gasolines
- D2622 Test Method for Sulfur in Petroleum Products by Wavelength Dispersive X-ray Fluorescence Spectrometry
- D2624 Test Methods for Electrical Conductivity of Aviation and Distillate Fuels
- D2700 Test Method for Motor Octane Number of Spark-Ignition Engine Fuel
- D3338 Test Method for Estimation of Net Heat of Combustion of Aviation Fuels
- ~~D3341 Test Method for Lead in Gasoline—Iodine Monochloride Method (Withdrawn 2022)³~~
- D4052 Test Method for Density, Relative Density, and API Gravity of Liquids by Digital Density Meter
- D4057 Practice for Manual Sampling of Petroleum and Petroleum Products
- D4171 Specification for Fuel System Icing Inhibitors
- D4177 Practice for Automatic Sampling of Petroleum and Petroleum Products
- D4306 Practice for Aviation Fuel Sample Containers for Tests Affected by Trace Contamination
- D4529 Test Method for Estimation of Net Heat of Combustion of Aviation Fuels
- D4809 Test Method for Heat of Combustion of Liquid Hydrocarbon Fuels by Bomb Calorimeter (Precision Method)
- D4865 Guide for Generation and Dissipation of Static Electricity in Petroleum Fuel Systems
- D5006 Test Method for Measurement of Fuel System Icing Inhibitors (Ether Type) in Aviation Fuels
- D5059 Test Methods for Lead and Manganese in Gasoline by X-Ray Fluorescence Spectroscopy
- D5191 Test Method for Vapor Pressure of Petroleum Products and Liquid Fuels (Mini Method)
- D5453 Test Method for Determination of Total Sulfur in Light Hydrocarbons, Spark Ignition Engine Fuel, Diesel Engine Fuel, and Engine Oil by Ultraviolet Fluorescence
- D6469 Guide for Microbial Contamination in Fuels and Fuel Systems
- D7547 Specification for Hydrocarbon Unleaded Aviation Gasoline
- E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications
- 2.2 *EI Standards:*⁴
- <https://standards.iteh.ai>
- <https://standards.iteh.ai/catalog/standards/astm/3e8034bf-0ae1-4f98-aea6-81ab5e39356c/astm-d910-24>
- [IP 270 Determination of Lead Content of Gasoline – Iodine Monochloride Method](#)

3. Terminology

3.1 Definitions:

3.1.1 *aviation gasoline, n*—gasoline possessing specific properties suitable for fueling aircraft powered by reciprocating spark ignition engines.

3.1.1.1 Discussion—

Principal properties include volatility limits, stability, detonation-free performance in the engine for which it is intended, and suitability for low temperature performance.

3.2 Abbreviations:

3.2.1 *LL*—low lead

3.2.2 *VLL*—very low lead

4. General

4.1 This specification, unless otherwise provided, prescribes the required properties of aviation gasoline at the time and place of delivery.

5. Classification

5.1 Three grades of leaded aviation gasoline are provided, known as:

Grade 100
Grade 100LL
Grade 100VLL

⁴ Available from Energy Institute, 61 New Cavendish St., London, W1G 7AR, U.K., <http://www.energyinst.org>

NOTE 1—The above grade names are based on their octane/performance numbers as measured by the now obsolete Test Method D614 (Discontinued 1970). A table for converting octane/performance numbers obtained by Test Method D2700 motor method into aviation ratings was last published in Specification D910–94 in the 1995 *Annual Book of ASTM Standards*, Vol 05.01.

5.2 Grades 100, 100LL, and 100VLL represent aviation gasolines identical in minimum antiknock quality but differing in maximum lead content and color. The color identifies the difference for engines that have a low tolerance to lead.

NOTE 2—Listing of, and requirements for, Avgas Grades 91/98, 108/135, and 115/145 appeared in the 1967 version of this specification. U.S. Military Specification MIL-G-5572F, dated January 24, 1978 (withdrawn March 22, 1988), also covers grade 115/145 aviation gasoline, and is available as a research report.⁵ Listing of, and requirements for, Avgas Grades 80 and 91 appeared in the 2016 and 2017 versions of this specification respectively. Provision for unleaded Grade 91, with an optional supercharge D909 test, has been made in Specification D7547.

5.3 Although the grade designations show only a single octane rating for each grade, they shall meet a minimum lean mixture motor rating and a minimum rich mixture supercharge rating (see X1.2.2).

6. Materials and Manufacture

6.1 Aviation gasoline, except as otherwise specified in this specification, shall consist of blends of refined hydrocarbons derived from crude petroleum, natural gasoline, or blends, thereof, with synthetic hydrocarbons or aromatic hydrocarbons, or both.

6.2 *Additives—Mandatory*, shall be added to each grade of aviation gasoline in the amount and of the composition specified in the following list of approved materials.

6.2.1 *Tetraethyl Lead*, shall be added in the form of an antiknock mixture containing not less than 61 % by mass of tetraethyl lead and sufficient ethylene dibromide to provide two bromine atoms per atom of lead. The balance shall contain no added ingredients other than kerosene, an approved oxidation inhibitor, and blue dye, as specified herein. The maximum concentration limit for each grade of gasoline is specified in Table 1.

6.2.1.1 If mutually agreed upon by the fuel producer and additive vendor, tetraethyl lead antiknock mixture may be diluted with 20 % by mass of a mixed aromatic solvent having a minimum flash point of 60 °C according to Test Methods D93 when the product is to be handled in cold climates. The TEL content of the dilute product is reduced to 49 % by mass, so that the amount of antiknock additive must be adjusted to achieve the necessary lead level. The dilute product still delivers two bromine atoms per atom of lead.

6.2.2 *Dyes*—The maximum concentration limits in each grade of gasoline are specified in Table 1.

6.2.2.1 The only blue dye that shall be present in the finished gasoline shall be essentially 1,4-dialkylaminoanthraquinone.

6.2.2.2 The only yellow dyes that shall be present in the finished gasoline shall be essentially p-diethylaminoazobenzene (Color Index No. 11021) or 1,3-benzenediol 2,4-bis [(alkylphenyl)azo-].

6.3 *Additives*—These may be added to each grade of aviation gasoline in the amount and of the composition specified in the following list of approved materials.⁶ The quantities and types shall be declared by the manufacturer. Additives added after the point of manufacture shall also be declared.

6.3.1 *Antioxidants*—The following oxidation inhibitors may be added to the gasoline separately, or in combination, in total concentration not to exceed 12 mg of inhibitor (not including weight of solvent) per litre of fuel.

6.3.1.1 2,6-ditertiary butyl-4-methylphenol.

6.3.1.2 2,4-dimethyl-6-tertiary butylphenol.

6.3.1.3 2,6-ditertiary butylphenol.

⁵ Supporting data have been filed at ASTM International Headquarters and may be obtained by requesting Research Report RR:D02-1255. Contact ASTM Customer Service at service@astm.org.

⁶ Supporting data (guidelines for the approval or disapproval of additives) have been filed at ASTM International Headquarters and may be obtained by requesting Research Report RR:D02-1125. Contact ASTM Customer Service at service@astm.org.

TABLE 1 Detailed Requirements for Leaded Aviation Gasolines^A

Property		Grade 100VLL	Grade 100LL	Grade 100	ASTM Test Method ^B
COMBUSTION					
Net heat of combustion, MJ/kg ^C	min	43.5	43.5	43.5	D4529 or D3338
Octane Rating					
Knock value, lean mixture ^D					
Motor Octane Number	min	99.6	99.6	99.6	D2700
Aviation Lean Rating	min	100.0	100.0	100.0	D2700
Knock value, rich mixture					
Octane number	min				D909
Performance number ^{E,F}	min	130.0	130.0	130.0	D909
COMPOSITION					
Sulfur, mass percent	max	0.05	0.05	0.05	D1266, D2622, or D5453
Tetraethyl lead^G					
TEL, mL/L	min	0.27	0.27	0.27	D3341 or D5059
TEL, mL/L	min	0.27	0.27	0.27	D5059 or IP 270
	max	0.43	0.53	1.06	
Pb, g/L	min	0.28	0.28	0.28	
	max	0.45	0.56	1.12	
Color					
Dye content ^{H,I} , mg/L					D2392
Blue dye	max	2.7	2.7	2.7	
Yellow dye	max	none	none	2.8	
Requirements for All Grades					
VOLATILITY					
Vapor pressure, 38 °C, kPa	min		38.0		D323 or D5191 ^J
	max		49.0		
Density at 15 °C, kg/m ³			Report		D1298 or D4052
Distillation, °C			Report		D86
Initial boiling point			Report		
Fuel Evaporated					
10 volume percent at °C	max		75		
40 volume percent at °C	min		75		
50 volume percent at °C	max		105		
90 volume percent at °C	max		135		
Final boiling point	max		170		
Sum of 10 % + 50 % evaporated temperatures	min		135		
Recovery volume percent	min		97		
Residue volume percent	max		1.5		
Loss volume percent	max		1.5		
FLUIDITY					
Freezing point, °C	max		-58 ^J		D2386
CORROSION					
Copper strip, 2 h at 100 °C	max		No. 1		D130
CONTAMINANTS					
Oxidation stability, mg/100 mL (5 h aging) ^{K,L}					D873
Potential gum	max		6		
Lead precipitate	max		3		
Water reaction					D1094
Volume change, mL	max		±2		
OTHER					
Electrical conductivity, pS/m	max		600 ^M		D2624

^A For compliance of test results against the requirements of Table 1, see 7.2.

^B The test methods indicated in this table are referred to in Section 11.

^C For all grades use either Eq 1 or Table 1 in Test Method D4529 or Eq 2 in Test Method D3338. Test Method D4809 may be used as an alternative. In case of dispute, Test Method D4809 shall be used.

^D Both Motor Octane Number (MON) and Aviation Lean Mixture values shall be reported.

^E A performance number of 130.0 is equivalent to a knock value determined using iso-octane plus 0.34 mL TEL/L.

^F Knock ratings shall be reported to the nearest 0.1 octane/performance number.

^G Historically, market survey and test engine data have indicated that for ASTM D910 leaded aviation gasolines, tetraethyl lead concentration typically must exceed 0.28 g lead per litre (0.265 mL tetraethyl lead per litre) for Grades 100, 100LL, and 100VLL. Fuels containing substantially less lead may not satisfy the octane requirements of reciprocating spark ignition aviation engines while meeting the lean and rich mixture limits specified in Table 1.

^H The maximum dye concentrations shown do not include solvent in dyes supplied in liquid form.

^I Test Method D5191 shall be the referee vapor pressure method.

^J If no crystals have appeared on cooling to -58 °C, the freezing point may be reported as less than -58 °C.

^K If mutually agreed upon between the purchaser and the supplier, a 16 h aging gum requirement may be specified instead of the 5 h aging gum test; in such case the gum content shall not exceed 10 mg/100 mL and the visible lead precipitate shall not exceed 4 mg/100 mL. In such fuel the permissible antioxidant shall not exceed 24 mg/L.

^L Test Method D381 existent gum test can provide a means of detecting quality deterioration or contamination, or both, with heavier products following distribution from refinery to airport. Refer to X1.7.1.

^M Applies only when an electrical conductivity additive is used; when a customer specifies fuel containing conductivity additive, the following conductivity limits shall apply under the condition at point of use: Minimum 50 pS/m; Maximum 600 pS/m. The supplier shall report the amount of additive added.

iTeh Standards
(<https://standards.iteh.ai>)
Document Preview

[ASTM D910-24](#)

<https://standards.iteh.ai/catalog/standards/astm/3e8034bf-0ae1-4f98-aea6-81ab5e39356c/astm-d910-24>

- 6.3.1.4 75 % minimum 2,6-ditertiary butylphenol plus 25 % maximum mixed *tertiary* and *tritertiary* butylphenols.
- 6.3.1.5 75 % minimum di- and tri-isopropyl phenols plus 25 % maximum di- and tri-*tertiary* butylphenols.
- 6.3.1.6 72 % minimum 2,4-dimethyl-6-tertiary butylphenol plus 28 % maximum monomethyl and dimethyl *tertiary* butylphenols.
- 6.3.1.7 N,N'-di-isopropyl-para-phenylenediamine.
- 6.3.1.8 N,N'-di-secondary-butyl-para-phenylenediamine.

6.3.2 *Fuel System Icing Inhibitor (FSII)*—One of the following may be used.

6.3.2.1 *Isopropyl Alcohol (IPA, propan-2-ol)*, in accordance with the requirements of Specification **D4171** (Type II). May be used in concentrations recommended by the aircraft manufacturer when required by the aircraft owner/operator.

NOTE 3—Addition of isopropyl alcohol (IPA) may reduce knock ratings below minimum specification values (see **X1.2.4**).⁷

6.3.2.2 *Di-Ethylene Glycol Monomethyl Ether (Di-EGME)*, conforming to the requirements of Specification **D4171** (Type III), may be used in concentrations of 0.10 % to 0.15 % by volume when required by the aircraft owner/operator.

6.3.2.3 Test Method **D5006** can be used to determine the concentration of Di-EGME in aviation fuels.

6.3.3 *Electrical Conductivity Additive*—Stadis 450⁸ in concentrations up to 3 mg/L is permitted. When loss of fuel conductivity necessitates retreatment with electrical conductivity additive, further addition is permissible up to a maximum cumulative level of 5 mg/L of Stadis 450.

6.3.4 *Corrosion Inhibitor Additive*—The following corrosion inhibitors may be added to the gasoline in concentrations not to exceed the maximum allowable concentration (MAC) listed for each additive.

DCI-4A	MAC = 24 g/m ³
DCI-6A	MAC = 15 g/m ³
HITEC 580	MAC = 22.5 g/m ³
NALCO 5403	MAC = 22.5 g/m ³
NALCO 5405	MAC = 11.0 g/m ³
PRI-19	MAC = 22.5 g/m ³
UNICOR J	MAC = 22.5 g/m ³
SPEC-AID 8Q22	MAC = 24.0 g/m ³
TOLAD 351	MAC = 24.0 g/m ³
TOLAD 4410	MAC = 22.5 g/m ³

7. Detailed Requirements

7.1 The aviation gasoline shall conform to the requirements prescribed in **Table 1**.

7.2 Test results shall not exceed the maximum or be less than the minimum values specified in **Table 1**. No allowance shall be made for the precision of the test methods. To determine the conformance to the specification requirement, a test result may be rounded to the same number of significant figures as in **Table 1** using Practice **E29**. Where multiple determinations are made, the average result, rounded according to Practice **E29**, shall be used.

8. Workmanship, Finish and Appearance

8.1 The aviation gasoline specified in this specification shall be free from undissolved water, sediment, and suspended matter. The odor of the fuel shall not be nauseating or irritating. No substances of known dangerous toxicity under usual conditions of handling and use shall be present except as permitted in this specification.

⁷ Supporting data have been filed at ASTM International Headquarters and may be obtained by requesting Research Report RR:D02-1526. Contact ASTM Customer Service at service@astm.org.

⁸ Stadis 450 is a registered trademark marketed by Innospec Inc., Innospec Manufacturing Park, Oil Sites Road, Ellesmere Port, Cheshire, CH65 4EY, UK.