INTERNATIONAL STANDARD



First edition 2005-08

Laminations for transformers and inductors –

Part 1: Mechanical and electrical characteristics

iTeh Standards (https://standards.iteh.ai) Document Preview

IEC 60740-1:2005 https://standards.iteh.ai/catalog/standards/iec/ca0df3e4-16b2-4391-a83f-a94aa3c4ef9b/iec-60740-1-2005



Reference number IEC 60740-1:2005(E)

Publication numbering

As from 1 January 1997 all IEC publications are issued with a designation in the 60000 series. For example, IEC 34-1 is now referred to as IEC 60034-1.

Consolidated editions

The IEC is now publishing consolidated versions of its publications. For example, edition numbers 1.0, 1.1 and 1.2 refer, respectively, to the base publication, the base publication incorporating amendment 1 and the base publication incorporating amendments 1 and 2.

Further information on IEC publications

The technical content of IEC publications is kept under constant review by the IEC, thus ensuring that the content reflects current technology. Information relating to this publication, including its validity, is available in the IEC Catalogue of publications (see below) in addition to new editions, amendments and corrigenda. Information on the subjects under consideration and work in progress undertaken by the technical committee which has prepared this publication, as well as the list of publications issued, is also available from the following:

IEC Web Site (<u>www.iec.ch</u>)

• Catalogue of IEC publications

The on-line catalogue on the IEC web site (<u>www.iec.ch/searchpub</u>) enables you to search by a variety of criteria including text searches, technical committees and date of publication. On-line information is also available on recently issued publications, withdrawn and replaced publications, as well as corrigenda.

IEC Just Published

This summary of recently issued publications (<u>www.iec.ch/online_news/ justpub</u>) is also available by email. Please contact the Customer Service Centre (see below) for further information.

Customer Service Centre

If you have any questions regarding this publication or need further assistance, please contact the Customer Service Centre:

dards.iteh.ai/catalog/standards/iec/ca0df3e4-16b2-4391-a83f-a94aa3c4ef9b/iec-60740-1-2005

Email: <u>custserv@iec.ch</u> Tel: +41 22 919 02 11 Fax: +41 22 919 03 00

INTERNATIONAL STANDARD



First edition 2005-08

Laminations for transformers and inductors –

Part 1: Mechanical and electrical characteristics

iTeh Standards (https://standards.iteh.ai) Document Preview

<u>IEC 60740-1:2005</u> https://standards.iteh.ai/catalog/standards/iec/ca0df3e4-16b2-4391-a83f-a94aa3c4ef9b/iec-60740-1-2005

© IEC 2005 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale International Electrotechnical Commission Международная Электротехническая Комиссия



XA

For price, see current catalogue

CONTENTS

FO	OREWORD6					
1	1 Scope					
2	Normative references	8				
3	Terms, definitions and symbols	9				
4	Materials and lamination thicknesses	13				
	4.1 Materials	13				
	4.2 Nominal lamination thickness	13				
	4.3 Minimum stacking factor	14				
5	Designation of laminations and lamination strips	14				
	5.1 Specified complete shapes	14				
	5.2 Lamination strips for specified shapes	15				
	5.3 Lamination strips for non-specified laminations	16				
6	Packing and marking	16				
7	Electrical tests	16				
	7.1 General	16				
	7.2 Core constants	16				
	7.3 Magnetic path length	17				
	7.4 Core cross-section	17				
8	General conditions for electrical measurements	18				
	8.1 Atmospheric conditions	18				
	8.2 Test coils	18				
	8.3 Test cores	18				
	8.4 Harmonic content of the voltage	18				
9	Measurements at high field strength	18				
	9.1 General	18				
	9.2 Measurement of power loss	19				
	9.3 Measurement of total apparent power	21				
10) Measurements at low and medium field strength	22				
	10.1 General	22				
	10.2 Measurement of amplitude permeability	22				
11	Preferred ranges of laminations	23				
12	2 Dimensions and tolerances	24				
	12.1 Dimensions	24				
	12.2 Tolerances	24				
	12.3 Symmetry tolerances	25				
13	3 Dimensions and effective parameters	25				
	13.1 General	25				
	13.2 Lamination strips Type YS	25				
	13.3 Laminations Type YEI 1	26				
	13.4 Laminations Type YUI 1	27				
	13.5 Lamination Types YUI 2	30				
	13.6 Lamination Types YEx 2, YEE 2 and YEI 2	32				
	13.7 Lamination Types YEE 2L	33				
	13.8 Lamination Types YEx 3, YEE 3, YEF 3, YEI 3 and YEL 3	35				

	13.9 Lamination Types YEx 4, YEE 4 and YEF 4	
	13.10Laminations Type YM 1	38
14	Electrical characteristics for materials	
15	Specific total apparent power for laminations	40
16	Specific power loss for laminations	41
17	Mechanical characteristics for laminations	
	17.1 General appearance and conditions	42
	17.2 Cut and punch edge	
	17.3 Camber	43
	17.4 Distortion	43
	17.5 Bending	43
	17.6 Insulation	43
	17.7 Welding	

Annex A (informative) Conversion of polarisation and field strength into specific	
total apparent power	45
A.1 Specific total apparent power from polarisation and field strength	45
A.2 Equations for the curves of the magnetic materials	49
A.3 Constants for non-oriented silicon steel C 21	50
A.4 Specific reactive power and specific power loss for non-oriented silicon steel C 21	52
A.5 Constants for grain-oriented silicon steel C 22	54
A.6 Specific reactive power and specific power loss for grain-oriented silicon steel C 22	56
A.7 Influence of the shape on the electrical characteristics for grain-oriented silicon steel C 22	58
//standards.iteh.ai/catalog/standards/iec/ca0df3e4-16b2-4391-a83f-a94aa3c4ef9t Bibliography)/iec-607 59

Figure 1 – Measurements at high field strength, direct and indirect method, single- phase cores	20
Figure 2 – Measurements at high field strength, direct method, three-phase cores	. 21
Figure 3 – Measurements at low and medium field strength	. 23
Figure 4 – Lamination strips Type YS, dimensions and tolerances	. 25
Figure 5 – Laminations Type YEI 1, dimensions	. 26
Figure 6 – Laminations Type YUI 1, dimensions	. 28
Figure 7 – Layer plan for the lamination strip shapes Type YSUI 1	. 29
Figure 8 – Laminations Type YUI 2, dimensions	30
Figure 9 – Layer plan for the lamination strip shapes Type YSUI 2	32
Figure 10 – Laminations Type YEx 2, dimensions	32
Figure 11 – Laminations Type YEE 2L, using two long E parts, dimensions	34
Figure 12 – Laminations Type YEx 3, dimensions	35
Figure 13 – Laminations Type YEx 4, dimensions	36
Figure 14 – Laminations Type YM 1, dimensions	38
Figure 15 – Definition and limit of camber	43
Figure 16 – Definition and limit of distortion	43
Figure 17 – Definition and limit of bending	43

Figure A.1 – Specific total apparent power for non-oriented silicon steel C 21	48
Table 1 – Preferred magnetic steel and alloys used for laminations	13
Table 2 – Material and lamination thickness	13
Table 3 – Tolerance of the thickness of laminations	14
Table 4 – Lamination thickness and stacking factor	14
Table 5 – Test conditions for the materials C 21, C 22 and F 1 for power loss and total apparent power	19
Table 6 – Conditions for the measurement of amplitude permeability of cores using laminations of silicon steel	22
Table 7 – Conditions for the measurement of amplitude permeability of cores using laminations of nickel-iron alloys	23
Table 8 – Summary of preferred shapes	24
Table 9 – Tolerance according to ISO 286-1	24
Table 10 – Tolerances for lamination strips	25
Table 11 – Laminations Type YEI 1, relation factor of dimensions and tolerances	27
Table 12 – Laminations Type YEI 1, diameter of the holes and tolerance factor x	27
Table 13 – Laminations Type YUI 1, relation of dimensions and tolerances	28
Table 14 – Laminations Type YUI 1, diameter of the holes and tolerance factor x	29
Table 15 – Laminations Type YUI 2, relation of dimensions and tolerances	31
Table 16 – Laminations Type YUI 2, diameter of the holes and tolerance factor x	31
Table 17 – Laminations Type YEx 2, dimensions and tolerances	33
Table 18 – Laminations Type YEx 2, effective parameters	33
Table 19 – Laminations Type YEE 2L, using two long E parts, dimensions and tolerances	34
Table 20 – Laminations Type YEE 2L, using two long E parts effective parameters	/iec_6074
Table 21 – Laminations Type YEx 3, dimensions and tolerances	35
Table 22 – Laminations Type YEx 3, effective parameters	36
Table 23 – Laminations Type YEE 4, dimensions and tolerances	37
Table 24 – Laminations Type YEF 4, dimensions and tolerances	37
Table 25 – Laminations Type YEx 4, effective parameters	37
Table 26 – Laminations Type YM 1, dimensions and tolerances	38
Table 27 – Laminations Type YM 1, effective parameters	39
Table 28 – Materials from IEC 60404-8-4 and IEC 60404-8-7 and Table 1. Characteristics for the electrical steel sheet and strips, and laminations for the specific total apparent power p_{S0} and the specific power loss p_{Fe0}	40
Table 29 – Specific total apparent power p_S in VA/kg for the materials from Table 1 for all types of laminations and limb width	41
Table 30 – Specific power loss <i>p</i> _{Fe} in W/kg for the materials from Table 1 for all types of laminations and limb width	42
Table 31 – Insulation resistance of coated surface of laminations made from material according to Table 1	44
Table 32 – Approximate values for the test of welding for laminations from materials C 21 and C 22	44
Table A.1 – Data for the specific total apparent power and the specific power loss for C 21 and C 22 materials	47

60740-1 © IEC:2005(E)

Table A.2 – Constants for the specific reactive powerof non-oriented silicon steelC 21	0
Table A.3 - Constants for the specific power loss of non-oriented silicon steel C 2151	1
Table A.4 – Specific reactive power for non-oriented silicon steel C 21	2
Table A.5 – Specific power loss for non-oriented silicon steel C 21	3
Table A.6 – Constants for the specific reactive power of grain-oriented silicon steel C 22	4
Table A.7 - Constants for the specific power loss of grain-oriented silicon steel C 22 55	5
Table A.8 – Specific reactive power for grain-oriented silicon steel C 22	6
Table A.9 – Specific power loss for grain-oriented silicon steel C22	7
Table A.10 – Parts of the magnetic path in rolling direction I_W / I_{Fe} and perpendicular to the rolling direction I_Q / I_{Fe} for laminations of 13.3 to 13.10	8

iTeh Standards (https://standards.iteh.ai) Document Preview

IEC 60740-1:2005

https://standards.iteh.ai/catalog/standards/iec/ca0df3e4-16b2-4391-a83f-a94aa3c4ef9b/iec-60740

INTERNATIONAL ELECTROTECHNICAL COMMISSION

LAMINATIONS FOR TRANSFORMERS AND INDUCTORS -

Part 1: Mechanical and electrical characteristics

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.

7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or

- tps:// other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and 40expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
 - 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
 - 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60740-1 has been prepared by IEC technical committee 51: Magnetic components and ferrite materials.

IEC 60740-1 cancels and replaces IEC 60740 published in 1982 and its amendment 1 (1991). The main changes are listed below:

- a) ranges with lamination strips YS, YSUI 1, YSUI 2 and laminations YEE 2-..L added;
- b) range YEI 1 extended at the above end;
- c) ranges YED 2, YEF 2, YEL 2, YES 2, Type YM 1-5a and YM 1-7a cancelled;
- d) national designations cancelled;
- e) electrical characteristics for the laminations specified;
- f) mechanical characteristics for laminations added;
- g) holes added for lamination types YEI 1, YUI 1, YUI 2, YM 1;
- h) in Annex A, a conversion of the polarisation J and the field strength Ĥ in a specific total apparent power is defined. For the characteristics of the reactive power and the power loss, equations and constants are specified.

The text of this standard is based on the following documents:

FDIS	Report on voting
51/823/FDIS	51/836/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IEC 60740 consists of the following parts under the general title Laminations for transformers and inductors:

- Part 1: Mechanical and electrical characteristics
- Part 2: Specification for the minimum permeabilities of laminations made of soft magnetic metallic materials.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or h Standards
- amended.

A bilingual version of this publication may be issued at a later date.

IEC 60740-1:2005

https://standards.iteh.ai/catalog/standards/iec/ca0df3e4-16b2-4391-a83f-a94aa3c4ef9b/iec-60740-1

LAMINATIONS FOR TRANSFORMERS AND INDUCTORS –

Part 1: Mechanical and electrical characteristics

1 Scope

This part of IEC 60740 specifies the characteristics of laminations. Their preferred use is cores for transformers and inductors. The laminations are made of sheets and strips of magnetic materials, specified in IEC 60404-8-4 and IEC 60404-8-7.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-221, International Electrotechnical Vocabulary (IEV) – Chapter 221: Magnetic materials and components

IEC 60404-1:2000, Magnetic materials – Part 1: Classification

IEC 60404-8-4:1998, Magnetic materials – Part 8-4: Specifications for individual materials – Cold-rolled non-oriented electrical steel sheet and strip delivered in the fully-processed state

IEC 60404-8-7:1998, Magnetic materials – Part 8-7: Specifications for individual materials – Cold-rolled grain-oriented electrical steel sheet and strip delivered in the fully-processed

state https://standards.iteh.ai/catalog/standards/iec/ca0df3e4-16b2-4391-a83f-a94aa3c4ef9b/iec-60740

IEC 60404-11:1999, Magnetic materials – Part 11: Method of test for the determination of surface insulation resistance of magnetic sheet and strip

IEC 61021-1:1990, Laminated core packages for transformers and inductors used in telecommunication and electronic equipment – Part 1: Dimensions

IEC 61021-2:1995, Laminated core packages for transformers and inductors used in telecommunication and electronic equipment – Part 2: Electrical characteristics for cores using YEE 2 laminations

ISO 286-1:1988, ISO system of limits and fits – Part 1: Bases of tolerances, deviations and fits

3 Terms, definitions and symbols

For the purposes of this document, the definitions of IEC 60050-221 and the following apply.

3.1

lamination

produced from a magnetic alloy sheet, usually consisting of one piece or several joined pieces, forming one complete layer of a laminated core

3.2

lamination strip

produced from a magnetic alloy sheet, which can be composed to a layer of laminations or stacks for limbs or yokes

3.3

square stack

results, if the height of the package $h_{\rm p}$ is equal to the limb width *d*.

3.4

specific power loss

loss of the core in an alternating field with specified frequency and sinusoidal waveform, generating a specified flux density divided by the core mass:

(https://st
$$p_{\text{Fe}} = \frac{P_{\text{Fe}}}{m_{\text{Fe}}}$$
rds.iteh.ai) (1)

where

 p_{Fe} is the specific power loss, in W/kg;

 P_{Fe} is the power loss, in W; IEC 60740-1:200

 $m_{\text{Fe}}^{\text{sta}}$ is the core mass, in kg. $m_{\text{standards}}/\text{iec}/\text{ca0df3e4-16b2-4391-a83f-a94aa3c4ef9b}/\text{iec-60740-1}$

NOTE 1 $\,$ In the power loss both $\,$ the hysteresis loss and eddy current loss are included.

NOTE 2 This is valid for cores with and without an air gap in the magnetic path.

3.5

specific reactive power

reactive power of the core in an alternating field by specified frequency and sinusoidal, specified flux density divided by the core mass:

$$p_{\rm BFe} = \frac{P_{\rm BFe}}{m_{\rm Fe}} \tag{2}$$

where

 p_{BFe} is the specific reactive power, in VA/kg;

 P_{BFe} is the reactive power, in VA;

 $m_{\rm Fe}$ is the core mass, in kg.

3.6

specific reactive power of the air gap

in an alternating field and sinusoidal, specified flux density is the r.m.s. reactive power in the air gap, divided by the core mass:

$$p_{\rm BL} = 0,25 \cdot \frac{l_{\rm L} \cdot f \cdot \hat{B}^2}{l_{\rm Fe} \cdot \rho} \tag{3}$$

where

 p_{BL} is the specific reactive power of the air gap, in VA/kg;

 \hat{B} is the peak flux density, in T;

f is the frequency, in Hz;

 ρ is the density of the core, in kg/dm³;

 $l_{\rm L}$ Is the length of the air gap, in μ m;

 $l_{\rm Fe}$ is the path length, in cm.

3.7

specific total apparent power of cores without air gap

in the mean flux path, the specific total apparent power consists of the specific reactive power and the specific power loss of the core and is the product of sinusoidal voltage and r.m.s. current divided by the core mass:

(https://sta_p_BFe + p_Fe ls.iteh.ai) (4)
Document Preview

$$p_{\rm S} = \frac{U \cdot I}{m_{\rm Fe}} = \frac{P_{\rm S}}{m_{\rm Fe}}$$
 (5)

https://standards.iteh.ai/catalog/standards/iec/ca0df3e4-16b2-4391-a83f-a94aa3c4ef9b/iec-60740-1

- $P_{\rm S}$ is the total apparent power, in VA;
- p_{S} is the specific total apparent power, in VA/kg;
- p_{BFe} is the specific reactive power, in VA/kg;
- p_{Fe} is the specific power loss, in W/kg;
- U is the voltage, in V;
- *I* is the r.m.s. current, in A;
- $m_{\rm Fe}$ is the core mass, in kg.

3.8

specific total apparent power of cores with air gap

in the mean flux path, the specific total apparent power consists of the specific reactive power of the core, the specific reactive power of the air gap and the specific power loss:

$$P_{S} = \sqrt{(p_{\mathsf{BFe}} + p_{\mathsf{BL}})^{2} + p_{\mathsf{Fe}}^{2}}$$
 (6)

– 10 –

where

p_{S}	is the	specific	total	apparent	power,	in	VA/kg;	
---------	--------	----------	-------	----------	--------	----	--------	--

- p_{BFe} is the specific reactive power of the core, in VA/kg;
- $p_{\rm BL}$ $\,$ is the specific reactive power of the air gap, in VA/kg;
- $p_{\rm Fe}$ is the specific power loss, in W/kg.

3.9

magnetic path length

arithmetic mean of the longest and the shortest path length of the core neglecting radii.

NOTE For details of the calculation for each core, see 13.3 to 13.10.

3.10 Symbols

A _{Fe}	core cross-section, in mm ² ;
\hat{B}	peak flux density, in T;
\hat{B}_{n}	nominal peak flux density, in T;
\hat{B}_0	peak flux density for the characteristic of the specific reactive power, in dT;
<i>C</i> ₁	core constant 1, in mm ⁻¹ ;
<i>C</i> ₂	core constant 2, in mm ⁻³ ;
^c 1, ^c 2	constants for the characteristic of the specific reactive power;
c3, c4	constants for the characteristic of the specific power loss;
d	limb width, in mm;
f	frequency, in Hz; Ocument Preview
\hat{H}	peak field strength, in A/m;
sh _{pstandards}	stack height, in mm; ards/jec/ca0df3e4-16b2-4391-a83f-a94aa3c4ef9b/jec-60740-1
Ι	current, in A;
I_1 , I_2 , I_3	currents in the phases of three-phase cores, in A;
\hat{J}	peak polarisation, in T;
l	magnetic path length, in mm;
l _{Fe}	magnetic path length, in mm;
l _{Fe1,} l _{Fe2}	magnetic path lengths for three-phase cores, in mm;
lL	path length of the air gap, in µm;
l _q	magnetic path length cross to the rolling direction, in mm;
l _w	magnetic path length in rolling direction, in mm;
m_{Fe}	core mass, in kg;
Ν	number of turns;
N ₁	number of turns of winding N ₁ ;
N ₂	number of turns of winding N ₂ ;
P_1 , P_2 , P_3	power loss in the phases of three-phase cores, in W;
P _{BFe}	reactive power of the core, in VA;
P _{BL}	reactive power of the air gap, in VA;
P _{Fe}	power loss, in W;

test value of the power loss, in W;
total apparent power, in VA;
specific reactive power, in VA/kg;
specific reactive power of the core, in VA/kg;
specific reactive power of the air gap, in VA/kg;
specific power loss; in W/kg;
cardinal value for the specific power loss, in W/kg;
specific total apparent power, in VA/kg;
cardinal value of the total apparent power, in VA/kg;
specific total apparent power at sinusoidal current; in VA/kg;
resistance of winding N_1 , in Ω ;
resistance of winding N ₂ , in Ω ;
precision resistor, in Ω ;
resistance of the voltmeter, in Ω ;
resistance of the voltage path of the wattmeter, in Ω ;
voltage, in V;
voltage of the source, in V; Standards
voltage of the winding N ₂ , in V;
peak value of the veltage perces P_{i} in V_{i}
peak value of the voltage across n_n , in v_n , $v_n = v_n$
core volume, in mm ³ ; IEC $60740-12005$
tolerance factor; then all catalog standards/lec/ca0d/Be4-16b2-4391-a831-a94aa3c4ef9b/lec-60740-1 auxiliary value for the characteristics of the specific reactive power;
constants for the characteristics of the specific reactive power;
constant for the characteristics of the specific power loss;
stacking factor;
magnetic constant, in H/cm (4 \cdot π \cdot 10 ⁻⁹ H/cm);
amplitude permeability;
initial permeability;
in this standard = 3,1416;
the density of the core alloy, in kg/dm ³ .