



Designation: F1764 – 97 (Reapproved 2024)

Standard Guide for Selection of Hardline Communication Systems for Confined-Space Rescue¹

This standard is issued under the fixed designation F1764; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This guide covers recommended criteria for the selection of hardwire communication systems for use in permit-required confined-space rescue operations.

1.2 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.3 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 ASTM Standards:²

F1490 [Terminology Relating to Search and Rescue](#) (Withdrawn 2011)³

2.2 Federal Standards:

29 [Code of Federal Regulations 1910.146 Permit Required Confined Spaces](#)⁴

29 [Code of Federal Regulations 1910.7 Definition and Requirements for a National Recognized Testing Laboratory](#)⁴

2.3 National Code:

[National Electrical Code \(NEC\)/NFPA 70](#)⁵

¹ This guide is under the jurisdiction of ASTM Committee F32 on Search and Rescue and is the direct responsibility of Subcommittee F32.01 on Equipment, Testing, and Maintenance.

Current edition approved April 1, 2024. Published April 2024. Originally approved in 1997. Last previous edition approved in 2018 as F1764 – 97 (2018). DOI: 10.1520/F1764-97R24.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ The last approved version of this historical standard is referenced on www.astm.org.

⁴ Available from Occupational Safety and Health Administration (OSHA), 200 Constitution Ave., NW, Washington, DC 20210, <http://www.osha.gov>.

⁵ Available from National Fire Protection Association (NFPA), 1 Batterymarch Park, Quincy, MA 02169-7471, <http://www.nfpa.org>.

3. Terminology

3.1 Definitions of Terms Specific to This Standard:

3.1.1 *confined space rescue*—rescue operations within spaces that meet the definition of “permit-required confined space” in Fed. Std. 29 CFR 1910.146.

3.1.2 *hardline communication system*—any communication system where all users are connected to the system by a hardline or wire.

4. Significance and Use

4.1 Because of the many unique requirements of permit-required confined-space rescue operations and the specific construction and composition of some confined spaces, hardline communications systems may be the only type that will meet the requirements for working within these spaces. Some of these requirements are set forth in federal regulations and some by safe operating procedures developed for working in confined spaces by industry.

4.2 This guide is not meant to preclude the use of other types of communication systems in confined-space rescue.

5. System Requirements

5.1 *System Safety*—The system must be safe for use in the atmosphere, or potential atmosphere, within the space.

NOTE 1—See [Annex A1](#).

5.2 The system must have continuous, hands-free voice communications capability.

NOTE 2—See [X1.1](#).

5.3 The system must be dedicated and private so operations cannot be interfered with by outsiders not involved with the rescue.

5.4 The system shall not affect the readings of other safety equipment (that is, gas detectors).

5.5 Systems that are battery powered must have a low-battery warning or a backup power source that provides a minimum of 30 min before communications are lost.

5.6 The system must accommodate a minimum of three users.

NOTE 3—See [X1.2](#).