



Designation: D6253 – 24

# Standard Practice for Treatment and/or Marking of Wood Packaging Materials<sup>1</sup>

This standard is issued under the fixed designation D6253; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reappraisal. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reappraisal.

## 1. Scope

1.1 This practice covers the development of recommended treatment, or marking practices, or both, for wood packaging materials (WPM) and aids in identifying WPM as to phytosanitary treatment, intended service cycles, repair, the specific specification used to manufacture or recycle, and other user designated characteristics.

1.2 This practice identifies WPM treated, or marked, or both in accordance with industry, government, or international recognized standards.

1.3 The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.5 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

## 2. Referenced Documents

2.1 *ASTM Standards:*<sup>2</sup>

- D996 Terminology of Packaging and Distribution Environments
- D6039/D6039M Specification for Open and Covered Wood Crates
- D6251/D6251M Specification for Wood-Cleated Panelboard Shipping Boxes

<sup>1</sup> This practice is under the jurisdiction of ASTM Committee D10 on Packaging and is the direct responsibility of Subcommittee D10.12 on Shipping Containers, Crates, Pallets, Skids and Related Structures.

Current edition approved March 1, 2024. Published April 2024. Originally approved in 1998. Last previous edition approved in 2016 as D6253 – 16. DOI: 10.1520/D6253-24.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

D6254/D6254M Specification for Wirebound Pallet-Type Wood Boxes

D6255/D6255M Specification for Steel or Aluminum Slotted Angle Crates

D6256/D6256M Specification for Wood-Cleated Shipping Boxes with Skidded, Load-Bearing Bases

D6573/D6573M Specification for General Purpose Wirebound Shipping Boxes

2.2 *MHIA Standard*<sup>3</sup>:

MHIA MH1–2005 Pallets, Slip Sheets, and Other Bases for Unit Loads

2.3 *Military Standard*<sup>4</sup>:

MIL-DTL-2427 Detail Specification, Box, Ammunition Packaging: Wood, Nailed

2.4 *NFPA Standard*<sup>5</sup>:

NFPA 704, Standard System for Identification of Hazards of Materials for Emergency Response

2.5 *International Standard*<sup>6</sup>:

International Standards for Phytosanitary Measures (ISPM) Publication No. 15, Regulation of Wood Packaging Material in International Trade

## 3. Terminology

3.1 *Definitions*—General definitions for the packaging and distribution environments are found in Terminology D996.

3.2 *Definitions of Terms Specific to This Standard:*

3.2.1 *certifying or inspection agency, n*—a qualified independent agency providing an audit service to verify the manufacturer or recycler has complied with government or industry-recognized programs.

3.2.2 *dielectric heat treatment (DH), n*—heating of WPM using dielectric heating in accordance with a specific time-temperature schedule that achieves a minimum wood core temperature of 60°C for a minimum of 1 continuous minute.

<sup>3</sup> Available from Material Handling Industry of America (MHIA), 8720 Red Oak Blvd., Suite 201, Charlotte, NC 28217–3992, <http://www.mhia.org>.

<sup>4</sup> Available from Document Automation and Production Service, Building 4/D, 700 Robbins Avenue, Philadelphia, PA 19111-5094, <http://assist.daps.dla.mil/quicksearch>.

<sup>5</sup> Available from National Fire Protection Association (NFPA), 1 Batterymarch Park, Quincy, MA 02269-9101.

<sup>6</sup> Available from the International Plant Protection Convention, [www.ippc.int](http://www.ippc.int).

3.2.3 *heat treatment (HT), n*—heating of WPM using a conventional steam or dry kiln heat chamber in accordance with a specific time-temperature schedule that achieves a minimum wood core temperature of 56°C for a minimum of 30 continuous minutes.

3.2.4 *intended service cycle, n*—a marking applied to a materials handling pallet to identify a multiple-use or single-use pallet (see 3.2.7 and 3.2.5).

3.2.5 *single-use (S) pallets, n*—intended for use in shipping only one unit load (also known as expendable or single-trip pallets) (see Table 1).

3.2.6 *methyl bromide (MB) fumigation, n*—fumigation of WPM with methyl bromide using an approved fumigation schedule.

3.2.7 *multiple-use (M) pallets, n*—intended for reuse in shipping unit loads (also known as a reusable or multi-trip pallets) (see Table 1).

3.2.8 *quality mark, n*—see *treatment mark*.

3.2.9 *phytosanitary treatment, n*—officially authorized procedure for the killing or removal of pests or rendering pests infertile.

3.2.10 *repaired-pallet (R), n*—describes a pallet with original components replaced or modified (see Table 1).

3.2.11 *sulfuryl fluoride (SF) fumigation, n*—fumigation of WPM with sulfuryl fluoride using approved fumigation schedule.

3.2.12 *treatment mark, n*—an official stamp or brand, internationally recognized, applied to a regulated article to attest its phytosanitary status.

3.2.13 *wood packaging material (WPM), n*—wood or wood products (excluding paper products) used in supporting, protecting or carrying a consignment. It covers wood packaging such as pallets, skids, containers, crates, boxes, packing blocks, drums, cases, load boards, pallet collars, and dunnage.

**4. Significance and Use**

4.1 This practice establishes the criteria to treat, or mark, or both WPM with permanent identification for the phytosanitary treatment, or intended service cycle, or both, repair, specification used, and other designated characteristics.

4.2 The marking of the WPM shall be performed after ensuring the material complies with the applicable specification.

**5. Summary of Practice for Phytosanitary Treatment and Marking of WPM**

5.1 Treatment or quality marking of WPM shall conform to the enforcement regulations and policy of the American Lumber Standard Committee (ALSC) WPM Program and ISPM 15.

5.2 Treatment or quality mark must meet the requirements of acceptable marks in ISPM 15 (see Fig. 1 and Fig. 2) and should include the following:

5.2.1 IPPC logo,

5.2.2 Two-letter US abbreviation, which must be separated by a hyphen from the producer/treatment provider code,

5.2.3 Unique number assigned by an inspection agency to the facility,

5.2.4 HT, DH, MB, or SF abbreviation, and

5.2.5 Inspection agency logo.

5.3 Irrespective of the type of treatment applied, wood packaging material must be made of debarked wood. Any number of visually separate and clearly distinct small pieces of bark may remain if they are:

5.3.1 Less than 3 cm in width (regardless of the length), or

5.3.2 Greater than 3 cm in width, with the total surface area of an individual piece of bark less than 50 cm<sup>2</sup>.

**6. Summary of Practice for Marking of Wood Pallets**

6.1 Marking of pallets shall conform to a published industry, government or international standard, as applicable.

6.1.1 The following divisions under this section, detail the marking (see Fig. 3) information to be applied to the pallet. Each identification will be separated by a space or mark. The location of the marking information is at the discretion of the pallet manufacturer.

6.1.1.1 The manufacturer, recycling or leasing company, or any identification code shall be applied to the pallet, for example, ABC, 123, FP, CHEP, PECO.

6.1.1.2 A marking identifying the industry, government or international specification (when applicable) followed during fabrication shall be applied to the pallet. The marking identifying the specification of conformance shall be coded, for example, GMA75, NNP71C, MH1, SPEQ.

6.1.1.3 The month and year of manufacture and repair shall be marked, for example, 10 94, 05 94, 01 95, 01 201, 02 210.

6.1.1.4 The intended service cycles identification code shall be applied, for example, M, S, R.

6.1.2 The following additional information may be included in the marking of pallets by the direction of the manufacturer, recycling company, or owner of the pallet.

6.1.2.1 The load rating of the pallet, for example, 2000 lb, 0953 kg.

6.1.2.2 The ownership of the pallet, for example, USA, ATT, CHEP.

6.1.2.3 The certifying agency mark, for example, TP, TPS.

6.1.2.4 Identify the materials used in the construction of pallets that exhibit health, flammability, or reactivity risk factors in accordance with the NFPA Hazard rating index, for example 1.B, 1.Y, 2.R (see Table 2).

6.2 *Marking Materials*—Any specification process, or material used in the marking application, or both, shall be durable enough to be readable for the duration of the pallet’s expected service life.

**TABLE 1 Pallet Intended Service Cycle Identification<sup>A</sup>**

Letter Designation	Explanation
S	Single-use pallet
M	Multiple-use pallet
R	Repaired pallet

<sup>A</sup> This information may be found in MHIA MH1–2015.